The Alignment Tax Is Graded: Task-Selective Capability Loss Under Length-Normalized DPO with SFT Retention

Ye Yuan
Independent Researcher
ye.yuan.phd@gmail.com

Abstract

Setting. We fine-tune Qwen3.5-4B with sparse LoRA and length-normalized DPO plus an SFT retention term (the RPO objective) on structured financial-filing tasks, and track downstream capability as the implicit reward margin grows to $\sim$7 β-scaled units (nf4 training backend; $\sim$3 under fp16 dequantized-base measurement). **Question.** Does margin growth degrade capability uniformly, as displacement theory and IPO's design motivation predict? **Findings.** In a pre-registered 8-seed study with artifact-aware scoring and TOST equivalence testing, we find the alignment tax is graded and task-selective: extraction is preserved ($\Delta = -0.55$, equivalent at ± 5), json loses little ($\Delta = -3.52$, equivalence fails on a clustered item-level interval), and router degrades severely ($\Delta = -30$). Router's loss concentrates in a format-break window at margin 1–3. The margin is accounted for entirely by rejected-completion suppression with chosen held flat by the retention term; the source of the behavioral damage is not attributed. Gold-logp deflation is task-selective (extraction -0.15, json -1.04, router -1.47 nats/token under fp16), with gold selectively protected relative to incorrect controls on extraction (8/8 seeds). Implicit reward margins under QLoRA differ up to $3.4\times$ between the nf4 training backend and fp16 dequantized measurement, axis-dependently. **Scope.** Length-normalized rewards with SFT retention, sparse LoRA on 8/32 layers, one 4B model, easily-separable synthetic preferences, three structured tasks. A no-retention control and a measured format-alignment metric are left to future work.

1 Introduction

DPO's implicit reward margin grows large under length-normalized rewards, reaching $\sim$7 β-scaled units in our experiments. This echoes the unbounded growth IPO was designed to prevent (our margins are per-token; see §3.1 for the conversion). The dominant framing treats this growth as pathological. Razin et al. [13] identify likelihood displacement, where chosen log-prob decreases and probability mass may flow to out-of-distribution completions. IPO [1] bounds the margin, treating unbounded growth as the core problem. Cal-DPO [15] observes absolute likelihood deflation and proposes a calibration fix. Yet the empirical basis comes primarily from judge-based evaluation or full fine-tuning at large scale. The common practical regime is understudied: small model, LoRA, length-normalized rewards, and structured exact-format tasks. A methodological gap compounds the empirical one: the literature lacks equivalence testing for capability preservation. Studies sometimes report "no significant difference" without the power to distinguish "preserved" from "underpowered to detect a real drop."

This is an empirical characterization study: we do not propose a new training algorithm, but measure how an existing one (length-normalized DPO with an SFT regularization term) affects downstream capability as its implicit reward margin grows. We present a pre-registered 8-seed study of a 4B model fine-tuned with LoRA. We measure behavioral capability (free-generation with artifact-aware scoring) and probability-layer dynamics (per-token gold/control log-probabilities) as the margin grows to $\sim$7. That value is from the nf4 training backend; the margin is $\sim$3 under fp16 dequantized-base measurement. Our objective combines length-normalized DPO with an SFT retention term

(weight 0.5) that anchors chosen-completion likelihood. This is a common practical choice. As we show, the full margin is then accounted for by rejected-completion suppression.

The alignment tax is real but graded. It is undetectable on extraction ($\Delta = -0.55$, TOST equivalence PASS), small but statistically genuine on json ($\Delta = -3.52$), and catastrophic on router ($\Delta = -30$). The gradient tracks format-alignment to the preference data's dominant style axis, consistently across all 8 seeds. With three tasks, we report this co-occurrence without claiming causation.

The mechanism is asymmetric. The retention term keeps chosen reward approximately stationary while DPO gradients drive rejected reward to -14.2 (nf4). As a result, margin growth comes entirely from rejected-completion collapse. The style axis dominates this suppression in aggregate under both backends, but per-pair ordering is backend-dependent (§4.3). The pre-registered prediction that style would dominate held-out per-pair margin at every checkpoint was falsified under both backends (fp16 0/4; nf4 2/4). Gold-logp deflation is itself task-selective and directionally consistent with behavioral outcomes, though non-linearly related (§4.3–4.4). A naive strict-match scorer masked this picture by producing a false capability collapse (see the scorer artifact in §3.2). Artifact-aware evaluation and pre-registered TOST equivalence testing prevented that error. Here TOST serves as the primary evaluation framework for capability assessment.

Our contributions are three. (1) A graded, task-selective alignment tax, with margin growth accounted for entirely by rejected-completion suppression; the source of the behavioral damage is not attributed pending a no-retention control; the format-alignment hypothesis for which tasks are affected is consistent with the data but not directly measured (§4.1–4.3). It includes non-monotonic format-break dynamics at margin ≈ 3 and a falsified pre-registered prediction on held-out per-pair margin. (2) Task-selective gold-logp deflation, with selective protection demonstrated on extraction (8/8 seeds, paired statistic) and robust across quantization backends (§4.4). (3) An artifact-aware evaluation protocol with pre-registered TOST equivalence testing (§3). Its falsification chronology (three falsified hypotheses, two refined characterizations) documents how pre-registration forced successive refinement of initially simpler claims (§5.2).

This study operates within explicit scope conditions: sparse LoRA on 8/32 layers (0.034% of parameters; not full fine-tuning), a single 4B model, length-normalized rewards with an SFT retention term (weight 0.5), easily-separable synthetic preferences, and three structured exact-format tasks. We do not study safety or refusal tasks, where Razin et al. demonstrated catastrophic displacement. We also do not study full fine-tuning, naturalistic human-written preferences, or models above 4B parameters. These are stated boundaries, not implicit weaknesses.

2 Related Work

Likelihood displacement. Razin et al. (ICLR 2025) [13] identify likelihood displacement under DPO: chosen log-prob decreases while mass may flow to out-of-distribution or harmful completions. They introduce the CHES score to flag pairs whose embedding proximity drives catastrophic displacement. Their analysis notes displacement is "not necessarily problematic"; it is catastrophic only when mass flows to opposite-meaning responses. Our SFT retention term anchors chosen likelihood. It is equivalent to RPO (Liu et al. [6]) and is the mitigation Razin et al. themselves propose. This chosen-decline dynamic is therefore largely suppressed (§4.3); whether displacement would emerge without it is untested. Pipano et al. [10] characterize which f-divergence losses are displacement-resistant by construction. Our approach instead retains the standard DPO loss and relies on the SFT term for anchoring.

The squeezing effect. Ren and Sutherland (ICLR 2025) [14] show DPO's gradient is dominated by negative gradients on rejected completions, concentrating mass onto the highest-probability token per position. They demonstrate this at the single-token level on Pythia and Qwen. We observe consistent dynamics on multi-token structured completions, though the transfer is assumed rather than proven. Our reward decomposition (§4.3) is textbook squeezing (rejected -14.2, chosen within -0.072 to $+0.052$, nf4). It also offers a candidate explanation for task-selective gold deflation (§4.4). Extraction outputs share entities with training data and may gain from mass concentration onto gold tokens. Router's terse format is maximally dissimilar from the verbose pairs, so router may not.

Ordering preservation and calibration. Cal-DPO (Xiao et al., NeurIPS 2024) [15] observes DPO preserves preference ordering while absolute likelihoods deflate, and calibrates the implicit reward to prevent chosen-reward decline. Our retention term achieves similar anchoring (§3.1). Chosen-flatness does not demonstrate Cal-DPO's concern is unfounded, but that it is already addressed.

Even with chosen anchored, the behavioral tax remains on off-target tasks (§4.1). The margin is accounted for by rejected suppression (§4.3), but the source of the damage is not attributed.

Bounding the margin. IPO (Azar et al., AISTATS 2024) [1] replaces DPO's log-sigmoid with a squared loss to bound the margin, treating unbounded growth as the core pathology. Our margin grows to $\sim$7 with graded, format-selective effects rather than the uniform catastrophe bounding targets (§4.1–4.2). This does not invalidate IPO. It characterizes a regime where damage concentrates in a margin 1–3 window and is task-selective.

Chosen-reward predictions. Rafailov et al. (COLM 2024) [12] predict from a Q-function framework that chosen log-prob should decrease under DPO. Our retention term largely counteracts this at the endpoint, though dequantized-base measurement reveals a residual transient dip (§5.3).

Equivalence testing and scoring. Manzoni (2026) [7] uses TOST with 8 seeds for SFT capability preservation in MoE fine-tuning. A concurrent paper (Bao and Abisado, *Symmetry* 2026) [2] applies TOST as incidental validation in a DPO context. To our knowledge, pre-registered TOST as the primary evaluation framework for DPO capability assessment is unprecedented in the DPO literature, though TOST is well-established in bioequivalence. Baxi (2025) [3] separates constraint compliance from semantic accuracy, establishing the decomposition. Our contribution is the trajectory dynamics: a transient format-break spike vs a monotonic content-error rise (§4.2). Minerva (Lewkowycz et al., 2022) [4] provides precedent for answer normalization preventing exact-match false negatives. Our canonicalization result is a concrete alignment-specific instance (see the scorer artifact in §3.2).

DPO dynamics and alignment-tax context. Li (2026) [5] finds none of 20 DPO variants outperforms vanilla DPO under Bonferroni correction. Young (2026) [16] frames the alignment tax as the projection of the safety direction onto the capability subspace. Our format-axis-alignment finding (§4.1) is an empirical instantiation. Pollanen (2026) [11] reports margin can anticorrelate with reasoning capability ($r = -0.91$, LLaMA on logic tasks, sweeping β). They vary β rather than observing within-run growth, so the result is related to, but distinct from, our trajectory analysis.

3 Method

3.1 Setup

We fine-tune Qwen3.5-4B with LoRA ($r = 8$, $\alpha = 16$, dropout $= 0.05$) using vanilla length-normalized DPO ($\beta = 0.5$) with an SFT retention term. Let π_θ denote the policy and π_{ref} the SFT reference. For a prompt x and completion y of length $|y|$ tokens, the length-normalized log-probability is

$$\ell_\theta(y \mid x) = \frac{1}{|y|} \sum_{t=1}^{|y|} \log \pi_\theta(y_t \mid x, y_{<t}). \tag{1}$$

Length normalization follows the per-token formulation discussed by Meng et al. [8]. The implicit reward of a completion is $r_\theta(x,y) = \ell_\theta(y \mid x) - \ell_{\text{ref}}(y \mid x)$, the policy log-probability minus the reference log-probability. Given a preference pair (x, y_w, y_l) with chosen y_w and rejected y_l, the β-scaled preference margin and the DPO preference loss are

$$m = \beta \left[r_\theta(x, y_w) - r_\theta(x, y_l) \right], \qquad \mathscr{L}_{\text{pref}} = -\log \sigma(m), \qquad \beta = 0.5. \tag{2}$$

Because Eq. (1) is per-token and $\beta = 0.5$, a reported margin of 7 corresponds to a per-token log-ratio difference of 14 nats. Under the policy, each rejected token is on average $e^{14} \approx 1.2 \times 10^6$ times less likely, relative to the reference, than each chosen token. This is near-total suppression of the rejected text. Displacement and IPO analyses typically reason about sequence-level log-ratios, so our margins are not directly comparable in scale.

The total training objective adds an assistant-only cross-entropy on the chosen completion, with system and user tokens masked:

$$\mathscr{L} = \mathscr{L}_{\text{pref}} + \lambda \mathscr{L}_{\text{sft}}, \qquad \mathscr{L}_{\text{sft}} = -\ell_\theta(y_w \mid x), \qquad \lambda = 0.5. \tag{3}$$

Equation (3) is the Regularized Preference Optimization (RPO) objective of Liu et al. [6]; a related DPO+NLL objective appears in Pang et al. [9]. We refer to the $\lambda \mathscr{L}_{\text{sft}}$ term as the SFT retention term throughout. Razin et al. [13] identify this SFT regularization as a mitigation for likelihood displacement. The retention term anchors chosen-completion likelihood during preference optimization.

Qwen3.5-4B is a hybrid architecture with 24 linear-attention layers and 8 full-attention layers (every 4th: layers 3, 7, 11, 15, 19, 23, 27, 31). LoRA adapts only the 8 full-attention layers (q/k/v/o_proj; 1.57M trainable parameters, 0.034% of 4.66B total), leaving the 24 linear-attention layers and all MLPs untouched. Training uses AdamW (lr 5×10^{-5}, constant schedule, weight decay 0.01), gradient clipping 1.0, batch size 8, and 180 fixed optimizer steps with no loss-based early stop. A divergence guard aborts on NaN or smoothed margin > 20. Eight seeds (0–7) start from the same SFT checkpoint (hash-verified; Appendix E). The chat template is byte-identical across sources, and tokenization is identical on all study inputs: the SFT adapter, DPO adapters, and base tokenizer configs differ in metadata (added-token count, pre-tokenizer regex) but produce identical token IDs on all 6,024 evaluation and preference strings, verified by direct token-ID comparison.

The preference data is 647 pairs (549 train, 98 held-out; deterministic split) on two axes. The correctness axis has 200 tool_calling pairs, 171 of them in the 549-pair training split. Its rejected completions are wrong-tool swaps: identical arguments, randomly substituted tool name, length-matched at $\sim$7.5 words. The style axis has 447 pairs, 378 of them in the training split. Its chosen completions are verbose analytical responses ($\sim$190–226 words). Its rejected completions are GPT-4o-mini degradations with numbers, dates, and section references stripped and text truncated to $\sim$86–100 words. Length normalization is applied because otherwise the 447 style pairs would be winnable on length alone. Seeds 0–4 ran in the first quota window and 5–7 in the second.

3.2 Tasks and Evaluation Suite

We evaluate three structured exact-format tasks, 160 items each, on SEC-filing queries (Table 1). Free generation uses greedy decoding with no constrained decoding and no LLM judge. All behavioral generations are produced under nf4 quantization, matching the training backend, so the TOST verdicts describe the deployed-quantization regime end-to-end. max_new_tokens = 16 (router) or 128 (json, extraction). The 16-token router limit truncates a few FORMAT_BREAK outputs (6/251 at margin3) but does not affect FORMAT_BREAK classification, which depends on the leading token. The baseline is the step-0 SFT checkpoint on the same suite and scorer, evaluated deterministically.

Table 1: Evaluation tasks: output format, example, and preference-data coverage.

Task	Output format	Example	Pref. coverage
Json	Structured JSON tool call (function name + typed args)	`{"tool": "search_filings", "arguments": {"ticker":"AAPL"}}`	On-target (200 tool_calling pairs)
Router	Bare UPPER_SNAKE_CASE label from a fixed 5-label set (FILING_ANALYSIS, FILING_DIFF, COMPANY_DEEP_DIVE, SIMPLE_QUERY, OUT_OF_SCOPE)	`COMPANY_ DEEP_DIVE`	Off-target (zero)
Extraction	Three-field JSON: ticker, section, filing_date	`{"ticker":"MSFT", "section":"Item 7", "filing_date": "2024-02-15"}`	Off-target (zero)

Scoring uses scorer v2, a frozen four-tier classification: FORMAT_BREAK (unparseable), PASS (semantically correct), SURFACE_FORM (correct content, surface-level format difference such as "Item 1" rendered as "1"), and SEMANTIC_ERROR (wrong content). FORMAT_BREAK rate is also tracked separately. The primary metric is semantic accuracy (PASS + SURFACE_FORM). The extraction canonicalization rule was frozen before the 8-seed confirmatory run (Appendix B). It matches section identifiers via regex `\d+[A-Z]?`, case-folded, ignoring appended titles.

The scorer artifact: strict versus canonicalized scoring

Under strict string matching, extraction accuracy at margin3 appears to crash, but canonicalized scoring recovers it: seed0 0.550 $\rightarrow$ 0.981 ($69/72 = 96\%$); 8-seed mean 0.616 $\rightarrow$ 0.988. The flipped items are surface-form register shifts ("Item 1" vs "1"), not semantic failures. This is the difference between "catastrophic collapse at margin $\approx$3" and "capability preserved with a transient register shift."

3.3 Suite Independence and Domain Overlap

No eval prompt appears verbatim in the preference or SFT data (exact-string match). However, both derive from EDGAR ticker$\times$section fetches, producing domain overlap by design. We report the most specific overlap available. Extraction shares a ticker$\times$section combination with a preference pair's source filing for $\geq$81/160 items (ticker$\times$section provenance recoverable for 209/647 pairs). Json shares a ticker for $\geq$131/160 items (section is not a json field). Extraction's preservation may therefore partly reflect entity familiarity rather than format-robustness alone. Router, with zero domain overlap, provides the cleanest independence test. Degeneracy floors (extraction 0.006, router 0.200, json 0.0125), class balance, zero duplicate prompts, and gold self-consistency (160/160 per task) are reported in Appendix D.

3.4 Pre-Registered Analysis Plan

The primary endpoint is per-task semantic accuracy at the final checkpoint (step 180) versus the step-0 SFT baseline, tested via TOST equivalence at $\pm$5 points. Let $\Delta = \text{acc}_{\text{final}} - \text{acc}_{\text{baseline}}$ in percentage points. TOST tests the composite null $H_0 : |\Delta| \geq \delta$ against $H_1 : |\Delta| < \delta$ with $\delta = 5$. The confidence-interval criterion requires the 90% confidence interval for Δ to lie entirely within $(-\delta, \delta)$:

$$\text{CI}_{90\%}(\Delta) \subset (-\delta, \delta) = (-5, 5). \tag{4}$$

We chose $\pm$5 as an a priori bound large enough to avoid trivially passing: a post hoc calculation using the observed per-seed standard deviations (2.28 points on extraction, 1.56 on json) gives power above 0.99 for the seed-level TOST criterion at $\pm$5 when the true Δ is 0. The bound is also small enough that passing is substantively meaningful: a 5-point drop corresponds to 8 items flipping, which we judged non-negligible. The bound was frozen before any data from the 8-seed confirmatory run existed. We acknowledge this is researcher judgment, not derived from an external standard.

Confidence intervals are constructed at two levels: seed-level (mean per-seed difference, t-based CI, df $= 7$) and item-level (bootstrap over items, seeds pooled). For a task to pass, both must satisfy Eq. (4), and $\geq$7 of 8 seeds must individually fall within $\pm$5. If all three tasks pass, the bounded-null headline holds; if any fails, the task-selective branch governs. No multiple-comparison correction is applied. The headline requires all tasks to pass (an intersection-union test), which is inherently conservative.

Final is saved at the fixed step 180. Margin1/3/5 are saved when the 20-sample smoothed training margin first crosses 1.0/3.0/5.0 (steps vary by seed: margin1 24–30, margin3 84–98, margin5 112–138). The smoothed margin at the save step is reported as each checkpoint's margin label. Cross-seed averages at these checkpoints pool seeds at matched margin but different optimizer steps; the primary endpoint (step 180) and step20 diagnostic are unaffected. Step20 is excluded from all endpoints. All outcome-to-interpretation mappings were frozen and date-stamped before the decisive runs (Notes 1–2, committed 2026-06-11 and 2026-06-18). The pre-registration was informed by pilot runs on seeds 0 and 1 and frozen (commit `62ab7c3`) before seeds 2–7 were run. Training is bitwise deterministic, so the confirmatory seeds 0 and 1 reproduce the pilot adapters: seed 0 at every checkpoint, seed 1 through margin5 (the pilot early-stopped at step 156; the confirmatory run continued to step 180). The confirmatory set therefore contains six seeds (2–7) whose outcomes were not visible at freeze time. All 8 seeds are reported; results restricted to seeds 2–7 are in Appendix A. The notes were committed in `e3be4d5` (Note 1) and `62ab7c3` (Note 2, frozen), and will be released with the code. The repository was first pushed publicly on 2026-10-18; the commit dates reflect local authorship and are not independently timestamped.

3.5 Probability-Layer Measurement

This study uses two quantization backends. *nf4* is the training and behavioral-evaluation backend. All training, checkpoint saving, behavioral generation (§4.1–4.2), and the reward decompo-

sition (§4.3) were performed under nf4. *fp16* is the dequantized-base measurement: the same adapters loaded onto an unquantized base. Because the adapters were trained against the nf4 base, neither backend is privileged; nf4 reports what the optimizer experienced, fp16 reports what the adapter weights encode when the base is not quantized. Gold-logp measurement (§4.4), the GOLD_PROTECTED paired statistic, KL trajectory, and the held-out margin recomputation were performed under fp16 on Mac. Cross-backend magnitude comparisons are not valid, so within-backend comparisons are used throughout. Cross-backend ratios appear only in the §4.5 sensitivity analysis.

To assess whether training selectively protects gold completions relative to incorrect alternatives, we teacher-force three completion types through each checkpoint: gold (correct), control A (well-formed, different section identifier), and control B (well-formed, different ticker). Both controls are structurally valid but semantically wrong. For each item i, let $\Delta^{(i)}_{\text{gold}}$ denote the change in ℓ_θ (Eq. (1)) for the gold completion from SFT baseline to final checkpoint, and $\Delta^{(i)}_A, \Delta^{(i)}_B$ the same for controls A and B. The paired statistic is

$$S = \frac{1}{N}\sum_{i=1}^{N}\left[\Delta^{(i)}_{\text{gold}} - \tfrac{1}{2}\left(\Delta^{(i)}_A + \Delta^{(i)}_B\right)\right], \tag{5}$$

with $N = 160$. A positive S indicates gold deflates less than the controls on average (selective protection). The pre-registered threshold is $S \geq X = 0.05$ nats/token, with a 95% bootstrap confidence interval excluding zero. Controls A and B are extraction-specific; on json and router, gold-logp is reported as absolute Δ_{gold} without a paired baseline. A full reconciliation of all pre-registered secondaries against their status is in Appendix C.

Reported quantities. Semantic accuracy for a task is the mean over its 160 items of an indicator that the output is PASS or SURFACE_FORM under scorer v2. FORMAT_BREAK rate and content-error (SEMANTIC_ERROR) rate are the corresponding means of their indicators. The smoothed margin used for checkpoint triggers is the mean of the per-pair margin m (Eq. (2)) over the 20 most recent training pairs (about 2.5 optimizer steps at batch size 8). Aggregate axis margin is $\sum_{i\in\text{axis}} m_i$ over the training pairs in that axis; mean per-pair margin is the same sum divided by the pair count. The seed-level confidence interval is a t interval over the 8 per-seed accuracy differences ($df = 7$). The item-level interval is a bootstrap over items with seeds pooled (10,000 resamples), which treats the 8 per-item observations as a cluster. Token-level KL is $\sum_v \pi_\theta(v)[\log \pi_\theta(v) - \log \pi_{\text{ref}}(v)]$ averaged over gold-token positions.

Reproducibility. Code, the 647 preference pairs, the three 160-item evaluation suites, scorer v2, and all 40 checkpoint adapters will be released at `https://github.com/yuan-phd/delta-filing`. The base model is Qwen3.5-4B (Hugging Face `Qwen/Qwen3.5-4B`). nf4 quantization uses bitsandbytes (4-bit NF4, double quantization, fp16 compute; installed unpinned via pip on Kaggle in June 2026, exact version not recorded). fp16 measurements use PyTorch MPS on Apple Silicon with `torch.float16` (no bf16 fallback).

4 Results

All 8 seeds completed 180 fixed optimizer steps without triggering the divergence guard. Under the nf4 training backend ($\beta = 0.5$), final margins range 6.08–7.68 (mean 6.73). Checkpoint margin labels are training-time smoothed values. The pooled value derived from Table 4 (all 549 train pairs) differs slightly (e.g. 6.73 smoothed vs 7.12 decomposed at final). Within each backend, held-out preference margin tracks training margin closely (nf4: 7.12 vs 6.98, within 2%; fp16: 2.95 vs 2.78, within 6%; Appendix F). This indicates that margin growth is not driven by train-set memorization. Absolute margins differ 2.4× (train) to 2.5× (held-out) between backends, and up to 3.4× on the style axis. §4.5 analyzes this quantization sensitivity.

4.1 Graded, Task-Selective Degradation

Table 2 reports the verdicts of the primary TOST equivalence test (Eq. (4)). The pre-registered falsifier fires: router degrades far beyond ±5, the bounded-null headline is dropped, and the task-selective branch governs.

Extraction passes all three criteria comfortably (point estimate −0.55, both CIs well within ±5, 8/8 seeds inside the bound). A per-item flip analysis finds no systematic asymmetry (15 gains vs 22

losses, sign test, $p = 0.32$). Capability is preserved as the margin grows to $\sim$7. Json fails, though marginally. The point estimate (-3.52) and seed-level CI are within ± 5. The equivalence test fails because the item-level pooled CI lower bound (-5.31) crosses -5. The seed count is not the cause, even though only 7/8 seeds fall inside: seed0 at -6.25 is outside, and seed4 at -5.00, at the inclusive boundary, passes. We apply $|\Delta| \leq 5$ inclusively; Note 2 did not specify strict versus inclusive. The per-item flips are 0 gains and 45 losses (McNemar with continuity correction, $p = 5.4 \times 10^{-11}$). With only 2 of 160 items incorrect at baseline, zero gains is structurally near-guaranteed, so the test's significance mainly reflects the number of losses rather than directional asymmetry. The degradation is small in absolute magnitude. The ceiling (baseline 98.75) caps gains, which reduces item variance; the item-level CI is wide because losses cluster on specific items. The 45 losses fall on 17 distinct items; five items account for 28 of them (one item lost on 7 of 8 seeds, two on 6 of 8). Because losses cluster within items, they are not independent across seeds, which further limits the McNemar test. Of the 45 losses, 35 are wrong-ticker errors in the free-text argument field (the tool name is correct), 7 are wrong-tool substitutions (6 on seed 0), and 3 are format breaks. Router degrades catastrophically (-30.16, both CIs far outside ± 5, 0/8 seeds inside). The endpoint distribution is roughly symmetric (mean 0.636, median 0.638, range 0.488–0.769) but wide (spread 0.281). This reflects high seed-to-seed variance despite consistent damage depth (§4.2).

Table 2: Primary TOST equivalence test (± 5 pts, semantic accuracy at step 180 vs baseline).

Task	Base	Final	Δ	Seed 90% CI	Item 90% CI	Seeds $\lvert\Delta\rvert \leq 5$	Verdict
Extraction	97.50	96.95	-0.55	$[-2.07, +0.98]$	$[-1.80, +0.86]$	8/8	Equivalent
Json	98.75	95.23	-3.52	$[-4.56, -2.47]$	$[-5.31, -1.95]$	7/8	Not equivalent
Router	93.75	63.59	-30.16	$[-35.65, -24.66]$	$[-34.92, -25.47]$	0/8	Not equivalent

The alignment tax is real, graded, and task-selective: undetectable (extraction, $\Delta = -0.55$), small but genuine (json, $\Delta = -3.52$), catastrophic (router, $\Delta = -30.16$). The gradient is directionally consistent with each task's format-alignment to the preference data across all 8 seeds. Router's terse enum format is the most orthogonal to the dominant verbose style axis, and router degrades most. Json has matching tool_calling coverage and degrades modestly. Extraction's orthogonal-but-non-antagonistic format is preserved. With only three tasks, we report this co-occurrence without claiming the causal link is established. Extraction also lacks direct preference coverage yet is preserved, so coverage absence alone does not predict degradation. Json has 200 matching tool_calling pairs yet still degrades. The per-axis dynamics (§4.3) explain why: tool_calling coverage provides partial but not complete protection against the dominant style-axis aggregate pressure.

4.2 Non-Monotonic Dynamics with Two Distinct Processes

Router's degradation is not monotonic in margin. Table 3 decomposes router accuracy at each checkpoint into its two failure modes, revealing two processes. FORMAT_BREAK rate is non-monotonic, peaking at margin $\approx$3 (0.196) then partly subsiding by final (0.106). Content-error rate rises monotonically ($0.148 \rightarrow 0.258$), never recovering. The partial recovery in overall accuracy after margin3 is driven by format-break subsiding, not by content correctness improving.

Table 3: Router trajectory decomposition (mean $\pm$ std over 8 seeds; nf4, training backend).

Checkpoint	Margin	Semantic acc	FORMAT_BREAK rate	Content-error rate
step20	0.75	0.852 ± 0.015	0.001 ± 0.002	0.148 ± 0.016
margin1	1.09	0.816 ± 0.030	0.007 ± 0.010	0.177 ± 0.038
margin3	3.12	0.587 ± 0.061	0.196 ± 0.089	0.217 ± 0.071
margin5	5.13	0.626 ± 0.049	0.133 ± 0.096	0.241 ± 0.083
final	6.73	0.636 ± 0.077	0.106 ± 0.070	0.258 ± 0.074

Format breaks at margin $\approx$3 take the form of invented UPPER_SNAKE_CASE pseudo-labels derived from query content (e.g., TOTAL_REVENUES_2023_Q2, REPORT_PER_ANALYSIS). The valid router labels are also UPPER_SNAKE_CASE, so the model generates in the correct register but invents labels outside the valid 5-category set. This is a label-vocabulary interference specific to




Figure 1: Per-seed margin-vs-capability trajectories for all three tasks (nf4, training backend). Thin lines are individual seeds; thick lines are the 8-seed mean; dashed lines are per-task baselines. Extraction (green) stays near baseline; json (blue) is volatile mid-trajectory but converges narrowly; router (red) fans out, with the trough at margin ≈3 on 6/8 seeds.

the preference data's financial domain, not degeneration, truncation, or style bleed. This replicates across the seeds of the 8-seed confirmatory run.

The margin ≈3 instability is not limited to router. On extraction, the SURFACE_FORM register-shift rate mirrors the non-monotonic shape: it spikes at margin ≈3 (mean 0.37, range 0.03–0.77) then subsides to 0.09 by final. Under the strict scorer this register shift counts as a capability collapse. Under scorer v2's canonicalization the apparent errors are surface-form shifts, not semantic failures (see the scorer artifact in §3.2). This is the paper's most concrete demonstration of why artifact-aware scoring is necessary.

Router accuracy reaches its trajectory minimum at margin3 on 6 of 8 seeds (mean 0.587, range 0.444–0.650). Two seeds drift slightly lower afterward. Degradation begins before the margin 1–3 interval: step20 already shows -8.6 pts from baseline (28% of the net -30.2 pt loss), and margin1 accounts for -12.2 pts (40%). Training uses a constant learning rate with no warmup, so some of this early loss may reflect optimization transient rather than margin-driven damage; we did not run a warmup ablation. The checkpoint resolution cannot pinpoint the trough more precisely than "between margin $\sim$1 and $\sim$3." Despite consistent trough depth, recovery is highly seed-dependent. Endpoint accuracy ranges 0.488 (seed5, near-zero recovery) to 0.769 (seed1), and the final format-break rate ranges 0.019–0.256. The damage is reproducible; the recovery is stochastic. Figure 1 shows per-seed margin-vs-capability trajectories. Extraction forms a tight band near baseline, json shows mid-trajectory volatility but a narrow endpoint range, and router forms a wide fan. The variance structure itself communicates the finding.

4.3 Mechanism: Rejected Collapse and Axis-Dependent Backend Sensitivity

We decompose the margin m (Eq. (2)) into its chosen and rejected reward components. Chosen reward is approximately stationary at the final checkpoint under both backends (nf4: $+0.052$; fp16: -0.028). This is consistent with the SFT retention term (weight 0.5) anchoring chosen-completion likelihood. Under fp16, chosen dips to -0.173 at margin3 before recovering. This is a transient decline in Rafailov et al.'s predicted direction, which the retention term dampens but does not fully block. nf4 shows a $2.4\times$ shallower dip at the same checkpoint (-0.072 vs -0.173). Rejected reward falls monotonically under both backends. Chosen's contribution is $\leq 4\%$ in magnitude at every checkpoint, so the full margin growth is accounted for by rejected-completion collapse alone. The retention term protects chosen likelihood but not rejected likelihood. Even with chosen explicitly anchored, the behavioral alignment tax remains: router loses 30 points and json loses 3.52. The margin decomposition shows where the margin comes from, not where the damage comes from. Both the DPO gradient on chosen and the gradient on rejected move the weights, and attributing the damage to one channel requires a no-retention control (§5.6). Implications for Cal-DPO and Rafailov et al. are discussed in §5.3. Figure 2 (nf4, training backend) shows the per-seed trajectories.




Figure 2: Reward decomposition into chosen and rejected components across checkpoints (nf4, training backend; thin lines per seed, thick lines 8-seed mean). Chosen reward stays flat near zero (retention term); rejected reward collapses, accounting for the full margin growth. Inset: mean per-pair rejected reward (nf4) at the final checkpoint (style vs tool_calling).

The per-axis decomposition reveals that per-pair ordering is not backend-invariant. Table 4 reports per-axis means at the final checkpoint under both backends.

Table 4: Per-axis reward decomposition at final checkpoint (8-seed mean; 549 training pairs: 378 style, 171 tool_calling).

Axis	Pairs	Margin (nf4)	Margin (fp16)	r_{ch} (nf4)	r_{rej} (nf4)	r_{ch} (fp16)	r_{rej} (fp16)
Style	378	8.119	2.466	+0.012	−16.226	−0.024	−4.955
Tool_calling	171	4.923	4.021	+0.142	−9.704	−0.038	−8.080

Under nf4, the training backend, style dominates on both per-pair margin (8.12 vs 4.92) and pair count. The aggregate margin is 3069 vs 842, a 3.65× ratio. These are the margins the optimizer actually experienced. Under fp16 dequantized-base measurement, the per-pair ordering reverses: tool_calling is higher (4.02 vs 2.47). Style still produces more aggregate margin through pair count (932 vs 688, 1.36×). The divergence is concentrated in the style axis's rejected completions (nf4 −16.2 vs fp16 −5.0; tool_calling −9.7 vs −8.1).

Under both backends, style produces more aggregate margin. The behavioral gradient is consistent with this aggregate pressure pattern: the task most format-orthogonal to the verbose style axis (router) absorbs the most damage.

This per-pair distinction is tested on held-out data. On 98 held-out pairs (69 style, 29 tool_calling), tool_calling margin exceeds style margin at every checkpoint under fp16 (8/8 seeds; Appendix F, Table 14). Under nf4, tool_calling leads at margin1–3 (8/8 seeds; Table 15) but style overtakes by margin5, consistent with the axis-dependent inflation measured on training pairs at final. The pre-registered prediction that style margin would exceed tool_calling margin at every checkpoint (Note 2, secondary #3) is falsified under both backends: the prediction holds at 0/4 checkpoints under fp16 and 2/4 under nf4. The final-checkpoint per-pair ordering is backend-dependent.

4.4 Gold-Logp Dynamics Are Task-Selective

We next examine whether gold completions on evaluation items are stable and whether the pattern generalizes across tasks. All Δ_{gold} values are computed in fp16 on Mac. Adapters were trained under nf4 on T4, but adapter weights are stored in full precision, so loading nf4-trained adapters onto an fp16 base is valid. Within-backend comparisons are internally consistent; absolute magnitudes may differ from nf4.

Table 5: Same-backend fp16 Δ_{gold} (gold_logp(final) − gold_logp(SFT)), 8-seed mean.

Task	Δ_{gold}	95% CI	Behavioral Δ
Extraction	-0.15	$[-0.18, -0.13]$	-0.55 pts (equivalent)
Json	-1.04	$[-1.20, -0.89]$	-3.52 pts (not equivalent)
Router	-1.47	$[-1.62, -1.35]$	-30 pts (not equivalent)

Gold deflation is task-selective (Table 5): extraction deflates modestly (-0.15 nats/token), json and router substantially (-1.04, -1.47). The ordering (extraction least, json intermediate, router most) is directionally consistent with the behavioral gradient across all 8 seeds, with non-overlapping CIs between tasks. The relationship is highly non-linear, however: router's gold deflates only $1.4\times$ more than json's, but its behavioral degradation is far larger (-30 vs -3.52 points). Gold-logp magnitude alone does not explain the behavioral gradient. Json shows substantial deflation (-1.04) but only minor behavioral loss (-3.52 pts). This suggests that structured output formats with redundant constraints (typed fields, function signatures) may maintain correct greedy-decode behavior despite large probability-mass redistribution. The json loss pattern is consistent with this: 35 of 45 losses land on the one free-text argument (ticker), not on the typed tool-selection field. Router's terse single-token enum format does not provide this task-structural buffer.

The task-selective ordering is robust across quantization backends. Using the nf4 records of the 8-seed confirmatory run (step20→final), the ordering extraction $\ll$ json $<$ router is identical (nf4 Δ_{gold}: extraction -0.008, json -0.22, router -1.59; non-overlapping CIs; Appendix G). Absolute magnitudes diverge: extraction's deflation nearly vanishes under nf4 (from -0.15 to -0.008), json compresses $\sim 5\times$, and router is essentially unchanged. This reflects both the quantization difference and the different baselines. Whether it reflects quantization-dependent sensitivity, baseline differences, or an interaction is unresolved. The task-selective ordering, which is the load-bearing claim, holds under both backends.

On extraction we can go further. We teacher-force gold alongside control A (different section identifier) and control B (different ticker) through each seed's final checkpoint. This yields the paired GOLD_PROTECTED statistic of Eq. (5) (Table 6, Figure 3). All 8 seeds return GOLD_PROTECTED: every stat exceeds the pre-registered threshold ($X = 0.05$) with CIs far from zero. Gold is selectively protected. It declines modestly (-0.10 to -0.23 nats/token) while incorrect controls collapse $2.1\times$ to $3.5\times$ more (-0.34 to -0.47). The ordering of correct over incorrect completions is preserved and strengthened. Because the controls are extraction-specific, whether gold is relatively protected on json and router is untested (Table 5 reports their absolute Δ_{gold} only). Two seeds from a preliminary probe run (seeds 0 and 1, nf4) show no evidence of the catastrophic CHES failure mode. On both seeds, a third control (rejected-register text) falls sharply (-4.6 to -5.1 nats/token). Control C was not in the 8-seed confirmatory run or the Mac runs. Finally, KL(policy $\|$ reference) on extraction gold completions rises from 0.022 at margin1 to 0.082 at final (Appendix G). This confirms mild policy drift that plateaus as margin grows from ~ 5 to ~ 7. KL is computed on extraction gold only, so drift on router may be larger.

Table 6: Paired GOLD_PROTECTED statistic (fp16, extraction, 160 items per seed).

Seed	Stat	95% CI	Δ_{gold}	Δ_{ctrl}
0	$+0.256$	$[+0.248, +0.264]$	-0.102	-0.358
1	$+0.242$	$[+0.235, +0.250]$	-0.226	-0.469
2	$+0.213$	$[+0.205, +0.220]$	-0.147	-0.360
3	$+0.239$	$[+0.232, +0.246]$	-0.102	-0.341
4	$+0.295$	$[+0.287, +0.304]$	-0.150	-0.446
5	$+0.217$	$[+0.211, +0.224]$	-0.194	-0.411
6	$+0.248$	$[+0.240, +0.255]$	-0.138	-0.386
7	$+0.267$	$[+0.257, +0.276]$	-0.168	-0.435

4.5 Backend Sensitivity of QLoRA Margins

Implicit reward margins under QLoRA differ up to $3.4\times$ between nf4 and fp16 dequantized-base measurement of the same adapters. Both backends use the same SFT adapter as reference, scored




Figure 3: Paired GOLD_PROTECTED statistic per seed with 95% CI (extraction, fp16). All 8 bars clear the pre-registered threshold $X = 0.05$ (dashed).

within each backend. The divergence is axis-dependent: style-axis margins inflate 3.3× (train) to 3.4× (held-out), while tool_calling inflates 1.2× on both splits. Style-rejected completions are long degraded-text sequences, while tool_calling-rejected completions are short tool-swaps. Length and content co-vary with axis, and the cause of the differential inflation is not isolated. Final-checkpoint chosen anchoring is backend-robust, but the mid-training trajectory is not: the margin3 transient is 2.4× deeper under fp16 (-0.173 vs nf4's -0.072).

In our measurements, this is directionally opposite to the gold-logp nf4/fp16 discrepancy (§4.4), where nf4 magnitudes are smaller for extraction (-0.008 vs -0.15) and json ($\sim$5×) and comparable for router. However, the gold-logp comparison is baseline-confounded (SFT vs step20), while the margin comparison uses the same SFT adapter scored within each backend. The contrast is therefore suggestive, not established. Chosen-flatness at the final checkpoint and aggregate ordering (style > tool under both backends) are backend-invariant; per-pair ordering is not. Margin-based monitoring of QLoRA-trained models is therefore backend-sensitive. Per-pair and per-axis comparisons require same-backend measurement.

5 Discussion

5.1 A Two-Level Mechanistic Account

The behavioral and probability-layer findings form a coherent account, though not a causally proven one. At the training level, the retention term anchors chosen-completion likelihood, and the full margin is accounted for by rejected suppression (§4.3). The style axis contributes more aggregate suppression than the correctness axis under both backends (3.65× under nf4, 1.36× under fp16). This is consistent with why the task most format-orthogonal to the verbose style axis (router) absorbs the most damage, while the task with direct tool_calling coverage (json) absorbs less. Per-pair ordering, by contrast, is backend-dependent. At the probability level, gold-logp deflation is task-selective and directionally consistent with the behavioral gradient. Extraction is the best-preserved task, and its gold completions overlap most with training-pair chosen completions (§3.3). On extraction, gold is selectively protected relative to incorrect controls (8/8 seeds). This is consistent with Ren and Sutherland's squeezing effect concentrating mass onto gold tokens that share entity vocabulary with training pairs. Router's dissimilar terse format may not enjoy this effect. Both backends' chosen minima sit at margin3, coinciding with the behavioral instability window (FORMAT_BREAK 0.196, SURFACE_FORM 0.37). Behavioral metrics are nf4-generated, and the fp16 chosen dip is a dequantized-base measurement, not the source of the behavioral instability. No causal claim is made.

The two levels do not form a single causal chain. Gold-logp magnitude is non-linearly related to behavior: router's gold deflates 1.4× more than json's but degrades far more (-30 vs -3.52 points). The behavioral gradient is better explained by format-alignment to the style-axis aggregate pressure than by gold-logp dynamics. We present the two levels as complementary, without claiming one causes the other. Rejected collapse explains which tasks are pressured; gold-logp dynamics describe how probability mass redistributes.

5.2 Falsification Chronology

The pre-registered plan forced three falsifications and two refinements. Each produced a more precise characterization than the hypothesis it replaced. Three further hypotheses were abandoned during design (Appendix C): a confounded causal-clamp experiment, router-as-primary after a non-monotonic transient appeared, and a targeted-displacement probe that pointed to global drift.

Three hypotheses were falsified outright. First, the bounded-null headline (all three tasks preserved within ± 5) was rejected when the falsifier fired on json and router (§4.1). Second, an apparent extraction collapse at margin ≈ 3 was traced to a scorer artifact (see the scorer artifact in §3.2): the apparent errors were surface-form register shifts. The measurement was killed, not refined. Third, the pre-registered prediction that style-axis held-out margin would exceed tool_calling margin at every checkpoint is falsified under both backends (fp16: 0/4 checkpoints; nf4: 2/4). The final-checkpoint per-pair ordering is backend-dependent (style $>$ tool under nf4, tool $>$ style under fp16). The falsification reveals that per-pair ordering is not backend-invariant; aggregate style dominance holds under both.

Two characterizations were refined. The pilot's "margin-independent early drop" on router became a damage window at margin $\approx$1–3 with two distinct processes (transient format-break + monotonic content-error), followed by stabilization (§4.2). The initial "gold barely moves" characterization came from nf4 ($|\Delta_{\text{gold}}| \leq 0.01$). It was refined to "gold is selectively protected but task-selectively deflates" once fp16 same-backend measurement revealed substantial json and router deflation (§4.4). Each pre-registered gate forced a more precise account. The result is more nuanced than any single prior framing predicted.

5.3 Engagement with Prior Work

Our data engages three displacement-literature claims. One caveat applies: our objective includes an SFT retention term (the RPO formulation; Liu et al. [6]; weight 0.5) on chosen completions, making it DPO + retention, not vanilla DPO. *Rafailov et al.* predict from their Q-function framework that chosen log-prob should decrease under DPO from an SFT-initialized model. Our retention term directly counteracts this. The chosen-flatness we observe (-0.072 to $+0.052$ over 7 units of margin growth) is therefore at least partly a consequence of the training objective, not purely an empirical finding about DPO dynamics. It confirms the retention term is effective in this regime. It cannot speak to whether chosen would decline under standard DPO without retention. The fp16 dequantized-base measurement reveals a transient mid-training chosen dip (-0.173 at margin3, recovering to -0.028 by final). This is a residual decline in the direction Rafailov et al. predict, dampened but not fully blocked by the retention term. Under nf4 the dip is $2.4\times$ shallower (-0.072). The retention term largely counteracts the predicted decline; dequantized-base measurement reveals the residual. *Cal-DPO* adds a calibration term to prevent chosen-reward decline; our retention term achieves a similar anchoring by a different mechanism. That chosen is anchored at the endpoint does not demonstrate Cal-DPO's concern is unfounded. It shows the concern is largely addressed. Even with chosen anchored, the behavioral tax remains, with the full margin accounted for by rejected suppression; which gradient channel produces the behavioral damage is untested. *IPO* was designed to bound the margin, treating unbounded growth as the core pathology. Our margin grows to $\sim$7 with graded, format-selective damage rather than uniform catastrophe. This does not invalidate IPO; it characterizes a regime where damage is concentrated in the margin 1–3 window and is format-selective.

5.4 Format-Alignment: What It Explains and What It Does Not

The behavioral gradient (extraction preserved $\rightarrow$ json small loss $\rightarrow$ router catastrophic) is directionally consistent with format-alignment to the preference data's style axis across all 8 seeds. With only three tasks, however, we report this co-occurrence without claiming a causal mechanism. Two limits deserve attention. First, extraction has zero direct preference coverage yet is preserved, so coverage absence alone does not predict degradation. The distinguishing factor may be format-orthogonality, domain overlap (§3.3), or the retention term anchoring chosen completions that share extraction's entity vocabulary. All three co-vary and cannot be disentangled with three tasks. Second, json has 200 on-target tool_calling pairs yet degrades slightly. Tool_calling coverage protects against the correctness axis but not against the dominant style-axis aggregate pressure. The damage mechanism and the protection mechanism therefore operate on different axes. Json shows substantial gold deflation (-1.04) but only minor behavioral loss (-3.52 points). This suggests redundant-constraint

formats may buffer greedy-decode behavior against probability-mass redistribution (see §4.1 for the loss breakdown). But extraction is also structured JSON yet deflates far less (-0.15), so format redundancy alone does not explain the difference; format-alignment co-varies. With two structured tasks and two co-varying variables, this hypothesis is illustrative, not testable.

5.5 Practical Implications

Three implications follow for practitioners running length-normalized DPO on small models with structured-output tasks. (1) Monitor format-break rate at margin ≈ 3, not just endpoint accuracy. The transient spike is where damage concentrates, and it may be invisible at the final checkpoint. (2) Audit preference-data composition for style-axis aggregate dominance. The behavioral gradient is consistent with aggregate training pressure under both backends, though per-pair ordering is backend-dependent and per-axis comparisons require same-backend measurement. (3) Consider including an SFT retention term. Its anchoring is endpoint-level: mid-training chosen can dip transiently under dequantized-base measurement. The no-retention counterfactual is untested.

5.6 Limitations

This study operates within explicit scope conditions: sparse LoRA on 8/32 layers (0.034% of parameters; not full fine-tuning), a single 4B model, length-normalized rewards with an SFT retention term (weight 0.5), easily-separable synthetic preferences, and three structured exact-format tasks. We do not study safety or refusal tasks, where Razin et al. demonstrated catastrophic displacement. Under naturalistic human preferences with higher chosen-rejected similarity (high CHES scores), the displacement dynamics Razin et al. characterize may produce different outcomes. Results may not generalize beyond these conditions. The no-retention counterfactual ($\lambda = 0$ in Eq. (3)) is untested; whether chosen declines and whether behavioral damage changes without the retention term are open questions.

Three pre-registered secondaries (#3, #4, #8) were computed post-hoc from saved adapters rather than logged during training: #4 under nf4 (Kaggle T4) with an fp16 dequantized-base measurement (Mac); #3 under fp16 (Mac) and nf4 (Kaggle T4); #8 under fp16 (Mac). Separately, the paired GOLD_PROTECTED statistic is extraction-only by design (controls A/B are task-specific). The format-alignment mechanism rests on $n = 3$ tasks. This is insufficient to distinguish format-orthogonality from coverage, domain overlap, or task difficulty. The checkpoint schedule cannot pinpoint the damage window more precisely than "between margin ~ 1 and ~ 3." Gold-logp absolute magnitudes differ substantially between fp16 and nf4. The task-selective ordering is robust across both, but absolute values are not directly comparable (§4.4, §4.5, Appendix G).

6 Conclusion

The alignment tax under length-normalized DPO with an SFT retention term is real but graded and task-selective. Router's catastrophic loss is temporally structured. Its onset is at step20 (-8.6 pts, 28% of net loss), and it concentrates in a margin 1–3 damage window where transient format-break and persistent content-error operate as distinct processes. The retention term anchors chosen completions, and the full margin growth is accounted for by rejected-completion suppression. The result is a graded behavioral outcome, with a format-alignment hypothesis consistent with but not established by the three-task gradient. Artifact-aware scoring corrected a false-collapse signal. Pre-registered TOST equivalence testing prevented both false-positive and false-negative capability claims. A disclosed chronology of three falsified hypotheses and two refined characterizations documents how pre-registration forced successive refinement of initially simpler claims. Margin growth to ~ 7 β-scaled units (nf4 training backend) produces graded rather than uniform degradation. Under the format-alignment hypothesis, this finding offers a differentiated picture (preservation where format-alignment is maintained, substantial risk where it is not) and a methodological template for future alignment-tax studies. These findings hold under specific scope conditions: sparse LoRA on 8/32 layers, a single 4B model, length-normalized rewards with an SFT retention term, and easily-separable synthetic preferences. They may not transfer to full fine-tuning, naturalistic preferences, or safety-critical tasks.

References

[1] Mohammad Gheshlaghi Azar, Zhaohan Daniel Guo, Bilal Piot, Remi Munos, Mark Rowland, Michal Valko, and Daniele Calandriello. A general theoretical paradigm to understand learning from human preferences. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2024.

[2] Shenghui Bao and Mideth Abisado. Pareto-aware dual-preference optimization for task-oriented dialogue. *Symmetry*, 18(2):372, 2026.

[3] Rahul Baxi. Separating constraint compliance from semantic accuracy: A novel benchmark for evaluating instruction-following under compression. *arXiv preprint arXiv:2512.17920*, 2025.

[4] Aitor Lewkowycz, Anders Andreassen, David Dohan, Ethan Dyer, Henryk Michalewski, Vinay Ramasesh, Ambrose Slone, Cem Anil, Imanol Schlag, Theo Gutman-Solo, Yuhuai Wu, Behnam Neyshabur, Guy Gur-Ari, and Vedant Misra. Solving quantitative reasoning problems with language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

[5] Xiaoyi Li. Do post-training algorithms actually differ? a controlled study across model scales uncovers scale-dependent ranking inversions. *arXiv preprint arXiv:2603.19335*, 2026.

[6] Zhihan Liu, Miao Lu, Shenao Zhang, Boyi Liu, Hongyi Guo, Yingxiang Yang, Jose Blanchet, and Zhaoran Wang. Provably mitigating overoptimization in RLHF: Your SFT loss is implicitly an adversarial regularizer. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. arXiv:2405.16436.

[7] Andrea Manzoni. MoE-sieve: Routing-guided LoRA for efficient MoE fine-tuning. *arXiv preprint arXiv:2603.24044*, 2026.

[8] Yu Meng, Mengzhou Xia, and Danqi Chen. SimPO: Simple preference optimization with a reference-free reward. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. arXiv:2405.14734.

[9] Richard Yuanzhe Pang, Weizhe Yuan, Kyunghyun Cho, He He, Sainbayar Sukhbaatar, and Jason Weston. Iterative reasoning preference optimization. *arXiv preprint arXiv:2404.19733*, 2024.

[10] Idan Pipano, Shoham Sabach, Kavosh Asadi, and Mohammad Ghavamzadeh. Displacement-resistant extensions of DPO with nonconvex f-divergences. In *International Conference on Learning Representations (ICLR)*, 2026. arXiv:2602.06788.

[11] Marco Pollanen. The viscosity of logic: Phase transitions and hysteresis in DPO alignment. *arXiv preprint arXiv:2601.17260*, 2026.

[12] Rafael Rafailov, Joey Hejna, Ryan Park, and Chelsea Finn. From r to q^*: Your language model is secretly a Q-function. In *Conference on Language Modeling (COLM)*, 2024.

[13] Noam Razin, Sadhika Malladi, Adithya Bhaskar, Danqi Chen, Sanjeev Arora, and Boris Hanin. Unintentional unalignment: Likelihood displacement in direct preference optimization. In *International Conference on Learning Representations (ICLR)*, 2025.

[14] Yi Ren and Danica J. Sutherland. Learning dynamics of LLM finetuning. In *International Conference on Learning Representations (ICLR)*, 2025.

[15] Teng Xiao, Yige Yuan, Huaisheng Zhu, Mingxiao Li, and Vasant G. Honavar. Cal-DPO: Calibrated direct preference optimization for language model alignment. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

[16] Robin Young. What is the alignment tax? *arXiv preprint arXiv:2603.00047*, 2026.

Appendices

A Full Per-Seed TOST Data

Complete data behind Table 2. Per-task semantic accuracy (%) at each checkpoint, all 8 seeds, plus the step-0 SFT baseline. $\Delta = \text{final} - \text{baseline}$ (percentage points). The TOST per-seed equivalence band is $|\Delta| \leq 5$.

Table 7: Extraction: per-seed semantic accuracy (%).

Seed	Baseline	step20	margin1	margin3	margin5	final	Δ	TOST
0	97.50	97.50	97.50	98.12	96.25	97.50	+0.00	PASS
1	97.50	98.75	100.00	98.75	98.75	94.38	−3.12	PASS
2	97.50	99.38	99.38	99.38	98.12	98.12	+0.62	PASS
3	97.50	98.12	99.38	98.12	97.50	98.12	+0.62	PASS
4	97.50	99.38	100.00	99.38	95.62	98.75	+1.25	PASS
5	97.50	100.00	100.00	99.38	99.38	95.00	−2.50	PASS
6	97.50	97.50	99.38	97.50	97.50	93.75	−3.75	PASS
7	97.50	99.38	100.00	100.00	100.00	100.00	+2.50	PASS

Table 8: Json: per-seed semantic accuracy (%).

Seed	Baseline	step20	margin1	margin3	margin5	final	Δ	TOST
0	98.75	82.50	93.75	93.12	94.38	92.50	−6.25	FAIL
1	98.75	93.75	95.62	80.62	89.38	96.88	−1.88	PASS
2	98.75	88.75	88.75	93.12	85.00	95.62	−3.12	PASS
3	98.75	96.88	95.00	93.75	93.75	96.25	−2.50	PASS
4	98.75	91.88	93.75	76.88	95.62	93.75	−5.00	PASS
5	98.75	95.00	95.00	94.38	96.25	96.88	−1.88	PASS
6	98.75	90.62	95.62	86.88	95.00	94.38	−4.38	PASS
7	98.75	95.62	93.75	93.75	94.38	95.62	−3.12	PASS

Table 9: Router: per-seed semantic accuracy (%).

Seed	Baseline	step20	margin1	margin3	margin5	final	Δ	TOST
0	93.75	85.62	78.12	59.38	61.88	64.38	−29.37	FAIL
1	93.75	87.50	86.88	61.25	66.88	76.88	−16.87	FAIL
2	93.75	86.25	83.75	61.25	60.62	58.13	−35.62	FAIL
3	93.75	83.75	77.50	65.00	61.25	63.12	−30.63	FAIL
4	93.75	82.50	80.62	54.37	69.38	61.88	−31.87	FAIL
5	93.75	84.38	82.50	44.38	51.88	48.75	−45.00	FAIL
6	93.75	85.62	83.75	61.25	64.38	69.38	−24.38	FAIL
7	93.75	85.62	79.38	62.50	64.38	66.25	−27.50	FAIL

Per-seed TOST pass/fail is shown in the final column; item-level bootstrap 90% CIs at the final checkpoint are reported per task in Table 2.

Seeds 0 and 1 are deterministic re-runs of the pilot (§3). Restricting to seeds 2–7: extraction mean $\Delta = -0.21$, json mean $\Delta = -3.33$, router mean $\Delta = -32.50$. All three verdicts are unchanged on the 6-seed subset (seed-level t intervals with df $= 5$; item-level bootstrap as in the main analysis). Extraction remains equivalent: seed-level 90% CI $[-2.18, +1.76]$, item-level $[-1.67, +1.35]$, and 6/6 seeds within ± 5. Json remains not equivalent: its seed-level CI $[-4.29, -2.38]$ and 6/6 seeds are within ± 5, but the item-level CI $[-5.42, -1.46]$ crosses -5. Router remains not equivalent: seed-level CI $[-38.44, -26.56]$, 0/6 seeds within ± 5. The router failure-mode decomposition across the checkpoint trajectory is in main-text Table 3; Figure 1 visualizes the same trajectory per seed.

B Scorer v2 Rules and Artifact Walkthrough

Scorer architecture. Scorer v2 applies a deterministic four-tier classification to each generated output. (1) **FORMAT_BREAK**: the output cannot be parsed by the task-specific format gate. For router, the gate requires a bare string matching one of the five valid labels; for json and extraction, it requires valid JSON with required keys. (2) **PASS**: the parsed output matches the gold answer after canonicalization. (3) **SURFACE_FORM**: the parsed output contains the correct semantic content but differs in surface form (e.g., "Item 1" vs "1"). (4) **SEMANTIC_ERROR**: the parsed,

well-formed output has incorrect content. Semantic accuracy counts PASS + SURFACE_FORM as correct; FORMAT_BREAK and SEMANTIC_ERROR are failures.

Canonicalization rules (extraction). The section-identifier field is canonicalized before comparison. The numeric portion is extracted via regex `\d+[A-Z]?` ("Item 7A" → "7A", "Item 1" → "1"). The alpha suffix is case-folded, and appended titles are ignored ("Item 7: Management's Discussion" → "7"). Ticker and filing_date use exact string match (case-insensitive for ticker).

The artifact: $0.550 \rightarrow 0.981$**.** At the margin3 checkpoint, extraction accuracy under strict string matching is 0.550 (seed0); under scorer v2's canonicalization the same checkpoint scores 0.981. The 69 items ($69/72 = 96\%$) that flip from strict-FAIL to SURFACE_FORM (semantically correct) are exclusively section-identifier surface-form variants. The model outputs "1" where gold says "Item 1", or "7A" where gold says "Item 7A". The semantic content is correct in every case, with no ticker or filing_date errors. The 8-seed mean is $0.616 \rightarrow 0.988$. The register-shift rate (SURFACE_FORM tier) peaks at margin $\approx$3 (mean 0.37 across 8 seeds), then subsides to 0.09 by final. This mirrors router's non-monotonic FORMAT_BREAK trajectory. The canonicalization rules were frozen before the 8-seed confirmatory run; no rules were added or modified after observing its results.

C Pre-Registration Reconciliation and Falsification Chronology

C.1 Secondary reconciliation. Every pre-registered secondary from Note 2 (frozen 2026-06-18) is accounted for below.

Table 10: Pre-registered secondary reconciliation.

#	Secondary	Status	Location
1	Trajectory-min per seed/task	Reported	§4.2 (router trough at margin3, 6/8)
2	FORMAT_BREAK trajectory	Reported	§4.2 (Table 3)
3	Held-out margin per category	Reported. **Falsified under both backends**: the prediction (style > tool at every checkpoint) holds at 0/4 checkpoints under fp16 and 2/4 under nf4. Final-checkpoint per-pair ordering is backend-dependent.	§4.3 (Tables 14, 15)
4	Chosen/rejected reward decomposition	Reported (post-hoc GPU inference)	§4.3, Fig. 2 (per-axis Table 4)
5	Gold-logp trajectory × 3 tasks	Reported (fp16, 8 seeds)	§4.4 (Table 5)
6	Probe statistic replication (paired)	Extraction 8/8 GOLD_PROTECTED; json/router not computable (extraction-specific controls)	§4.4 (Table 6)
7	Register-shift tracking	Reported (SURFACE_FORM rate)	§4.2
8	KL-from-reference per checkpoint	Reported (post-hoc, fp16, 8 seeds)	§4.4 (Appendix G)

Secondaries #4 and #8 were not logged during training in the 8-seed confirmatory run. #4 was computed via a dedicated GPU inference run on saved adapters (Kaggle T4). #8 was computed via Mac inference on saved adapters (fp16, proper token-level KL). #3 was computed via Mac inference on saved adapters. All three use the same checkpoint adapters as the confirmatory run; no retraining was involved. The primary TOST analysis (§4.1) was unaffected.

C.2 Pre-registration deviations. *Checkpoint mechanism:* the pre-registered design (Note 2) specified fixed-step checkpoints with margin as a post-hoc label; the implementation used

margin-crossing triggers for intermediate checkpoints (margin1: steps 24–30, margin3: 84–98, margin5: 112–138). Step20 and final (step 180) are fixed and identical across seeds, so the primary endpoint is unaffected. Cross-seed averages at intermediate checkpoints pool seeds at matched margin but different optimizer steps. *Early-stop configuration:* the design specified `max_opt_steps=180` and `no_early_stop=True`. Both were enforced at runtime in `matrix_kernel.py` and `run_matrix.py`, and all 8 seeds terminated at exactly step 180. However, `train_config.json` records module-level constants only and does not serialize these runtime parameters. This may create a misleading impression when inspecting saved artifacts. The execution matched the pre-registration; the config-file serialization did not. *Seed overlap:* seeds 0 and 1 of the confirmatory set are bitwise re-runs of the pilot seeds (seed 0 fully; seed 1 through margin5). Six of eight confirmatory seeds were unseen at freeze time. The repository was first pushed publicly on 2026-10-18; the commit dates reflect local authorship and are not independently timestamped. *Backend:* the pre-registration did not specify a quantization backend for any secondary. Secondary #3 (held-out per-category margin) was computed under fp16 (Mac) and nf4 (Kaggle T4); the per-pair ordering is backend-dependent at the final checkpoint (§4.3).

C.3 Falsification chronology. *Design phase (before the 8-seed confirmatory run):* (a) A causal-clamp experiment was designed but dropped as confounded. Clamping the margin also alters the KL penalty and total optimization pressure, making "margin magnitude $\rightarrow$ capability loss" untestable. (b) Router was initially the primary endpoint. It moved to a secondary with trajectory decomposition after pilot analysis revealed a non-monotonic transient. (c) A targeted-displacement hypothesis was reformulated as "selective deflation." A preliminary probe had found that controls fell more than gold, indicating global drift rather than targeted displacement. (d) Three exploration-phase numbers lacking on-disk artifacts were re-measured or dropped. The 80-item baselines were re-derived from the 160-item suite, the router baseline was corrected from 0.950 to 0.938, and gate floors were re-derived (extraction 0.006, router 0.200, json 0.0125). (e) The suite was expanded from 80 to 160 items per task to improve TOST power, and frozen before the confirmatory run. (f) The GOLD_PROTECTED threshold ($X = 0.05$) was frozen before a preliminary 12-item probe existed.

Confirmatory-run phase: **Falsified:** (i) the bounded-null headline (json and router failed the ± 5 TOST); (ii) the extraction collapse at margin ≈ 3 ($0.550 \rightarrow 0.981$ under canonicalization; the measurement was killed, not refined); (iii) style margin $>$ tool_calling on held-out. Item (iii) is falsified under both backends: the prediction (style $>$ tool at every checkpoint) holds at 0/4 checkpoints under fp16 and 2/4 under nf4. Final-checkpoint per-pair ordering is backend-dependent. **Refined:** "margin-independent early drop" became a damage window at margin ≈ 1–3 with two distinct processes. "Gold absolutely stable" ($|\Delta_{\text{gold}}| \leq 0.01$, nf4) became "gold selectively protected but task-selectively deflates" (fp16 revealed json -1.04, router -1.47, extraction -0.15).

D Suite Hygiene

Source files: `data_eval/track1_{router,json,extraction}.jsonl`; leakage reference `kaggle_upload/training_data/dpo_pytorch.jsonl`; degeneracy floors `kaggle_upload/audit_eval.py:91`; gold self-consistency via `kaggle_upload/scorer.py`.

Table 11: Suite hygiene properties.

Property	extraction	json	router
n items	160	160	160
Unique prompts	160	160	160
Duplicate prompts	0	0	0
Verbatim leakage (eval $\cap$ train)	0	0	0
Gold self-consistency (gold-as-output PASS)	160/160	160/160	160/160
Degeneracy floor (always-one-answer)	$\sim$0.006	0.0125	0.20

Class balance. *router* (5 classes): COMPANY_DEEP_DIVE, FILING_ANALYSIS, FILING_DIFF, OUT_OF_SCOPE, SIMPLE_QUERY = 32 each. *json* (8 tool classes): analyst_ratings, company_metrics, company_news, diff_filing_sections, get_filing_section, insider_trades, search_filings, stock_price = 20 each. *extraction* (6 section classes): Item 1 = 27, Item 1A = 27, Item 3 = 26, Item 7 = 27, Item 7A = 26, Item 8 = 27.

Zero verbatim leakage: 0/160 eval prompts appear as a training `question` (exact-string match) for all three tasks. Gold self-consistency: 160/160 gold answers pass their own scorer. Zero duplicate prompts: 160 unique prompts / 160 items. Degeneracy floors (a constant always-one-answer policy): extraction 0.006, router 0.20 (5 balanced classes), json 0.0125 ($2/160$). Extraction golds are unique (constant-output floor $1/160 \approx 0.006$); router has 5 balanced classes ($32/160 = 0.20$); json has 18 duplicate tool-call tuples ($2/160 = 0.0125$, maximum multiplicity 2).

E Training Configuration and Hash Verification

SFT checkpoint: hash `29a3794b...585f02`, verified identical across all 8 seed runs; adapter weights loaded from `adapters/sft_pytorch/adapter_model.safetensors`. **Tokenizer and chat template:** the chat template is byte-identical across sources (SHA-256 hash comparison). For the tokenizer, tokenization is identical on all study inputs: the SFT adapter, DPO adapters, and base tokenizer configs differ in metadata (added-token count, pre-tokenizer regex) but produce identical token IDs on all 6,024 evaluation and preference strings, verified by direct token-ID comparison.

LoRA configuration: $r = 8$, $\alpha = 16$, dropout $= 0.05$; `target_modules` = [q_proj, k_proj, v_proj, o_proj] (explicitly configured, not peft default); bias = none; peft version 0.19.1. Injected layers: 3, 7, 11, 15, 19, 23, 27, 31 (the 8 full-attention layers in Qwen3.5-4B's hybrid architecture; 1.57M trainable parameters, 0.034% of 4.66B total).

Training hyperparameters: AdamW, lr $= 5 \times 10^{-5}$, constant schedule, weight_decay $= 0.01$; gradient clipping 1.0; batch size 8 (gradient accumulation); β (DPO) $= 0.5$; SFT retention weight $= 0.5$. Max optimizer steps are 180, enforced via a `matrix_kernel.py` runtime parameter. Early stop is disabled (`no_early_stop=True` via `run_matrix.py`). The divergence guard aborts if the loss is NaN or the smoothed margin exceeds 20.

Config-file note: `train_config.json` records module-level constants and does not serialize the runtime parameters `max_opt_steps` and `no_early_stop`; runtime enforcement was applied in `matrix_kernel.py` and `run_matrix.py`, confirmed by source-code inspection. All 8 seeds terminated at exactly step 180. **Checkpoint adapters on disk:** 8 seeds $\times$ 5 checkpoints $= 40$ adapter directories, all verified present with complete `adapter_model.safetensors` files.

F Reward Decomposition and Held-Out Margin Per-Seed

Source: `reward_decomposition/summary.json` (β=0.5, reference = sft_baseline). r = policy_logp − sft_logp (length-normalized); margin $= \beta \cdot (r_{\text{chosen}} - r_{\text{rejected}})$. The 8-seed-mean per-axis decomposition under both backends is in main-text Table 4; per-seed nf4 values follow.

Table 12: F.1: r_{chosen}, r_{rejected}, margin per checkpoint, per seed (nf4).

Seed	Ckpt	r_{chosen}	r_{rejected}	margin
0	margin1	−0.044	−2.087	1.021
0	margin3	−0.094	−5.569	2.738
0	margin5	−0.001	−11.016	5.508
0	final	0.051	−14.518	7.285
1	margin1	−0.082	−2.365	1.141
1	margin3	−0.060	−6.380	3.160
1	margin5	0.006	−10.146	5.076
1	final	0.055	−15.344	7.699
2	margin1	−0.039	−2.075	1.018
2	margin3	−0.063	−5.714	2.825
2	margin5	−0.033	−10.861	5.414
2	final	0.052	−15.909	7.981
3	margin1	−0.045	−2.024	0.990
3	margin3	−0.052	−5.822	2.885
3	margin5	−0.033	−9.320	4.644
3	final	0.060	−14.615	7.337
4	margin1	−0.054	−2.285	1.116
4	margin3	−0.074	−6.235	3.080
4	margin5	0.013	−8.973	4.493
4	final	0.054	−12.302	6.178
5	margin1	−0.047	−2.014	0.984
5	margin3	−0.100	−6.196	3.048
5	margin5	0.018	−9.233	4.626
5	final	0.059	−12.631	6.345
6	margin1	−0.051	−2.005	0.977
6	margin3	−0.075	−5.799	2.862
6	margin5	−0.023	−11.535	5.756
6	final	0.057	−13.346	6.701
7	margin1	−0.051	−2.052	1.001
7	margin3	−0.057	−6.206	3.074
7	margin5	0.020	−10.166	5.093
7	final	0.032	−14.890	7.461

Table 13: F.2: Per-axis margin at final checkpoint (style vs tool_calling), per seed (nf4).

Seed	style r_{ch}	style r_{rej}	style margin	tool r_{ch}	tool r_{rej}	tool margin
0	0.023	−16.560	8.291	0.113	−10.005	5.059
1	0.013	−17.726	8.870	0.147	−10.077	5.112
2	0.013	−18.820	9.417	0.139	−9.475	4.807
3	0.019	−16.696	8.358	0.149	−10.016	5.082
4	0.013	−13.536	6.774	0.147	−9.572	4.860
5	0.018	−14.142	7.080	0.149	−9.292	4.720
6	0.016	−15.118	7.567	0.148	−9.428	4.788
7	−0.019	−17.206	8.594	0.144	−9.770	4.957

Table 14: F.3: Held-out margin by category per checkpoint, per seed (fp16; 98 pairs: 69 style, 29 tool_calling; β=0.5). Under fp16, tool_calling margin exceeds style margin at all four checkpoints for all 8 seeds.

Seed	Ckpt	style margin	tool_calling margin
0	margin1	0.650	1.301
0	margin3	1.738	2.664
0	margin5	2.480	3.253
0	final	2.501	4.034
1	margin1	0.698	1.484
1	margin3	1.843	3.069
1	margin5	2.241	3.383
1	final	2.476	3.905
2	margin1	0.615	1.361
2	margin3	1.729	2.961
2	margin5	2.498	3.285
2	final	1.904	3.709
3	margin1	0.671	1.189
3	margin3	1.987	2.743
3	margin5	2.989	3.184
3	final	2.230	4.002
4	margin1	0.721	1.411
4	margin3	1.882	2.895
4	margin5	2.044	3.270
4	final	2.115	3.856
5	margin1	0.595	1.230
5	margin3	1.977	2.782
5	margin5	2.225	3.230
5	final	1.998	3.814
6	margin1	0.680	0.952
6	margin3	1.859	2.777
6	margin5	2.568	3.297
6	final	1.998	3.739
7	margin1	0.706	1.077
7	margin3	2.055	2.913
7	margin5	2.490	3.505
7	final	3.354	3.908

Table 15: F.4: Held-out per-category margin under nf4 (8-seed mean; 98 pairs: 69 style, 29 tool_calling). Tool_calling leads through margin3; style overtakes by margin5 under axis-dependent nf4 inflation.

Checkpoint	Style (nf4)	Tool (nf4)
margin1	0.780	1.466
margin3	2.620	3.426
margin5	5.435	4.020
final	7.919	4.753

Table 16: F.5: fp16 train reward decomposition, pooled per checkpoint (8-seed mean; 549 train pairs: 378 style, 171 tool_calling; β=0.5, reference = sft_baseline). Chosen dips transiently at margin3 (-0.173) before recovering; rejected falls monotonically.

Checkpoint	r_{chosen}	r_{rejected}	margin
margin1	-0.045	-1.785	0.870
margin3	-0.173	-4.661	2.244
margin5	-0.126	-5.743	2.809
final	-0.028	-5.928	2.950

G Gold-Logp Per-Seed Data, nf4 Cross-Check, and KL Trajectory

G.1 fp16 same-backend Δ_{gold} (per-seed). Source: `gold_3task_summary.json` (fp16_mac, reference = sft_baseline). Δ_{gold} = gold(final) − gold(sft), per-token length-normalized. Bracketed values are per-seed bootstrap 95% CI.

Table 17: G.1: per-seed fp16 Δ_{gold} with 95% CI.

Seed	Extraction	Json	Router
0	-0.102 $[-0.108, -0.095]$	-1.505 $[-1.581, -1.430]$	-1.259 $[-1.645, -0.902]$
1	-0.226 $[-0.232, -0.220]$	-1.177 $[-1.281, -1.074]$	-1.616 $[-2.029, -1.226]$
2	-0.147 $[-0.153, -0.141]$	-1.001 $[-1.078, -0.925]$	-1.458 $[-1.903, -1.044]$
3	-0.102 $[-0.108, -0.096]$	-0.957 $[-1.057, -0.858]$	-1.305 $[-1.723, -0.919]$
4	-0.150 $[-0.157, -0.143]$	-0.906 $[-1.001, -0.812]$	-1.915 $[-2.406, -1.451]$
5	-0.194 $[-0.200, -0.188]$	-0.761 $[-0.854, -0.671]$	-1.307 $[-1.692, -0.939]$
6	-0.138 $[-0.145, -0.131]$	-1.175 $[-1.252, -1.101]$	-1.377 $[-1.749, -1.028]$
7	-0.168 $[-0.177, -0.160]$	-0.803 $[-0.904, -0.703]$	-1.539 $[-1.999, -1.109]$

Across-seed means (8 seeds): extraction -0.153 $[-0.182, -0.126]$, json -1.036 $[-1.204, -0.891]$, router -1.472 $[-1.624, -1.345]$.

G.2 nf4 cross-check. nf4 Δ_{gold} is computed as gold_logp(final) − gold_logp(step20), using the records of the 8-seed confirmatory run; no nf4 SFT baseline gold-logp was recorded, so step20 is the earliest available reference.

Table 18: G.2: nf4 Δ_{gold} (step20→final), 8-seed mean.

Task	Δ_{gold} (nf4)	95% CI	Δ_{gold} (fp16) for comparison
Extraction	-0.008	$[-0.014, -0.003]$	-0.15
Json	-0.22	$[-0.34, -0.11]$	-1.04
Router	-1.59	$[-1.99, -1.19]$	-1.47

Table 19: G.2: per-seed nf4 Δ_{gold} (step20→final).

Seed	Extraction	Json	Router
0	-0.0089	-0.1495	-1.6280
1	-0.0134	-0.5054	-1.6686
2	-0.0089	-0.1291	-1.0105
3	-0.0004	-0.3407	-1.7108
4	$+0.0002$	-0.1034	-1.9370
5	-0.0164	-0.1119	-2.4182
6	-0.0047	-0.2077	-0.9808
7	-0.0141	-0.2485	-1.3311

The task-selective ordering (extraction $\ll$ json $<$ router) is identical under both backends, with non-overlapping CIs. Absolute magnitudes diverge, reflecting both the quantization difference and the different baselines (fp16 uses the pure SFT adapter; nf4 uses step20, which has absorbed 20 DPO steps). The divergence is itself task-selective: extraction's deflation nearly vanishes under nf4 (from -0.15 to -0.008), json compresses $\sim 5\times$, while router's magnitude is essentially unchanged.

G.3 GOLD_PROTECTED paired statistic (fp16, extraction, per-seed). Source: `gold_controls_summary.json` (fp16 unquantized, paired stat $\Delta_{\text{gold}} - \Delta_{\text{mean}(A,B)}$, reference = sft_baseline, X=0.05). GOLD_PROTECTED verdict when stat $\geq X$.

Table 20: G.3: per-seed GOLD_PROTECTED statistic.

Seed	stat	95% CI	Δ_{gold}	Δ_{ctrl} (mean A,B)	Verdict
0	0.2561	$[0.2480, 0.2644]$	-0.1016	-0.3576	GOLD_PROTECTED
1	0.2425	$[0.2348, 0.2502]$	-0.2262	-0.4687	GOLD_PROTECTED
2	0.2125	$[0.2053, 0.2198]$	-0.1470	-0.3595	GOLD_PROTECTED
3	0.2389	$[0.2316, 0.2462]$	-0.1022	-0.3411	GOLD_PROTECTED
4	0.2953	$[0.2870, 0.3038]$	-0.1502	-0.4455	GOLD_PROTECTED
5	0.2172	$[0.2108, 0.2236]$	-0.1938	-0.4110	GOLD_PROTECTED
6	0.2477	$[0.2403, 0.2553]$	-0.1379	-0.3856	GOLD_PROTECTED
7	0.2666	$[0.2574, 0.2756]$	-0.1684	-0.4350	GOLD_PROTECTED

Aggregate: 8/8 seeds GOLD_PROTECTED.

G.4 KL(policy $\|$ reference) trajectory.

Table 21: G.4: KL trajectory (extraction gold, fp16, 8-seed mean $\pm$ std).

Checkpoint	Mean KL	Std
margin1	0.022	0.005
margin3	0.057	0.017
margin5	0.083	0.014
final	0.082	0.008

KL rises monotonically through margin5 then plateaus ($0.083 \rightarrow 0.082$), confirming mild policy drift (all values < 0.1 nats/token) that saturates as margin continues to grow from $\sim$5 to $\sim$7. KL is computed on extraction gold completions only; drift on other tasks may be larger. Per-seed KL at final: seed0 $= 0.071$, seed1 $= 0.089$, seed2 $= 0.081$, seed3 $= 0.075$, seed4 $= 0.077$, seed5 $= 0.092$, seed6 $= 0.077$, seed7 $= 0.093$.

H Validation Margin Trajectories

Source: `track1_dpo_seed*_margin.jsonl`. `val_margin` is logged only at the evaluation cadence (`eval_every` $= 50 \rightarrow$ steps 50, 100, 150); it is not recorded at the checkpoint steps. The table reports every logged val_margin step.

Table 22: Validation margin at logged steps, with intermediate checkpoint steps for reference.

Seed	val@50	val@100	val@150	(margin1 step)	(margin3 step)	(margin5 step)
0	1.701	3.534	5.752	27	84	134
1	1.648	3.091	5.904	29	93	131
2	1.685	3.618	5.746	26	87	124
3	1.660	3.506	7.397	28	90	112
4	1.701	3.483	6.449	30	91	130
5	1.804	3.502	4.968	24	87	135
6	1.743	3.522	6.709	27	88	138
7	1.528	3.288	5.768	26	98	135

The 8-seed mean val_margin at step 150 is 6.087 (rounds to 6.1).

Val-subset note. The training-time `val_margin` logged in the margin files is computed over a fixed 20-pair subset (15 style, 5 tool_calling) of the 98 held-out pairs under the nf4 training backend, not the full 98-pair set. Post-hoc fp16 recomputation on the same 20 pairs yields a mean of 2.987 at the final checkpoint, versus 7.519 under nf4: a $2.52\times$ backend ratio. The logged `val_margin` values are therefore not comparable to the fp16 held-out margins in Table 14.