

CSC 33200 (L) - Operating Systems – Fall 2021

Lab 2: Process Management System Calls

Date: 09/17/2021

Process

- A process is basically a single running program
- Each running process has a unique number - a process identifier, pid (an integer value)
- Each process has its own address space
- Processes are organized hierarchically. Each process has a **parent** process which explicitly arranged to create it. The processes created by a given parent are called its **child** processes
- The C function **getpid()** will return the pid of process
- A child inherits *many* of its attributes from the parent process
- The UNIX command **ps** will list all current processes running on your machine and will list the **pid**
- **Remark:** When UNIX is first started, there is only one visible process in the system. This process is called init with pid 1. The only way to create a new process in UNIX is to duplicate an existing process, so init is the ancestor of all subsequent processes

Process Creation

- Each process is named by a process ID number
- A unique process ID is allocated to each process when it is created
- Processes are created with the fork() system call (the operation of creating a new process is sometimes called forking a process)
- The fork() system call does not take an argument
- If the fork() system call fails, it will return -1
- If the fork() system call is successful, the process ID of the child process is returned in the parent process and a 0 is returned in the child process
- When a fork() system call is made, the operating system generates a copy of the parent process which becomes the child process
- Some of the specific attributes of the child process that differ from the parent process are:
 - The child process has its own unique process ID
 - The parent process ID of the child process is the process ID of its parent process
 - The child process gets its own copies of the parent process's open file descriptors. Subsequently changing attributes of the file descriptors in the parent process won't affect the file descriptors in the child, and vice versa
 - When the lifetime of a process ends, its termination is reported to its parent and all the resources including the PID is freed.

Example of fork() system call structure

Here a process P calls `fork()`, the operating system takes all the data associated with P , makes a brand-new copy of it in memory, and enters a new process Q into the list of current processes. Now both P and Q are on the list of processes, both about to return from the `fork()` call, and they continue.

The `fork()` system call returns Q 's process ID to P and 0 to Q . This gives the two processes a way of doing different things. Generally, the code for a process looks something like the following.

```
int child = fork();
if(child == 0)
{
    //code specifying how the child process Q is to behave
}
else
{
    //code specifying how the parent process P is to behave
}
```

Process Identification

- You can get the process ID of a process by calling `getpid()`
- The function `getppid()` returns the process ID of the parent of the current process
- Your program should include the header files `unistd.h` and `sys/types.h` to use these functions

`waitpid()` System Call

- A parent process usually needs to synchronize its actions by waiting until the child process has either stopped or terminated its actions
- The `waitpid()` system call gives a process a way to wait for a process to stop. It's called as follows.

```
pid = waitpid(child, &status, options);
```

In this case, the operating system will block the calling process until the process with ID `child` ends

- The `options` parameter gives ways of modifying the behavior to, for example, not block the calling process. We can just use 0 for `options` here.
- When the process `child` ends, the operating system changes the `int` variable `status` to represent how `child` passed away (incorporating the exit code, should the calling process want that information), and it unblocks the calling process, returning the process ID of the process that just stopped.
- If the calling process does not have any child associated with it, `wait` will return immediately with a value of -1

Pipe

pipe() creates a pipe, a unidirectional data channel that can be used for interprocess communication. The array `pipefd` is used to return two file descriptors referring to the ends of the pipe.

`pipefd[0]` refers to the read end of the pipe. `pipefd[1]` refers to the write end of the pipe. Data written to the write end of the pipe is buffered by the kernel until it is read from the read end of the pipe.

TASK 2. Marks: 20

1. Write a program ***children.c***, and let the parent process produce two child processes. One prints out **"I am child one, my pid is: " PID**, and the other prints out **"I am child two, my pid is: " PID**. Guarantee that the parent terminates after the children terminate (Note, you need to wait for two child processes here). Use the `getpid()` function to retrieve the PID.

2. Consider the parent process as P. The program consists of `fork()` system call statements placed at different points in the code to create new processes Q and R. The program also shows three variables: `a`, `b`, and `pid` - with the print out of these variables occurring from various processes. Show the values **of pid, a, and b printed by the processes P, Q, and R.**

```
//parent P
int a=10, b=25, fq=0, fr=0
fq=fork()    // fork a child - call it Process Q
if(fq==0)    // Child successfully forked
    a=a+b
    print values of a, b, and process_id

    fr=fork() // fork another child - call it Process R
    if(fr!=0)
        b=b+20
        print values of a, b, and process_id

    else
        a=(a*b)+30
        print values of a,b and process_id
else
    b = a+b -5
    print values of a, b, and process_id
```

3. Consider a series, $S_1 = 2 + 4 + 6 + \dots + 10$ and another series $S_2 = 1 + 3 + 5 + \dots + 9$. and Another series $S_3 = 1 + 2 + 3 + \dots + 10$.

We know that $S_1 + S_2 = S_3$.

Now write a program, where a parent process creates 2 child process and computes S_1 and S_2 . And Parent process computes S_3 . The input argument for program will be the end of series number for S_3 .

For example, if the execution file name is series.exe then, the argument will be
./series.exe 10

Child 1 will compute the series from 1 to upto 10 with difference 2. So, it would be $1 + 3 + 5 + 7 + 9$
Child 2 will compute the series from 2 to upto 10 with difference 2. So, it would be $2 + 4 + 6 + 8 + 10$

Parent will compute the series from 1 to 10 with difference 1. So, it would be,
 $1 + 2 + 3 + 4 + 5 + 6 + 7 + 8 + 9 + 10$

please show intermediate steps computed by children and parent.

4. Open a file called readme.txt in the child process, read the contents and pass to the parent process. Parent process will write to readme.txt, "Parent is writing:" and write the contents it received from the child to the readme.txt file. (Hint: Use Pipe)

Submission Instructions

- All the programs MUST be clearly indented and internally documented
- Make sure your programs compile and run without any errors
- Save all your programs with meaningful names and zip into a single folder as: task2_[your last name here].zip (e.g., task2_Xyz.zip)
- Email your code with the subject line, "Task2-CSC33200(L)-Class# 12345-lastname" (e.g., Task2 - CSC33200(L)-Class #63858-Xyz)
- Email: sdebnath@ccny.cuny.edu

Office Hours: Thursday 10:00 – 11:00 pm

Join Zoom Meeting

<https://ccny.zoom.us/j/85722468391?pwd=RG9sREJ2WUVBMzhsOWp6eWZHTmE3QT09>

Meeting ID: 857 2246 8391

Passcode: 561041

One tap mobile

+16465588656,,85722468391# US (New York)

+13126266799,,85722468391# US (Chicago)

Dial by your location

+1 646 558 8656 US (New York)

+1 312 626 6799 US (Chicago)

+1 301 715 8592 US (Washington DC)

+1 669 900 6833 US (San Jose)

+1 253 215 8782 US (Tacoma)

+1 346 248 7799 US (Houston)

Meeting ID: 857 2246 8391

Find your local number: <https://ccny.zoom.us/j/kek94YYHZu>

IMPORTANT NOTE: Please connect with zoom with a valid CCNY or CITYMAIL email id. Please sign up with the CITYMAIL or CCNY email address at :

<https://www.ccny.cuny.edu/it/zoom>