



**UNIVERSITY OF MARYLAND**  
Department of Fire Protection Engineering



## Performance-Based Approach to Fire Safety Design

A. JAMES CLARK SCHOOL of ENGINEERING • UNIVERSITY of MARYLAND

---

---

---

---

---

---

---

---



**Performance Based Approach**



- Introduce Concept
- Discuss Elements
  - Goals
  - Assessments
  - Designs
- Example Applications
- Choosing Appropriate Design



---

---

---


---

---


---

---

---



**What is Performance Based Design (PBD)?**



- Evaluation of Hazard or Risk based on defined goals
- Scenario specific
  - Fires
  - Building
  - Occupants
- Hazard-Consequences
- Risk-Consequences X Probability

---

---

---


---

---

---

---

---




---

---

---


---

---

---

---

---




---

---

---

---

---



---

---

---

### How is it different from code?

- Based on Fire Risk/Hazard Assessment Evaluation
- Evaluates specific building or structure

---

---

---

---

---



---

---

---

### Why use PBD?

- Prescriptive code not feasible
- Based on system performance
- Addresses project specific needs

---

---

---

---

---

---

---

---

### Develop Performance Goals

**Life Safety:**

- Protect occupants not intimate with fire for time needed to evacuate

**Building Structure:**

- Minimize damage to major structural elements

**Building Appearance:**

- Minimize impact of strategies on architectural features and openness of galleries

**Facility Operations:**

- Minimize undue loss of operations due to fire
- Prevent damage from fire to critical equipment




---

---

---

---

---


---

---

---

### Example of Life Safety Performance

- Performance Criteria: Maintain visibility of >10 m



- CO / COHb
- Temperature
- Structural Integrity

Egress Time + Safety Factor < Time to Hazardous Conditions

---

---

---


---

---

---

---

---




---

---

---


---

---

---

---

---




---

---

---

---

---

---

---

---

### Perform Fire Risk Assessment

Frequency →	Beyond extremely unlikely $f < 10^{-6}$ (1 in 1,000,000)	Extremely unlikely $10^{-6} < f < 10^{-5}$ (1 in 100,000)	Unlikely $10^{-5} < f < 10^{-4}$ (1 in 10,000)	Anticipated $f > 10^{-4}$ (1 in 1,000)
Extreme		7	4	1
High	16	6	3	2
Moderate		9	6	3
Low	11		12	

• Apply to each fire scenario.

• Determine relative fire risk.

• Evaluate for Trial Designs.

■ "High" risk

■ "Moderate" risk

■ "Low" risk

"Negligible" risk

---

---

---


---

---

---

---

---




---

---


---

---

---

---

---




---

---

---

---

---

---

---