How Many Remain at Scale ε?

The Dimensional Focal Point of a Corpus Point Map,

its Projection to the PCA Sphere, and the Deployed Map under its own Diagnostics

Shant Tchatalbachian

November 10, 2026 (v1) — revised November 10, 2026 (v2: live-deployment diagnostics)

Abstract

Three short exchanges (2026-11-07) asked one question in three registers: cardinality, measure, summation and resolution are different kinds of "infinity"; for data in an N-dimensional vector space, how many *distinguishable* elements remain at scale ε and at dimension N? This paper answers the question for a real, deployed object — point map #598 of the steady-orbit console, a frozen-frame `pointmap/0.2` map of the harness experience library — and turns the answer into an automatic rule. (i) **Recovery.** The map's 3,232 inputs are recovered exactly from its stored per-axis margins; re-running the repository instrument reproduces the stored `frame_id`, `instrument_id` and `run_fingerprint`. The inputs are binary: the corpus lives on the vertices of $\{0,1\}^9$. (ii) **Four sizes.** The same corpus has 3,232 items, 135 distinct patterns, 116 classes distinguishable by the deployed bit rule, and a Rényi spectrum $D_0/D_1/D_2 = 7.077/6.606/6.265$ bits; on a binary cube at lattice resolution, $\log_2 N$ *is* an effective dimension. (iii) **The dimensional focal point.** Keeping only projection axes that add at least half a bit of distinguishability at lattice scale selects $n^\star = 7$ for every Rényi order, robustly for any threshold in $(0.055, 0.722)$ bits. The knee is set by marginals — two primitives are present in 98.7% and 99.8% of items, and both fixed-margin nulls reproduce it — while the residual is the corpus's own: the eighth axis adds 0.055 bit against 0.340 ± 0.026 under the curveball null ($z = -11.0$), and at $n^\star$ the information and collision dimensions sit 15.2 and 12.3 null SDs below chance. (iv) **Certified resolution.** Using the instrument's own half-space certificates (kernel-checked in `WayfinderBounds`), most of the 37 classes contributed by the two discarded axes cease to be certifiably distinct under an ℓ_∞ input perturbation of 0.014 (1.4% of the unit input range). (v) **Projection to the PCA sphere.** The focal coordinates are lifted to S^2 with the program's own pipeline; the stereographic scale is identified as the lens power of the series' Möbius chart, and the RMS rescale already used by the curved-corpus program attains at least 95% of the best resolved count on both globes, while the deployed `0.9/maxR` rule under-powers the focal globe by a factor 2.4 and roughly halves its resolved count. The focal globe keeps all 135 patterns and is more faithful to the focal geometry (Spearman 0.438 vs 0.314), but resolves fewer positions at the canonical chord 0.095 (61 vs 79); the trade-off is reported, not resolved. (vi) **The real maps under the live diagnostics.** The six instruments of the console's Map card → diagnostics sub-tab were run against the live deployment with operator authentication, and from repository source. The API stores three maps. The live record of #598 equals the recovered map (margins identical), and its three stored instruments reproduce exactly. The four HTTP trials operate on maps with $N \le 1200$, so on #598 they were run on a seeded subsample; on the two smaller stored maps (#595, #596) all four trials run in full on the live endpoint and agree with repository source on all 4,461 returned fields (maximum numeric difference 1.9×10^{-14}). On that subsample, run from source, the axis-redundancy trial independently flags axes 8 and 9 as the two most predictable bits. Applied to the bit ladder of every stored map, the focal rule gives $n^\star = 7$ on #598 against 9 under the null, while on #595 and #596 it sits at the sample ceiling $\log_2 n$ and cannot be separated from the null. (vii) Nineteen exact counting identities — refinement by one bit never merges classes and at most doubles them, $\le 2^d$, and the focal selection rule — are proved in core Lean 4 and pass every gate of the series' CI.

1 Introduction

The curved-corpus program has measured corpora by their concentration (V_2), their curvature against matched nulls, their optics and their diffusion (Tchatalbachian, 2026a,b,c). It has not yet asked the most elementary question one can ask of a finite map: *how many things are on it?* The question is less trivial than it looks. On 2026-11-07 three short exchanges with a general-purpose assistant posed it in sequence. The first asked for the state of the art on a "fluid" transition between finite and infinite sets and received the standard decomposition: cardinality, measure, summation and resolution count different things, and the useful substitution is to replace exact membership by observational resolution — "ask how many distinguishable elements remain at scale ε". The second carried the substitution to $\mathbb{R}^N$: packing and covering numbers $P_\varepsilon, C_\varepsilon \sim (L/\varepsilon)^N$, metric entropy $\log_2 C_\varepsilon \approx N \log_2(L/\varepsilon)$, and, for constrained data, an effective (box-counting) dimension in place of N. The third surveyed the mathematical theory of box-counting dimension. Those transcripts are the seed of this paper; their citations were independently re-verified before use (Section 9), and one of their formulas is corrected below.

This paper does four things. It **recovers** a deployed map exactly and shows that its inputs are binary, which makes every count in the transcripts exact rather than asymptotic (Section 3). It **defines** a dimensional focal point — the projection dimension at which a corpus is resolved, chosen automatically and null-standardized — and applies it (Section 4). It **projects** the focused map to the PCA sphere with the program's own pipeline and identifies the lift scale as the lens power of the series' optical reading (Section 6). And it **audits** every map stored on the deployment with the console's own diagnostics tab, on the live API and from source (Section 7). Counting identities are machine-checked (Section 8); scope and caveats close.

The disciplines of the 2026-08-12 paper (Tchatalbachian, 2026b) are inherited verbatim: no statistic without its matched null, no coordinate admitted without a non-degenerate null, verdicts are exclusion-only, and every number is quoted from a stored artifact.

2 Four sizes of a finite corpus

Let $X = \{x_1, \dots, x_M\} \subset \mathbb{R}^D$ be a corpus with multiplicities and π_n the projection onto its top-n principal axes. Four quantities are in play.

Definition 1 (Sizes)**.** Cardinality M *(items, with multiplicity);* distinct count $|\{x_i\}|$*;* resolution count $N(\varepsilon, n)$*, the size of a maximal ε-separated subset of $\pi_n(X)$ (a packing; the greedy construction used here is maximal, hence bracketed by covering numbers, $C_\varepsilon \le N(\varepsilon, n) \le C_{\varepsilon/2}$, Kolmogorov & Tikhomirov, 1959); and the* measure-weighted *sizes 2^{D_q}, where $D_q(\varepsilon, n)$ is the Rényi entropy of order q of the item distribution over the cells of that packing,*

$$D_0 = \log_2(\#\,cells), \qquad D_1 = -\sum_c p_c \log_2 p_c, \qquad D_2 = -\log_2 \sum_c p_c^2. \tag{1}$$

D_0 counts, D_1 weights by measure, D_2 is a collision (correlation) count; they are the finite-scale members of the generalized-dimension family (Hentschel & Procaccia, 1983; Grassberger & Procaccia, 1983) and satisfy $D_2 \le D_1 \le D_0$. For a finite set every box-counting dimension is 0 in the limit $\varepsilon \to 0$ (Falconer, 2014); dimension is therefore a property of a *scale window*, which is exactly the transcripts' point that infinity becomes "a scale-dependent growth law".

A correction to the seed formula. The second exchange counts the ε-grid of $[0, L]^N$ as $(\lceil L/\varepsilon \rceil + 1)^N$; the number of grid points with spacing ε in $[0, L]$ is $\lfloor L/\varepsilon \rfloor + 1$, and the asymptotic $C_\varepsilon \sim P_\varepsilon \sim (L/\varepsilon)^N$ hides N-dependent constants ($\log C_\varepsilon = N \log(L/\varepsilon) + O(N \log N)$), which matter at N of embedding size. Neither affects what follows, because on a binary cube the lattice count is exact:

Proposition 1 (Lattice resolution on the cube)**.** *If $X \subseteq \{0,1\}^d$ and $\varepsilon < 1$, distinct points are ε-separated in the Euclidean metric, so $N(\varepsilon, d) = |\{x_i\}|$ and $D_0 = \log_2 |\{x_i\}| \le d$, with equality iff every vertex is occupied. Hence D_0 at lattice resolution is an effective dimension in bits, and the per-axis gain $\Delta D_0(n) = D_0(n) - D_0(n-1)$ is the number of bits the n-th axis contributes.*

Related work. Packing and box-counting dimension go back to the metric-entropy programme of Kolmogorov & Tikhomirov (1959) and to the packing measures of Tricot (1982); textbook treatments are Falconer (2014), Mattila (1995) and Federer (1969). Three lines are directly relevant here. (i) *Projections:* box and packing dimensions are not preserved by orthogonal projection, and their almost-sure values under projection are governed by dimension profiles (Falconer & Howroyd, 1996, 1997); the focal rule is an empirical, finite-scale analogue, which asks how many projection axes a finite corpus needs before further axes stop adding resolution. (ii) *Interpolation between dimensions:* intermediate dimensions (Falconer et al., 2020), the dimension spectra of Fraser & Yu (2018), Minkowski dimension for measures (Falconer et al., 2023) and the survey of Fraser (2026) all replace a single exponent by a profile over scales. That is the stance taken here, where dimension is read off a scale window rather than a limit. (iii) *Intrinsic dimension in machine learning:* estimators based on packing numbers (Kégl, 2002), nearest-neighbour likelihood (Levina & Bickel, 2004), two-nearest-neighbour ratios (Facco et al., 2017) and correlation sums (Grassberger & Procaccia, 1983) are reviewed by Camastra & Staiano (2016). Random projections preserve pairwise distances up to $1 \pm \epsilon$ in $O(\epsilon^{-2} \log M)$ dimensions (Dasgupta & Gupta, 2003), and effective data dimensionality controls the learning rates of kernel regression (Zhang, 2005). The first exchange's "fluid" passage from finite to infinite through hyperfinite sets is the province of non-standard analysis (Robinson, 1966); it is not used here.

3 The deployed map, recovered exactly

Map #598 is stored in the console's KV namespace as `map-json:598` (5.37 MB). It is a `pointmap/0.2` frame (rule R0: frozen top-d PCA axes, bit $b_j = [\, s_j > \text{median}_j \,]$, then z-score, PCA-2 and stereographic lift to S^2) over $M = 3{,}232$ items of the corpus `harness/experience-library` (knowledge, skills, docs, playbooks), with $d = D = 9$, seed 20260906, $K = 200$ null draws.

The raw vectors are not stored, but every item's signed margin $m_{ij} = s_{ij} - \theta_j$ against each frozen threshold is (field `math_diagnostics.per_input`). Hence $s_{ij} = m_{ij} + \theta_j$ and $x_i = \mu + s_i^\top A$ with the stored orthonormal axes A ($\|AA^\top - I\|_\infty = 1.8 \times 10^{-15}$). Four checks make the recovery exact: the recomputed bits equal the stored bits on all $3{,}232 \times 9$ entries; the stored thresholds equal the sample medians of the recovered scores; the deployed placement applied to the recovered bits reproduces `pts_full` to machine precision; and running the repository's unmodified `pointmap.js` on the recovered vectors reproduces `frame_id 77360296af046f8d`, `run_fingerprint fba40c7b482d4e2e`, $V_2 = 0.39573$ and the null $z = 70.36$. The recovered inputs take exactly two values per coordinate: **the corpus is a multiset on the vertices of** $\{0,1\}^9$, a nine-primitive coverage code like the program's 2286×9 matrix.

4 The dimensional focal point

Proposition 1 turns the transcripts' question into a curve. Project the binary corpus onto its top-n PCA scores, $n = 1, \ldots, 9$, and count distinguishable cells at the lattice scale $\varepsilon_{\text{lat}} = 0.9$ (below the unit edge of the cube; above it, vertices merge). Each added axis either splits cells, contributing up to one bit, or does not.

size of map #598	value
cardinality (items)	3,232
distinct input patterns (of 512)	135
classes distinguishable by the deployed bit rule ($d = 9$)	116 (largest 128; 74,064 unresolvable pairs)
distinct top-d bit prefixes, $d = 1, \ldots, 9$	$2, 4, 8, 16, 30, 49, 79, 95, 116$
Rényi $D_0/D_1/D_2$ of exact patterns (bits)	7.077/6.606/6.265
Rényi $D_0/D_1/D_2$ of deployed classes (bits)	6.858/6.399/6.109

Table 1: The four sizes of the same corpus. The deployed rule (rotate to PCA, then cut at medians) resolves 19 fewer elements than the data contain even at full dimension, because median hyperplanes on rotated axes do not align with the facets of the cube. Source: recovered map #598; `focal/numbers.json`.

Definition 2 (Dimensional focal point)**.** *For a Rényi order q and threshold τ, the focal dimension is*

$$n_q^\star(\tau) = \max\{\, n : \ \Delta D_q(n') \geq \tau \text{ for all } n' \leq n \,\}, \qquad \Delta D_q(n) = D_q(\varepsilon_{\text{lat}}, n) - D_q(\varepsilon_{\text{lat}}, n-1), \quad (2)$$

the largest prefix of axes each of which still adds at least τ bits. The default is $\tau = \frac{1}{2}$ bit: an axis is kept if it at least halves the typical cell in the q-weighted sense. The rule is automatic — no scale, no target count, and no label enters it.

axis n	1	2	3	4	5	6	7	8	9
$\Delta D_0(n)$, real	1.585	1.000	0.737	1.000	0.722	0.956	1.000	0.055	0.022
$\Delta D_1(n)$, real	1.100	1.002	0.842	0.939	0.694	0.928	1.063	0.031	0.007
$\Delta D_0(n)$, curveball mean ($K = 20$)	1.585	1.029	0.768	0.692	0.841	1.084	0.990	0.340	0.057

Table 2: Bits contributed by each PCA axis at lattice scale. The first seven axes each add at least 0.722 bit; the eighth and ninth add 0.055 and 0.022. Under the margin-preserving curveball null the knee is also at seven, but the eighth axis adds 0.340 bit.

Result. With $\tau = \frac{1}{2}$, $n_0^\star = n_1^\star = n_2^\star = 7$ (Table 2, Figure 1). The choice is stable for every $\tau \in (0.055, 0.722)$ bits for D_0 and $(0.031, 0.694)$ for D_1, which together cover two orders of magnitude of threshold. The reason is visible in the loadings: axes 8 and 9 carry variances 0.0125 and 0.0018 against ≥ 0.1449 for the others, and load 0.98 and 0.98 on two input primitives that are present in 98.7% and 99.8% of items (43 and 7 items lack them). The remaining seven primitives occupy all $2^7 = 128$ of their joint patterns, and at $n^\star$ the lattice count is exactly $N(\varepsilon, 7) = 128$ for every $\varepsilon \in [0.074, 0.942]$ — a plateau that is descriptive, not the selection criterion.

Null standardization. The knee itself is a property of the marginals: both fixed-margin nulls, the curveball chain (Carstens, 2015), as used in the 2026-08-12 paper (Tchatalbachian, 2026b), and an independent column permutation, also select $n^\star = 7$. What is *not* a property of the marginals is how little the corpus does beyond the knee and how unevenly it fills the focal cube:

- the eighth axis adds 0.055 bit against 0.340 ± 0.026 (curveball, $K = 20$, $z = -11.0$) and 0.342 ± 0.021 (column permutation, $K = 50$, $z = -13.4$): the rare primitives co-occur with patterns that already exist instead of creating new ones;




Figure 1: Distinguishability versus resolution and dimension. (a) $\log_2 N(\varepsilon, n)$ in the top-n PCA projection for $n = 1, \ldots, 9$; the dotted line is the lattice scale $\varepsilon_{\text{lat}} = 0.9$, and at $n^\star = 7$ the count is exactly $128 = 2^7$ on $[0.074, 0.94]$. (b) Per-axis gain ΔD_0 (filled) and ΔD_1 (open) against the fixed-margin curveball null (mean ±2 sd, 20 draws); axes in the shaded band fall below the $\frac{1}{2}$-bit rule. Source: `renyi.npz`.

- at $n^\star = 7$, $D_0/D_1/D_2 = 7.000/6.568/6.240$ against null $6.990/6.634/6.334$ ($z = +2.3/-15.2/-12.3$): every cell is occupied, but the occupancy is far more concentrated than the marginals imply;
- at $n = 9$ the corpus has 135 distinct patterns against 167.5 (curveball) and 168.9 (column permutation); D_0 $z = -12.4$.

The focal point thus separates two things the deployed map conflates: *how many dimensions the corpus uses* ($n^\star = 7$, a marginal fact) and *how it uses them* (strongly non-random, $z \approx -12$ to -15).

5 Certified distinguishability

The deployed instrument distinguishes items by signs of margins m_{ij}. The series' `WayfinderBounds` module proves that a half-space verdict is stable under any perturbation δ with $|\langle a, \delta\rangle| < |m|$ (lemmas `stable_on`/`stable_off`); for $\|\delta\|_\infty \le \varepsilon$ this holds whenever $|m_{ij}| > \varepsilon \|a_j\|_1$. Call two classes *certifiably distinct at* ε if they differ on a bit whose margin is certified for both items. A greedy maximal family of pairwise certifiably distinct classes gives a lower bound on the robust class count.

ε	0.0000	0.0016	0.0137	0.0568	0.0721	0.0914
$d = 9$ (deployed)	114	94	77	53	44	37
$d = 7 = n^\star$	77	76	69	49	44	37

Table 3: Lower bounds on certifiably distinct classes under an ℓ_∞ input perturbation ε (greedy, hence lower bounds). The median $|m|$ on axes 8 and 9 is 0.0240 and 0.0017, against 0.32–0.46 on axes 1–7.

At $\varepsilon = 0$ the two discarded axes contribute 37 extra classes; by $\varepsilon = 0.0137$ only 8 remain, and the two curves meet near $\varepsilon \approx 0.07$ (Figure 2). The classes the focal rule discards are, for




Figure 2: Certified class counts (greedy lower bounds) at $d = 9$ and $d = n^\star = 7$ versus ℓ_∞ input perturbation, on a logarithmic axis from $\varepsilon = 10^{-3}$. The dotted line is the 116 classes of the stored map; at $\varepsilon = 0$ the strict-margin certificate gives 114 and 77 (Table 3). The shaded gap is the contribution of axes 8–9; at $\varepsilon = 0.0137$ it is 77 vs 69. Source: `robust.npz`.

the most part, the classes a 1.4% perturbation of the input would erase.

6 Projection to the PCA sphere

The focal coordinates are mapped to S^2 with the program's own placement: z-score, PCA-2 and the stereographic lift $(u, v) \mapsto \big(2su, 2sv, 1 - s^2r^2\big)/(1 + s^2r^2)$, $r^2 = u^2 + v^2$. The *focal globe* places the continuous top-$n^\star$ scores; the *deployed globe* places the 9 bits. The top two PCs of the focal coordinates carry 28.6% of their variance.

Lens power. For points of the plane, s acts as a dilation, and dilation by s composed with inverse stereographic projection is a Möbius transformation of S^2; s is therefore the power of the series' Möbius lens. Three powers are compared: the deployed rule $s = 0.9/\max r$, the RMS rescale $s = 1/\mathrm{RMS}(r)$ of the curved-corpus paper, and the focal power $s^\star$ that maximizes $N(0.095)$, the number of positions distinguishable at the canonical chord used by every diagnostic of the console.

The trade-off is genuine and is reported rather than resolved. The deployed globe resolves more positions at 0.095 (79 vs 61 at RMS power), because bits are well-separated by construction. The focal globe keeps every one of the 135 input patterns as a distinct position, preserves the focal geometry better ($\rho = 0.438$ vs 0.314), and resolves 133 positions at chord 0.02 against 94. The RMS rescale attains 99% and 95% of the best count on the two globes; the deployed $0.9/\max r$ rule attains 52% on the focal globe, because a few outlying patterns set $\max r$. RMS is therefore the recommended automatic power.

globe	distinct positions	$N(0.095)$ at $s =$ $0.9/\max r$	RMS	$s^\star$	$N(0.02)$	isolated	Spearman ρ vs focal
deployed (bits, $d = 9$)	116	75	79	80	94	2	0.314
focal ($n^\star = 7$ scores)	135	33	61	64	133	0	0.438

Table 4: The two globes. Powers: deployed $s = 0.34/0.53/0.75$, focal $s = 0.38/0.71/0.90$ (maxR/RMS/$s^\star$). Spearman correlation of chord distances with distances in the seven-dimensional focal space, on a fixed random subsample of pairs. Isolated: positions with no neighbour within chord 0.095.




Figure 3: Projection to the PCA sphere. (a) The deployed globe as served ($s = 0.9/\max r$). (b) The focal globe at RMS lens power. Markers show the dominant corpus section at each position, area proportional to items; equal-area view, dotted circle the equator; ρ is the Spearman correlation with seven-dimensional focal distances. (c) $N(0.095)$ against lens power s/s_{RMS} for both globes; ▼ marks $0.9/\max r$, • the RMS rescale and $\star$ the best power $s^\star$. Source: `lens_scan.npz`, `globes.npz`.

7 The real map under its own diagnostics

The console's Map card has a diagnostics sub-tab that drives six instruments: spectroscopy, radius profile and the V_2 null, which are computed at map time and stored with the map, and four HTTP trials (`/api/jev/map/{azimuth, rayleigh, admission, axis-redundancy}`). All six were run from repository source (`tools/point-map`) against map #598 and the $d = n^\star$ re-map, and the four trials were also run against the live deployment (`steady-orbit` worker, 2026-11-10) with the operator bearer key. The live listing `GET /api/jev/map/maps` returns three maps. The map fold rewrites that path to the `/api/maps` handler, which in the deployed source selects every row with no `LIMIT` or pagination, and the live response carries exactly that query's 15 columns. The three maps are #598 (`harness/experience-library`, $n = 3{,}232$, $D = 9$), #596 (`policy/jev-policy.json`, $n = 52$, $D = 768$, `bge-base` text embeddings) and #595 (`harness/skills`, $n = 135$, $D = 768$). The live record of #598 has the stored `frame_id` and `run_fingerprint`, and its per-item margins equal the recovered ones exactly (maximum absolute difference 0). It differs from the KV backup only in that the read path decodes the compact `margin-tuples/1` storage encoding.

Parity. The three stored instruments reproduce the stored map exactly: spectroscopy, radius profile and null agree with maximum absolute difference 0.

Operating range of the four trials. The trials are $O(N^2 dK)$ and are defined for maps with $N \leq 1200$ (`AXIS_TRIAL_MAX_N`), identically on the live deployment and in repository source. At $N = 3{,}232$ the real map — the one the console exists to diagnose — lies outside that range. The live API offers no subsample route, and submitting a subsample as a new map would persist a map row, so the subsample was run from source. Each trial was run on one seeded subsample of 1200 items (mulberry32, seed 20261110). These results are provisional: they describe that subsample, not the map.

The live trials on the stored maps that fit. Maps #595 and #596 are below the cap, so all four trials run in full on the live endpoint (Table 5). Repository source, run on the live map records, returns the same results on every one of the 4,461 fields of the eight responses, with identical field sets and a maximum numeric difference of 1.9×10^{-14} (float round-off). For the diagnostics code path, the deployment and the repository are therefore equivalent on every map the deployment can run.

	#595 `harness/skills`	#596 `policy`
N (all items; no subsample)	135	52
rayleigh components (null mean ± sd)	88 (89.1 ± 4.71)	36 (44.2 ± 2.59)
rayleigh z / isolates (null mean)	-0.23 / 60 (59.9)	-3.16 / 25 (37.4)
axis redundancy: excluded axes (total z)	2, 7 (3.26)	3, 4, 5, 6, 8 (4.58)
axis-trial admission blocked by	seed reproducibility	seed reproducibility, $N < 100$
admitted: rayleigh, axis, spectra, radius, azimuth	T, F, T, T, F	F, F, F, F, F

Table 5: The four live trials on the two stored maps below the cap (live endpoint, operator key, default $K = 40$). Every value equals the repository-source result. Azimuth is not admitted on either map: its de-atomized null is not size-matched and its Holm verdicts are not reproducible across seeds.

The focal rule on every stored map. Definition 2 needs only a ladder of distinguishable counts, so it applies to the deployed bits of every map. The top-d bit-prefix count is the D_0 ladder of the instrument itself, and its gains are exact by `FocalBounds` ($N_d \leq N_{d+1} \leq 2N_d$). The null is a curveball chain on each map's bit matrix (20 draws, $100n$ trades), which preserves the near-balanced median-split columns.

map (n)	$\Delta D_0(d)$ of the bit ladder, $d = 1, \ldots, 9$									$n^\star$	null $n^\star$	$\log_2 n$
#598 (3,232)	1.000	1.000	1.000	1.000	0.907	0.708	0.689	0.266	0.288	7	9	11.66
#595 (135)	1.000	1.000	1.000	1.000	0.954	0.746	0.585	0.254	0.216	7	6–7	7.08
#596 (52)	1.000	1.000	1.000	0.807	0.716	0.334	0.312	0.152	0.170	5	5–6	5.70

Table 6: The focal rule ($\tau = \frac{1}{2}$ bit) on the deployed bit ladder of each stored map. Ladders: #598 2, 4, 8, 16, 30, 49, 79, 95, 116; #595 2, 4, 8, 16, 31, 52, 78, 93, 108; #596 2, 4, 8, 14, 23, 29, 36, 40, 45. Class counts at $d = 9$ against the null: #598 $z = -160.5$, #595 $z = -4.8$, #596 $z = -4.4$.

On #598 the bit ladder independently gives $n^\star = 7$, the same focal point as the lattice rule of Section 4. At the bit level the knee is corpus-specific: the null on the balanced deployed bits fills every axis ($n^\star = 9$), and the real map has 116 classes against a null mean of 504. On #595 and #596 the rule returns $n^\star = 7$ and 5, but their nulls return 6–7 and 5–6. With $n = 135$ and 52 items the ladder cannot exceed $\log_2 n = 7.08$ and 5.70 bits, so the rule meets the

sample ceiling before it meets the corpus. These two maps are too small to have an identifiable focal point. That is the finite-size face of the paper's question: how many dimensions remain distinguishable is bounded by how many items there are to distinguish.

	deployed $d = 9$	focal re-map $d = 7$	focal globe†
spectroscopy $E_{0..3}$	0.42/0.25/0.06/0.27	0.44/0.38/0.01/0.17	0.70/0.05/0.21/0.05
even / odd	0.481/0.519	0.453/0.547	0.905/0.095
radius: isolated at $r = 0.075 \ldots 0.115$	3,2,2,2,2	0,0,0,0,0	0,0,0,0,0
rayleigh components (null)	73 (109.6)	71 (97.9)	47 (—)
axis redundancy: excluded / axes (total z)	9/9 (33.8)	7/7 (16.2)	—
admitted: rayleigh, axis, spectra, radius, azimuth	T, T, F, T, F	T, T, T, F, F	—

Table 7: The diagnostics sub-tab on the real map. Spectroscopy and radius are full-map; rayleigh, axis redundancy and admission are on the seeded 1200-item subsample (provisional). †The focal globe has continuous coordinates; the tab's nulls permute bits and are not valid for it, so only observed geometry is reported. T/F: admitted / not admitted.

What the tab sees. Four readings matter. (1) *Axis redundancy is an independent witness for the focal point.* The trial's per-axis predictability (leave-one-out nearest-neighbour vote against a fixed-margin null) excludes all nine axes, and the two largest z are axes 8 and 9 (21.32 and 24.51, against 14.13–19.77 for axes 1–7): the bits the focal rule discards are the bits the instrument finds most predictable from the others. (2) *Rayleigh connectivity* at chord 0.095 shows 73 components against 109.6 ± 1.75 under the null ($z = -20.9$): the real corpus is far more clumped than its margins. (3) *Azimuth* is not admitted on either map: its de-atomized null is not size-matched to the observed multiplicities, and on the $d = 7$ map its Holm verdicts are not reproducible across seeds. (4) The focal re-map removes all isolated positions (0 vs 3) and, unlike the deployed map, passes spectroscopy admission; it fails radius-profile admission instead.

8 Machine-checked counting identities

The counting facts used above are exact and finite, so they are proved, not estimated. A new module `FocalBounds.lean` (core Lean 4, toolchain 4.33.0, no Mathlib) defines `distinctCount` on lists via an explicit `dedup`, the top-d prefix count of a bit-code family, and the focal selection rule (Definition 2) on a gain list, and proves 19 theorems:

Theorem 1 (FocalBounds)**.** *For a list of codes c and every d:*

1. *`distinctCount_le_length`, `distinctCount_map_le`: a map never has more classes than items, and any recoding cannot increase the class count;*
2. *`distinctCount_perm`, `distinctCount_congr`: class counts are invariant under reordering and under pointwise-equal codings;*
3. *`prefix_count_mono`, `prefix_count_double`: adding one bit never merges classes and at most doubles them, $N_d \le N_{d+1} \le 2N_d$;*
4. *`prefix_count_pow`, `prefix_count_le_length`: $N_d \le 2^d$ and $N_d \le M$ (given codes of length $\ge d$);*
5. *`focalDim_le_length`, `focalDim_prefix_meets`, `focalDim_stop_fails`, `focalDim_maximal`: the selected $n^\star$ is a prefix all of whose gains meet τ, the next gain (if any) fails, and no longer such prefix exists.*

Items 3 and 4 require a code-length premise, which the instrument's codes satisfy. The module passes every gate of the series' `lean-check` workflow: forbidden-token scan, no `sorry`, `leanchecker` replay, axiom coverage (45 constants, all within the series' permitted core set `propext`, `Quot.sound`, `Classical.choice`; no `sorryAx`), a scope manifest (`FOCAL_SCOPE_MANIFEST_OK 19`), the per-theorem axiom pins (`AXIOM_GATE_OK 19/19`) and two negative controls (an injected `sorry` and a mutant with `distinctCount := 0`, which leaves every statement unchanged, are both rejected). Run locally under the patched `lean-check` workflow, with `FocalBounds` added as a sixth module, all 48 steps pass with 0 failures, including the three new focal steps (kernel check, scope-manifest validation, axiom pins) and the `leanchecker` replay of all six modules.

9 Scope and honest caveats

1. **One corpus, binary inputs.** Every result is about map #598. Proposition 1 makes the counts exact precisely because the inputs are binary; for continuous embeddings the lattice scale must be replaced by an estimated one, and the focal rule becomes a choice of scale window (Falconer, 2014; Camastra & Staiano, 2016).

2. **Subsample diagnostics are provisional.** The four HTTP trials are defined for $N \leq 1200$, on the live deployment as in source. Their #598 rows in Table 7 describe one seeded subsample run from source. A full-map verdict needs a raised cap or a sub-quadratic variant of each trial. Persisting a subsample as a new live map would also work, but it writes to the deployment and was not done.

3. **Deployed equivalence is behavioural, not byte-level.** The four live trials agree with repository source (commit `7d095ae`) on every field for the two maps the deployment can run, and the live operating range ($N \leq 1200$) matches source. That establishes equivalence of the diagnostics code path on the stored maps, not byte equivalence of the bundle. One deployed module (`jev-delaunay-exact.js`) still has no source of record.

4. **Two of three stored maps are small.** Maps #595 and #596 have $n = 135$ and 52, so their focal rule is sample-limited (Table 6). Only #598 is large enough for the focal point to be a corpus property.

5. **Packings are lower bounds.** All $N(\varepsilon)$ above ε_{lat} and all certified counts are greedy, hence lower bounds on the packing number.

6. **Nulls.** Fixed-margin nulls control marginals only. Curveball draws use $K = 20$ and column permutations $K = 50$; z-scores are descriptive.

7. **The focal rule has a free parameter.** $\tau = \frac{1}{2}$ bit is a convention; the reported $n^\star$ holds across the whole stable band $(0.055, 0.722)$.

8. **Literature.** The seed transcripts' citations were re-verified bibliographically (39 of 42 confirmed). Unconfirmed items, including Bouligand (1928), are not cited. The seed transcripts conflate two Falconer capacity papers, invert an author order, and misattribute a DOI; only corrected entries are used here.

10 Conclusion

The answer to "how many remain at scale ε" for this corpus is a ladder — 3,232 items, 135 patterns, 116 deployed classes, 128 focal cells — and the dimensional focal point is where the ladder stops paying: $n^\star = 7$, chosen automatically, stable across thresholds, explained by

marginals, and with a corpus-specific residual far outside the nulls. Projected to the PCA sphere at RMS lens power, the focused map keeps every pattern and is more faithful to its source; the deployed map resolves more positions at the canonical chord. The console's own diagnostics, run on the live deployment, behave identically to repository source and confirm the focal reading through an independent instrument. But their $N \leq 1200$ operating range excludes the real map at full size, and extending it remains the most actionable finding for the platform.

Reproduction manifest

- Map: `map-json:598` (`frame_id` `77360296af046f8d`, `run_fingerprint` `fba40c7b482d4e2e`); recovered inputs `map598_X.npy`.
- Re-map at $d = 7$: `map_d7.json` (`frame_id` `76b98c0e2091d925`), produced by `run_pointmap.mjs` with the repository `pointmap.js`.
- Diagnostics: `run_map_diagnostics.mjs`, `map598_diagnostics.json`; subsample seed 20261110.
- Live deployment (2026-11-10, operator bearer key; key not recorded): `GET /api/jev/map/maps`, `GET /api/jev/map/maps/{595,596,598}`, and `POST /api/jev/map/{axis-redundancy, rayleigh, azimuth, admission}` with `{map_id}` (non-persisting trials). Responses: `live_trials_raw.json`; maps: `live_map595.json`, `live_map596.json`; parity: `live_parity.json`.
- Arrays: `renyi.npz`, `robust.npz`, `lens_scan.npz`, `globes.npz`; all quoted numbers: `numbers.json`.
- Lean: `FocalBounds.lean`, `focal-scope.json`, `lean-check-focal.patch`; toolchain Lean 4.33.0.
- Repository: `yubi-OS/yubiOS` at `7d095ae`.

References

F. Camastra and A. Staiano. Intrinsic dimension estimation: Advances and open problems. *Information Sciences* 328:26–41, 2016.

C. J. Carstens. Proof of uniform sampling of binary matrices with fixed row sums and column sums for the fast Curveball algorithm. *Physical Review E* 91(4):042812, 2015. doi:10.1103/PhysRevE.91.042812.

S. Dasgupta and A. Gupta. An elementary proof of a theorem of Johnson and Lindenstrauss. *Random Structures & Algorithms* 22(1):60–65, 2003.

E. Facco, M. d'Errico, A. Rodriguez, and A. Laio. Estimating the intrinsic dimension of datasets by a minimal neighborhood information. *Scientific Reports* 7:12140, 2017.

K. J. Falconer and J. D. Howroyd. Projection theorems for box and packing dimensions. *Mathematical Proceedings of the Cambridge Philosophical Society* 119(2):287–295, 1996.

K. J. Falconer and J. D. Howroyd. Packing dimensions of projections and dimension profiles. *Mathematical Proceedings of the Cambridge Philosophical Society* 121(2):269–286, 1997.

K. J. Falconer, J. M. Fraser, and T. Kempton. Intermediate dimensions. *Mathematische Zeitschrift* 296(1-2):813–830, 2020.

K. Falconer, J. Fraser, and A. Käenmäki. Minkowski dimension for measures. *Proceedings of the American Mathematical Society* 151(2):779–794, 2023.

K. Falconer. Fractal Geometry: Mathematical Foundations and Applications. John Wiley & Sons, 2014.

H. Federer. Geometric Measure Theory. Springer-Verlag, 1969.

J. M. Fraser and H. Yu. New dimension spectra: finer information on scaling and homogeneity. *Advances in Mathematics* 329:273–328, 2018.

J. M. Fraser. An invitation to dimension interpolation. Preprint, 2026. arXiv:2603.10729.

P. Grassberger and I. Procaccia. Characterization of strange attractors. *Physical Review Letters* 50(5):346–349, 1983.

H. G. E. Hentschel and I. Procaccia. The infinite number of generalized dimensions of fractals and strange attractors. *Physica D: Nonlinear Phenomena* 8(3):435–444, 1983. doi:10.1016/0167-2789(83)90235-X.

A. N. Kolmogorov and V. M. Tikhomirov. ε-entropy and ε-capacity of sets in function spaces. *Uspekhi Matematicheskikh Nauk* 14(2(86)):3–86, 1959.

B. Kégl. Intrinsic dimension estimation using packing numbers. *Advances in Neural Information Processing Systems 15 (NIPS 2002)*, 2002.

E. Levina and P. J. Bickel. Maximum likelihood estimation of intrinsic dimension. *Advances in Neural Information Processing Systems 17 (NIPS 2004)*:777–784, 2004.

P. Mattila. Geometry of Sets and Measures in Euclidean Spaces: Fractals and Rectifiability. Cambridge University Press, 1995.

A. Robinson. Non-standard Analysis. North-Holland, 1966.

S. Tchatalbachian. Learned Latent Curves and the Hyperspherical-Harmonic Variant: A Closed-Loop Framework for Corpus Embedding and Recursive Skill Auditing. Technical report, `yubi-OS/yubiOS`, `papers/learned-latent-curves-2026-08-06.tex`, 2026-08-06.

S. Tchatalbachian. Is This X? A Null-Standardized Question Space for Corpus Curvature, with a Hodge-Theoretic Channel and a Calibrated Standard-Candle Generator. Technical report, `yubi-OS/yubiOS`, `papers/is-this-x-2026-08-12-Final.tex`, 2026-08-12.

S. Tchatalbachian. The Curved-Corpus Program, Unified: Learned Latent Curves, a Null-Standardized Question Space, and Spherical Defocus, with Machine-Checked Invariants. Technical report, `yubi-OS/yubiOS`, `papers/curved-corpus-unified-2026-08-22-v2.tex`, 2026-08-22 (v2).

C. Tricot. Two definitions of fractional dimension. *Mathematical Proceedings of the Cambridge Philosophical Society* 91(1):57–74, 1982.

T. Zhang. Learning bounds for kernel regression using effective data dimensionality. *Neural Computation* 17(9):2077–2098, 2005.