

ML HW2

B06303126 Lo Yun Chien

November 2020

Question 1

Correct answer:(b)
The calculation is

$$(0.1)^2(1 - \frac{12}{N}) < 0.006$$

Which means

$$N < 30$$

Question 2

Correct answer:(a)

For any X is a m by n matrix, $X^T X = A$ is a n by n matrix. Whether A is a full rank, $Aw = X^T y$ exists solution for w . If A is full rank, then the solution is unique. if not, there are many solution.

Question 3

Correct answer:(c)

Consider H is a projection matrix, projecting y to the column space of X . Then, multiply each row by $\frac{1}{n}$ may create different basis of the space.

Question 4

Correct answer:(e)

The first argument is right by Hoeffding, notice that θ is mean and v is sample mean is this Bernoulli trial.

The likelihood function is $f(x|\theta) = (\theta)^x(1 - \theta)^{1-x}$ for x is 0 or 1. For N times, the total likelihood is $F(x|\theta) = (\theta)^{Nv}(1 - \theta)^{N(1-v)}$, then both take \ln and differentiate is w.r.t θ , we get $F'(\theta) = Nv(1 - \theta) - (N - Nv)\theta$. To maximize it, we need $F'(\hat{\theta}) = 0$. Then $v = \hat{\theta}$

Calculate ∇E_{in} , we have $\nabla E_{in} = \frac{2}{N} \sum_{n=1}^N (\hat{y} - y_n)$. When $\hat{y} = 0$, $\nabla E_{in}|_{\hat{y}=0} = \frac{2}{N} \sum_{n=1}^N (-y_n) = -2v$. To minimize it, we want $\nabla E_{in} = 0$, hence $\hat{y} = v$.

Question 5

Correct answer:(c)

Define $F_\theta(y) = \frac{y}{\theta}$ as the cdf of $\text{uniform}(0, \theta)$, we found the likelihood is

$$\prod_{i=1}^n F_\theta(y_n) = \prod_{i=1}^n \frac{y_n}{\theta}$$

Question 6

Correct answer:(b)

$$\nabla E_{in} = -\frac{\eta}{N} \sum_{n: y_n \neq \text{sign}(w_t^T x_n)} y_n x_n$$

By integration and suppose $E_{in} = 0$ if every points are correctly classified. we have

$$E_{in} = -\frac{\eta}{N} \sum_{n: y_n \neq \text{sign}(w_t^T x_n)} y_n w^T x_n$$

By guessing that err will give correct points 0 error, we have

$$E_{in} = \frac{\eta}{N} \sum_{i=1}^N \max\{0, -y_n w^T x_n\}$$

So the pointwise error function may be $\max\{0, -y_n w^T x_n\}$

Question 7

Correct answer:(a)

By the err function given as $e^{-y w^T x}$, the corresponding $\nabla e^{-y w^T x}$ is

$$\nabla e^{-y w^T x} = e^{-y_n w^T x_n} - y_n x_n$$

Question 8

Correct answer: (b)

Simply calc. approximated $\nabla E(w)$

$$\nabla E(w) = b_E(u) + A_E(u)(w - u)$$

We still want $\nabla E(w) = 0$, combining $w = v + u$, so it imply

$$b_E(u) + A_E(u)(w - u) = 0 \implies v = (A_E(u))^{-1} - b_E(u)$$

Question 9

Correct answer: (b)

In linear regression, we have

$$E_{in} = \frac{1}{n} \|Xw - y\|^2$$

Now for ∇E_{in}

$$\nabla E_{in} = \frac{2}{n} (X^T Xw - X^T y)$$

Now for $\nabla^2 E_{in}$

$$\nabla^2 E_{in} = \frac{2}{n} X^T X$$

Question 10

Correct answer: (b)

$$\text{err}(W, x, y) = -\ln h_y(x) = -\sum_{k=1}^K [y = k] (\ln h_k(x))$$

Calc. the partial derivative.

$$\frac{\partial \text{err}(W, x, y)}{\partial W_{ik}} = -[y = k] \left(\frac{h_k(x)'}{h_k(x)} \right)$$

Now calculate

$$\frac{\partial h_k(x)}{\partial W_{ik}} = \frac{e^{w_k^T x}}{\sum_{i=1}^K e^{w_i^T x}} x_i - \frac{e^{w_k^T x}}{(\sum_{i=1}^K e^{w_i^T x})^2} x_i e^{w_k^T x} x_i$$

The conclusion is

$$-[y = k] \left(\frac{h_k(x)'}{h_k(x)} \right) = -[y = k] (x_i - h_k(x) x_i) = x_i [y = k] (h_k(x) - 1)$$

Question 11

I don't know

Question 12

Correct answer: (e)

Proof by programming

Question 13

I don't know neither

```
In [78]: import pandas as pd
import numpy as np
import random
import math
```

Reading train data

```
In [79]: train_data = pd.read_table("hw3_train.dat.txt", header = None)
train_data = train_data.rename(columns = {0: "x_{1}", 1: "x_{2}", 2: "x_{3}", 3: "x_{4}", 4: "x_{5}",
5: "x_{6}", 6: "x_{7}", 7: "x_{8}", 8: "x_{9}", 9: "x_{10}", 10: "y"})
train_data["x_{0}"] = 1

cols = train_data.columns.tolist()
cols = cols[-1:] + cols[:-1]

train_data = train_data[cols]
```

Define E_in function

```
In [80]: def E_in(w, X, Y):
return pow(np.linalg.norm(np.add(np.dot(X,w), -Y)), 2) / len(Y)
```

Conduct linear regression

```
In [81]: def linear_regression(X, Y):
Transpose_X = X.T
X_T_X = Transpose_X.dot(X)
X_T_X_inv = pd.DataFrame(np.linalg.pinv(X_T_X.values), X_T_X.column
```

```
s, X_T_X.index)  
    w_lin = (X_T_X_inv.dot(Transpose_X)).dot(Y)  
    return w_lin
```

Problem 14:

Correct answer: (d)0.60

linear regression with colsed form

```
In [82]: Y = train_data["y"]  
        X = train_data.drop(["y"], axis = 1)
```

```
In [83]: w_lin = linear_regression(X, Y)  
        sqr_error = E_in(w_lin, X, Y)  
        sqr_error
```

Out[83]: 0.6053223804672917

Problem 15

Correct answer: (c) 1800

Linear regression with SGD

```
In [84]: N_list = []  
  
        for times in range(1000):  
            sgd_error = 999  
            N = 0  
            w = np.zeros(11)  
            while (sgd_error >= 1.01 * sqr_error):  
                N += 1  
                n = random.randint(1, 1000)  
                y_n = Y.loc[n-1]  
                x_n = X.loc[n-1]
```

```
w = np.add(w, (y_n - w.T.dot(x_n)) * 2 * 0.001 * x_n)
sgd_error = E_in(w, X, Y)
N_list.append(N)
```

```
In [85]: N_list = pd.DataFrame(N_list)
N_list.mean()
```

```
Out[85]: 0    1949.903
dtype: float64
```

Problem 16, 17

Correct answer: (c) 0.56

Correct answer: (b) 0.50

logistic regression with SGD

define E_in_log

```
In [106]: def theta_f(x):
          return 1 / (1 + pow(math.e, -x))

def E_in_log(w, X, Y):
    total_error = 0
    for i in range(len(Y)):
        y_n = Y.loc[i]
        x_n = X.loc[i]
        total_error += math.log(1 + pow(math.e, - (y_n * w.T.dot(x_n
    )))
    return total_error / len(Y)
```

```
In [107]: error_list = []

for i in range(1000):
    sgd_error = 999
    w = np.zeros(11)
    for j in range(500):
        n = random.randint(1, 1000)
```

```
y_n = Y.loc[n-1]
x_n = X.loc[n-1]
w = np.add(w, theta_f(-y_n * w.T.dot(x_n)) * 0.001 * y_n * x_n)
sgd_error = E_in_log(w, X, Y)
error_list.append(sgd_error)
```

```
In [108]: error_df = pd.DataFrame(error_list)
          error_df.mean()
```

```
Out[108]: 0    0.568543
          dtype: float64
```

```
In [109]: error_list = []

          for i in range(1000):
              sgd_error = 999
              w = w_lin
              for j in range(500):
                  n = random.randint(1, 1000)
                  y_n = Y.loc[n-1]
                  x_n = X.loc[n-1]
                  w = np.add(w, theta_f(-y_n * w.T.dot(x_n)) * 0.001 * y_n * x_n)
                  sgd_error = E_in_log(w, X, Y)
                  error_list.append(sgd_error)

          error_df = pd.DataFrame(error_list)
          error_df.mean()
```

```
Out[109]: 0    0.502844
          dtype: float64
```

Problem 18:

Correct answer: (a) 0.32

Calculate binary classification error

```
In [86]: test_data = pd.read_table("hw3_test.dat.txt", header = None)
test_data = test_data.rename(columns = {0: "x_{1}", 1: "x_{2}", 2: "x_{3}", 3: "x_{4}", 4: "x_{5}", 5: "x_{6}", 6: "x_{7}", 7: "x_{8}", 8: "x_{9}", 9: "x_{10}", 10: "y"})
test_data["x_{0}"] = 1

cols = test_data.columns.tolist()
cols = cols[-1:] + cols[:-1]

test_data = test_data[cols]
```

```
In [87]: Y_test = test_data["y"]
X_test = test_data.drop(["y"], axis = 1)
```

```
In [88]: def binary(x):
        if x > 0:
            return 1
        else:
            return -1

def Error_binary(w, X, Y):
    total_error = 0
    for i in range(len(Y)):
        if binary(w.T.dot(X.loc[i])) == Y.loc[i]:
            pass
        else:
            total_error += 1
    return total_error / len(Y)
```

```
In [89]: print(abs(Error_binary(w_lin, X, Y) - Error_binary(w_lin, X_test, Y_test)))
```

0.3226666666666666

Problem 19, 20:

Correct answer: (b) 0.36

Correct answer: (d) 0.44

Nonlinear transform

```
In [90]: def phi(x, Q):  
        phi_array = np.array([1])  
        for i in range(Q):  
            q_list = [pow(xi, i+1) for xi in x]  
            q_array = np.array(q_list)  
            phi_array = np.append(phi_array, q_array)  
        return phi_array
```

```
In [91]: X_3 = X.drop(["x_{0}"], axis=1)  
X_3 = X_3.apply(phi, axis=1, args=(3,))  
X_3 = pd.DataFrame(X_3.tolist())  
  
X_test_3 = X_test.drop(["x_{0}"], axis=1)  
X_test_3 = X_test_3.apply(phi, axis=1, args=(3,))  
X_test_3 = pd.DataFrame(X_test_3.tolist())
```

```
In [92]: w_lin_3 = linear_regression(X_3, Y)
```

```
In [93]: abs(Error_binary(w_lin_3, X_3, Y) - Error_binary(w_lin_3, X_test_3, Y_test))
```

```
Out[93]: 0.37366666666666665
```

```
In [94]: X_10 = X.drop(["x_{0}"], axis=1)  
X_10 = X_10.apply(phi, axis=1, args=(10,))  
X_10 = pd.DataFrame(X_10.tolist())  
  
X_test_10 = X_test.drop(["x_{0}"], axis=1)  
X_test_10 = X_test_10.apply(phi, axis=1, args=(10,))  
X_test_10 = pd.DataFrame(X_test_10.tolist())
```

```
In [95]: w_lin_10 = linear_regression(X_10, Y)
         abs(Error_binary(w_lin_10, X_10, Y) - Error_binary(w_lin_10, X_test_10,
         Y_test))
```

```
Out[95]: 0.446
```