

Tamil Character Recognition using Canny Edge Detection Algorithm

P. Selvakumar
Research Scholar,
Department of Computer Science,
Research and Development Centre, Bharathiar University
Coimbatore, Tamilnadu, India.
selvagacalr@gmail.com

Dr. S. Hari Ganesh
Assistant Professor,
Department of Computer Science,
HH The Rajah's College (Autonomous),
Pudukkottai, Tamilnadu, India.
hariganesh17@gmail.com

Abstract- The division of the content from the recorded debased picture reports is an extremely difficult undertaking on the grounds that the varieties between the closer view content and foundation content are difficult to decide. In this paper we have actualized canny edge detection algorithm to examine and remove the words from a corrupted picture; the procedure conveyed here is the picture contrast which is adaptively found to settle the issue. At first the differentiation guide is taken from the debased record pictures. The mix of nearby picture angle and the neighborhood picture difference is the versatile picture differentiation, and afterward it is changed over to double level and joined with canny edge detection algorithm and artificial neural network to concentrate content edge pixels. The record content is further portioned by a nearby limit that is evaluated in view of the powers of distinguished content stroke edge pixels inside a neighborhood window.

Keywords: Canny edge detection, character identification, Binarization, image contrast, artificial neural network

I. INTRODUCTION

Record Image Binarization is performed in the preprocessing stage for archive investigation and it plans to section the frontal area content from the report foundation. A quick and precise record picture binarization method is critical for the following archive picture handling assignments, for example, optical character acknowledgment. In spite of the fact that record picture binarization has been examined for a long time, the thresholding of debased archive pictures is still an unsolved issue because of the high entomb/intra-variety between the content stroke and the report foundation crosswise over various archive pictures. A non-specific Optical Character Recognition (OCR) framework includes diverse stages like preprocessing, division, highlight extraction and order. Preprocessing is one of the most intriguing and testing subjects in DAR. Preprocessing of archive includes changing over filtered pictures or shot pictures of machine printed or manually written content which may incorporate numbers, letters and images into framework processable configuration. Division is a vital task of any OCR framework and it isolates the picture content records into lines, words and characters. Consequently the exactness of OCR framework basically relies on upon the division

calculation been utilized. Division of written by hand content of Indian dialects is testing when contrasted and Latin based dialects due to its basic entanglement and nearness of compound characters. This many-sided quality increments further if were to perceive content of antiquated Indian or non-Indian epigraphically records. The epigraphically records engraved on stones, rocks, columns or on a few other composition material are non-straight in their shapes and non-uniform in their sizes. Crude picture of an epigraph contains undesirable images or stamps, commotion installed and message engraved with much skew. The separating amongst characters furthermore between the lines and the skew could muddle the way toward interpreting the scripts. Some touching lines and additionally characters muddles the procedure of division which is contribution for the acknowledgment procedure in the later stages. Subsequently the info archive picture of epigraphs is to be preprocessed for evacuation of commotion, skew recognition and amendment, trailed by division of characters. In spite of a few positive takes a shot at OCR over the world, improvement of OCR devices in Indian dialects is still a testing assignment. Character division assumes a critical part in character acknowledgment since mistakenly sectioned characters are helpless to be perceived wrongly. Henceforth the proposed work concentrates on preprocessing and division of antiquated transcribed reports. This is an underlying stride towards creating OCR for antiquated scripts, which can be utilized by archeologists and antiquarians for digitization and further investigation of old records.

The majority of the Tamil chronicled records were initially written in Palm scripts. These archives are incomprehensible because of different reasons. So as to concentrate the message from those archives, the pictures of these verifiable archives are prepared. Picture binarization has been utilized to understand this issue. Despite the fact that binarization works successfully in removing the message from the harmed reports, thresholding still stays as major issue [1]. More clarity can be acquired by utilizing the shrewd using artificial neural network in the post preparing of the binarization procedure [2]. Edge location is viewed as vital in picture division. Here in this paper shrewd edge finder is utilized. The Canny edge finder is an edge location

administrator that uses a multi-stage calculation to identify a wide scope of edges in pictures. Vigilant edge indicator has a decent confinement property that it can stamp the edges near genuine edge areas in the recognizing picture [3]. Notwithstanding this, artificial neural network is utilized to improve the thresholding procedure. ANN strategy is utilized to naturally perform group thresholding and to diminish the dim level picture into a parallel picture. The paper is arranged with section.2 clarifying the related work. The proposed technique is given in section.3 and its outcome in the section.4 taking after its examination.

I. LITERATURE SUREVEY

Gupta et al. [4] reviewed about content retrieval from historical manuscript. In this paper, form based picture division; object extractions assume an imperative part. In this technique they execute morphological edge finder with locale developing procedures. The initial step required here is picture improvement utilizing morphological shutting operation and identification procedure is done by morphological expansion utilizing edge indicator. Here they execute morphological administrator with a specific end goal to upgrade the picture over the edges and we actualize locale developing and district combining procedure for recognizing exact edge extraction and to defeat picture division issues. Here, the information picture is worked to a morphological shutting operation what's more, edge locator then we executed locale developing with district consolidating procedures keeping in mind the end goal to execute the picture division. This division can be actualized just in the picture then prepared by utilizing morphological operation with a specific end goal to get an unmistakable form of the picture.

Saula et al. deliberated adaptive document for image binarization [5]. Another strategy is displayed for versatile record picture binarization, where the page is considered as an accumulation of subcomponents, for example, content, foundation and picture. The issues brought about by clamor, brightening and numerous source sort related corruptions are tended to. Two new calculations are connected to decide a neighborhood limit for every pixel. The execution assessment of the calculation uses test pictures with ground-truth, assessment measurements for binarization of printed and engineered pictures. The proposed calculations were tried with pictures including different sorts of archive parts and debasements.

Patvardhan et al. denoising and binarization plan of record pictures undermined by white Gaussian clamor and Impulse commotion is introduced utilizing Curvelet Transform. The capacity of meager representation and edge conservation of Curvelet change is used. Motivation clamor gets included amid record checking or after binarization of filtered report pictures. White Gaussian commotion debases the report pictures amid transmission. The nearness of either sort of clamor or a blend of them can seriously debase the execution of any OCR framework. In the proposed denoising plan, the curvelet change is utilized with level ward edge ascertained by altered sqtwolog technique (all inclusive edge) at every scale with estimation of clamor standard deviation.

The uproarious curvelet coefficients are thresholded by Hard Thresholding strategy. After curvelet based denoising, the picture is binarized utilizing worldwide Otsu strategy and post prepared to smoothen the content limits and expel separated pixels for better OCR execution. The curvelet based plan is contrasted and a wavelet change based plan and an altered wavelet based plan with edge protection. The outcomes demonstrate that curvelet based plan performs better in the event of pictures containing Gaussian, Impulse and a mix of both the clamors [6].

Sonia et al. enhanced a method to improving debased archive pictures division is one of the troublesome undertaking due to back ground and frontal area variety. This paper displays another methodology for upgrade of corrupted reports. Picture binarization is the way toward separating of pixels into double accumulations dark as forefront and white as foundation. Thresholding has observed to be a notable procedure utilized for binarization of report pictures [7]. In corrupted reports where broad foundation commotion or distinction in the complexity and splendor exist, there exist numerous pixels which can't be arranged easily as closer view and foundation. In such cases neighborhood thresholding has significant over accessible systems.

Binarization is procedure to produce double picture from report picture [8]. Record picture binarization has effectively under examination from past numerous years, and numerous binarization calculations have been proposed for various sorts of corrupted archive pictures. Archive picture Binarization is extremely well known to update old manually written and machine printed reports. Still to recoup debased report is exceptionally dreary occupation. Such report has the much harmed likewise nearness of clamor and debasement. There is a great deal of extension to enhance old and corrupted reports [9]. Picture division is technique which utilized as often as possible as a part of picture handling. Thresholding is a vital pre-handling venture for the corrupted picture to upgrade their quality. The between the forefront content and the foundation of various archive pictures is a troublesome undertaking. New Binarization strategy utilizing picture division utilizing limit division is proposed. Proposed strategy can conquer the downside of vigilant edge map.

Abhishek et al. [10] utilized from bygone time to save information and the colossal colloquialisms. Broadened scripts are utilized as a part of composing dialects over the globe, in such a domain it is important to comprehend the script furthermore, the dialects in the pictures or record before selecting an well-suited character recognition and archive examination or ancient engraving investigation calculation. Various strategies for the programmed character recognizable proof and script acknowledgment have been prescribed in this way. This original copy is a laconic study on the picture earlier preparing methods, division procedures furthermore, highlight extraction and arrangement by means of dimensionality diminishment strategies. Wide research has already been finished in this area however the old engraving character acknowledgment is as yet difficult and needs more productive systems. This audit will serve as premise for the for

starters to picture pre-preparing also, the adequacy of dimensionality diminishment approaches in highlight and order.

Verifiable records contain vital contemporary data around a man, put, occasions of that period. A lovely work on prescription, religion and science composed by the researchers, called Veda, is protected in India. The histories of civic establishments are put away in libraries and historical centers. Around the globe, there is a fortune of fabulous writing, which can't be gotten to by a large portion of the general population in the world due to time and travel cost [11]. Picture reclamation is the procedure which is utilized to reestablish a debased record back to the first picture.

One of the most established medium of composing and imparting in South Asia are palm leaf compositions. These are additionally the real hotspots for composing and painting in South East Asian nations including Thailand, Nepal, India, Barma, Indonesia and so on. Henceforth it is required to build up a computerized framework to interpret these engravings. The framework takes the camera snatched or examined pictures of the engravings as an information and procedures it before the character acknowledgment is taken up. The pictures so caught have real issues like the broken letters, eradicated letters, bending because of fossils settled et cetera [12].

II. PROPOSED WORK

Record pictures regularly experience the ill effects of various sorts of debasement that renders the archive picture binarization a testing assignment. Existing framework displays a record picture binarization procedure that fragments the content from gravely corrupted report pictures precisely. Here it evaluates an archive foundation surface through an iterative polynomial smoothing method. This technique is straightforward, it cannot work legitimately on corrupted record pictures with an unpredictable archive foundation. To beat this, we propose another system in which an versatile complexity guide is initially developed for a given corrupted archive picture and the content stroke edges are at that point identified through the mix of the binarized versatile complexity map and the vigilant edge map. The content is at that point divided in view of the nearby edge that is assessed from the recognized content stroke edge pixels. A few post-preparing is further connected to enhance the report Binarization quality.




Fig. 1. Block diagram of Proposed Work

A. Image Contrast

The versatile picture difference is a mix of the neighborhood picture contrast and the nearby picture inclination that is excessively learnt, making it impossible to content and foundation variety brought about by distinctive sorts of archive corruptions.

B. Artificial Neural Network

Artificial Neural technique is utilized for programmed binarization level choice, in light of the state of the histogram. The calculation accept that the picture is made out of two essential classes: Foreground and Foundation. It then registers an ideal edge esteem that minimizes the weighted inside class differences of these two classes in which it minimizes the class difference to decide the binarization level. It naturally plays out the grouping based picture thresholding, or, the decrease of a dark level picture to a paired picture.

C. Canny Edge Detection

The Canny edge finder is adequately an edge location administrator which utilizes a multi stage calculation to recognize an extensive variety of edges in pictures. The primary point of this calculation was to find the ideal edge discovery calculation. In this circumstance, an "ideal" edge locator implies:

1. Great discovery - the calculation ought to stamp the same number of genuine edges in the picture as could be expected under the circumstances.
2. Great confinement - edges stamped ought to be as close as conceivable to the edge in the genuine picture.
3. Negligible reaction - a given edge in the picture ought to just be checked once, and where conceivable, picture commotion should not make false edges.

The Canny Edge discovery calculation keeps running in 4 separate strides:

1. Smoothing:

Obscuring of the picture to expel commotion.

2. Finding slopes:

The edges ought to be stamped where the angles of the picture has extensive sizes.

2. Non-most extreme concealment:

Just nearby maxima ought to be set apart as edges.

3. Double thresholding:

Potential edges are dictated by thresholding. Last edges are dictated by stifling all edges that are not associated with an exceptionally certain (solid) edge.

The binarization result is further enhanced by post handling. The segregated forefront pixels that don't associate with other frontal area pixels are sifted through to make the edge pixel set definitely. The area pixel pair that lies on

symmetric sides of a content stroke edge pixel should have a place with various classes (i.e., either the report foundation or the closer view content). One pixel of the pixel pair is subsequently named to the next class if both of the two pixels have a place with the same class. At long last, some single pixel curios along the content stroke limits are separated out by utilizing a few legitimate administrators and consequently the picture is fragmented.

III. RESULT AND DISSCUSSION

The input picture is changed over here into dim scale picture with the span of 512*512. This change is done in request to apply some scientific conditions. By this transformation there is no commotion event in the info picture. A picture angle is a directional change in the power or shading in a picture. The picture inclination has been broadly utilized for edge location and the content stroke edges of the documental pictures adequately. To separate just the stroke edges appropriately, the picture inclination needs to be standardized to remunerate the picture variety inside the record foundation




Fig. 2. Input Image

To the dark scale picture here we apply vigilant edge calculation to the concentrate the limit obviously. The human visual framework is delicate to differentiate than luminance. The difference is dictated by the distinction between the shading and the brilliance of the object.




Fig. 3. RGB to Gray

A twofold picture is a computerized picture that has as it were two conceivable qualities for every pixel. Ordinarily the two hues utilized for a double picture are high contrast however any two hues can be utilized.




Fig. 4. Image Contrast




Fig. 5. Binarization using ANN

The binarization result is further enhanced by post preparing. The secluded frontal area pixels that don't associate with other frontal area pixels are sifted through to make the edge pixel set correctly. The area pixel pair that lies on symmetric sides of a content stroke edge pixel should have a place with various classes (i.e., either the report foundation or the closer view content). One pixel of the pixel pair is along these lines named to the next classification if both of the two pixels have a place with the same class. At long last, some single pixel ancient rarities along the content stroke limits are separated out by utilizing a few legitimate administrators and henceforth the picture is portioned.

ANN is diverted from Operational Test Bolster Unit. It is mechanized through edge esteem in the picture. This OTSU thresholding depends on the histogram of the information picture. Otsu thresholding is a basic yet successful worldwide programmed thresholding strategy for binarizing dark scale pictures, for example, forefronts and foundations.




Fig. 6. Canny Edge Detection Algorithm

IV. CONCLUSION

This paper introduces a versatile picture contrast based record picture binarization strategy that is tolerant to various sorts of record debasement, for example, uneven brightening and archive smear. The proposed method is straightforward and strong, just couple of parameters are included. In addition, it works for various types of corrupted archive pictures. It makes utilization of the neighborhood picture differentiate that is assessed taking into account the neighborhood greatest and least and it has been tried on the different datasets. Tests demonstrate that the proposed technique outflanks most reported archive binarization techniques.

REFERENCES

- [1] Bolan Su, Shijian Lu, Chew Lim Tan, "Robust Document Image Binarization Technique for Degraded Document Images", IEEE Transactions on Image Processing, Vol. 22, Issue 4, April 2013.
- [2] Hossein Ziaei Nafchi, Reza Farrahi Moghaddam, "Phase Based Binarization of Ancient Document Images: Model and Applications", IEEE Transactions on Image Processing, Vol. 23, Issue 7, July 2014.
- [3] Shazia Akram, Mehraj-Ud-Din Dar, Aasia Quyoum, "Document Image Processing- A Review", International Journal of Computer Applications (0975-8887), Vol. 10, Issue 5, November 2010.
- [4] Kitty Gupta, Rishav Dewan, "Content Retrieval from Historical Manuscript Images: A Review", International Journal of Computer Applications, ISSN :(0975 – 8887, 2015.
- [5] J. Sauvola, M. PietikaKinen, "Adaptive document image binarization", Pattern Recognition, volume 33, pp.225-236, 2000.
- [6] C. Patvardhan, A. K. Verma, C. V. Lakshmi, "Denoising of Document Images using Discrete Curvelet Transform for OCR Applications", International Journal of Computer Applications (0975 – 8887) Volume 55– No.10, October 2012.
- [7] Sonia saini, Ms. Richa Dogra, "Robust Document Image Binarization Technique For Degraded Document Images", Global Journal of Computers & Technology, Vol. 3, No. 2, September 23, 2015.
- [8] Rekha Chaudhari, Dinesh Patil, "Document Image Binarization Using Threshold Segmentation", International Journal of Innovative Research in Computer and Communication Engineering, Vol. 3, Issue 3, March 2015.
- [9] Soumya A, G Hemantha Kumar, "Enhancement and Segmentation of Historical Records", ACITY, DPPR, VLSI, WiMNET, AIAA, CNDC, pp. 95–113, 2015.
- [10] Abhishek Tomar, Minu Choudhary, Amit Yerpude, "Ancient Indian Scripts Image Pre-Processing and Dimensionality Reduction for Feature Extraction and Classification: A Survey", International Journal of Computer Trends and Technology (IJCTT), Volume 21 Number 2 – Mar 2015.
- [11] Neha Kundal, Anantdeep, "Performance Evaluation of Novel Historical Documents Restoration Algorithm", IJCSET, Vol 5, Iss 7, pp. 278-282, 2015.
- [12] Neelu Maheshwari, Pankaj Singh Parihar, Anurag Maloo, "A Review of Digital Image Enhancement Method of Degraded Indian Ancient Manuscripts", International Journal for Scientific Research & Development, Vol. 3, Issue 03, 2015.