

Homework 7

DS Student

04, 14, 2022

```
library('keras')
library('ElemStatLearn')
library('nnet')
library('dplyr')
```

```
##
## Attaching package: 'dplyr'
## The following objects are masked from 'package:stats':
##
##   filter, lag
## The following objects are masked from 'package:base':
##
##   intersect, setdiff, setequal, union
```

Question 1 Use the Keras library to re-implement the simple neural network discussed during lecture for the mixture data

```
# dataset
data <- mixture.example
train_x <- mixture.example$x
train_y <- mixture.example$y
test_x <- mixture.example$xnew
```

```
model <- keras_model_sequential()
```

```
## Loaded Tensorflow version 2.6.0
```

```
model %>% layer_dense(units=10, activation = "relu", input_shape = c(2))%>% layer_dense(units =2, activation = "softmax")
model %>% compile(optimizer = "rmsprop",
                  loss = "sparse_categorical_crossentropy",
                  metric=c("accuracy"))
```

```
model %>% fit(train_x, train_y,
             epochs = 10,
             batch_size = 5)
```

```
fit_nnet <- nnet(x = train_x, y= train_y, size=10, entropy=TRUE, decay=0.02)
```

```
## # weights: 41
## initial value 170.298732
## iter 10 value 102.176693
## iter 20 value 93.350233
## iter 30 value 88.802415
```

```
## iter 40 value 87.172780
## iter 50 value 86.752669
## iter 60 value 86.506805
## iter 70 value 86.271908
## iter 80 value 86.212327
## iter 90 value 86.196772
## iter 100 value 86.182970
## final value 86.182970
## stopped after 100 iterations
```

Create a figure to illustrate that the predictions are (or are not) similar using the ‘nnet’ function versus the Keras model.

```
prediction_keras <- model%>% predict(test_x)

classes_keras <- rep(0,1)
for (i in 1:6831){
  if (prediction_keras[i,1] > prediction_keras[i,2]){
    classes_keras[i] <- 1
  }else{
    classes_keras[i] <- 2
  }
}

prediction_nnet <- fit_nnet%>% predict(test_x)
classes_nnet<- rep(0,1)
for (i in 1:6831){
  if (prediction_nnet[i,1] > 0.5){
    classes_nnet[i] <- 1
  }else{
    classes_nnet[i] <- 2
  }
}

plot_mixture_data <- expression({
  plot(data$x[,1], data$x[,2],
       col=ifelse(dat$y==0, 'blue', 'orange'),
       pch=20,
       xlab=expression(x[1]),
       ylab=expression(x[2]))
  ## draw Bayes (True) classification boundary
  prob <- matrix(dat$prob, length(dat$px1), length(dat$px2))
  cont <- contourLines(dat$px1, dat$px2, prob, levels=0.5)
  rslt <- sapply(cont, lines, col='purple')
})


plot_keras_preds <- function(fit, dat=mixture.example) {

  ## create figure
  eval(plot_mixture_data)
```

```

## compute predictions from nnet
probs <- prediction_keras[,1]
preds <- classes_keras
probm <- matrix(probs, length(data$px1), length(data$px2))
cls <- contourLines(data$px1, data$px2, probm, levels=0.5)
rslt <- sapply(cls, lines, col='black')
}
plot_keras_preds(model)

```




```

plot_nnet_preds <- function(fit, dat=mixture.example) {

  ## create figure
  eval(plot_mixture_data)

  ## compute predictions from nnet
  probs <- prediction_nnet
  preds <- prediction_nnet
  probm <- matrix(probs, length(data$px1), length(data$px2))
  cls <- contourLines(data$px1, data$px2, probm, levels=0.5)
  rslt <- sapply(cls, lines, col='black')
}
plot_nnet_preds(model1)

```



From the plot we can see that the predictions are not similar. The points don't have much overlap.

Convert the neural network into CNN

```
fashion_mnist <- dataset_fashion_mnist()
c(train_images, train_labels) %<-% fashion_mnist$train
c(test_images, test_labels) %<-% fashion_mnist$test

img_rows <- 28
img_cols <- 28

train_images<- array_reshape(train_images, c(nrow(train_images), img_rows, img_cols, 1))
test_images <- array_reshape(test_images, c(nrow(test_images), img_rows, img_cols, 1))

train_images <- train_images/255
test_images <- test_images/255

class_names = c('T-shirt/top',
                 'Trouser',
                 'Pullover',
                 'Dress',
                 'Coat',
                 'Sandal',
                 'Shirt',
                 'Sneaker',
                 'Bag',
                 'Ankle boot')

train_labels <- to_categorical(train_labels, 10)
test_labels <- to_categorical(test_labels, 10)
```

```

model1 <- keras_model_sequential() %>%
  layer_conv_2d(filters = 32, kernel_size = c(3,3), activation = 'relu', input_shape = c(28,28,1)) %>%
  layer_max_pooling_2d(pool_size = c(2, 2)) %>%
  layer_conv_2d(filters = 64, kernel_size = c(3,3), activation = 'relu') %>%
  layer_max_pooling_2d(pool_size = c(2, 2)) %>%
  layer_dropout(rate = 0.25) %>%
  layer_flatten() %>%
  layer_dense(units = 128, activation = 'relu') %>%
  layer_dropout(rate = 0.5) %>%
  layer_dense(units = 10, activation = 'softmax')

```

```

model1 %>% compile(
  loss = loss_categorical_crossentropy,
  optimizer = optimizer_adadelta(),
  metrics = c('accuracy')
)

history <- model1 %>%
  fit(
    x = train_images, y = train_labels,
    epochs = 10
  )

```

```
plot(history)
```

