

Operator 6: Sub-space Spectral Sieve & Splicing Operator ($\mathcal{P}_{\text{sieve}} \cup \mathcal{O}_{\text{splice}}$)

Strict Mathematical Specification, Derivation, and Verification (Final Peer-Review Specification)

Author: Yue Lu

Version: 1.1

Resource-Availability Statement This framework is built upon Status-Relational Entropy (SRE) Dynamics. All theoretical materials are archived in the Zenodo open-access repository. **This manuscript suite, including system papers, application developments, scientific hypotheses, full algebraic derivations for operators 1-6 and simulation code, is fully open-source.** Operators 7, 8, 9, 10 are subsequent closed-source commercial core modules and are not part of this manuscript suite.

Additionally, you may access the Tencent intelligent-document space supporting AI-assisted reading, which is available on both PC and WeChat mobile clients.

As of 2026-08-14, constrained by Google's terms-of-service, the author no longer maintains or updates the SRE document library hosted in Google Gemini Notebook. The link below serves only as a historical archive and must not be used as a formal citation source:

- Google Gemini Notebook (historical archive, no further updates):

<https://notebooklm.google.com/notebook/ef52bf5a-f6d0-4a2a-aed4-b25d6520ab2c>

- Tencent Intelligent Document Space: <https://docs.qq.com/space/DUkRjYUtNWFdyV253>

According to the SRE principle, the physical foundation originates from information statistics.

According to the pipeline configuration specified in the *SRE Universal Graph Operator Pipeline & Release Roadmap*, **Operator 6** is designated as the **Sub-space Spectral Sieve & Splicing Operator** ($\mathcal{P}_{\text{sieve}} \cup \mathcal{O}_{\text{splice}}$). Operating as the final convergence component of the **Phase 1: Homogeneous Metric** cluster, this operator continuously streams its computed spectral prior invariants down to the subsequent pipelines of Operator 4 and Operator 5.

The core engineering objective of Operator 6 is to multiplex topological invariants within the local overlapping domains of the directed chain complex via **Algebraic Rayleigh-Ritz Splicing Kernels**. This mechanism successfully crushes the temporal computational overhead of global spectral space resolution from the traditional cubic synchronous deadlocks of $\mathcal{O}(n^3)$ down to a sparse sub-domain upper bound of $\mathcal{O}(m_g \cdot k_{\text{rank}})$, thoroughly eliminating global synchronous stalls across distributed Actor clusters.

I. Top-Level Algebraic Space Specification and Design Philosophy

In conventional graph signal processing and high-dimensional manifold reconstruction, executing a full spectral decomposition over the global Graph Laplacian matrix stands as the unique analytical method to extract global topological connectivity priors, such as the Fiedler vector and the algebraic connectivity $\lambda_2(n)$. However, global spectral decomposition induces two fatal deadlocks under distributed asynchronous Actor architectures:

1. **Global Synchronous Stalls:** State-of-the-art eigensolvers (e.g., the QR algorithm) require global synchronous data coordination across all localized partition Actors. The temporal overhead scales as $\mathcal{O}(n^3)$, triggering severe pipeline hanging under macro-scale system inflation.
2. **Information Renormalization Redundancy:** According to the high-dimensional renormalization pool principles of Status-Relational-Entropy (SRE) dynamics, the spontaneous mutation of low-dimensional macroscopic manifolds and causal information streams are exclusively locked by a minority of extreme eigenvalues at the bottom of the spectrum (e.g., $\lambda_2(n)$) and boundary limits. Computing higher-order spectral sub-spaces represents an extreme waste of algebraic overhead since they belong entirely to isotropic chaotic heat-death noise.

To rigidly bypass the $\mathcal{O}(n^3)$ complexity redline, Operator 6 completely abolishes global matrix spectral space scanning, substituting it with **Localized Sub-space Orthogonal Sieving** ($\mathcal{P}_{\text{sieve}}$) and **Boundary Homological Algebraic Splicing** ($\mathcal{O}_{\text{splice}}$).

1. Unified Mathematical Notation Index

To secure the algebraic completeness of the operator pipeline, the core algebraic symbols governing Operator 6 are defined as follows:

Symbol / Operator	Algebraic Description and Core Domain
$n \in \mathbb{N}^+$	Total node population of the global network (macro-scale system extension horizon).
$m_g \in \mathbb{N}^+$	Total count of independent local sub-domains (partition slices) segmented across the sparse network.
$N_K \in \mathbb{N}^+$	Upper bound of node population contained within a single local sub-domain (local horizon), strictly satisfying $N_K \ll n$.
$k_{\text{rank}} \in \mathbb{N}^+$	Low-rank invariant approximation order extracted by local Lanczos solvers, acting as a system-level hard-coded fixed hyperparameter.
$\mathbf{M}_\Omega \in \mathcal{M}_{\text{spin}}^{(N_K)}$	Read-only realized local matrix inherited by distributed Actors, populated purely by non-zero binary spin elements.
$\mathbf{L}_G \in \mathbb{R}^{n \times n}$	Global Graph Laplacian matrix (implicitly existing, requiring no physical storage or global assembly).
$\mathbf{K}_{\text{RR}}$	The compact Algebraic Rayleigh-Ritz Splicing Kernel matrix, with dimensions rigidly locked to $(m_g \cdot k_{\text{rank}}) \times (m_g \cdot k_{\text{rank}})$.

- **Mapping Coordinate Domain:**

$$\mathcal{P}_{\text{sieve}} \cup \mathcal{O}_{\text{splice}} : \mathcal{M}_{\text{spin}}^{(N_K)} \times \mathbb{R}^k \longrightarrow \mathbb{R}^+ \times \mathbb{R}^+$$

II. Mathematical Derivation of the Algebraic Rayleigh-Ritz Splicing Kernel

To extract the low-order extreme eigenpairs of the global Laplacian operator $\mathbf{L}_G$ without storing or assembling global matrices, Operator 6 constructs strict algebraic projection mappings over the local overlapping perimeters of the chain complex.

1. The Localized Sub-space Orthogonal Sieve Operator ($\mathcal{P}_{\text{sieve}}$)

Let the high-dimensional directed manifold grid be partitioned along the directed chain complex into m_g mutually overlapping local topological sub-domains $\Omega_1, \Omega_2, \dots, \Omega_{m_g}$. For any specific sub-domain Ω_α , its corresponding localized Laplacian matrix is denoted as $\mathbf{L}_{\Omega_\alpha} \in \mathbb{R}^{N_K \times N_K}$.

Operator 6 first activates the local spectral sieve operator $\mathcal{P}_{\text{sieve}}$. Utilizing Krylov subspace Lanczos iterations, this operator independently and concurrently extracts the k_{rank} lowest, topologically coherent eigenvectors at the local Actor level. This constructs the localized orthogonal sub-space basis matrix $\mathbf{V}_\alpha \in \mathbb{R}^{N_K \times k_{\text{rank}}}$, which strictly complies with the internal normalization constraint:

$$\mathbf{V}_\alpha^T \mathbf{V}_\alpha = \mathbf{I}_{k_{\text{rank}}} \quad (\forall \alpha \in \{1, 2, \dots, m_g\})$$

2. The Homological Topological Splicing Kernel Operator ($\mathcal{O}_{\text{splice}}$)

We define the Adjoint Splicing Mapping operator $\mathcal{O}_{\text{splice}}$, which synthesizes a global trial sub-space orthogonal basis matrix $\mathbf{V}_{\text{global}} \in \mathbb{R}^{n \times (m_g \cdot k_{\text{rank}})}$ by establishing algebraic restriction homologies across the overlap perimeters of adjacent sub-domains:

$$\mathbf{V}_{\text{global}} \equiv \bigoplus_{\alpha=1}^{m_g} \mathbf{V}_\alpha / \sim$$

where $\sim$ denotes the homological equivalence class slicing constraints executed across overlapping perimeter boundary nodes.

Utilizing this global trial subspace matrix as a macro-scale renormalization operator, the global complex Graph Laplacian $\mathbf{L}_G$ is implicitly projected into the low-dimensional trial subspace, constructing the highly compact **Rayleigh-Ritz Splicing Kernel matrix $\mathbf{K}_{\text{RR}}$** :

$$\mathbf{K}_{\text{RR}} \equiv \mathbf{V}_{\text{global}}^T \mathbf{L}_G \mathbf{V}_{\text{global}} \in \mathbb{R}^{(m_g \cdot k_{\text{rank}}) \times (m_g \cdot k_{\text{rank}})}$$

At runtime, due to the sparse nature of the global Laplacian $\mathbf{L}_G$ and the block-orthogonalized structure of the trial basis $\mathbf{V}_{\text{global}}$, each coordinate entry of $\mathbf{K}_{\text{RR}}$ can be evaluated locally by multiplexing the local fluid flux variances passed between distributed Actors along their overlap perimeters. **The entire routine bypasses the explicit construction, allocation, or physical storage of the global matrix $\mathbf{L}_G$.**

3. Closed-Form Extraction of Prior Spectral Invariants and Error Bound Clamping

By resolving the spectrum of the low-dimensional compact matrix $\mathbf{K}_{\text{RR}}$ via a local sub-step solver, the theoretical extreme boundaries of the global eigenvalues are extracted:

$$\lambda_2(n) \approx \lambda_2(\mathbf{K}_{\text{RR}}), \quad \alpha_n \approx \lambda_{\text{max}}(\mathbf{K}_{\text{RR}})$$

Theorem 6.1: Rayleigh-Ritz Approximation Accuracy Bound Theorem

According to the Ritz variational principle and classical projection error formulations, the absolute approximation error bounded between the Ritz eigenvalue $\lambda_i(\mathbf{K}_{\text{RR}})$ and the true global eigenvalue $\lambda_i(\mathbf{L}_G)$ is strictly governed by the maximal projection residual of the global trial subspace:

$$|\lambda_i(\mathbf{L}_G) - \lambda_i(\mathbf{K}_{\text{RR}})| \leq \gamma \cdot \|(\mathbf{I} - \mathbf{V}_{\text{global}} \mathbf{V}_{\text{global}}^T) \mathbf{L}_G \mathbf{V}_{\text{global}}\|_2^2$$

where $\gamma \in \mathbb{R}^+$ represents a constant linked to the spectral gap configuration. This bound ensures a quadratic polynomial convergence velocity as the homological consistency across overlap perimeters scales up.

Because the antecedent **Pre-Pruning Operator 2-Batch** ($\mathcal{O}_{\text{gate_batch}}$) acts as an early causal firewall that screens and intercepts all non-homomorphic bridge edges, the global topological connectivity of the maternal network is rigidly protected. According to foundational algebraic graph invariants, this guarantees that the global Fiedler prior streamed into the downstream pipelines constantly satisfies the strict closed positive-definite boundary:

$$\lambda_2(n) > 0$$

This non-zero lower bound directly immunizes the logarithmic and rational control parameters of Operator 4 and Operator 5 against floating-point singularities in zero-degree vacuum cuts.

■ Theorem 6.1 is complete.

III. Verification of Engineering Complexity Boundaries at Runtime

To comply strictly with the complexity boundary invariants dictated by the third segment of the systemic roadmap, Operator 6 must achieve complete decoupling from the cubic scaling expansion of the global node population under the thermodynamic limit.

Theorem 6.2: Sparse Sub-domain Clamping Theorem for Operator 6 Complexity

As the macro-scale system population scales infinitely ($n \rightarrow \infty$), the single-step temporal computational overhead $T_{\mathcal{O}_6}(n)$ of the composite operator ($\mathcal{P}_{\text{sieve}} \cup \mathcal{O}_{\text{splice}}$) extracting global extreme prior spectral invariants is rigidly clamped within the sparse sub-domain upper bound of $\mathcal{O}(m_g \cdot k_{\text{rank}})$. This algebraic reduction thoroughly eliminates global synchronous stalls across asynchronous distributed Actor slices.

Rigorous Proof

1. **Localized Sieve Phase:** Each distributed Actor independently executes the $\mathcal{P}_{\text{sieve}}$ operator over its designated slice. Because the endogenous topological firewall rigidly deadlocks the local horizon population of each partition subdomain to a finite, independent boundary constant ($N_K = |\Omega_{\text{local}}| \ll n$), extracting k_{rank} extreme eigenpairs via the local Lanczos solver requires a localized computational bound of $\mathcal{O}(N_K \cdot k_{\text{rank}})$.

Given that the m_g sub-domains undergo concurrent algebraic stream flow across the distributed Actor layer, total temporal overhead of this parallel execution phase is strictly determined by the maximal overhead generated by a single standalone partition slice. Consequently, the total concurrent overhead of this parallel stage collapses into a constant upper boundary:

$$\max_{\alpha} \mathcal{O}(N_K \cdot k_{\text{rank}}) = \mathcal{O}(1)$$

2. **Kernel Splicing Phase:** The evaluation of the non-zero elements within the compact Rayleigh-Ritz Splicing Kernel $\mathbf{K}_{\text{RR}}$ is determined exclusively by the boundary flux streams propagating along the overlapping perimeters. Computing the low-dimensional algebraic projection matrix product $\mathbf{V}_{\text{global}}^T \mathbf{L}_G \mathbf{V}_{\text{global}}$ requires a cumulative count of elementary scalar floating-point operations that scales linearly with the total partition count m_g and the localized invariant approximation order k_{rank} . This isolates the computational complexity of the projection phase strictly to $\mathcal{O}(m_g \cdot k_{\text{rank}})$.
3. **Kernel Spectrum Resolution Phase:** A dense eigensolver is activated to compute the extreme invariants of the compact Rayleigh-Ritz matrix $\mathbf{K}_{\text{RR}}$, yielding a nominal computational complexity bound of $\mathcal{O}((m_g \cdot k_{\text{rank}})^3)$. However, the low-rank invariant approximation order k_{rank} is an immutable system-level hyperparameter structurally deadlocked at the hardware logic plane. In standard physical deployments, this low-rank order is permanently constrained to satisfy:

$$k_{\text{rank}} \leq 6 \ll n$$

As a direct mathematical consequence, the cubic growth velocity of the matrix kernel spectrum term, expressed as $(m_g \cdot k_{\text{rank}})^3$, scales at a rate significantly weaker than any conventional polynomial expanding with respect to the macro-scale global node population n . This cubic term degenerates into a fixed constant coefficient overhead during asymptotic scaling analysis and ceases to govern or dominate the leading-order trend of the overarching complexity formulation.

4. **Asymptotic Convergence and Total Overhead Synthesization:** We assemble and evaluate the cumulative temporal overhead by performing a global algebraic summation of the independent processing phases resolved above. As the global network scales towards the thermodynamic limit ($n \rightarrow \infty$), the cubic divergence series dictated by global synchronous spectral operations is completely shattered.

The leading-order computational term of the operator is mathematically forced to settle within a strict linear upper bound governed exclusively by the total number of localized partition sub-domains. The ultimate asymptotic temporal complexity of Operator 6 is rigidly secured at:

$$\lim_{n \rightarrow \infty} T_{\mathcal{O}_6}(n) = \mathcal{O}(m_g \cdot k_{\text{rank}})$$

■ Theorem 6.2 is complete.

This formally satisfies the strict complexity boundary limits required to ensure uninterrupted execution across long-range distributed network iterations.

Operator 6 (Psieve U Osplice) Computational Complexity and Accuracy Clamping




Figure -1: Numerical verification suite for Operator 6.

Subplot 1: Complexity destruction red-line: execution-time comparison. The global synchronous spectral solver (red dashed) exhibits severe $\mathcal{O}(n^3)$ cubic growth as network size n increases. Operator 6 splicing-kernel runtime (green solid) remains weakly growing, verifying the $\mathcal{O}(m_g \cdot k_{\text{rank}})$ sparse-subdomain complexity bound.

Subplot 2: Algebraic approximation accuracy baseline for Theorem 6.1. Relative error of Fiedler eigenvalue $\lambda_2(n)$ decays monotonically with rising global node count n , confirming the convergence property of the Rayleigh-Ritz splicing projection.