

HTTP Performance

Abram Hindle

abram.hindle@ualberta.ca

Department of Computing Science

University of Alberta

<http://softwareprocess.es/>

CC-BY-SA 4.0

Performance on the Web

- Performance is a non functional requirement referring to how well a web site or service responds.
- Performance can be measured in terms
 - Requests
 - Volume
 - Latency
 - Bandwidth
 - Utilization

Google says...

- Web Performance Best Practices

https://developers.google.com/speed/docs/best-practices/rules_intro

- Optimizing caching — keeping your application's data and logic off the network altogether
- Minimizing round-trip times — reducing the number of serial request-response cycles
- Minimizing request overhead — reducing upload size
- Minimizing payload size — reducing the size of responses, downloads, and cached pages
- Optimizing browser rendering — improving the browser's layout of a page
- Optimizing for mobileNew! — tuning a site for the characteristics of mobile networks and mobile devices
 - Portions of this page are modifications based on work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.

Caching!

- Caching increase locality
- Locality increases bandwidth
- Locality decreases latency
- Levels of cache:
 - CPU
 - Memory
 - Disk
 - Network

Caching!

```
> GET /static/SoftwareProcess.es.html HTTP/1.1
> User-Agent: curl/7.32.0
> Host: softwareprocess.es
> Accept: */*
>
< HTTP/1.1 200 OK
< Date: Mon, 07 Apr 2014 03:09:26 GMT
* Server Apache is not blacklisted
< Server: Apache
< Last-Modified: Mon, 07 Apr 2014 03:00:05 GMT
< ETag: "215f-4f66b107fc739"
< Accept-Ranges: bytes
< Content-Length: 8543
< Vary: Accept-Encoding
< Content-Type: text/html; charset=utf-8
<
```

Caching! Do it Again!

```
> GET /static/SoftwareProcess.es.html HTTP/1.1
> User-Agent: curl/7.32.0
> Host: softwareprocess.es
> Accept: */*
>
< HTTP/1.1 200 OK
< Date: Mon, 07 Apr 2014 03:10:50 GMT
* Server Apache is not blacklisted
< Server: Apache
< Last-Modified: Mon, 07 Apr 2014 03:00:05 GMT
< ETag: "215f-4f66b107fc739"
< Accept-Ranges: bytes
< Content-Length: 8543
< Vary: Accept-Encoding
< Content-Type: text/html; charset=utf-8
<
```

Cold GET

softwareprocess.es/static/SoftwareProcess.es.html

Google



Abram is an assistant professor at the **University of Alberta**, in Edmonton, Alberta, Canada within the **Department of Computing Sciences**. He researches software engineering, mining software repositories, software process recovery and green mining (the study of software change versus software power consumption).

- **A general overview of my Research Record DBLP**
- **Current Version of my Curriculum Vitae**
- **I'd like to thank my numerous collaborators!**

Method	File	Domain	Type	Size	0 ms	160 ms	320 ms	480 ms	640 ms	800 ms
GET	SoftwareProcess.es.html	softwareprocess.es	html	8.34 KB	→ 204 ms					
GET	static.css	softwareprocess.es	css	4.08 KB	→ 100 ms					
GET	abram-smiling-profile.png	softwareprocess.es	png	24.86 KB	→ 412 ms					
GET	web-at-softwareprocess-do...	softwareprocess.es	png	3.74 KB	→ 169 ms					
GET	whiteback.png	softwareprocess.es	png	2.21 KB	→ 241 ms					
GET	gears.png	softwareprocess.es	png	17.66 KB	→ 338 ms					
GET	whitegrad.png	softwareprocess.es	png	0.37 KB	→ 228 ms					

All

HTML

CSS

JS

XHR

Fonts

Images

Media

Flash

7 requests, 61.29 KB, 0.72 s

Clear

Refresh

Research Promotion Site of Abram Hindle



Abram is an assistant professor at the **University of Alberta**, in Edmonton, Alberta, Canada within the **Department of Computing Sciences**. He researches software engineering, mining software repositories, software process recovery and green mining (the study of software change versus software power consumption).

Method	File	Domain	Type	Size	0 ms	160 ms	320 ms	480 ms
GET	SoftwareProcess.es.html	softwareprocess.es	html	8.34 KB	→ 175 ms			
GET	static.css	softwareprocess.es	css	4.08 KB	→ 106 ms			
GET	abram-smiling-profile.png	softwareprocess.es	png	24.86 KB	→ 98 ms			
GET	web-at-softwareprocess-do...	softwareprocess.es	png	3.74 KB	→ 94 ms			
GET	whiteback.png	softwareprocess.es	png	2.21 KB	→ 91 ms			
GET	gears.png	softwareprocess.es	png	17.66 KB	→ 98 ms			
GET	whitegrad.png	softwareprocess.es	png	0.37 KB	→ 88 ms			

All HTML CSS JS XHR Fonts Images Media Flash

7 requests, 61.29 KB, 0.49 s Clear


If I just type in the URL again

SoftwareProcess.es Wiki - Abram Hindle: SoftwareProcess.es - Nightly

SoftwareProcess.es W...

softwareprocess.es/static/SoftwareProcess.es.html

Research Promotion Site of Abram Hindle



Abram is an assistant professor at the **University of Alberta**, in Edmonton, Alberta, Canada within the **Department of Computing Sciences**. He researches software engineering, mining software repositories, software process recovery and green mining (the study of software change versus software power consumption).

- **A general overview of my Research Record** [DBLP](#)
- **Current Version of my Curriculum Vitae**
- **I'd like to thank my numerous collaborators!**
- **Abram's Blog**

What can I offer you?

Method: GET, File: SoftwareProcess.es.html, Domain: softwareprocess.es, Type: html, Size: 8.34 KB, 0 ms, 160 ms, 192 ms

Headers

Request URL: http://softwareprocess.es/static/SoftwareProcess.es.html
Request method: GET
Status code: 304 Not Modified

Response headers (0.185 KB)

- Connection: "Keep-Alive"
- Date: "Mon, 07 Apr 2014 03:23:55 GMT"
- Etag: "\"215f-4f66b107fc739\""
- Keep-Alive: "timeout=2, max=100"
- Server: "Apache"
- Vary: "Accept-Encoding"

Request headers (0.464 KB)

- Host: "softwareprocess.es"
- User-Agent: "Mozilla/5.0 (X11; Ubuntu; ...cko/20100101 Firefox/29.0)"

All, HTML, CSS, JS, XHR, Fonts, Images, Media, Flash, One request, 8.34 K..., Clear

Request URL: <http://softwareprocess.es/static/static.css>
Request method: GET
Status code: 200 OK Edit and Resend

New

Filter headers


Response headers (0.263 KB)

Accept-Ranges: "bytes"
Connection: "Keep-Alive"
Content-Length: "4187"
Content-Type: "text/css"
Date: "Mon, 07 Apr 2014 03:28:41 GMT"
Etag: "\"105b-47c394a65ac80\""
Keep-Alive: "timeout=2, max=99"
Last-Modified: "Sun, 03 Jan 2010 02:23:30 GMT"
Server: "Apache"

Request headers (0.377 KB)

Host: "softwareprocess.es"
User-Agent: "Mozilla/5.0 (X11; Ubuntu; ...ecko/20100101 Firefox/29.0"
Accept: "text/css,*/*;q=0.1"
Accept-Language: "en-US,en;q=0.5"
Accept-Encoding: "gzip, deflate"
DNT: "1"
Referer: "http://softwareprocess.es/static/SoftwareProcess.es.html"
Connection: "keep-alive"
Pragma: "no-cache"
Cache-Control: "no-cache"

Cache Headers



Request URL: `http://softwareprocess.es/static/static.css`
Request method: GET
Status code: 304 Not Modified Edit and Resend

Filter headers

Response headers (0.162 KB)

Connection: "Keep-Alive"
Date: "Mon, 07 Apr 2014 03:29:35 GMT"
Etag: "\"105b-47c394a65ac80\""
Keep-Alive: "timeout=2, max=100"
Server: "Apache"

Request headers (0.445 KB)

Host: "softwareprocess.es"
User-Agent: "Mozilla/5.0 (X11; Ubuntu; ...ecko/20100101 Firefox/29.0"
Accept: "text/css,*/*;q=0.1"
Accept-Language: "en-US,en;q=0.5"
Accept-Encoding: "gzip, deflate"
DNT: "1"
Referer: "http://softwareprocess.es/static/SoftwareProcess.es.html"
Connection: "keep-alive"
If-Modified-Since: "Sun, 03 Jan 2010 02:23:30 GMT"
If-None-Match: "\"105b-47c394a65ac80\""
Cache-Control: "max-age=0"

Refresh

Cache Headers

The diagram consists of a central point labeled 'Cache Headers' with four arrows pointing to specific headers in the network tool's display. One arrow points to the 'Etag' header in the response headers section. Another arrow points to the 'If-None-Match' header in the request headers section. A third arrow points to the 'If-Modified-Since' header in the request headers section. A fourth arrow points to the 'Cache-Control' header in the request headers section.

User Agent (Browser) Cache

- *Also, if the response does have a Last-Modified time, the heuristic expiration value SHOULD be no more than some fraction of the interval since that time. A typical setting of this fraction might be 10%. – RFC2616 section 13*
- This means if it was modified 10 minutes ago, you should probably hit it up again in a minute.
 - Where as if it was modified 100 days ago, you should get a new version 10 days from now.

User Agents (Browser) Cache

- Thus it is up to the browser to emit a request
- They do so upon expiry or last modified time heuristic
- Or the user forces a refresh
 - CTRL-SHIFT-R or ctrl-shift click on the refresh button
- In browser cache is the most local and high performance cache!

Cache-control

- Generally sent by User Agent
- Indicates how they want to handle this request
- It signals proxies and caches how to handle the request

Cache-Control: no-cache

- You must revalidate
 - We didn't give it a time
- A 304 response is fine
- Forces a request out to the server
- max-age=0 means the same thing

Cache-Control: no-store

- Don't store anything
- Suggests that the results are not-cacheable and ephemeral.
- Will not act as DRM

Cache-Control: max-age=

- Cache-Control: max-age=seconds in a HTTP response tells the Use-Agent the maximum age they should let this resource last
- Easy to deploy
- Cache-Control: max-age=259200
 - 3 Days
- Benefit: no date math for you!
- Benefit: No date formatting!
- Disadvantage: Have to predict max-age!

Response Header: Expires

- Expires tells the Use-Agent after which date they should ask for a new instance of the resource.
- Easiest to deploy
- Very simple
- Causes lots of problems if set wrong!
- Expires: Mon, 07 Apr 2014 03:00:05 GMT

Request Header: If-Modified-Since

- Conditional HTTP Request
- Return a 304 if not modified since
- If-Modified-Since: Mon, 07 Apr 2014 03:00:05 GMT
 - Don't send me anything new unless the resource has been modified after that time.
- If the response is anything but a 200 OK, return a normal response instead of the 304
-

Response Header: Last-Modified

- *The Last-Modified entity-header field value is often used as a cache validator. In simple terms, a cache entry is considered to be valid if the entity has not been modified since the Last-Modified value. – HTTP RFC 2616 Fielding et al.*
<http://www.w3.org/Protocols/rfc2616/rfc2616-sec13.html#sec13.3.1>

Response Header: Last-Modified

- Last-Modified is a date that the resource was last modified
- Used for simple caching
- Requires the HTTP server to respond

HTTP ETag

- What if you cannot guess or estimate the time that content will be safe?
- What if content updates all the time, unpredictably?
- What if content updates but all changes aren't that important:
 - E.g. your age does increase every second but maybe it isn't important to caching to have your age updated per each second?

HTTP ETag

- How do you make it?
- If strong (exact content) just use a hash like SHA1
- If weak then hash some content you think is relevant and prefix with W/"etagvalue" to indicate it is a weak hash
- If hashing is pointless make an etag of actual values in plaintext
- Keep it short

ETags: Entity Tags!

- HTTP Response Header
- Contains a name or tag indicating the content or revision of a resource.
 - Is not date related
 - Tends to be content related
 - Can be any value
 - Can use any hash

ETags: If-None-Match

- HTTP Request Header that makes the request conditional.
- If any of the provided e-tags match send us back a 304 status code, otherwise send us the resource!
- If-None-Match: "someetag"
- If-None-Match: "*" // rely on the date stuff, not etags
- If-None-Match: "etag1", "etag2"

ETags: If-Match

- HTTP Request Header that makes the request conditional.
- Used in updates to ensure the wrong version is not being updates (like a revision id)
- Provide "*" or an ETag
 - "*" means anything (e.g. you probably have it or it might not exist, but you're just checking)
- If-Match: "someetag"
- If-Match: "*"
- If-Match: "etag1", "etag2"

Dangers of the Etag

- Cookies part II
 - Etags allow for vendors (advertisers) to finger print your client because your client will send the etags back.
 - If you deny cookies, you tend to send etags.
 - AOL, Spotify, GigaOm, Etsy, KISSmetrics sued over undeletable tracking cookies
<http://www.extremetech.com/internet/91966-aol-spotify-gigaom-etsy-kissmetrics-sued-over-undeletable-tracking-cookies>
 - Ayenson, Mika, et al. "Flash cookies and privacy II: Now with HTML5 and ETag respawning." World Wide Web Internet And Web Information Systems (2011).
<ftp://peramides.com.ar/SSRN-id1898390.pdf>

Dangers of the Etag

- Too much information
 - Some Etags contain irrelevant information!
 - What if the browser reboots and the Etags are lost?
 - If the browser/user-agent had a timing guarantee this wouldn't be a problem

Performance, the Cross Cutting Concern

- Performance is a cross cutting concern because it interacts with other functionality:
 - Security
 - Lack of encryption means global proxying
 - Authentication can limit caching
 - Authentication can imply state
 - State
 - State can limit caching
 - State can limit layering

Round Trips

- DNS Lookups, Connections, HTTP transactions
- Async is fast: Just send it! Who cares when it arrives
- Rountrips are synchronous and slow: We must wait for a response!
 - Avoid HTTP Redirects that aren't cacheable
 - Rewrite Server Side
 - Avoid too many HTTP hosts
 - Can you piggyback?
 - CSS Sprites are often recommended to reduce number of image requests
 - Avoid CSS imports

Round Trip Tricks

- Use multiple static content hostnames:
 - Take a hit in DNS lookup
 - But improve parallel download performance
 - Static hosts should not be dynamic and have stable IPs

Reduce Request Size

- Giant Cookies – NOOOOOO
- Giant URIs -- NOOOOO
- Too many headers? NOOOOO
- Remember all that networking we went over?
 - Try to fit within the MTU!

Avoid Dynamism and Cookies for Static Content

- For static content, do GETs to get it
 - For static content avoid dynamism and cookies
 - Cookies imply state and can mess up caching
- Use separate domains for static content to avoid statefulness

Minimize Resource Size

- Images – too big
- Javascript – minify (I dislike this one)
- GZIP Encoding!
- Sound – too big
- Video – too big
 - You can fake Sound and Video in JS!

Minimize Number of Resources

- 1 or 0 CSS Files
- 1 or 0 Javascript Files
- 1 or 0 Images (CSS Sprites)
- 1 or 0 HTML Files
 - You could generate a page in JS and take no hit.
- 1 giant page has the problem if it is dynamic, but if it is 1 giant page that does dynamic things you can cache that page and never have to get HTML/JS/CSS again.

Optimize Rendering

- Recommendations:
 - CSS at the top
 - Javascript at the bottom
 - Content in the middle
- Give appropriate sizes and hints
 - The layouter is quite expensive, give some hints and it will go to town.

Defer Javascript

- Nasty trick:
 - Encode javascript as a string and eval it later when you need it.
 - Avoids heavy page loading and JS parsing with the browser is working hard.
 - CPU driven

Content Delivery Networks

- These are global networks of content providers that can mirror your content.
- Excellent latency and locality
- Great for static stuff
- \$\$\$

GZIP It!

- Turn on GZIP encoding to make things smaller
 - Watch out! This affects latency
 - Improves bandwidth
 - Balancing act
 - Generally recommended

Fix DNS

- Use A and AAAA records instead of CNAMEs
- Have your authoritative name server give the results
- Allow for caching of DNS requests to avoid excessive lookups
- Provide many A records in 1 response
- Reduce number of hosts on 1 page
- Some recommend using CNAME to allow multiple connections (so it depends!)

Avoid Indirection

- Redirections
- Imports
- Dynamic choosing of content
- Javascript downloading of content

Avoid POST

- POST is not idempotent
- POST is not cacheable
- POST is dynamic
- POST smashes all the performance infrastructure in a fine powder and blows it into your face.

Check for Errors

- 403s, 404s, 410s, etc. Are all slow
 - Often the server works harder to serve an error than it does to serve real content.
 - Errors cause exceptions, exceptions cause latency and pain and reporting.
 - Errors cause logging – more IO
 - Errors are worthless requests hogging up resources

Encoding!

- Sending a JSON encoding is not always appropriate in terms of size.
- Sending an audio stream as ASCII text? Bad idea. Use an appropriate format.
- Do you need lossy or lossless?
- Do you need XML? JSON? CSV? Binary?

Repeat yourself or don't repeat yourself

- Cache matters if the cache can avoid you repeating yourself then go for it.
- But sometimes denormalizing data and providing duplicate information avoids more requests.

Async over Sync

- Asynchronous means that you can do other things while something is occurring.
- Synchronous is blocking which implies latency.
- Synchronous means round trips
- Async means parallelizable
- Synchronous means serialized

Javascript Includes...

- Some people like to include common libraries from the library homepage.
 - Benefit: Someone else has done this so the user has cached it.
 - Disadvantage: What if they get hacked
 - Disadvantage: What if they are slower than you?
 - Disadvantage: What if you lose locality?

Resources

- RFC 2616 Section 13
<http://www.w3.org/Protocols/rfc2616/rfc2616-sec13.html>
- RFC 2616 Section 14
<http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html>
- Web Performance Best Practices
https://developers.google.com/speed/docs/best-practices/rules_intro

Resources

- HTTP Caching
<https://developers.google.com/speed/articles/caching>
- Best Practices for Speeding Up Your Web Site
<http://developer.yahoo.com/performance/rules.html>
- Browser Cache Matters
<http://yuiblog.com/blog/2007/01/04/performance-research-part-2/>

Resources

- Chapter 10 — Improving Web Services Performance
<http://msdn.microsoft.com/en-us/library/ff647786.aspx>
- 19 Tuning Web Services
http://docs.oracle.com/cd/E24329_01/web.1211/e24390/webservicestune.htm