Lab 2: Hexadecimal and Branching

J. Nelson Amaral

What you need to do

Given a 32-bit word:

bbbb bbbb bbbb bbbb bbbb bbbb bbbb bbbb

if *it is the binary code of a MIPS branch instruction*

then

print the assembly of the instruction using the following format (example):

beq $8, $9, 0x00400130

else

do nothing

Address of the branch target instruction

How do you know if it is the code of a MIPS Instruction?

MIPS branch-instruction encodings

Instruction	Binary
bgez $s, offset	0000 01ss sss0 0001 iiii iiii iiii iiii
bgezal $s, offset	0000 01ss sss1 0001 iiii iiii iiii iiii
bltz $s, offset	0000 01ss sss0 0000 iiii iiii iiii iiii
bltzal $s, offset	0000 01ss sss1 0000 iiii iiii iiii iiii
beq $s, $t, offset	0001 00ss ssst tttt iiii iiii iiii iiii
bne $s, $t, offset	0001 01ss ssst tttt iiii iiii iiii iiii
blez $s, offset	0001 10ss sss0 0000 iiii iiii iiii iiii
bgtz $s, offset	0001 11ss sss0 0000 iiii iiii iiii iiii

Printing Format

Address of the branch target instruction

beq $8, $9, 0x00400130

How is this 32-bit value obtained?



The input to disassembleBranch

$a0 contains the address of the assembly instruction.



The input to disassembleBranch

$a0 contains the address of the assembly instruction.



Hexadecimal

Value	Binary	Digit
0	0000	0
1	0001	1
2	0010	2
3	0011	3
4	0100	4
5	0101	5
6	0110	6
7	0111	7

Value	Binary	Digit
8	1000	8
9	1001	9
10	1010	a
11	1011	b
12	1100	c
13	1101	d
14	1110	e
15	1111	f

- Example: eca8 6420
  - 1110 1100 1010 1000 0110 0100 0010 0000

Manipulating the Offset

$a0 contains the address of the assembly instruction.



Computing the Target

$a0 contains the address of the assembly instruction.





Computing the Target



ASCII Table

Dec	Hx	Oct	Char	Dec	Hx	Oct	Html	Chr	Dec	Hx	Oct	Html	Chr	Dec	Hx	Oct	Html	Chr
0	0	000	NUL (null)	32	20	040		Space	64	40	100	@	@	96	60	140	`	`
1	1	001	SOH (start of heading)	33	21	041	!	!	65	41	101	A	A	97	61	141	a	a
2	2	002	STX (start of text)	34	22	042	"	"	66	42	102	B	B	98	62	142	b	b
3	3	003	ETX (end of text)	35	23	043	#	#	67	43	103	C	C	99	63	143	c	c
4	4	004	EOT (end of transmission)	36	24	044	$	$	68	44	104	D	D	100	64	144	d	d
5	5	005	ENQ (enquiry)	37	25	045	%	%	69	45	105	E	E	101	65	145	e	e
6	6	006	ACK (acknowledge)	38	26	046	&	&	70	46	106	F	F	102	66	146	f	f
7	7	007	BEL (bell)	39	27	047	'	'	71	47	107	G	G	103	67	147	g	g
8	8	010	BS (backspace)	40	28	050	(	(	72	48	110	H	H	104	68	150	h	h
9	9	011	TAB (horizontal tab)	41	29	051	)	)	73	49	111	I	I	105	69	151	i	i
10	A	012	LF (NL line feed, new line)	42	2A	052	*	*	74	4A	112	J	J	106	6A	152	j	j
11	B	013	VT (vertical tab)	43	2B	053	+	+	75	4B	113	K	K	107	6B	153	k	k
12	C	014	FF (NP form feed, new page)	44	2C	054	,	,	76	4C	114	L	L	108	6C	154	l	l
13	D	015	CR (carriage return)	45	2D	055	-	-	77	4D	115	M	M	109	6D	155	m	m
14	E	016	SO (shift out)	46	2E	056	.	.	78	4E	116	N	N	110	6E	156	n	n
15	F	017	SI (shift in)	47	2F	057	/	/	79	4F	117	O	O	111	6F	157	o	o
16	10	020	DLE (data link escape)	48	30	060	0	0	80	50	120	P	P	112	70	160	p	p
17	11	021	DC1 (device control 1)	49	31	061	1	1	81	51	121	Q	Q	113	71	161	q	q
18	12	022	DC2 (device control 2)	50	32	062	2	2	82	52	122	R	R	114	72	162	r	r
19	13	023	DC3 (device control 3)	51	33	063	3	3	83	53	123	S	S	115	73	163	s	s
20	14	024	DC4 (device control 4)	52	34	064	4	4	84	54	124	T	T	116	74	164	t	t
21	15	025	NAK (negative acknowledge)	53	35	065	5	5	85	55	125	U	U	117	75	165	u	u
22	16	026	SYN (synchronous idle)	54	36	066	6	6	86	56	126	V	V	118	76	166	v	v
23	17	027	ETB (end of trans. block)	55	37	067	7	7	87	57	127	W	W	119	77	167	w	w
24	18	030	CAN (cancel)	56	38	070	8	8	88	58	130	X	X	120	78	170	x	x
25	19	031	EM (end of medium)	57	39	071	9	9	89	59	131	Y	Y	121	79	171	y	y
26	1A	032	SUB (substitute)	58	3A	072	:	:	90	5A	132	Z	Z	122	7A	172	z	z
27	1B	033	ESC (escape)	59	3B	073	;	;	91	5B	133	[	[	123	7B	173	{	{
28	1C	034	FS (file separator)	60	3C	074	<	<	92	5C	134	\	\	124	7C	174			|
29	1D	035	GS (group separator)	61	3D	075	=	=	93	5D	135	]	]	125	7D	175	}	}
30	1E	036	RS (record separator)	62	3E	076	>	>	94	5E	136	^	^	126	7E	176	~	~
31	1F	037	US (unit separator)	63	3F	077	?	?	95	5F	137	_	_	127	7F	177	&#127;	DEL

Source: www.LookupTables.com

ASCII Table

Dec	Hx	Oct	Html	Chr
48	30	060	0	0
49	31	061	1	1
50	32	062	2	2
51	33	063	3	3
52	34	064	4	4
53	35	065	5	5
54	36	066	6	6
55	37	067	7	7
56	38	070	8	8
57	39	071	9	9

Dec	Hx	Oct	Html	Chr
96	60	140	`	`
97	61	141	a	a
98	62	142	b	b
99	63	143	c	c
100	64	144	d	d
101	65	145	e	e
102	66	146	f	f

Printing the Target

beq $8, $9, 0x00400130

Convert into 0x?? (The ASCII code for '0')

0000 0000 0100 0000 0001 0011 0000

$t1 0x0040 0130