

An Overview Of Immersive Scientific Visualization

Zhongyuan Yu

algoyu@163.com

Stefanie Krell

stefanie.krell@mailbox.tu-dresden.de

1. Introduction

Scientific Visualization is the visualization of scientific phenomena. That includes the visualization of flow, particles, terrain, volume and tensors. The purpose is to enable scientists to understand, illustrate and get insight from their data. The data is often very large and most of the time 3D. The use of stereoscopic images can improve the depth cue and the perception of the spatial relationships which might be crucial for scientist when analyzing data.

Virtual reality can give a sense of presence or immersion in an 3D environment. It is a class of computer-controlled multisensory communication technologies that allow more intuitive interactions with data and involve human senses in new ways. Nowadays head mounted displays (HMDs) like Oculus Rift1 or HTC Vive2 are widely available. That is one way to experience VR. As described in this paper [1], another way are systems like the CAVE. It is an immersive virtual reality environment where projectors are directed to between three and six of the walls of a room-sized cube. It uses motion capture system, which records the real time position of the user, for interaction. When using VR for Scientific Visualization, scientists can explore the data in ways which might lead to insights they would otherwise not get.

2. Difficulties in This Field

2.1. Processing Data:

In immersive VR, exploring in a high complexity or a high dimensionality modern data set is difficult. According to Donalek et al. [2], collaborative investigating in abstract representation of high-dimensional data and feature spaces is even harder. More advanced techniques should be introduced to view feature vectors in a space of tens to hundreds of dimensions.

2.2. Rendering:

General challenges in VR are stereo rendering, the high rendering quality and high frame rates of 90 fps to avoid nausea. Because of these reasons applications reduce precision and density to match the criteria. For rendering of 3D point clouds, thinning respective point clouds [3] and

converting them to 3D meshes [4] can be a way. Discher et al. [5] introduced performance optimization techniques e.g. Reverse Painter's Algorithm and image optimization techniques like adaptive point size and paraboloid rendering.

In [6] they used a distributed, image-parallel algorithm to perform volume rendering of electron density fields and to ray-cast ball-and-stick glyph in one pass to speed up rendering for large-scale molecular dynamics simulations. For molecular visualization Stone et al. [7] used a 2-phase rendering system that combines omnidirectional stereoscopic ray tracing with high-performance view-dependent rasterization to provide one or multiple users with high-quality immersive visualization. When viewing primary representations of molecular, the performance of the system is significantly degraded with increasing amount of atoms and bonds model. To solve this, Wiebrands et al. [1] implemented the system with GPU instance rendering method in Unity3d engine.

Interactive scenes such as those used in games are costly in terms of memory and computation. Of the rendering methods used for particle fluids, most are not suitable for real-time use in games. This could be achieved by improving the algorithms or mathematical formulations during the rendering process. In [8] they have incorporated a few ideas from Level-sets method, and reduced the computational complexity for the purpose of real-time performance.

2.3. Interaction:

Tracing labeled neurons manually is time-consuming, may require months to reconstruct even small portions of the brain. It is more challenging working with image slices with fixed viewpoint [9]. Tools such as Vaa3D and NeuroLucida 360 also have their drawbacks. A better tool with immersive environment for tracing should be build.

2.4. Displaying:

Current running stereoscopic 3D applications using large screen multiuser display are generally an order of magnitude slower than on high end desktop PCs. For example, paper [1] tries to solve this problem. Thus, faster displaying algorithms specialized for large screens should be introduced.

References

- [1] Michael Wiebrands, Chris J. Malajczuk, Andrew J. Woods, Andrew L. Rohl, and Ricardo L. Mancera. Molecular Dynamics Visualization (MDV): Stereoscopic 3D Display of Biomolecular Structure and Interactions Using the Unity Game Engine. *Journal of Integrative Bioinformatics*, 15(2):1–8, 2018.
- [2] Ciro Donalek, S G Djorgovski, Alex Cioc, Anwell Wang, Jerry Zhang, Elizabeth Lawler, Stacy Yeh, Ashish Mahabal, Matthew Graham, Andrew Drake, Scott Davidoff, Jeffrey S Norris, and Giuseppe Longo. Immersive and Collaborative Data Visualization Using Virtual Reality Platforms. pages 609–614, 2014.
- [3] Ravi Peters and Hugo Ledoux. Robust approximation of the medial axis transform of lidar point clouds as a tool for visualisation. *Computers & geosciences*, 90:123–133, 2016.
- [4] Matthew Berger, Andrea Tagliasacchi, Lee M Seversky, Pierre Alliez, Gael Guennebaud, Joshua A Levine, Andrei Sharf, and Claudio T Silva. A survey of surface reconstruction from point clouds. 36(1):301–329, 2017.
- [5] Sören Discher, Leon Masopust, Sebastian Schulz, Rico Richter, and Jürgen Döllner. A Point-Based and Image-Based Multi-Pass Rendering Technique for Visualizing Massive 3d Point Clouds in VR Environments. *Journal of WSCG*, 26(2), 2018.
- [6] Khairi Reda, Aaron Knoll, Ken-ichi Nomura, Michael E. Papka, Andrew E. Johnson, and Jason Leigh. Visualizing large-scale atomistic simulations in ultra-resolution immersive environments. pages 59–65, October 2013.
- [7] J. E. Stone, W. R. Sherman, and K. Schulten. Immersive Molecular Visualization with Omnidirectional Stereoscopic Ray Tracing and Remote Rendering. pages 1048–1057, May 2016.
- [8] Wladimir J. van der Laan, Simon Green, and Miguel Sainz. Screen space fluid rendering with curvature flow. 1(212):91, 2009.
- [9] Will Usher, Pavol Klacansky, Frederick Federer, Peer Timo Bremer, Aaron Knoll, Jeff Yarch, Alessandra Angelucci, and Valerio Pascucci. A Virtual Reality Visualization Tool for Neuron Tracing. *IEEE Transactions on Visualization and Computer Graphics*, 24(1):994–1003, 2018.