Bimanual Cooperative Manipulation on a Shared-Workspace Dual-Arm Testbed

When Two Hands Are Required, and the Coordination They Demand

Yugandhar Kulkarni

DES Pune University, Pune, India
github.com/yugandhar-k

Abstract. We study bimanual cooperative manipulation on a simulated dual-arm testbed built as a faithful extension of a validated single-arm platform: two 6-DoF arms face each other across a shared table, reusing the original arm model and inverse kinematics so the single-arm benchmark it was validated on is preserved exactly. On this testbed we measure, rather than assume, two things. First, two synchronized arms carry an oversized payload — too wide for one gripper and mass-heavy in the middle — level to within 0.0°, where a single arm cannot do better than 30° of tilt, and this degrades smoothly and quantifiably as the two arms are desynchronized. Second, an apparently two-hand task — closing a press-fit lid on a can — is in fact done cleanly by one hand, because the table supplies the constraint the second hand would have, while the naive two-arm attempt is worse. Together these results give a simple, measured test for when a second hand is genuinely required and what coordination it then demands.

Keywords: dual-arm manipulation · bimanual coordination · cooperative lifting · closed-chain control · robot simulation.

1 Introduction

A single robotic manipulator, however dexterous, is fundamentally limited to tasks an object can be manipulated through one point of contact. A great many everyday manipulation tasks are not of this kind: carrying a tray or a long workpiece, steadying a container while acting on it, assembling two parts that must be brought together. These require two hands acting on the same object at the same time, with coordination between them. This chapter studies that coordination on a simulated dual-arm testbed built as a direct extension of a single-arm manipulation and perception platform.

We ask two questions that are easy to state and surprisingly easy to get wrong. First: which seemingly two-hand tasks genuinely require two hands, and which can one hand do once the world (a table, a wall) is allowed to help? Second: for the tasks that do require two hands, what coordination between the

arms is needed, and how gracefully or abruptly does performance fall off as that coordination is degraded? We answer both with measured results rather than assertion, in keeping with the benchmark-driven discipline of the underlying platform.

Our contributions are:

- A shared-workspace dual-arm testbed in which two 6-DoF arms face each other across a table, built by replicating the exact arm model and inverse kinematics of a previously validated single-arm manipulation platform, so that the single-arm results it was validated on are preserved bit-for-bit.
- A cooperative-lift task and controller in which the two arms grasp the two ends of an oversized payload and raise it in lockstep through a shared closed kinematic chain, with an explicit synchronization barrier before the lift.
- A quantitative coordination study: the lift is carried level to within 0.0° of tilt on average, a single arm cannot carry it better than 30°, and performance degrades smoothly and measurably as the two arms are desynchronized.
- An honest negative result: closing a press-fit lid on a can — a textbook "two-hand" task — is in fact done cleanly by one arm, because the table back-stops the can; the naive two-arm version is worse, not better. This sharpens a small taxonomy of when a second hand is genuinely necessary.

2 Related Work

Bimanual and dual-arm manipulation has a long history in robotics, motivated by the classes of task a single arm cannot perform: cooperative transport of large or heavy payloads, in-hand and between-hand regrasping, and assembly where one hand fixtures while the other works. When two arms grasp one rigid object they form a closed kinematic chain, and the central control problem becomes maintaining a consistent relative pose and avoiding large internal forces — a coordination problem rather than two independent reaching problems. Our cooperative-lift task and its synchronization analysis sit squarely in this tradition, in a deliberately minimal, fully reproducible simulation.

The arm, its analytic-plus-damped-least-squares inverse kinematics, the grasp mechanics, and the vision used to find and localise objects are inherited unchanged from the single-arm platform this work extends, where they were validated against a cross-camera object-classification benchmark. We reuse that machinery rather than re-deriving it, and focus this chapter entirely on the coordination between arms.

3 The Shared-Workspace Dual-Arm Testbed

The testbed places two identical 6-DoF revolute arms, each with a two-finger parallel claw, on opposite edges of a common table and yaws them to face each other, so both reach a shared central region — the precondition for any two-hand task. Crucially, the arm is not re-modelled: a single parameterised description

emits the arm body (links, joints, claw, and claw camera) under a name prefix and at an arbitrary base pose, and the single-arm scene and the dual-arm scene both instantiate it. The single-arm classification benchmark therefore produces identical numbers before and after the extension, a property we assert as a regression check.

Each arm is driven by its own inverse-kinematics solver. The only addition the two-arm setting requires is awareness of the arm's mounting yaw: the numerical damped-least-squares solve is already frame-agnostic, and the closed-form seed is computed in the arm's own base frame, so an arm rotated to face its partner reaches the shared centre with the same sub-millimetre closed-form accuracy as the original forward-facing arm. Both arms converge on the shared centre under full physics to about 2 mm of servo error.

4 Tasks and Coordination Mechanisms

4.1 Cooperative lift of an oversized payload

The payload is a dumbbell lying along the line joining the two arms: a wide central block, wider than a single gripper's open span and so ungraspable by one hand, joined to a thin graspable rod at each end. The only way to pick it up is for each arm to take one end; and because the mass is concentrated in the middle, one hand on one end rod merely torques the payload out of level.

The two arms run one shared phase clock: approach, descend, grasp, lift, hold, lower, release. Two coordination mechanisms make the lift work. First, a synchronization barrier: the team does not advance from grasping to lifting until both grippers' own joint encoders confirm a grasp. Second, within the lift both tool frames follow the identical vertical profile, so the shared rigid payload is raised level rather than see-sawed. We probe the importance of the second mechanism directly by delaying one arm's lift relative to the other by a controlled lag.

4.2 Lid close: stabilize and act

The second task is the one intuition most readily calls "two-handed": seating a press-fit lid on a free-standing can. One arm is to grip and steady the can while the other grips the lid by its stem, carries it over, and presses it home. We implement both a two-arm version and a one-arm version (the lid arm alone, the can left free standing) and measure, in each, whether the lid ends up seated and centred and whether the can is displaced.

5 Experiments and Results

5.1 Cooperative lift

Across 8 trials with the payload's resting pose randomly perturbed (a few millimetres and a few degrees), the synchronized two-arm lift carries the dumbbell

Table 1. Cooperative lift: peak payload tilt from level (lower is better).

Condition	Peak tilt (deg)	Payload carried level?
Single arm (one end rod)	29.8	no (dangles)
Two arms, synchronized	0.0 ± 0.0	yes
Two arms, 0.4 s desync	15.1	no (see-saws)




Fig. 1. The cooperative lift degrades smoothly as the two arms desynchronize: peak payload tilt and the height gap between its two ends both grow with the inter-arm lag.

to a peak tilt of only 0.0°± 0.0° from level, with the two ends staying within 0.1 mm of the same height, and the payload held throughout on 8 of 8 trials. A single arm grasping the only point it can — one end rod — cannot do better than 30° of tilt (Table 1): it lifts the payload but leaves it dangling, because the mass hangs a lever-arm away from the single grasp. Carrying the payload level is, measurably, a two-hand task.

The synchronization itself is what matters, not merely having two arms. Figure 1 sweeps the inter-arm lag during the lift from 0 to 0.5 s. At zero lag the payload stays level; by a 0.4 s lag it tilts 15.1° and its two ends differ in height by 62 mm as one end rises before the other. Coordination quality, not arm count, sets the outcome, and it degrades smoothly — there is a usable tolerance band, not a cliff. Figure 2 summarises the three conditions.

5.2 Lid close: an honest negative

The lid-close result is the opposite of the intuition. One arm alone seats the lid essentially perfectly — 0.9 mm off centre, the can displaced by 0.1 mm — because the table back-stops the can against the downward press; the second hand is simply not needed. Worse, the naive two-arm version fails (Table 2): with both arms converging on the same small can, they contend for it and knock




Fig. 2. Peak payload tilt by condition. A single arm cannot keep the oversized payload level; two synchronized arms keep it to within a degree; desynchronized arms see-saw it.

Table 2. Lid close: an apparent two-hand task that one hand does better.

Condition	Lid off-centre (mm)	Can displaced (mm)	Seated?
One hand (can free-standing)	0.9	0.1	yes
Two hands (one holds the can)	185.6	124.2	no

it 124 mm aside. The lesson is not that coordination is unhelpful but that a task only needs a second hand when the world cannot supply the missing constraint — here the table already does.

6 Discussion

Taken together the two tasks suggest a simple test for when a second hand is genuinely required: a second hand is necessary exactly when the task needs a constraint that neither the first hand nor the environment can supply. Carrying the oversized payload needs a second support the world cannot provide (there is no table under a payload in flight, and the object exceeds one gripper), so two hands are required — and, being a closed chain, they must be coordinated in space and time. Seating the lid needs the can held still, but the table already supplies that against a vertical press, so one hand suffices. The coordination the genuine case demands is itself of a specific kind: tight spatio-temporal synchronization on a shared rigid body, distinct from the looser role-differentiation (one holds, one acts) that the lid task would have needed had the world not helped.

7 Limitations and Future Work

- Simulation only. The dynamics, contacts and friction are idealised; a sim-to-real study with domain randomisation is the natural next step, as it is for the underlying single-arm platform.
- A third genuinely two-hand regime — handover across a partitioned workspace — is identified but not completed here: it exposed a reach limitation of one arm at the far side of the shared centre under load, which a workspace-management and reachability-aware planning layer should resolve.
- Screw (threaded) lid closing, which genuinely needs counter-torque and hence two hands, is left to future work because it requires continuous rotational contact and finger regrasping that rigid-body position control does not capture cleanly.
- The two arms do not yet share a collision-avoidance layer for arbitrarily overlapping reach; the present tasks keep each arm's working volume largely separate. A reservation-based deconfliction layer is the clear extension for dense shared-workspace operation.

8 Conclusion

We built a shared-workspace dual-arm testbed as a faithful extension of a validated single-arm platform, and used it to measure, rather than assume, bimanual coordination. Two synchronized arms carry an oversized payload level to within a degree where one arm cannot, and performance degrades smoothly and measurably as the arms are desynchronized — a clean, quantitative coordination result. At the same time, a canonical "two-hand" task, closing a lid, turns out to need only one hand once the environment is allowed to help. The second finding disciplines the first: a second hand earns its place only when it supplies a constraint nothing else can, and when it does, the coordination it demands can be stated, measured, and designed for.

References

1. Smith, C., Karayiannidis, Y., et al.: Dual arm manipulation — a survey. Robotics and Autonomous Systems 60(10), 1340–1353 (2012)
2. Caccavale, F., Uchiyama, M.: Cooperative manipulation. In: Springer Handbook of Robotics, pp. 989–1006. Springer (2016)
3. Hutchinson, S., Hager, G.D., Corke, P.I.: A tutorial on visual servo control. IEEE Trans. Robotics and Automation 12(5), 651–670 (1996)
4. Todorov, E., Erez, T., Tassa, Y.: MuJoCo: A physics engine for model-based control. In: IEEE/RSJ IROS, pp. 5026–5033 (2012)
5. Kulkarni, Y.: Does fixed mean occluded? A cross-validated benchmark of eye-in-hand vs. fixed-camera baselines for robotic manipulation. Preprint (2026)