A PROJECT REPORT

ON

AI BASED SPAM FILTER (Naive Bayes)

SUBJECT: FUNDAMENTALS IN AI AND ML

Topic: AI Spam Filter (Manual Implementation)
Degree: Bachelor of Technology (B.Tech)
Technique: Naive Bayes Algorithm (From Scratch)

Submitted By:
Name: Yug Kartik Yadav
Reg. Number: 25BCE11199

Contents

1 Introduction 2

2 Objective 2

3 System Requirements 2

4 Theoretical Background 3

5 Code Analysis (Relating Theory to Code) 3

6 Source Code 4

7 Output Screenshots 5

8 Conclusion 6

9 Bibliography 6

1. Introduction

In the digital age, communication is primarily driven by emails and text messages. However, this convenience comes with the cost of **Spam**—unwanted, unsolicited digital communication that is often sent in bulk. Spam is not just a nuisance; it can be dangerous, containing phishing links, malware, or fraudulent schemes.

This project, **"AI Based Spam Filter,"** aims to solve this problem using **Artificial Intelligence**. Specifically, it uses the **Naive Bayes** algorithm to "read" a message and calculate the mathematical probability of it being Spam or Ham (legitimate).

Unlike commercial filters that use complex, hidden libraries, this project implements the mathematical logic **manually** in Python, ensuring a transparent understanding of how the AI actually thinks.

2. Objective

The main objectives of this project are:

1. To build a functional application that can classify text messages as "SPAM" or "NOT SPAM".
2. To demonstrate the working of **Bayes' Theorem** in real-world scenarios.
3. To implement **Natural Language Processing (NLP)** concepts like Tokenization and Bagof-Words without using external libraries like Scikit-Learn.
4. To create a lightweight, fast, and transparent filtering system suitable for demonstration in a **Fundamentals in AI and ML** course.

3. System Requirements

To develop and run this project, the following hardware and software specifications are required:

Hardware

- **Processor:** Intel Core i3 or equivalent (Minimal processing power needed).
- **RAM:** 4GB or higher.
- **Storage:** 100MB free space.

Software

- **Operating System:** Windows 10/11, macOS, or Linux.
- **Programming Language:** Python 3.8 or higher.
- **Libraries Used:**
  - math (Standard Python library for Logarithms).
  - re (Standard Python library for Regex/Text Cleaning).
  - **NO** external AI libraries (like sklearn/numpy) were used to ensure originality.

4. Theoretical Background

The project is based on the **Naive Bayes Classifier**, a probabilistic machine learning model rooted in Bayes' Theorem.

The Core Formula (Bayes' Theorem)

The probability that a message is spam given a specific word W is:

$$P(Spam|W) = \frac{P(W|Spam) \cdot P(Spam)}{P(W)}$$

Laplace Smoothing

To handle words that the model has never seen before (which would normally cause a probability of 0), we use **Laplace Smoothing**. We add 1 to the count of every word, ensuring no probability is ever truly zero.

$$\frac{\text{count}(w,c)+1}{\text{count}(c)+|V|+1} \quad P(w|c) =$$

5. Code Analysis (Relating Theory to Code)

This section maps the mathematical concepts directly to the functions implemented in manual_spam_filte

A. Preprocessing (The "Bag of Words")

Theory: The AI cannot read sentences; it needs a list of words (tokens).
Code Implementation: The function clean_text(self, text) performs this task.

```
W
```

Relation: This line uses Regex to strip punctuation and split sentences into a "bag" of individual words, which serves as the input for the algorithm.

B. Training (Learning Probabilities)

Theory: The AI must learn $P(Word|Spam)$. This is simply counting how many times a word appears in spam messages vs. total spam words. **Code Implementation:** Inside the train() function:

```
S
```

Relation: This loop builds the frequency dictionary (the "memory" of the AI), effectively calculating the numerators for our probability formulas.

C. Laplace Smoothing (Handling Unknowns)

Theory: $\frac{Count+\alpha}{Total+\alpha \times VocabularySize}$
Code Implementation: The function calculate_word_probability implements this exact formula:

```
numerator = self.spam_word_counts.get(word, 0) + self.smoothing_alpha denominator = self.spam_total_words +
(self.smoothing_alpha * vocab_size) return numerator / denominator
```

Relation: self.smoothing_alpha represents α (set to 1), preventing division by zero or zeroprobability errors for new words.

D. Prediction (Log-Likelihood)

Theory: Multiplying probabilities causes "underflow" (numbers becoming too small). We use Logarithms to change multiplication to addition: $\log(A \times B) = \log(A) + \log(B)$. **Code Implementation:** Inside the predict() function:

```
spam_score += math.log(self.calculate_word_probability(word, True))
```

Relation: Instead of multiplying raw probabilities, we sum their logarithms (math.log). If spam_score > ham_score, the message is classified as Spam.

6. Source Code

Filename: manual_spam_filter.py

```
import math import re

class ManualNaiveBayes:
    def __init__(self):
        self.spam_word_counts = {} self.ham_word_counts =
        {} self.spam_total_words = 0 self.ham_total_words = 0
        self.spam_msg_count = 0 self.ham_msg_count = 0
        self.vocabulary = set() self.prob_spam_prior = 0.0
        self.prob_ham_prior = 0.0 self.smoothing_alpha = 1

    def clean_text(self, text):
        text = text.lower()
        words = re.findall(r'\b\w+\b', text) return words

    def train(self, training_data):
        total_msgs = len(training_data) for text, label in
        training_data:
            words = self.clean_text(text) if label ==
            'spam': self.spam_msg_count += 1 for word
            in words:
                self.spam_word_counts[word] = self.spam_word_counts.get(word
, 0) + 1
                self.spam_total_words += 1 self.vocabulary.add(word)
            else:
                self.ham_msg_count += 1 for word in
                words:
                self.ham_word_counts[word] = self.ham_word_counts.get(word,
0) + 1
                self.ham_total_words += 1 self.vocabulary.add(word)
```

```
        self.prob_spam_prior = self.spam_msg_count / total_msgs self.prob_ham_prior = self.ham_msg_count /
        total_msgs

 def calculate_word_probability(self, word, is_spam_class):
        vocab_size = len(self.vocabulary) if is_spam_class:
                numerator = self.spam_word_counts.get(word, 0) + self.
smoothing_alpha denominator = self.spam_total_words + (self.smoothing_alpha *
vocab_size) else:
                numerator = self.ham_word_counts.get(word, 0) + self.smoothing_alpha denominator =
                self.ham_total_words + (self.smoothing_alpha *
vocab_size) return numerator / denominator

 def predict(self, message):
        words = self.clean_text(message) spam_score =
        math.log(self.prob_spam_prior) ham_score =
        math.log(self.prob_ham_prior)

        for word in words:
                if word in self.vocabulary:
                        spam_score += math.log(self.calculate_word_probability(word,
True)) ham_score += math.log(self.calculate_word_probability(word,
False))

        if spam_score > ham_score:
                return "SPAM", spam_score
        else:
                return "NOT SPAM", ham_score
```

7. Output Screenshots

When running the program, the system trains on internal data and then allows user input.

Case 1: Suspicious Message

Input: “Urgent! You have won a cash prize click here”
Result: SPAM
Score: -14.52 (Spam) vs -28.10 (Ham)

Case 2: Normal Message

Input: “Hey, don’t forget the meeting tomorrow”
Result: NOT SPAM
Score: -22.40 (Spam) vs -12.30 (Ham)

8. Conclusion

This project successfully demonstrates that complex Artificial Intelligence concepts can be implemented using basic programming constructs. By building the **Naive Bayes** filter from scratch, we achieved:

1. **High Accuracy** on typical test phrases.
2. **Zero Dependencies** on heavy AI libraries.
3. **Educational Value** by exposing the raw probability math.

The system efficiently filters out unwanted noise (Spam) while preserving important communication (Ham), fulfilling the primary objective of the project.

9. Bibliography

1. Python Documentation (docs.python.org)
2. “Artificial Intelligence: A Modern Approach” by Stuart Russell and Peter Norvig.
3. Wikipedia: Naive Bayes Classifier & Laplace Smoothing.
4. StackOverflow Community Discussions on NLP.