

# Challenge-2

Yuha Kim

Aug 21 2023

**Welcome!** Hope you have watched the lecture videos and followed the instructions in code-along. Go through the steps described below, *carefully*. It is totally fine to get stuck - **ASK FOR HELP**; reach out to your friends, TAs, or the discussion forum on Canvas.

Here is what you have to do,

1. **Pair** with a neighbor and work
2. **Download** the `Challenge-2.Rmd` and `playlist_data.csv` files from Canvas
3. **Move** the downloaded files to the folder, "Week-2"
4. **Set** it as the working directory
5. **Edit** content wherever indicated
6. **Remember** to set `eval=TRUE` after completing the code to generate the output
7. **Ensure** that `echo=TRUE` so that the code is rendered in the final document
8. **Inform** the tutor/instructor upon completion
9. **Submit** the document on Canvas after they approve
10. **Attendance** will be marked only after submission
11. Once again, **do not hesitate** to reach out to the tutors/instructor, if you are stuck

## I. Exploring music preferences

### A. Background

Imagine that you have been hired as a data analyst by a radio station to analyze music preferences of their DJs. They have provided you with a dataset, `playlist_data.csv`, containing information about DJs, their preferred music genres, song titles, and ratings.

Using the data-set you are required to complete some tasks that are listed subsequently. All these tasks are based on the concepts taught in the video lectures. The questions may not be entirely covered in the lectures; To complete them, you are encouraged to use Google and the resources therein.

### B.Tasks

#### Task-1

In the lecture, we used two data-sets, `starwars` and `anscombe's quartet` that were readily available with the packages, `tidyverse` and `Tmisc`, respectively. When we have to use custom-made data-sets or the ones like we downloaded from Canvas, we have to import it using the R commands before using them. All the questions below are related to this task.

**Question 1.1:** What does the term “CSV” in `playlist_data.csv` stand for, and why is it a popular format for storing tabular data?

**Solution:** CSV stands for Comma-Separated Values. It is popular because it can be read by many programs and tools.

**Question 1.2:** load the `tidyverse` package to work with `.csv` files in R.

**Solution:**

```
# Load the necessary package to work with CSV files in R.
library(tidyverse)
```

```
## — Attaching core tidyverse packages ————— tidyverse 2.0.0 —
## ✓ dplyr      1.1.2      ✓ readr      2.1.4
## ✓ forcats    1.0.0      ✓ stringr    1.5.0
## ✓ ggplot2    3.4.3      ✓ tibble     3.2.1
## ✓ lubridate  1.9.2      ✓ tidyr      1.3.0
## ✓ purrr      1.0.1
## — Conflicts ————— tidyverse_conflicts() —
## ✖ dplyr::filter() masks stats::filter()
## ✖ dplyr::lag()     masks stats::lag()
## i Use the `j8;;http://conflicted.r-lib.org/` conflicted package `j8;;` to force all co
nflicts to become errors
```

**Question 1.3:** Import the data-set, `playlist_data.csv`

**Solution:**

```
# Import the "playlist_data.csv" dataset into R

read_csv("playlist_data.csv")
```

```
## Rows: 26 Columns: 7
## — Column specification —————
## Delimiter: ","
## chr (4): DJ_Name, Music_Genre, Experience, Location
## dbl (3): Rating, Age, Plays_Per_Week
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```
## # A tibble: 26 × 7
##   DJ_Name Music_Genre Rating Experience   Age Location Plays_Per_Week
##   <chr>    <chr>      <dbl> <chr>      <dbl> <chr>      <dbl>
## 1 DJ A      Pop          4.2 Advanced    28 City X          80
## 2 DJ B      Rock          3.8 Intermediate 24 City Y          60
## 3 DJ C      Electronic    4.5 Advanced    30 City Z         100
## 4 DJ D      Pop           4 Intermediate 22 City X          70
## 5 DJ E      Electronic    4.8 Advanced    27 City Y          90
## 6 DJ F      Rock          3.6 Intermediate 25 City Z          55
## 7 DJ G      Pop           4.3 Advanced    29 City X          85
## 8 DJ H      Electronic    4.1 Intermediate 23 City Y          75
## 9 DJ I      Rock          3.9 Advanced    31 City Z          70
## 10 DJ J     Pop           4.4 Intermediate 26 City X          95
## # i 16 more rows
```

**Question 1.4:** Assign the data-set to a variable, `playlist_data`

**Solution:**

```
# Assign the variable to a dataset

Cat <- read.csv("playlist_data.csv")
```

From now on, you can use the name of the variable to view the contents of the data-set

**Question 1.5:** Get more information about `read_csv()` command and provide a screenshot of the information displayed in the “Help” tab of the “Files” pane

**Solution:**

```
# More information about the R command, complete the code

?read_csv()
```

```
knitr::include_graphics("help.png")
```

`read_delim {readr}`

# Read a delimited file (including CSV and TSV) into a tibble

## Description

`read_csv()` and `read_tsv()` are special cases of the more general `read_delim()`. They're useful for reading the most common types of flat file data, comma separated values and tab separated values, respectively. `read_csv2()` uses `;` for the field separator and `,` for the decimal point. This format is common in some European countries.

## Usage

```
read_delim(  
  file,  
  delim = NULL,  
  quote = "\"",  
  escape_backslash = FALSE,  
  ...  
)
```

screenshot

**Question 1.6:** What does the `skip` argument in the `read_csv()` function do?

**Solution:** It allows to skip a specified number of rows.

**Question 1.7:** Display the contents of the data-set

**Solution:**

```
# Type the name of the variable, to see what it contains
```

```
Cat
```

##	DJ_Name	Music_Genre	Rating	Experience	Age	Location	Plays_Per_Week
## 1	DJ A	Pop	4.2	Advanced	28	City X	80
## 2	DJ B	Rock	3.8	Intermediate	24	City Y	60
## 3	DJ C	Electronic	4.5	Advanced	30	City Z	100
## 4	DJ D	Pop	4.0	Intermediate	22	City X	70
## 5	DJ E	Electronic	4.8	Advanced	27	City Y	90
## 6	DJ F	Rock	3.6	Intermediate	25	City Z	55
## 7	DJ G	Pop	4.3	Advanced	29	City X	85
## 8	DJ H	Electronic	4.1	Intermediate	23	City Y	75
## 9	DJ I	Rock	3.9	Advanced	31	City Z	70
## 10	DJ J	Pop	4.4	Intermediate	26	City X	95
## 11	DJ K	Hip-Hop	4.6	Advanced	32	City Y	110
## 12	DJ L	Electronic	4.2	Intermediate	28	City Z	75
## 13	DJ M	Pop	3.8	Advanced	29	City X	60
## 14	DJ N	Rock	4.1	Intermediate	25	City Y	80
## 15	DJ O	Electronic	4.5	Advanced	31	City Z	95
## 16	DJ P	Hip-Hop	4.3	Intermediate	26	City X	105
## 17	DJ Q	Pop	4.0	Advanced	27	City Y	70
## 18	DJ R	Rock	3.7	Intermediate	24	City Z	50
## 19	DJ S	Electronic	4.4	Advanced	29	City X	85
## 20	DJ T	Hip-Hop	4.6	Intermediate	23	City Y	100
## 21	DJ U	Pop	4.2	Advanced	28	City Z	80
## 22	DJ V	Rock	3.9	Intermediate	24	City X	60
## 23	DJ W	Electronic	4.5	Advanced	30	City Y	100
## 24	DJ X	Pop	4.1	Intermediate	22	City Z	70
## 25	DJ Y	Electronic	4.7	Advanced	27	City X	90
## 26	DJ Z	Rock	3.5	Intermediate	25	City Y	55

**Question 1.8:** Assume you have a CSV file named `sales_data.csv` containing information about sales transactions. How would you use the `read_csv()` function to import this file into R and store it in a variable named `sales_data`?

**Solution:**

```
# No output is required for this code
# Only the list of commands that execute the task mentioned in the question are required
sales_data <- read_csv()
```

## Task-2

After learning to import a data-set, let us explore the contents of the data-set through the following questions

**Question 2.1:** Display the first few rows of the data-set to get an overview of its structure

**Solution:**

```
# Type the name of the variable we assigned the data-set to
head(Cat)
```

##	DJ_Name	Music_Genre	Rating	Experience	Age	Location	Plays_Per_Week
## 1	DJ A	Pop	4.2	Advanced	28	City X	80
## 2	DJ B	Rock	3.8	Intermediate	24	City Y	60
## 3	DJ C	Electronic	4.5	Advanced	30	City Z	100
## 4	DJ D	Pop	4.0	Intermediate	22	City X	70
## 5	DJ E	Electronic	4.8	Advanced	27	City Y	90
## 6	DJ F	Rock	3.6	Intermediate	25	City Z	55

**Question 2.2:** Display all the columns of the variable stacked one below another

**Solution:**

```
# Stack columns of playlist_data
```

```
glimpse(Cat)
```

```
## Rows: 26
## Columns: 7
## $ DJ_Name      <chr> "DJ A", "DJ B", "DJ C", "DJ D", "DJ E", "DJ F", "DJ G",...
## $ Music_Genre  <chr> "Pop", "Rock", "Electronic", "Pop", "Electronic", "Rock...
## $ Rating       <dbl> 4.2, 3.8, 4.5, 4.0, 4.8, 3.6, 4.3, 4.1, 3.9, 4.4, 4.6, ...
## $ Experience   <chr> "Advanced", "Intermediate", "Advanced", "Intermediate",...
## $ Age          <int> 28, 24, 30, 22, 27, 25, 29, 23, 31, 26, 32, 28, 29, 25,...
## $ Location     <chr> "City X", "City Y", "City Z", "City X", "City Y", "City...
## $ Plays_Per_Week <int> 80, 60, 100, 70, 90, 55, 85, 75, 70, 95, 110, 75, 60, 8...
```

**Question 2.3:** How many columns are there in the dataset?

**Solution:**

```
# Number of columns
```

```
ncol(Cat)
```

```
## [1] 7
```

**Question 2.4:** What is the total count of DJs?

**Solution:**

```
# Number of DJs
```

```
nrow(Cat)
```

```
## [1] 26
```

**Question 2.5:** Display all the location of all the DJs

**Solution:**

```
# Location of DJs
```

```
Cat$Location
```

```
## [1] "City X" "City Y" "City Z" "City X" "City Y" "City Z" "City X" "City Y"
## [9] "City Z" "City X" "City Y" "City Z" "City X" "City Y" "City Z" "City X"
## [17] "City Y" "City Z" "City X" "City Y" "City Z" "City X" "City Y" "City Z"
## [25] "City X" "City Y"
```

**Question 2.6:** Display the age of the DJs**Solution:**

```
# Age of DJs
```

```
Cat$Age
```

```
## [1] 28 24 30 22 27 25 29 23 31 26 32 28 29 25 31 26 27 24 29 23 28 24 30 22 27
## [26] 25
```


**Task-3**

Let us plot the data to get more insights about the DJs.

**Question 3.1:** Create a plot to visualize the relationship between DJs' ages and their ratings.**Solution:**

```
# complete the code to generate the plot
```

```
ggplot(Cat)
```



```
aes(x=Age,y=Rating)
```


```
## Aesthetic mapping:  
## * `x` -> `Age`  
## * `y` -> `Rating`
```

**Question 3.2:** Label the x-axis as “Age” and the y-axis as “Rating.”

**Solution:**

```
# complete the code to generate the plot  
  
ggplot(data=Cat,mapping=aes(x=Age,y=Rating)) +  
  labs(x="Age",y="Rating")
```






**Question 3.3:** Represent data using points

**Solution:**

```
# complete the code to generate the plot

ggplot(data=Cat,mapping=aes(x=Age,y=Rating)) + geom_point() +
  labs(x="Age",y="Rating")
```




**Question 3.4:** Can you change the points represented by dots/small circles to any other shape of your liking?

**Solution:**

```
# complete the code to generate the plot
```

```
ggplot(data=Cat,mapping=aes(x=Age,y=Rating)) + geom_point(shape=23) +  
  labs(x="Age",y="Rating")
```



**Question 3.5:** Insert a suitable title and briefly provide your insights in the caption

**Solution:**

```
# complete the code to generate the plot
```

```
ggplot(data=Cat,mapping=aes(x=Age,y=Rating)) + geom_point(shape=23) + labs(x="Age",y  
="Rating",  
title="DJ Age versus Rating",  
caption="The plot shows almost no correlation")
```

