DOTS   Y. Hayashi
Internet-Draft   NTT
Intended status: Informational   M. Chen
Expires: January 2, 2022   Li. Su
                                                                   CMCC
                                                          July 01, 2021

          Use Cases for DDoS Open Threat Signaling (DOTS) Telemetry
                  draft-ietf-dots-telemetry-use-cases-02

Abstract

   Denial-of-service Open Threat Signaling (DOTS) Telemetry enriches the
   base DOTS protocols to assist the mitigator in using efficient DDoS-
   attack-mitigation techniques in a network. This document presents
   sample use cases for DOTS Telemetry: what components are deployed in
   the network, how they cooperate, and what information is exchanged to
   effectively use these techniques.

Status of This Memo

   This Internet-Draft is submitted in full conformance with the
   provisions of BCP 78 and BCP 79.

   Internet-Drafts are working documents of the Internet Engineering
   Task Force (IETF). Note that other groups may also distribute
   working documents as Internet-Drafts. The list of current Internet-
   Drafts is at https://datatracker.ietf.org/drafts/current/.

   Internet-Drafts are draft documents valid for a maximum of six months
   and may be updated, replaced, or obsoleted by other documents at any
   time. It is inappropriate to use Internet-Drafts as reference
   material or to cite them other than as "work in progress."

   This Internet-Draft will expire on January 2, 2022.

Table of Contents

1. Introduction

   Denial-of-Service (DDoS), attacks such as volumetric attacks and
   resource-consumption attacks, are critical threats to be handled by
   service providers. When such DDoS attacks occur, service providers
   have to mitigate them immediately to protect or recover their
   services.

   Therefore, for service providers to immediately protect their network
   services from DDoS attacks, DDoS mitigation needs to be automated.
   To automate DDoS-attack mitigation, multi-vendor components involved
   in DDoS-attack detection and mitigation should cooperate and support
   standard interfaces to communicate.

   DDoS Open Threat Signaling (DOTS) is a set of protocols for real-time
   signaling, threat-handling requests, and data filtering between the
   multi-vendor elements [I-D.ietf-dots-rfc8782-bis][RFC8783].
   Furthermore, DOTS Telemetry enriches the DOTS protocols with various
   telemetry attributes allowing optimal DDoS-attack mitigation
   [I-D.ietf-dots-telemetry]. This document presents sample use cases
   for DOTS Telemetry, which makes concrete overview and purpose

described in [I-D.ietf-dots-telemetry]: what components are deployed
in the network, how they cooperate, and what information is exchanged
to effectively use attack-mitigation techniques.

2. Terminology

   The readers should be familiar with the terms defined in [RFC8612]

   In addition, this document uses the following terms:

   Top-talker: A top N list of attackers who attack the same target or
      targets. The list is ordered in terms of a two-tuple bandwidth
      such as bps or pps.

   Supervised Machine Learning: A machine-learning technique that maps
      an input to an output based on example input-output pairs.

   Unsupervised Machine Learning: Unsupervised Learning is a machine
      learning technique in which the users do not need to supervise the
      model.

3. Use Cases

   This section describes DOTS-Telemetry use cases that use attributes
   included in DOTS Telemetry specifications.

3.1. Mitigation Resources Assignment

3.1.1. Mitigating Attack Flow of Top-talker Preferentially

   Large-scale DDoS attacks, such as amplification attacks, often occur.
   Some transit providers have to mitigate large-scale DDoS attacks
   using DMS with limited resources, which is already deployed in their
   network.

   The aim of this use case is to enable transit providers to use their
   DMS efficiently under volume-based DDoS attacks whose bandwidth is
   more than the available capacity of the DMS. To enable this, attack
   traffic of top talkers is redirected to the DMS preferentially by
   cooperation among forwarding nodes, flow collectors, and
   orchestrators. Figure 1 gives an overview of this use case.
   Figure 2 provides an example of a DOTS telemetry message body that is
   used to signal top-talkers.

(Internet Transit Provider)

```
                     +----------+      +--------------+ e.g., SNMP
   e.g., IPFIX +-----------+| DOTS  |              |<---
          --->| Flow     ||C<-->S| Orchestrator |  e.g., BGP Flowspec
             | collector |+       |              |---> (Redirect)
             +----------+      +--------------+

                     +------------+
         e.g., IPFIX +-------------+| e.g., BGP Flowspec
                <---| Forwarding ||<---    (Redirect)
                    |    nodes    ||
                    |            ||          DDoS Attack
   [ Target  ]<===========|=============================
   [   or    ]            |     ++========================[top talker]
   [ Targets ]            |     || ++=====================[top talker]
                    +----|| ||---+
                         || ||
                         || ||
                         || ||
                         |/ |/
                    +----x--x----+
                    | DDoS       | e.g., SNMP
                    | mitigation |<---
                    | system     |
                    +-----------+
```

* C is for DOTS client functionality
* S is for DOTS client functionality

Figure 1: Mitigating DDoS Attack Flow of Top-talker Preferentially

```
{
   "ietf-dots-telemetry:telemetry": {
     "pre-or-ongoing-mitigation": [
       {
         "target": {
           "target-prefix": [
             "2001:db8::1/128"
           ]
         },
         "total-attack-traffic-protocol": [
           {
             "protocol": 17,
             "unit": "megabit-ps",
             "mid-percentile-g": "900"
           }
         ],
```

```
            "attack-detail": [
              {
                "vendor-id": 1234,
                "attack-id": 77,
                "start-time": "1957811234",
                "attack-severity": "high",
                "top-talker":{
                  "talker": [
                    {
                      "source-prefix": "2001:db8::2/128",
                      "total-attack-traffic":[
                        {
                          "unit": "megabit-ps",
                          "mid-percentile-g": "100"
                        }
                      ]
                    },
                    {
                      "source-prefix": "2001:db8::3/128",
                      "total-attack-traffic":[
                        {
                          "unit": "megabit-ps",
                          "mid-percentile-g": "90"
                        }
                      ]
                    }
                  ]
                }
              }
            ]
          }
        ]
      }
    ]
  }
}
```

Figure 2: Example of Message Body to Signal Top-Talkers

In this use case, the forwarding nodes always send statistics of
traffic flow to the flow collectors by using monitoring functions
such as IPFIX[RFC7011]. When DDoS attacks occur, the flow collectors
detect attack traffic and send (src_ip, dst_ip, bandwidth)-tuple
information of the top talker to the orchestrator using the target-
prefix and top-talkers attribute of DOTS Telemetry. The orchestrator
then checks the available capacity of DMS by using a network
management protocol such as SNMP[RFC3413]. After that, the
orchestrator orders forwarding nodes to redirect as much of the top
taker's traffic to the DMS as possible by dissemination of flow-
specification-rule protocols such as BGP Flowspec[RFC5575].

In this case, the flow collector implements a DOTS client while the
orchestrator implements a DOTS server.

3.1.2. Optimal DMS Selection for Mitigation

Transit providers, which have a number of DMSs, can deploy the DMSs
in clustered form. In the form, they can select DMS to be used to
mitigate DDoS attack under attack time.

The aim of this use case is to enable transit providers to select an
optimal DMS for mitigation based on the bandwidth of attack traffic,
capacity of a DMS. Figure 3 gives an overview of this use case.
Figure 4 provides an example of a DOTS telemetry message body that is
used to signal various attack traffic percentiles.

(Internet Transit Provider)

```
                      +----------+      +--------------+ e.g., SNMP
  e.g., IPFIX +----------+| DOTS   |      |              |<---
        --->| Flow     ||C<-->S| Orchestrator |  e.g., BGP
            | collector |+       |      |              |---->   (Redirect)
            +----------+      +--------------+


                      +-----------+
        e.g., IPFIX +------------+| e.g., BGP
            <---| Forwarding ||<---   (Redirect)
                |    nodes   ||
                |            ||            DDoS Attack
  [Target]      | ++============================
  [Target]      | ||  ++======================
              +-||--||-----+
                ||   ||
        ++====++  ||    (congested DMS)
        ||       ||   +----------+
        ||       ||/  |   DMS3   |
        ||  +-----x------+        |<--- e.g., SNMP
        |/  |      DMS2  |--------+
      +--x---------+     |<--- e.g., SNMP
        |    DMS1  |------+
        |          |<--- e.g., SNMP
        +-----------+
```

* C is for DOTS client functionality
* S is for DOTS client functionality

Figure 3: Optimal DMS selection for Mitigation

```
{
  "ietf-dots-telemetry:telemetry": {
    "pre-or-ongoing-mitigation": [
      {
        "target": {
          "target-prefix": [
            "2001:db8::1/128"
          ]
        },
        "total-attack-traffic": [
          {
            "unit": "megabit-ps",
            "low-percentile-g": "600",
            "mid-percentile-g": "800",
            "high-percentile-g": "1000",
            "peak-g":"1100",
            "current-g":"700"
          }
        ]
      }
    ]
  }
}
```

Figure 4: Example of Message Body with Total Attack Traffic

In this use case, the forwarding nodes always send statistics of traffic flow to the flow collectors by using monitoring functions such as IPFIX[RFC7011]. When DDoS attacks occur, the flow collectors detect attack traffic and send (dst_ip, bandwidth)-tuple information to the orchestrator using the target-prefix and total-attack-traffic attribute of DOTS Telemetry. The orchestrator then checks the available capacity of the DMSs by using a network management protocol such as SNMP[RFC3413]. After that, the orchestrator chooses optimal DMS which each attack traffic should be redirected. The orchestrator then orders forwarding nodes to redirect the attack traffic to the optimal DMS by a routing protocol such as BGP[RFC4271]. The algorithm of selecting a DMS is out of the scope of this draft.

In this case, the flow collector implements a DOTS client while the orchestrator implements a DOTS server.

3.1.3. Best-path Selection for Redirection

A transit-provider network, which adopts a mesh network, has multiple paths to convey attack traffic to a DMS. In this network, attack traffic can be conveyed while avoiding congested links by selecting an available path.

The aim of this use case is to enable transit providers to select an optimal path for redirecting attack traffic to a DMS according to the bandwidth of the attack traffic and total traffic. Figure 5 gives an overview of this use case. Figure 6 provides an example of a DOTS telemetry message body that is used to signal various attack traffic percentiles and total traffic percentiles.

(Internet Transit Provider)

```
                +-----------+       +---------------+ DOTS
    e.g.,   +-----------+|       |               |S<---
    IPFIX | Flow      ||  DOTS | Orchestrator  |
       -->| collector ||C<-->S|               | e.g., BGP Flow spec
          |           |+      |               |--->    (Redirect)
          +-----------+       +-------------+


              DOTS +------------+  DOTS +------------+ e.g., IPFIX
              --->C| Forwarding |  --->C| Forwarding |--->
   e.g., BGP Flow spec |   node     |      |   node     |
        (Redirect) --->|            |      |            | DDoS Attack
   [Target]            |         ++===============================
                +-------||---+       +------------+
                       ||              /
                       ||             / (congested link)
                       ||            /
              DOTS +-||---------------+ e.g., BGP Flow spec
              --->C|  ||  Forwarding   |<---    (Redirect)
                   | ++===  node       |
                +----||-------------+
                   |/
                +--x-----------+
                |    DMS       |
                +-------------+
```

   * C is for DOTS client functionality
   * S is for DOTS client functionality

   Figure 5: Best-path Selection for Redirection

{
  "ietf-dots-telemetry:telemetry": {
    "pre-or-ongoing-mitigation": [
      {
        "target": {
          "target-prefix": [
            "2001:db8::1/128"
          ]

```
        },
        "total-traffic": [
          {
            "unit": "megabit-ps",
            "mid-percentile-g": "1300",
            "peak-g":"800"
          }
        ],
        "total-attack-traffic": [
          {
            "unit": "megabit-ps",
            "low-percentile-g": "600",
            "mid-percentile-g": "800",
            "high-percentile-g": "1000",
            "peak-g":"1100",
            "current-g":"700"
          }
        ],
        "attack-detail": [
          {
            "vendor-id": 1234,
            "attack-id": 77,
            "start-time": "1957811234",
            "attack-severity": "high",
            "top-talker":{
              "talker": [
                {
                  "source-prefix": "2001:db8::2/128",
                  "total-attack-traffic":[
                    {
                      "unit": "megabit-ps",
                      "mid-percentile-g": "300"
                    }
                  ]
                },
                {
                  "source-prefix": "2001:db8::3/128",
                  "total-attack-traffic":[
                    {
                      "unit": "megabit-ps",
                      "mid-percentile-g": "400"
                    }
                  ]
                }
              ]
            }
          }
        ]
```

```
      }
    ]
  }
}
```

Figure 6: Example of Message Body with Total Attack Traffic and Total Traffi
c

   In this use case, the forwarding nodes always send statistics of
   traffic flow to the flow collectors by using monitoring functions
   such as IPFIX[RFC7011]. When DDoS attacks occur, the flow collectors
   detect attack traffic and send (dst_ip, bandwidth)-tuple information
   to the orchestrator using a target-prefix and total-attack-traffic
   attribute of DOTS Telemetry. On the other hands, forwarding nodes
   send bandwidth of total traffic passing the node to the orchestrator
   using total-traffic attributes of DOTS Telemetry. The orchestrator
   then selects an optimal path to which each attack-traffic flow should
   be redirected. After that, the orchestrator orders forwarding nodes
   to redirect the attack traffic to the optimal DMS by dissemination of
   flow-specification-rules protocols such as BGP Flowspec[RFC5575].
   The algorithm of selecting a path is out of the scope of this draft.

3.1.4. Short but Extreme Volumetric Attack Mitigation

   Short but extreme volumetric attacks, such as pulse wave DDoS
   attacks, are threats to internet transit provider networks. It is
   difficult for them to mitigate an attack by DMS by redirecting attack
   flows because it may cause route flapping in the network. The
   practical way to mitigate short but extreme volumetric attacks is to
   offload a mitigation actions to a forwarding node.

   The aim of this use case is to enable transit providers to mitigate
   short but extreme volumetric attacks. Furthermore, the aim is to
   estimate the network-access success rate based on the bandwidth of
   attack traffic. Figure 7 gives an overview of this use case.
   Figure 8 provides an example of a DOTS telemetry message body that is
   used to signal various attack traffic percentiles and total traffic
   percentiles.

(Internet Transit Provider)

```
                +------------+      +---------------+
e.g.,           | Network    | DOTS | Administrative |
Alert --->| Management |C<--->S| System              | e.g., BGP Flow spec
                | System     |      |               |---> (Rate-Limit)
                +------------+      +---------------+

            +------------+      +------------+ e.g., BGP Flow spec
            | Forwarding |      | Forwarding |<---  (Rate-Limit X bps)
            |   node     |      |   node     |
            |            |      |            | DDoS & Normal traffic
[Target]<--------------------------------------================
Pipe        +------------+      +------------+  Attack Traffic
Capability                                      Bandwidth
e.g., X bps                                     e.g., Y bps

                  Network access success rate
                       e.g., X / (X + Y)
```

* C is for DOTS client functionality
* S is for DOTS client functionality

Figure 7: Short but Extreme Volumetric Attack Mitigation

```
{
  "ietf-dots-telemetry:telemetry": {
    "pre-or-ongoing-mitigation": [
      {
        "target": {
          "target-prefix": [
            "2001:db8::1/128"
          ]
        },
        "total-traffic": [
          {
            "unit": "megabit-ps",
            "mid-percentile-g": "1300",
            "peak-g":"800"
          }
        ],
        "total-attack-traffic": [
          {
            "unit": "megabit-ps",
            "low-percentile-g": "600",
            "mid-percentile-g": "800",
            "high-percentile-g": "1000",
            "peak-g":"1100",
            "current-g":"700"
          }
        ]
      }
    ]
  }
}
```

Figure 8: Example of Message Body with Total Attack Traffic and Total Traffic

   In this use case, when DDoS attacks occur, the network management
   system receives alerts. It then sends the target ip address and
   bandwidth of the DDoS attack traffic to the administrative system
   using the target-prefix and total-attack-traffic attributes of DOTS
   Telemetry. After that, the administrative system orders upper
   forwarding nodes to carry out rate-limit all traffic destined to the
   target based on the pipe capability by the dissemination of the flow-
   specification-rules protocols such as BGP Flowspec[RFC5575]. In
   addition, the administrative system estimates the network-access
   success rate of the target, which is calculated by total pipe
   capability / (total pipe capability + total attack traffic). Note
   that total pipe capability information can be gatherd by telemetry
   setup in advance.

3.1.5. Selecting Mitigation Technique Based on Attack Type

   Some volumetric attacks, such as amplification attacks, can be
   detected with high accuracy by checking the layer-3 or layer-4
   information of attack packets. These attacks can be detected and
   mitigated through cooperation among forwarding nodes and flow
   collectors using IPFIX[RFC7011]. On the other hand, it is necessary
   to inspect the layer-7 information of attack packets to detect
   attacks such as DNS Water Torture Attacks. Such attack traffic
   should be detected and mitigated at a DMS.

   The aim of this use case is to enable transit providers to select a
   mitigation technique based on the type of attack traffic:
   amplification attack or not. To use such a technique, attack traffic
   is blocked at forwarding nodes or redirected to a DMS based on attack
   type through cooperation among forwarding nodes, flow collectors, and
   an orchestrator. Figure 9 gives an overview of this use case.
   Figure 10 provides an example of a DOTS telemetry message body that
   is used to signal various attack traffic percentiles, total traffic
   percentiles, total attack connection and attack type.

         (Internet Transit Provider)

```
              +-----------+ DOTS +--------------+ e.g.,
    e.g., +-----------+|<---->|              | BGP (Redirect)
    IPFIX | Flow      ||C   S| Orchestrator | BGP Flowspec (Drop)
      --->| collector |+     |              |--->
          +-----------+      +--------------+


                   +------------+ e.g., BGP (Redirect)
      e.g., IPFIX +------------+|          BGP Flowspec (Drop)
           <---| Forwarding ||<---
               |    nodes   ||              DDoS Attack
               |    ++=====||=================
               |    ||     ||x<==============[e.g.,DNS Amp]
               |    ||     |+x<==============[e.g.,NTP Amp]
           +-----||-----+
                 ||
                 |/
          +-----x------+
          | DDoS       |
          | mitigation |
          | system     |
          +------------+
```

    * C is for DOTS client functionality
    * S is for DOTS server functionality

   Figure 9: DDoS Mitigation Based on Attack Type

```
{
  "ietf-dots-telemetry:telemetry": {
    "pre-or-ongoing-mitigation": [
      {
        "target": {
          "target-prefix": [
            "2001:db8::1/128"
          ]
        },
        "total-attack-traffic": [
          {
            "unit": "megabit-ps",
            "low-percentile-g": "600",
            "mid-percentile-g": "800",
            "high-percentile-g": "1000",
            "peak-g":"1100",
            "current-g":"700"
```

```
          }
        ],
        "total-attack-traffic-protocol": [
          {
            "protocol": 17,
            "unit": "megabit-ps",
            "mid-percentile-g": "500"
          },
          {
            "protocol": 15,
            "unit": "megabit-ps",
            "mid-percentile-g": "200"
          }
        ],
        "total-attack-connection":[
        {
           "mid-percentile-l":[
            {
              "protocol": 15,
              "connection": 200
            }
           ],
           "high-percentile-l":[
            {
              "protocol": 17,
              "connection": 300
            }
           ]
        }
        ],
        "attack-detail": [
          {
            "vendor-id": 1234,
            "attack-id": 77,
            "start-time": "1957811234",
            "attack-severity": "high",
            "attack-description":"dns-amp"
          },
          {
            "vendor-id": 1234,
            "attack-id": 92,
            "start-time": "1957811234",
            "attack-severity": "high",
            "attack-description":"ntp-amp"
          }
        ]
      }
    ]
```

```
   }
}
```

Figure 10: Example of Message Body with Total Attack Traffic, Total Attack T
raffic Protocol, Total Attack Connection and Attack Type

   In this use case, the forwarding nodes send statistics of traffic
   flow to the flow collectors by using a monitoring function such as
   IPFIX[RFC7011]. When DDoS attacks occur, the flow collectors detect
   attack traffic and send (dst_ip, attack_type)-tuple information to
   the orchestrator the using vendor-id and attack-id attribute of DOTS
   Telemetry. The orchestrator then resolves abused port and orders
   forwarding nodes to block the (dst_ip, src_port)-tuple flow of amp
   attack traffic by dissemination of flow-specification-rule protocols
   such as BGP Flowspec[RFC5575]. On the other hand, the orchestrator
   orders forwarding nodes to redirect other traffic than the amp attack
   traffic by a routing protocol such as BGP[RFC4271].

   In this case, the flow collector implements a DOTS client while the
   orchestrator implements a DOTS server.

3.2. Detailed DDoS Mitigation Report

   It is possible for the transit provider to add value to the DDoS
   mitigation service by reporting on-going and detailed DDoS
   countermeasure status to the enterprise network. In addition, it is
   possible for the transit provider to know whether the DDoS counter
   measure is effective or not by receiving reports from the enterprise
   network.

   The aim of this use case is to share the information about on-going
   DDoS counter measure between the transit provider and the enterprise
   network mutually. Figure 11 gives an overview of this use case.
   Figure 12 provides an example of a DOTS telemetry message body that
   is used to signal various total traffic percentiles, total attack
   traffic percentiles and attack detail.

```
    +-----------------+        +-----------------------+
    | Enterprise      |        | Upstream              |
    | Network         |        | Internet Transit      |
    |   +-----------+  |        | Provider              |
    |   | Network   |C |        | S+-------------+      |
    |   | admini-   |<----DOTS---->| Orchestrator |      |
    |   | strator   |  |        | +-------------+      |
    |   +-----------+  |        |       C ^            |
    |                  |        |         | DOTS       |
    |                  |        |       S v            |
    |                  |        | +---------------+ DDoS Attack
    |                  |        | |      DMS      |+=======
    |                  |        | +---------------+  |
    |                  |        |     || Clean     |
    |                  |        |     |/ Traffic   |
    |   +---------+    |        | +---------------+  |
    |   | DDoS    |    |        | | Forwarding    | Normal Traffic
    |   | Target  |<==============| Node          |=======
    |   +---------+    | Link |  | +---------------+  |
    +-----------------+        +-----------------------+
```

  * C is for DOTS client functionality
  * S is for DOTS server functionality

  Figure 11: Detailed DDoS Mitigation Report

```
{
  "ietf-dots-telemetry:telemetry": {
    "pre-or-ongoing-mitigation": [
      {
        "tmid": 567,
        "target": {
          "target-prefix": [
            "2001:db8::1/128"
          ]
        },
        "target-protocol": [
          17
        ],
        "total-traffic": [
          {
            "unit": "megabit-ps",
            "mid-percentile-g": "800"
          }
        ],
        "total-attack-traffic": [
          {
            "unit": "megabit-ps",
            "mid-percentile-g": "100"
          }
        ],
        "attack-detail": [
          {
            "vendor-id": 1234,
            "attack-id": 77,
            "start-time": "1957818434",
            "attack-severity": "high"
          }
        ]
      }
    ]
  }
}
```

Figure 12: Example of Message Body with Total Traffic, Total Attack Traffic Protocol and Attack Detail

   In this use case, the network management system in the enterprise
   network reports limits of incoming traffic volume from the transit
   provider to the orchestrator in the transit provider in advance. It
   is reported by using total-pipe-capacity in DOTS telemetry setup.

   when DDoS attacks occur, DDoS Orchestration [RFC8903] is carried out
   in the transit provider. Then, the DDoS mitigation systems reports
   status of DDoS counter measure to the orchestrator by using DOTS

telemetry such as attack-detail. After that, the orchestrator
integrates the reports from the DDoS mitigation system, while
removing duplicate contents, and send it to network administrator by
using DOTS telemetry periodically.

During the DDoS mitigation, the orchestrator in the transit provider
retrieves link congestion status from the network administrator in
the enterprise network by using total-traffic in DOTS telemetry.
Then, the orchestrator checks whether DDoS countermeasure is
effective or not by comparing the total-traffic and the total-pipe-
capacity.

In this case, the DMS implements a DOTS server while the orchestrator
implements a DOTS client and server in the transit provider. In
addition, the network administrator implements a DOTS client.

3.3. Tuning Mitigation Resources

3.3.1. Supervised Machine Learning of Flow Collector

DDoS detection based on monitoring functions, such as IPFIX[RFC7011],
is a lighter weight method of detecting DDoS attacks than DMSs in
internet transit provider networks. On the other hand, DDoS
detection based on the DMSs is a more accurate method of detecting
attack traffic or DDoS attacks better than flow monitoring.

The aim of this use case is to increases flow collector's detection
accuracy by carrying out supervised machine-learning techniques
according to attack detail reported by the DMSs. To use such a
technique, forwarding nodes, flow collector, and a DMS should
cooperate. Figure 13 gives an overview of this use case. Figure 14
provides an example of a DOTS telemetry message body that is used to
signal various total attack traffic percentiles and attack detail.

```
                              +----------+
                           +----------+| DOTS
         e.g., IPFIX | Flow       ||S<---
               --->| collector ||
                           +----------++


                              +-----------+
         e.g., IPFIX +-----------+|
               <---| Forwarding ||
                      |    nodes     ||              DDoS Attack
   [ Target ]         |   ++=============================
                      |   || ++=========================
                      |   || || ++=====================
                      +---||-|| ||-+
                          || || ||
                          |/ |/ |/
            DOTS   +---X--X--X--+
              --->C| DDoS       |
                   | mitigation |
                   | system     |
                   +-----------+
```

        * C is for DOTS client functionality
        * S is for DOTS client functionality

    Figure 13: Training Supervised Machine Learning of Flow Collector

```
   {
     "ietf-dots-telemetry:telemetry": {
       "pre-or-ongoing-mitigation": [
         {
           "target": {
             "target-prefix": [
               "2001:db8::1/128"
             ]
           },
           "attack-detail": [
             {
               "vendor-id": 1234,
               "attack-id": 77,
               "start-time": "1957811234",
               "attack-severity": "high",
               "top-talker": {
                 "talker": [
                   {
                     "source-prefix": "2001:db8::2/128"
                   },
                   {
                     "source-prefix": "2001:db8::3/128"
                   }
                 ]
               }
             }
           ]
         }
       ]
     }
   }
```

   Figure 14: Example of Message Body with Attack Type and Top Talkers

   In this use case, the forwarding nodes always send statistics of
   traffic flow to the flow collectors by using monitoring functions
   such as IPFIX[RFC7011]. When DDoS attacks occur, DDoS orchestration
   use case[RFC8903] is carried out and the DMS mitigates all attack
   traffic destined for a target. The DDoS-mitigation system reports
   the vendor-id, attack-id and top-talker to the flow collector using
   DOTS telemetry.

   After mitigating a DDoS attack, the flow collector attaches teacher
   labels, which shows normal traffic or attack type, to the statistics
   of traffic flow of top-talker based on the reports. The flow
   collector then carries out supervised machine learning to increase
   its detection accuracy, setting the statistics as an explanatory
   variable and setting the labels as an objective variable.

In this case, the DMS implements a DOTS client while the flow
collector implements a DOTS server.

3.3.2. Unsupervised Machine Learning of Flow Collector

DMSs can detect DDoS attack traffic, which means DMSs can also
identify clean traffic. The aim of this use case is to carry out
unsupervised machine-learning for anomaly detection according to
baseline reported by DMSs. To use such a technique, forwarding
nodes, flow collector, and a DMS should cooperate. Figure 15 gives
an overview of this use case. Figure 16 provides an example of a
DOTS telemetry message body that is used to signal baseline.

```
                         +-----------+
                         +-----------+|
                 DOTS   | Flow       ||
                 --->S| collector  ||
                         +-----------++


                         +------------+
                         +------------+|
                         | Forwarding ||
                         |    nodes   ||                Traffic
  [ Dst ]  <====================++==============================
                         |    ||          ||
                         |    ||          |+
                         +---||-------+
                             ||
                             |/
                 DOTS   +---X--------+
                  --->C| DDoS        |
                         | mitigation |
                         | system     |
                         +------------+
```

        * C is for DOTS client functionality
        * S is for DOTS client functionality

    Figure 15: Training Unsupervised Machine Learning of Flow Collector

```
     {
       "ietf-dots-telemetry:telemetry-setup": {
         "telemetry": [
           {
             "baseline": [
               {
                 "id": 1,
                 "target-prefix": [
                   "2001:db8:6401::1/128"
                 ],
                 "target-port-range": [
                   {
                     "lower-port": "53"
                   }
                 ],
                 "target-protocol": [
                  17
                 ],
                 "total-traffic-normal": [
                   {
                     "unit": "megabit-ps",
                     "mid-percentile-g": "30",
                     "mid-percentile-g": "50",
                     "high-percentile-g": "60",
                     "peak-g": "70"
                   }
                 ]
               }
             ]
           }
         ]
       }
     }
```

Figure 16: Example of Message Body with Baseline

In this use case, the forwarding nodes carry out mirroring traffic
destined a dst ip address. The DMS then identifies clean traffic and
reports the baseline attributes to the flow collector using DOTS
telemetry.

The flow collector then carries out unsupervised machine learning to
be able to carry out anomaly detection.

In this case, the DMS implements a DOTS client while the flow
collector implements a DOTS server.

4. Security Considerations

   DOTS telemetry security considerations are discussed in
   [I-D.ietf-dots-telemetry]. This document does not add new
   considerations.

5. IANA Considerations

   This document does not require any action from IANA.

6. Acknowledgement

   The authors would like to thank among others Mohamed Boucadair for
   their valuable feedback.

7. References

7.1. Normative References

   [I-D.ietf-dots-telemetry]
              Boucadair, M., Reddy, T., Doron, E., Chen, M., and J.
              Shallow, "Distributed Denial-of-Service Open Threat
              Signaling (DOTS) Telemetry", draft-ietf-dots-telemetry-15
              (work in progress), December 2020.

   [RFC3413] Levi, D., Meyer, P., and B. Stewart, "Simple Network
              Management Protocol (SNMP) Applications", STD 62,
              RFC 3413, DOI 10.17487/RFC3413, December 2002,
              <https://www.rfc-editor.org/info/rfc3413>.

   [RFC4271] Rekhter, Y., Ed., Li, T., Ed., and S. Hares, Ed., "A
              Border Gateway Protocol 4 (BGP-4)", RFC 4271,
              DOI 10.17487/RFC4271, January 2006,
              <https://www.rfc-editor.org/info/rfc4271>.

   [RFC5575] Marques, P., Sheth, N., Raszuk, R., Greene, B., Mauch, J.,
              and D. McPherson, "Dissemination of Flow Specification
              Rules", RFC 5575, DOI 10.17487/RFC5575, August 2009,
              <https://www.rfc-editor.org/info/rfc5575>.

   [RFC7011] Claise, B., Ed., Trammell, B., Ed., and P. Aitken,
              "Specification of the IP Flow Information Export (IPFIX)
              Protocol for the Exchange of Flow Information", STD 77,
              RFC 7011, DOI 10.17487/RFC7011, September 2013,
              <https://www.rfc-editor.org/info/rfc7011>.

   [RFC8612] Mortensen, A., Reddy, T., and R. Moskowitz, "DDoS Open
              Threat Signaling (DOTS) Requirements", RFC 8612,
              DOI 10.17487/RFC8612, May 2019,
              <https://www.rfc-editor.org/info/rfc8612>.

   [RFC8903] Dobbins, R., Migault, D., Moskowitz, R., Teague, N., Xia,
              L., and K. Nishizuka, "Use Cases for DDoS Open Threat
              Signaling", RFC 8903, DOI 10.17487/RFC8903, May 2021,
              <https://www.rfc-editor.org/info/rfc8903>.

7.2. Informative References

   [I-D.ietf-dots-rfc8782-bis]
              Boucadair, M., Shallow, J., and T. Reddy.K, "Distributed
              Denial-of-Service Open Threat Signaling (DOTS) Signal
              Channel Specification", draft-ietf-dots-rfc8782-bis-06
              (work in progress), March 2021.

   [RFC8783] Boucadair, M., Ed. and T. Reddy.K, Ed., "Distributed
              Denial-of-Service Open Threat Signaling (DOTS) Data
              Channel Specification", RFC 8783, DOI 10.17487/RFC8783,
              May 2020, <https://www.rfc-editor.org/info/rfc8783>.

Authors' Addresses

   Yuhei Hayashi
   NTT
   3-9-11, Midori-cho
   Musashino-shi, Tokyo 180-8585
   Japan

   Email: yuuhei.hayashi@gmail.com

   Meiling Chen
   CMCC
   32, Xuanwumen West
   BeiJing, BeiJing 100053
   China

   Email: chenmeiling@chinamobile.com

   Li Su
   CMCC
   32, Xuanwumen West
   BeiJing   100053
   China

   Email: suli@chinamobile.com