

Package ‘rsegfit’

September 7, 2017

Type Package

Title An r package for segfit

Version 0.1

Date 2017-09-05

Description An r interface to segfit algorithm

Depends R (>= 2.15.0)

License GPL (>= 2)

NeedsCompilation yes

RoxygenNote 6.0.1

R topics documented:

plot.segfit	1
segfit	2
summary.segfit	3

Index	4
--------------	----------

plot.segfit	<i>Plot a segfit object</i>
-------------	-----------------------------

Description

Plot a segfit object

Usage

```
## S3 method for class 'segfit'
plot(x, y = "", col.data = "black", col.seg = "red",
     legend.pos = "topleft")
```

Arguments

<code>x</code>	If <code>x</code> is a <code>segfit</code> object, input <code>y</code> is ignored.
<code>y</code>	A <code>segfit</code> object, If not provided, <code>x</code> must be a <code>segfit</code> object.
<code>col.data</code>	color of data
<code>col.seg</code>	color of segments
<code>legend.pos</code>	legend positions

Details

Plot a `segfit` object

<code>segfit</code>	<i>segfit a sequence</i>
---------------------	--------------------------

Description

Do segmentation on "data"

Usage

```
segfit(data, smp = 2.3, lb = -6, ub = 6, maxiter = 1000, factr = 5000,
       pgtol = 1e-04)
```

Arguments

<code>data</code>	The series to be segfitted
<code>smp</code>	The smaller, the more segments will be found
<code>lb</code>	lower bound of parameter <code>\$b\$</code> of each segment
<code>ub</code>	upper bound of parameter <code>\$b\$</code> of each segment
<code>maxiter</code>	maximum iteration in optimisation
<code>factr</code>	maximum function evaluation
<code>pgtol</code>	tolerance used in optimisation

Details

"Segment and fit" a sequence. Each sequence will be described by $y=a*x^b+c$ where $x=1:\text{seg.length}$ (`order==0`) or $x = \text{seg.length}:1$ (`order==1`). The segmentation is to minimise the sum of mse of each segments plus `smp*numSegment`.

Value

A "segfit" object. It contains the params of all the segments. For each segment, it contains the head index (`hi`), tail index (`ei`), parameter `a` (`a`) parameter `b` (`b`), parameter `c` (`c`), fitting order (`order`), fitted values (`fit`), and fitting residuals (`residual`). It also has a attribute "data" for the original data

summary.segfit	<i>Summarise a segfit object</i>
----------------	----------------------------------

Description

Summarise a segfit object

Usage

```
## S3 method for class 'segfit'
summary(sf)
```

Arguments

sf	The segfit object to summarise
----	--------------------------------

Details

Summarise a segfit object

Index

`plot.segfit`, [1](#)

`segfit`, [2](#)

`summary.segfit`, [3](#)