COMP1035-04 2020-02-04 1:55:19 AM

### Assign#3

Yu-Hsuan Huang - 200443723

### 2.1.4.6

# PART 1

- 2 b) 9600
- 2 d) S1>
- 3 a) connect
- 3 c) telnet, terminal

# PART 2

- 1 a) Turn on privileged commands
- 1 d) 5 (clear, clock, configure, connect, copy)

## PART 3

- 1 a) \*0:11:1.97 UTC Mon Mar 1 1993, 1993
- 2 b) % Ambiguous command: "cl",
  - % Incomplete command,
  - % Invalid input detected at '^' marker,
  - % Invalid input detected at '^' marker

### 2.3.2.5

## PART 1

5) copy running-config startup-config

## PART 2

2 b) Failure because we don't set up IP address for the switch.

### PART 3

1) We need to active interface because interface shutdown by default.

```
C:\>ping 192.168.1.2
Pinging 192.168.1.2 with 32 bytes of data:
Reply from 192.168.1.2: bytes=32 time<1ms TTL=128
C:\>ping 192.168.1.253
Pinging 192.168.1.253 with 32 bytes of data:
Request timed out.
Reply from 192.168.1.253: bytes=32 time<1ms TTL=255
C:\>ping 192.168.1.254
Pinging 192.168.1.254 with 32 bytes of data:
Request timed out.
Reply from 192.168.1.254: bytes=32 time<1ms TTL=255</pre>
```