Sensitivity Analysis for Irregular Assessment Times with General Outcome Types

An example using simulated ARC trial data

Contents

1 Overview **2**
- 1.1 Brief review of the method . . . 2

2 Setup **2**
- 2.1 Working directory . . . 2
- 2.2 Packages and functions . . . 3
- 2.3 Running time . . . 3

3 Data **4**

4 Estimation of the mean outcome **5**
- 4.1 Point estimates and influence-function-based variance . . . 5
- 4.2 Parametric bootstrap confidence intervals . . . 6

5 Visualization **7**
- 5.1 Estimated mean curves . . . 7
- 5.2 Confidence intervals at the target times . . . 9
- 5.3 Contour plots of the treatment effect . . . 11
  - 5.3.1 Estimation on a fine grid of α . . . 11
  - 5.3.2 Treatment effect estimates and confidence intervals . . . 13
  - 5.3.3 Contour plot of the point estimates . . . 14
  - 5.3.4 Contour plot of the confidence intervals . . . 15

6 Selection of the sensitivity parameter **18**
- 6.1 Point estimates and bias-corrected point estimates . . . 18
  - 6.1.1 Algorithm 1: original point estimates . . . 18
  - 6.1.2 Algorithm 2: multiplier bootstrap bias correction . . . 19
- 6.2 Confidence set for (α_a^l, α_a^u) . . . 20
  - 6.2.1 Algorithm 3: double bootstrap . . . 20

7 Other outcome types and options **24**
- 7.1 Binary outcome (AC indicator) . . . 24
- 7.2 Summary of main options . . . 25

8 Session information **25**

1 Overview

This vignette shows how to use our code to carry out the sensitivity analysis proposed in the paper, for randomized trials in which the outcome is assessed at **irregular times** and assessment may depend on the outcome itself. The code supports general outcome types through a link function (identity, log, or logit).

We use a simulated data set generated from the Asthma Research for the Community (ARC) trial, following the simulation design in the paper. The vignette covers:

1. **Estimation of the mean outcome** $\mu^a(t)$ in each arm for fixed values of the sensitivity parameter α_a, with influence-function-based and parametric-bootstrap confidence intervals.
2. **Visualization**: the estimated mean curves, confidence intervals at the target times (3, 6, 9, and 12 months), and contour plots of the treatment effect $\delta(t) = \mu^1(t) - \mu^0(t)$ over a grid of (α_0, α_1).
3. **Selection of the sensitivity parameter**: point estimates (Algorithm 1), multiplier bootstrap bias-corrected estimates (Algorithm 2), and double bootstrap confidence sets (Algorithm 3) for the range (α_a^l, α_a^u).

1.1 Brief review of the method

For each arm a, the sensitivity parameter α_a enters through the exponential tilting assumption

$$dF\{y(t) \mid \Delta N(t) = 0, \overline{O}(t)\} \propto \exp(\alpha y)\, dF\{y(t) \mid \Delta N(t) = 1, \overline{O}(t)\},$$

so that a negative (positive) α_a means that unobserved outcomes at time t tend to be lower (higher) than observed outcomes among similar participants. Setting $\alpha_a = 0$ gives the explainable assessment assumption.

The mean outcome is modeled as $\mu(t) = s\{B(t)'\beta\}$ for $t \in [t_1, t_2]$, where $B(t)$ is a cubic spline basis and $s = g^{-1}$ is a known inverse link function. Here we use $[t_1, t_2] = [60, 460]$ days and a spline with one interior knot at $t = 260$. The coefficient β is estimated by an augmented inverse intensity-weighted (AIIW) estimator based on the influence function in the paper, with one of two weight functions, $W_1(t; \beta)$ or $W_2(t; \beta)$.

Two observed-data models are fitted within each arm:

- the assessment intensity $\lambda\{t \mid \overline{O}(t)\}$, using an Andersen–Gill model stratified by assessment number; and
- the conditional distribution of observed outcomes, using a single-index model with predictors `Prev_outcome`, `time`, and `Lag_time`.

To choose plausible values of α_a, clinical experts give a plausible range (μ_a^l, μ_a^u) for the mean outcome. Based on the monotonicity of $\mu^a(t; \alpha_a)$ in α_a, the set of values for which $\mu_a^l < \mu^a(t; \alpha_a) < \mu_a^u$ for all $t \in [t_1, t_2]$ is an interval (α_a^l, α_a^u), which we estimate from the data.

2 Setup

2.1 Working directory

The working directory is set to the folder that contains this R Markdown file, so the function files (`1. function_inference.R` and `1. function_selection.R`) and the simulated data sets should

be placed in the same folder. When knitting, `setwd()` only affects the chunk it is called in, so we also set `root.dir`, which makes all later chunks run in this folder.

```
if (isTRUE(getOption("knitr.in.progress"))) {
  # when knitting
  path <- dirname(knitr::current_input(dir = TRUE))
} else if (requireNamespace("rstudioapi", quietly = TRUE) &&
           rstudioapi::isAvailable()) {
  # when running chunks interactively in RStudio
  path <- dirname(rstudioapi::getSourceEditorContext()$path)
} else {
  # otherwise, use the current working directory
  path <- getwd()
}

setwd(path)
knitr::opts_knit$set(root.dir = path)
```

2.2 Packages and functions

All functions for estimation and inference are stored in `1. function_inference.R`. All functions for sensitivity parameter selection are stored in `1. function_selection.R`. The single-index model is fitted with functions from the SensIAT package (version 0.3.0 or later, available on CRAN).

```
library(dplyr)
library(survival)
library(MAVE)
library(dfoptim)
library(orthogonalsplinebasis)
library(BB)
library(statmod)   # Gauss-Legendre quadrature
library(parallel)
library(ggplot2)
library(metR)      # contour plots
library(isoband)
library(SensIAT)   # single-index model

# functions for estimation and inference
source("1. function_inference.R")
# functions for sensitivity parameter selection
source("1. function_selection.R")
```

2.3 Running time

Several steps (parametric bootstrap, multiplier bootstrap, and especially the double bootstrap) are computationally intensive and are designed to run in parallel with `parallel::mclapply()`. The number of cores is set by `n_cores` below. Note that `mclapply()` does not support more than one core on Windows.

To avoid re-running these steps every time the vignette is knitted, we use a small helper that saves each time-consuming result to the `cache` folder and loads it on later runs. Delete the corresponding `.rds` file to re-run a step. The helper also hides the progress messages printed by the estimation functions, so that they do not appear in the PDF.

```
n_cores   <- 96   # e.g., 64 or 96 on a cluster; use 1 on Windows
cache_dir <- "cache"
dir.create(cache_dir, showWarnings = FALSE, recursive = TRUE)

run_or_load <- function(name, expr) {
  file <- file.path(cache_dir, paste0(name, ".rds"))
  if (file.exists(file)) return(readRDS(file))
  # run only if no saved result exists; progress messages are hidden
  invisible(utils::capture.output(result <- expr))
  saveRDS(result, file)
  result
}
```

3 Data

The simulated data set is based on the ARC trial and is generated using the simulation method described in the paper. Each arm is stored as a separate data set:

- `ARC_simu_data_200_neg_trt` and `ARC_simu_data_200_neg_crl`: the original ACQ score for the intervention (PT+HV) arm and the control (PT) arm. The ACQ score ranges from 0 to 6, and either the log link or the identity link can be applied.
- `ARC_simu_data_200_logistic_trt` and `ARC_simu_data_200_logistic_crl`: the binary asthma control (AC) indicator, which should be analyzed with the logit link.

```
data_ARC_trt_continuous <- readRDS(file = "ARC_simu_data_200_neg_trt")
data_ARC_crl_continuous <- readRDS(file = "ARC_simu_data_200_neg_crl")

# binary AC indicator (logit link)
# data_ARC_trt_binary <- readRDS(file = "ARC_simu_data_200_logistic_trt")
# data_ARC_crl_binary <- readRDS(file = "ARC_simu_data_200_logistic_crl")

head(data_ARC_trt_continuous)
```

```
##     id time event Prev_outcome prev_time Lag_time visit  outcome
## 129  1  830     0     4.666667         0      830     1       NA
## 2    2  192     1     2.166667         0      192     1 2.500000
## 210  2  578     1     2.500000       192      386     2 1.666667
## 211  2  670     1     1.666667       578       92     3 2.000000
## 4    2  830     0     2.000000       670      160     4       NA
## 109  3  130     1     2.666667         0      130     1 1.333333
```

The data are in long format, with one row per assessment and one additional row at the end of follow-up (day 830) for each participant, where `event = 0` and `outcome = NA`. The variables are the participant identifier `id`, the assessment time `time` (days since randomization), the assessment

indicator `event`, the outcome at the previous assessment `Prev_outcome`, the time of the previous assessment `prev_time`, the time since the previous assessment `Lag_time`, the assessment number `visit`, and the outcome `outcome`.

4 Estimation of the mean outcome

Throughout this section, we use the **log link** for the ACQ score and the first weight function $W_1(t;\beta)$ as an example. For other link functions or weight functions, change the `link_type` and `IF_type` arguments in each function.

We consider $\alpha \in \{-1.2, -0.8, -0.4, 0, 0.4, 0.8\}$ for the ACQ score. These values lie within the bias-corrected 95% confidence set for (α_a^l, α_a^u) obtained in the last part of this vignette. Some of them, such as $\alpha = 0.8$, lie outside the estimated range itself, so the corresponding mean curves may fall partly outside the plausible range $(1.2, 3.0)$.

```
Alpha_seq <- c(-1.2, -0.8, -0.4, 0, 0.4, 0.8)
```

4.1 Point estimates and influence-function-based variance

`f_data_analysis_point()` returns, for each value of α, the estimated mean outcome $\widehat{\mu}(t) = s\{B(t)'\widehat{\beta}\}$ at 3, 6, 9, and 12 months, together with the influence-function-based variance estimate.

```
result_trt_log_weight1 <- run_or_load("result_trt_log_weight1",
  f_data_analysis_point(data      = data_ARC_trt_continuous,
                        link_type = "log",       # "log", "logit", "identity"
                        Alpha_seq = Alpha_seq,   # values of alpha
                        IF_type   = "weight1",   # "weight1" or "weight2"
                        SIM_model = "norm1coef")
)
```

The output is a list of two matrices. Each row corresponds to one value of α, and the columns correspond to the target times.

```
# point estimates of mu(t) at 3, 6, 9 and 12 months
result_trt_log_weight1[[1]]
```

```
##      Alpha   month3   month6   month9  month12
## [1,]  -1.2 1.266921 1.302730 1.193441 1.145256
## [2,]  -0.8 1.506160 1.499981 1.422928 1.369032
## [3,]  -0.4 1.822623 1.748302 1.722639 1.675810
## [4,]   0.0 2.238196 2.076359 2.107548 2.083038
## [5,]   0.4 2.737782 2.518863 2.582039 2.572956
## [6,]   0.8 3.270377 3.078076 3.128075 3.095330
```

```
# influence-function-based variance estimates
result_trt_log_weight1[[2]]
```

```
##      Alpha      month3      month6      month9     month12
## [1,]  -1.2 0.007003940 0.002694925 0.005702619 0.009368380
## [2,]  -0.8 0.006828712 0.003061730 0.005488218 0.008517975
```

```
## [3,]  -0.4 0.008471687 0.004208197 0.006554048 0.009993466
## [4,]   0.0 0.013338219 0.006710440 0.009656670 0.014092929
## [5,]   0.4 0.019020171 0.010424194 0.015245384 0.019375519
## [6,]   0.8 0.020559845 0.013792384 0.024364191 0.029366297
```

These can be used to construct Wald confidence intervals with the influence-function-based variance:

```
est <- result_trt_log_weight1[[1]][, -1]
se  <- sqrt(result_trt_log_weight1[[2]][, -1])

IF_CI <- data.frame(Alpha    = rep(Alpha_seq, times = 4),
                    Month    = rep(c(3, 6, 9, 12), each = length(Alpha_seq)),
                    Estimate = as.vector(est),
                    Lower_ci = as.vector(est - qnorm(0.975) * se),
                    Upper_ci = as.vector(est + qnorm(0.975) * se))
head(IF_CI)
```

```
##   Alpha Month Estimate Lower_ci Upper_ci
## 1  -1.2     3 1.266921 1.102893 1.430950
## 2  -0.8     3 1.506160 1.344196 1.668123
## 3  -0.4     3 1.822623 1.642224 2.003021
## 4   0.0     3 2.238196 2.011837 2.464554
## 5   0.4     3 2.737782 2.467477 3.008088
## 6   0.8     3 3.270377 2.989344 3.551411
```

4.2 Parametric bootstrap confidence intervals

As an alternative to the influence-function-based variance, we can use the parametric bootstrap. We first generate $B = 200$ parametric bootstrap data sets with `inner_ARC_SIR_sim_data_count_paraboot()`, and then estimate $\mu(t)$ in each of them with `f_data_analysis_line()`. Here, setting `spline_seq_orig = c(90, 180, 270, 360)` returns the estimates at 3, 6, 9, and 12 months.

```
set.seed(123)  # for the treatment group
B <- 200       # number of parametric bootstrap data sets
Index_sim <- sample(1:50000000, B, replace = FALSE)

result_simu <- run_or_load("paraboot_data_trt",
  parallel::mclapply(Index_sim,
                     inner_ARC_SIR_sim_data_count_paraboot,
                     SIM_model = "norm1coef",
                     data      = data_ARC_trt_continuous,
                     mc.cores  = n_cores)
)

# apply an estimation function to the index-th bootstrap data set
call_function_with_data <- function(index, fun, ...) {
  data <- result_simu[[index]][[1]]
  fun(data, ...)
}
```

```
result_trt <- run_or_load("paraboot_est_trt",
  parallel::mclapply(seq_len(B),
                     call_function_with_data,
                     f_data_analysis_line,
                     link_type       = "log",
                     IF_type         = "weight1",
                     SIM_model       = "norm1coef",
                     Alpha_seq       = Alpha_seq,
                     spline_seq_orig = c(90, 180, 270, 360),
                     mc.cores        = n_cores)
)
```

With `link = "log"`, `paraboot_var()` computes the parametric bootstrap variance of $\log \widehat{\mu}(t)$ for a given α and month. Given the point estimate and this variance on the log scale, `Wald_CI()` returns the point estimate and the 95% Wald confidence interval on the log scale, and `exp()` transforms them back to the original scale. For example, for month 3 and $\alpha = -1.2$:

```
SIM_treat_03 <- result_trt_log_weight1[[1]][, 2]   # estimates at month 3
month <- 3
alpha <- -1.2

refer_mean   <- SIM_treat_03 |> log()
var_paraboot <- paraboot_var(data = result_trt, alpha, month,
                             Alpha_seq = Alpha_seq, link = "log")
mean_orig    <- refer_mean[which(Alpha_seq == alpha)]

t_SIM_treat_03 <- Wald_CI(mean_orig, var_orig = var_paraboot) |> exp()
t_SIM_treat_03   # point estimate, lower bound, upper bound
```

```
## [1] 1.266921 1.066780 1.504610
```

5 Visualization

5.1 Estimated mean curves

To draw the mean curves, we estimate $\mu(t)$ on the full time grid $t \in \{60, 61, \ldots, 460\}$, which is the default of `f_data_analysis_line()`. This function returns point estimates only. The dotted lines show the plausible range $(1.2, 3.0)$ for the mean ACQ score given by the clinical collaborators.

```
spline_seq  <- seq(60, 460, by = 1)
range_value <- c(1.2, 3)

df_trt <- run_or_load("line_est_trt",
  f_data_analysis_line(data      = data_ARC_trt_continuous,
                       link_type = "log",
                       Alpha_seq = Alpha_seq,
                       IF_type   = "weight1",
```


```
                        SIM_model = "norm1coef")
)
```

```
plot_df_trt <- data.frame(
  Time  = rep(spline_seq, length(Alpha_seq)),
  Mean  = as.vector(t(df_trt[[1]][, -1])),
  Alpha = rep(as.character(Alpha_seq), each = length(spline_seq))
)

alpha_colours <- c("#253494", "#41b6c4", "#a1dab4",
                   "#ffffb2", "#fd8d3c", "#bd0026")
alpha_breaks  <- c("0.8", "0.4", "0", "-0.4", "-0.8", "-1.2")

line_plot_trt <- ggplot(plot_df_trt,
                        aes(x = Time, y = Mean, colour = Alpha)) +
  geom_line(linewidth = 1.5) +
  theme_bw() +
  expand_limits(x = c(30, 480), y = c(0, 5)) +
  scale_x_continuous(breaks = seq(90, 450, by = 90)) +
  scale_colour_manual(values = alpha_colours, breaks = alpha_breaks) +
  labs(x = "Time (Days)", y = "ACQ Score", colour = expression(alpha)) +
  theme(axis.title   = element_text(size = 25),
        legend.title = element_text(size = 20),
        axis.text    = element_text(size = 18),
        legend.text  = element_text(size = 18)) +
  annotate("text", x = 400, y = 4.5, label = "PT+HV Arm", size = 6) +
  geom_hline(yintercept = range_value, linetype = "dotted", linewidth = 2)

line_plot_trt
```



5.2 Confidence intervals at the target times

Next, we compute the parametric bootstrap Wald confidence intervals for all values of α at 3, 6, 9, and 12 months. The helper below repeats the calculation above for each α at a given month. The points are slightly shifted horizontally so that the intervals do not overlap.

```
Orig_res_trt <- result_trt_log_weight1
months       <- c(3, 6, 9, 12)
centre_days  <- c(90, 180, 270, 360)

ci_by_month <- function(month, paraboot_res, orig_res) {
  refer_mean <- orig_res[[1]][, which(months == month) + 1] |> log()
  out <- t(sapply(Alpha_seq, function(alpha) {
    mean_orig    <- refer_mean[which(Alpha_seq == alpha)]
    var_paraboot <- paraboot_var(data = paraboot_res, alpha, month,
                                 Alpha_seq = Alpha_seq, link = "log")
    Wald_CI(mean_orig, var_orig = var_paraboot) |> exp()
  }))
  data.frame(Alpha    = as.character(Alpha_seq),
             Time     = centre_days[months == month] + seq(-15, 10, by = 5),
             Estimate = out[, 1],
             Lower_ci = out[, 2],
             Upper_ci = out[, 3])
}


plot_df_SIM_treat <- do.call(rbind, lapply(months, ci_by_month,
                                           paraboot_res = result_trt,
```

```
                                          orig_res     = Orig_res_trt))
plot_df_SIM_treat
```

```
##    Alpha Time Estimate  Lower_ci Upper_ci
## 1   -1.2   75 1.266921 1.0667805 1.504610
## 2   -0.8   80 1.506160 1.3116243 1.729548
## 3   -0.4   85 1.822623 1.6223680 2.047596
## 4      0   90 2.238196 2.0001090 2.504623
## 5    0.4   95 2.737782 2.4167532 3.101455
## 6    0.8  100 3.270377 2.8360363 3.771238
## 7   -1.2  165 1.302730 1.1170128 1.519325
## 8   -0.8  170 1.499981 1.3155042 1.710328
## 9   -0.4  175 1.748302 1.5556868 1.964765
## 10     0  180 2.076359 1.8518002 2.328148
## 11   0.4  185 2.518863 2.2199189 2.858065
## 12   0.8  190 3.078076 2.6530415 3.571204
## 13  -1.2  255 1.193441 1.0218179 1.393891
## 14  -0.8  260 1.422928 1.2483607 1.621907
## 15  -0.4  265 1.722639 1.5295626 1.940087
## 16     0  270 2.107548 1.8693106 2.376148
## 17   0.4  275 2.582039 2.2680182 2.939539
## 18   0.8  280 3.128075 2.7032553 3.619656
## 19  -1.2  345 1.145256 0.9720458 1.349330
## 20  -0.8  350 1.369032 1.1918779 1.572517
## 21  -0.4  355 1.675810 1.4777438 1.900425
## 22     0  360 2.083038 1.8408676 2.357067
## 23   0.4  365 2.572956 2.2496143 2.942773
## 24   0.8  370 3.095330 2.6468548 3.619793
```

```
CI_plot_trt <- ggplot(plot_df_SIM_treat,
                      aes(x = Time, y = Estimate, colour = Alpha)) +
  geom_point(size = 3) +
  geom_errorbar(aes(ymin = Lower_ci, ymax = Upper_ci), linewidth = 1) +
  theme_bw() +
  expand_limits(x = c(30, 480), y = c(0, 5)) +
  scale_x_continuous(breaks = seq(90, 450, by = 90)) +
  scale_colour_manual(values = alpha_colours, breaks = alpha_breaks) +
  labs(x = "Time (Days)", y = "ACQ Score", colour = expression(alpha)) +
  theme(axis.title   = element_text(size = 25),
        legend.title = element_text(size = 20),
        axis.text    = element_text(size = 18),
        legend.text  = element_text(size = 18)) +
  annotate("text", x = 400, y = 4.5, label = "PT+HV Arm", size = 6) +
  geom_hline(yintercept = range_value, linetype = "dotted", linewidth = 2)

CI_plot_trt
```



The same code applies to the control arm after replacing `data_ARC_trt_continuous` with `data_ARC_crl_continuous`.

5.3 Contour plots of the treatment effect

To study the treatment effect $\delta(t) = \mu^1(t) - \mu^0(t)$ under different combinations of (α_0, α_1), we estimate $\mu^a(t)$ in **both** arms on a fine grid $\alpha \in \{-1.2, -1.18, \ldots, 0.8\}$, using both the original data and $B = 200$ parametric bootstrap data sets.

5.3.1 Estimation on a fine grid of α

```
Alpha_seq_contour <- seq(-1.2, 0.8, by = 0.02)
```

```
# treatment group: original data
result_trt_log_weight1_contour <- run_or_load("contour_orig_trt",
  f_data_analysis_line(data            = data_ARC_trt_continuous,
                       Alpha_seq       = Alpha_seq_contour,
                       spline_seq_orig = c(90, 180, 270, 360),
                       link_type       = "log",
                       IF_type         = "weight1",
                       SIM_model       = "norm1coef")
)

# treatment group: parametric bootstrap
set.seed(456)
B <- 200
Index_sim <- sample(1:50000000, B, replace = FALSE)
```

```
result_simu <- run_or_load("contour_paraboot_data_trt",
  parallel::mclapply(Index_sim,
                     inner_ARC_SIR_sim_data_count_paraboot,
                     data      = data_ARC_trt_continuous,
                     SIM_model = "norm1coef",
                     mc.cores  = n_cores)
)

result_trt_contour <- run_or_load("contour_paraboot_est_trt",
  parallel::mclapply(seq_len(B),
                     call_function_with_data,
                     f_data_analysis_line,
                     link_type       = "log",
                     IF_type         = "weight1",
                     SIM_model       = "norm1coef",
                     spline_seq_orig = c(90, 180, 270, 360),
                     Alpha_seq       = Alpha_seq_contour,
                     mc.cores        = n_cores)
)
```

```
# control group: original data
result_crl_log_weight1_contour <- run_or_load("contour_orig_crl",
  f_data_analysis_line(data            = data_ARC_crl_continuous,
                       Alpha_seq       = Alpha_seq_contour,
                       spline_seq_orig = c(90, 180, 270, 360),
                       link_type       = "log",
                       IF_type         = "weight1",
                       SIM_model       = "norm1coef")
)

# control group: parametric bootstrap
set.seed(345)
B <- 200
Index_sim <- sample(1:50000000, B, replace = FALSE)

result_simu <- run_or_load("contour_paraboot_data_crl",
  parallel::mclapply(Index_sim,
                     inner_ARC_SIR_sim_data_count_paraboot,
                     data      = data_ARC_crl_continuous,
                     SIM_model = "norm1coef",
                     mc.cores  = n_cores)
)

result_crl_contour <- run_or_load("contour_paraboot_est_crl",
  parallel::mclapply(seq_len(B),
                     call_function_with_data,
```

```
                    f_data_analysis_line,
                    link_type       = "log",
                    IF_type         = "weight1",
                    SIM_model       = "norm1coef",
                    spline_seq_orig = c(90, 180, 270, 360),
                    Alpha_seq       = Alpha_seq_contour,
                    mc.cores        = n_cores)
)
```

5.3.2 Treatment effect estimates and confidence intervals

For each pair (α_1, α_0), `Wald_CI_effect()` returns the estimated treatment effect $\widehat{\delta}(t)$ and its 95% Wald confidence interval, where the variance is estimated from the parametric bootstrap estimates of $\widehat{\mu}^1(t) - \widehat{\mu}^0(t)$.

Note that `Wald_CI_effect()` reads the objects `data_trt`, `data_crl`, `SIM_treat`, and `SIM_control` from the global environment, so they must be defined with exactly these names before it is called.

```
# parametric bootstrap estimates
data_trt    <- result_trt_contour
data_crl    <- result_crl_contour
# estimates from the original data
SIM_treat   <- result_trt_log_weight1_contour[[1]]
SIM_control <- result_crl_log_weight1_contour[[1]]

contour_df <- function(month) {
  grid <- expand.grid(Alpha_crl = Alpha_seq_contour,
                      Alpha_trt = Alpha_seq_contour)
  res  <- t(mapply(function(a_trt, a_crl) {
    Wald_CI_effect(alpha_trt = a_trt,
                   alpha_crl = a_crl,
                   month     = month,
                   Alpha_seq = Alpha_seq_contour)
  }, grid$Alpha_trt, grid$Alpha_crl))
  # the last two columns are the lower and upper confidence limits
  k <- ncol(res)
  data.frame(Alpha_trt    = grid$Alpha_trt,
             Alpha_crl    = grid$Alpha_crl,
             Estimate_vec = res[, 1],
             Lower_ci     = res[, k - 1],
             Upper_ci     = res[, k])
}

df_m6  <- contour_df(month = 6)
df_m12 <- contour_df(month = 12)
head(df_m6)
```

```
##   Alpha_trt Alpha_crl Estimate_vec   Lower_ci  Upper_ci
```

```
## 1      -1.2     -1.20    0.3924939 0.14322609 0.6417617
## 2      -1.2     -1.18    0.3813163 0.13196721 0.6306653
## 3      -1.2     -1.16    0.3699326 0.12052900 0.6193362
## 4      -1.2     -1.14    0.3583388 0.10865434 0.6080232
## 5      -1.2     -1.12    0.3465306 0.09628647 0.5967747
## 6      -1.2     -1.10    0.3345038 0.08415377 0.5848538
```


```r
# sanity check: lower limit <= estimate <= upper limit
ci_ok <- function(df) {
  with(df, all(Lower_ci <= Estimate_vec & Estimate_vec <= Upper_ci))
}
stopifnot(ci_ok(df_m6), ci_ok(df_m12))
```

5.3.3 Contour plot of the point estimates

The first plot shows the estimated treatment effect at 6 months for each combination of α_0 (PT arm, x-axis) and α_1 (PT+HV arm, y-axis). The dot at $(0, 0)$ corresponds to the explainable assessment assumption in both arms.

```r
SIM_p1 <- ggplot(df_m6,
                 aes(x = Alpha_crl, y = Alpha_trt, z = Estimate_vec)) +
  geom_contour_fill(binwidth = 0.4, show.legend = FALSE) +
  scale_fill_divergent(mid = "white", low = "forestgreen",
                       high = "orange") +
  geom_contour2(aes(z = Estimate_vec, label = after_stat(level)),
                colour = "black", size = 0.5, binwidth = 0.4, skip = 0.4,
                margin = grid::unit(c(5, 5, 5, 5), "pt"),
                label.placer = label_placer_fraction(
                  frac = 0.38, rot_adjuster = angle_fixed()),
                label_size = 7) +
  theme_bw() +
  labs(x = "Alpha for PT Arm", y = "Alpha for PT+HV Arm") +
  theme(axis.title = element_text(size = 25),
        axis.text  = element_text(size = 18)) +
  geom_vline(xintercept = 0, linetype = "dotted", linewidth = 1) +
  geom_hline(yintercept = 0, linetype = "dotted", linewidth = 1) +
  geom_point(x = 0, y = 0, size = 3) +
  scale_x_continuous(breaks = Alpha_seq) +
  scale_y_continuous(breaks = Alpha_seq)

SIM_p1
```



5.3.4 Contour plot of the confidence intervals

The next two plots summarize evidence of a treatment effect at 6 and 12 months, respectively. For each (α_0, α_1), we record the confidence limit closest to 0 when the interval excludes 0, and 0 otherwise:

- `CI_info` = lower bound, if the lower bound > 0 (the PT+HV arm has a higher mean ACQ score);
- `CI_info` = upper bound, if the upper bound < 0 (the PT+HV arm has a lower mean ACQ score, i.e., better asthma control);
- `CI_info` = 0, if the interval contains 0.

White regions therefore indicate insufficient evidence of a treatment effect. Because a lower ACQ score indicates better asthma control, green regions favor the home visits intervention.

```
# confidence limit closest to 0 if the CI excludes 0, and 0 otherwise
ci_info <- function(df) {
  with(df, Lower_ci * (Lower_ci > 0) + Upper_ci * (Upper_ci < 0))
}

plot_ci_contour <- function(df, title) {
  df2 <- mutate(df, CI_info = ci_info(df))
```

```
  ggplot(df2, aes(x = Alpha_crl, y = Alpha_trt, z = CI_info)) +
    geom_contour_fill(breaks = c(seq(-2.6, -0.2, by = 0.4), -1e-8, 1e-8, seq(0.2,
    ↪  2.6, by = 0.4))) +
    scale_fill_divergent(mid = "white", low = "forestgreen",
                         high = "orange", midpoint = 0) +
    theme_bw() +
    theme(legend.title = element_blank()) +
    labs(x = "Alpha for PT Arm", y = "Alpha for PT+HV Arm", title = title) +
    theme(plot.title      = element_text(size = 25),
          axis.title      = element_text(size = 25),
          axis.text       = element_text(size = 18),
          legend.text     = element_text(size = 14),
          legend.key.size = unit(1, "cm")) +
    geom_vline(xintercept = 0, linetype = "dotted", linewidth = 1) +
    geom_hline(yintercept = 0, linetype = "dotted", linewidth = 1) +
    geom_point(x = 0, y = 0, size = 3) +
    scale_x_continuous(breaks = Alpha_seq) +
    scale_y_continuous(breaks = Alpha_seq)
}

# check that the breaks cover the range of CI_info
range(ci_info(df_m6))
```


```
## [1] -1.705141  1.691407
```

```
range(ci_info(df_m12))
```


```
## [1] -1.661636  1.688590
```

```
SIM_p2_m6  <- plot_ci_contour(df_m6,  title = "Month 6")
SIM_p2_m12 <- plot_ci_contour(df_m12, title = "Month 12")

SIM_p2_m6
```


Month 6
Alpha for PT+HV Arm
Alpha for PT Arm
0.8
0.4
0.0
−0.4
−0.8
−1.2
−1.2
−0.8
−0.4
0.0
0.4
0.8
1
0
−1

```
SIM_p2_m12
```



If the range of `CI_info` printed above falls outside $[-2.6, 2.6]$, extend the `breaks` in `geom_contour_fill()`. The two breaks at $\pm 10^{-8}$ ensure that only the region where the confidence interval contains 0 is shown in white.

6 Selection of the sensitivity parameter

We now estimate the range (α_a^l, α_a^u) of sensitivity parameter values under which the mean ACQ score stays within the plausible range $(\mu_a^l, \mu_a^u) = (1.2, 3.0)$ for all $t \in [60, 460]$. We use the initial search grid $\mathcal{A}_M = \{-3, -2.99, \ldots, 3\}$. The time grid $\mathcal{T}_K$ is handled internally by Gauss–Legendre quadrature nodes on $[60, 460]$. We illustrate the procedure for the treatment arm with the log link and weight function $W_1(t; \beta)$. The control arm is handled in the same way.

6.1 Point estimates and bias-corrected point estimates

6.1.1 Algorithm 1: original point estimates

`fun_est_IF_onestep_analysis()` implements Algorithm 1. For each $\alpha \in \mathcal{A}_M$, it solves the estimating equation for $\widehat{\beta}^a(\alpha)$ and stores the influence-function-based information needed by the bootstrap procedures (the estimated influence functions and the inverse of their derivatives). The first element of the output contains the original point estimates $(\widehat{\alpha}_a^l, \widehat{\alpha}_a^u)$. If no value in $\mathcal{A}_M$ satisfies the constraint, the output is `NA`, and Algorithms 2 and 3 cannot be performed.

```
orig_trt_log_weight1 <- run_or_load("alg1_orig_trt",
  fun_est_IF_onestep_analysis(df_sim    = data_ARC_trt_continuous,
                              Alpha_seq = seq(-3, 3, by = 0.01),
```

```
                                range     = c(1.2, 3),
                                link_type = "log",
                                SIM_model = "norm1coef",
                                IF_type   = "weight1")
)
```

6.1.2 Algorithm 2: multiplier bootstrap bias correction

`f_onestep_bias_adaptive()` implements one replicate of Algorithm 2 with the one-step multiplier bootstrap estimator. The main options are:

- `weight_type`: the distribution of the multiplier weights, `"rademacher"`, `"normal"`, or `"exp"`;
- `search_method`: `"grid"` evaluates all values in $\mathcal{A}_M$; `"binary"` uses binary search based on monotonicity; `"adaptive"` (recommended) uses binary search first and switches to grid search if NA values occur.

```
search_method <- "adaptive"

set.seed(123)
Boot_num <- 200
Boot_seed_all <- sample(500000000, size = Boot_num, replace = TRUE)

result_bias <- run_or_load("alg2_bias_trt",
  parallel::mclapply(Boot_seed_all,
                     f_onestep_bias_adaptive,
                     orig_input    = orig_trt_log_weight1,
                     Alpha_seq     = seq(-3, 3, by = 0.01),
                     weight_type   = "rademacher",
                     link_type     = "log",
                     search_method = search_method,
                     range         = c(1.2, 3),
                     mc.cores      = n_cores)
)
```

Each replicate returns the bootstrap estimates $(\widehat{\alpha}_a^{l,b}, \widehat{\alpha}_a^{u,b})$ in its first element and the search method that was actually used in its second element. The bias-corrected estimates are

$$\widehat{\alpha}_a^{l,corr} = 2\widehat{\alpha}_a^{l} - \frac{1}{B}\sum_{b=1}^{B}\widehat{\alpha}_a^{l,b}, \qquad \widehat{\alpha}_a^{u,corr} = 2\widehat{\alpha}_a^{u} - \frac{1}{B}\sum_{b=1}^{B}\widehat{\alpha}_a^{u,b}.$$

Replicates that fail to identify a feasible α are recorded as `NA` and excluded.

```
Alpha_l_trt_point_orig <- orig_trt_log_weight1[[1]][1]
Alpha_u_trt_point_orig <- orig_trt_log_weight1[[1]][2]

corr_trt_log_weight1 <- result_bias

Boot_est_l <- rep(NA, Boot_num)
Boot_est_u <- rep(NA, Boot_num)
```

```
Type       <- rep(NA, Boot_num)

for (j in 1:Boot_num) {
  temp <- corr_trt_log_weight1[[j]]
  Boot_est_l[j] <- temp[[1]][1]
  Boot_est_u[j] <- temp[[1]][2]
  Type[j]       <- temp[[2]]
}

Alpha_l_trt_point_corr <- 2 * Alpha_l_trt_point_orig -
  mean(Boot_est_l, na.rm = TRUE)
Alpha_u_trt_point_corr <- 2 * Alpha_u_trt_point_orig -
  mean(Boot_est_u, na.rm = TRUE)

# original point estimates of (alpha_l, alpha_u)
trt_log_weight1_orig <- c(Alpha_l_trt_point_orig, Alpha_u_trt_point_orig)
trt_log_weight1_orig
```

```
## [1] -1.09  0.40
```

```
# bias-corrected point estimates of (alpha_l, alpha_u)
trt_log_weight1_corr <- c(Alpha_l_trt_point_corr, Alpha_u_trt_point_corr)
trt_log_weight1_corr
```

```
## [1] -1.20610  0.46655
```

```
# search method used in each bootstrap replicate
table(Type)
```

```
## Type
## binary
##    200
```

6.2 Confidence set for (α_a^l, α_a^u)

6.2.1 Algorithm 3: double bootstrap

`f_double_boot_onestep_adaptive()` implements one outer replicate of Algorithm 3, including `L` inner replicates. We use $B_1 = 400$ outer and $B_2 = 50$ inner replicates. This is the most time-consuming step.

```
orig_input <- orig_trt_log_weight1

Boot_outer    <- 400
Boot_inner    <- 50
search_method <- "adaptive"

set.seed(567)
Boot_seed_all <- sample(500000000, size = Boot_outer, replace = TRUE)
```

```
result_double <- run_or_load("alg3_double_trt",
  parallel::mclapply(Boot_seed_all,
                     f_double_boot_onestep_adaptive,
                     orig_input    = orig_input,
                     Alpha_seq     = seq(-3, 3, by = 0.01),
                     range         = c(1.2, 3),
                     weight_type   = "rademacher",
                     link_type     = "log",
                     IF_type       = "weight1",
                     search_method = search_method,
                     L             = Boot_inner,   # inner bootstrap size
                     mc.cores      = n_cores)
)
```

Each outer replicate b_1 returns a list with five elements:

1. the outer bootstrap estimates $(\widehat{\alpha}_a^{l,b_1}, \widehat{\alpha}_a^{u,b_1})$;
2. the inner bootstrap estimates $\{\widehat{\alpha}_a^{l,b_1,b_2}\}_{b_2=1}^{B_2}$;
3. the inner bootstrap estimates $\{\widehat{\alpha}_a^{u,b_1,b_2}\}_{b_2=1}^{B_2}$;
4. the number of inner replicates with `NA`, for the lower and the upper bound;
5. the search method that was actually used.

We then follow Steps 2–4 of Algorithm 3:

- Bias-corrected outer estimates: $\widehat{\alpha}_a^{l,b_1,corr} = 2\widehat{\alpha}_a^{l,b_1} - B_2^{-1}\sum_{b_2}\widehat{\alpha}_a^{l,b_1,b_2}$, and similarly for the upper bound.
- Bias-corrected point estimates: $\widehat{\alpha}_a^{l,corr} = 2\widehat{\alpha}_a^{l} - B_1^{-1}\sum_{b_1}\widehat{\alpha}_a^{l,b_1}$, and similarly for the upper bound.
- 95% confidence sets:
  - **Basic bootstrap**: $(2\widehat{\alpha}_a^{l,corr} - C_{0.975}^{l},\ 2\widehat{\alpha}_a^{u,corr} - C_{0.025}^{u})$, where $C_{0.975}^{l}$ is the 97.5% quantile of $\{\widehat{\alpha}_a^{l,b_1,corr}\}$ and $C_{0.025}^{u}$ is the 2.5% quantile of $\{\widehat{\alpha}_a^{u,b_1,corr}\}$.
  - **Wald**: $(\widehat{\alpha}_a^{l,corr} - q_{0.975}\,\mathrm{sd}\{\widehat{\alpha}_a^{l,b_1,corr}\},\ \widehat{\alpha}_a^{u,corr} + q_{0.975}\,\mathrm{sd}\{\widehat{\alpha}_a^{u,b_1,corr}\})$, where $q_{0.975}$ is the 97.5% quantile of the standard normal distribution.

For comparison, we also compute the same confidence sets without bias correction.

```
Orig <- orig_trt_log_weight1
temp <- result_double

alpha_u_boot_outer_orig <- rep(NA, Boot_outer)
alpha_l_boot_outer_orig <- rep(NA, Boot_outer)
alpha_u_boot_outer_corr <- rep(NA, Boot_outer)
alpha_l_boot_outer_corr <- rep(NA, Boot_outer)
NA_count_l_i <- rep(NA, Boot_outer)
NA_count_u_i <- rep(NA, Boot_outer)
Type         <- rep(NA, Boot_outer)

for (j in 1:Boot_outer) {
```

```
  alpha_l_boot_outer_orig[j] <- temp[[j]][[1]][1]
  alpha_u_boot_outer_orig[j] <- temp[[j]][[1]][2]
  alpha_l_boot_outer_corr[j] <- 2 * alpha_l_boot_outer_orig[j] -
    mean(temp[[j]][[2]], na.rm = TRUE)
  alpha_u_boot_outer_corr[j] <- 2 * alpha_u_boot_outer_orig[j] -
    mean(temp[[j]][[3]], na.rm = TRUE)

  NA_count_l_i[j] <- temp[[j]][[4]][1]
  NA_count_u_i[j] <- temp[[j]][[4]][2]

  Type[j] <- temp[[j]][[5]]
}

# bias-corrected point estimates
Orig_corr_l <- 2 * Orig[[1]][1] - mean(alpha_l_boot_outer_orig, na.rm = TRUE)
Orig_corr_u <- 2 * Orig[[1]][2] - mean(alpha_u_boot_outer_orig, na.rm = TRUE)

# basic bootstrap confidence set: bias-corrected and original
CI_perc_low_alpha_l_trt_corr1 <- 2 * Orig_corr_l -
  quantile(alpha_l_boot_outer_corr, 0.975, na.rm = TRUE)
CI_perc_upper_alpha_u_trt_corr1 <- 2 * Orig_corr_u -
  quantile(alpha_u_boot_outer_corr, 0.025, na.rm = TRUE)

CI_perc_low_alpha_l_trt_orig1 <- 2 * Orig[[1]][1] -
  quantile(alpha_l_boot_outer_orig, 0.975, na.rm = TRUE)
CI_perc_upper_alpha_u_trt_orig1 <- 2 * Orig[[1]][2] -
  quantile(alpha_u_boot_outer_orig, 0.025, na.rm = TRUE)

# Wald confidence set: bias-corrected and original
CI_perc_low_alpha_l_trt_corr2 <- Orig_corr_l -
  qnorm(0.975) * sd(alpha_l_boot_outer_corr, na.rm = TRUE)
CI_perc_upper_alpha_u_trt_corr2 <- Orig_corr_u +
  qnorm(0.975) * sd(alpha_u_boot_outer_corr, na.rm = TRUE)

CI_perc_low_alpha_l_trt_orig2 <- Orig[[1]][1] -
  qnorm(0.975) * sd(alpha_l_boot_outer_orig, na.rm = TRUE)
CI_perc_upper_alpha_u_trt_orig2 <- Orig[[1]][2] +
  qnorm(0.975) * sd(alpha_u_boot_outer_orig, na.rm = TRUE)
```

The tables below summarize the point estimates and the 95% confidence sets for (α_a^l, α_a^u). The bias-corrected rows correspond to the quantities reported in Table 1 of the paper; note that the paper's results are based on the real ARC data rather than on this simulated data set.

```
selection_summary_point <- data.frame(
  Quantity = c("Original point estimate",
               "Bias-corrected (Algorithm 2; 200 replicates)",
               "Bias-corrected (Algorithm 3; 400 outer replicates)"),
```

```
  alpha_l = c(trt_log_weight1_orig[1], trt_log_weight1_corr[1], Orig_corr_l),
  alpha_u = c(trt_log_weight1_orig[2], trt_log_weight1_corr[2], Orig_corr_u),
  row.names = NULL
)
knitr::kable(selection_summary_point, digits = 2, booktabs = TRUE)
```

Quantity	alpha_l	alpha_u
Original point estimate	-1.09	0.40
Bias-corrected (Algorithm 2; 200 replicates)	-1.21	0.47
Bias-corrected (Algorithm 3; 400 outer replicates)	-1.23	0.50

```
selection_summary_set <- data.frame(
  Quantity = c("95% basic bootstrap CI (original)",
               "95% Wald CI (original)",
               "95% basic bootstrap CI (bias-corrected)",
               "95% Wald CI (bias-corrected)"),
  Lower = c(CI_perc_low_alpha_l_trt_orig1,
            CI_perc_low_alpha_l_trt_orig2,
            CI_perc_low_alpha_l_trt_corr1,
            CI_perc_low_alpha_l_trt_corr2),
  Upper = c(CI_perc_upper_alpha_u_trt_orig1,
            CI_perc_upper_alpha_u_trt_orig2,
            CI_perc_upper_alpha_u_trt_corr1,
            CI_perc_upper_alpha_u_trt_corr2),
  row.names = NULL
)
knitr::kable(selection_summary_set, digits = 2, booktabs = TRUE)
```

Quantity	Lower	Upper
95% basic bootstrap CI (original)	-1.44	0.80
95% Wald CI (original)	-1.33	0.74
95% basic bootstrap CI (bias-corrected)	-1.72	1.01
95% Wald CI (bias-corrected)	-1.55	0.93

Finally, we check the number of `NA` values in the inner bootstrap replicates and the search method used in each outer replicate.

```
max(NA_count_l_i)
```

```
## [1] 0
```

```
max(NA_count_u_i)
```

```
## [1] 0
```

```r
table(Type)
```

```
## Type
## binary
##    400
```

The estimated range and its confidence set, together with clinical input, can then be used to choose the values of α_a reported in the main analysis. For example, the values $\alpha_a \in \{-1.2, -0.8, -0.4, 0, 0.4, 0.8\}$ used for the ACQ score lie within the bias-corrected 95% confidence set.

7 Other outcome types and options

7.1 Binary outcome (AC indicator)

For the binary AC indicator, use the logit link and the corresponding plausible range $(0.2, 0.5)$:

```r
data_ARC_trt_binary <- readRDS(file = "ARC_simu_data_200_logistic_trt")

Alpha_seq_binary <- c(-0.8, -0.4, 0, 0.4, 0.8, 1.2)

result_trt_logit_weight1 <- f_data_analysis_point(
  data      = data_ARC_trt_binary,
  link_type = "logit",
  Alpha_seq = Alpha_seq_binary,
  IF_type   = "weight1",
  SIM_model = "norm1coef"
)

orig_input_binary <- fun_est_IF_onestep_analysis(
  df_sim    = data_ARC_trt_binary,
  Alpha_seq = seq(-3, 3, by = 0.01),
  range     = c(0.2, 0.5),
  SIM_model = "norm1coef",
  link_type = "logit",
  IF_type   = "weight1"
)
```

Three points to note when changing the outcome type:

- When calling `paraboot_var()`, pass `Alpha_seq = Alpha_seq_binary` and `link = "logit"` for the binary outcome.
- For the logit link, use `qlogis()` instead of `log()` to compute `refer_mean`, and `plogis()` instead of `exp()` to transform the point estimate and the confidence interval back to the probability scale.
-
  - Set `range = c(0.2, 0.5)` and `link_type = "logit"` in all three sensitivity parameter selection functions:
  - `fun_est_IF_onestep_analysis()`,
  - `f_onestep_bias_adaptive()`, and

– `f_double_boot_onestep_adaptive()`.

7.2 Summary of main options

Argument	Values	Description
`link_type`	`"log"`, `"logit"`, `"identity"`	Link function g in the marginal mean model $\mu(t) = g^{-1}\{B(t)'\beta\}$
`IF_type`	`"weight1"`, `"weight2"`	Weight function $W_1(t;\beta)$ or $W_2(t;\beta)$ in the influence function
`SIM_model`	`"norm1coef"`, `"fixed_coef"`, `"fixed_band"`	Fitting method for the single-index outcome model
`Alpha_seq`	numeric vector	Values of the sensitivity parameter
`spline_seq_orig`	numeric vector	Times (days) at which $\mu(t)$ is reported by `f_data_analysis_line()`
`range`	`c(1.2, 3)`, `c(0.2, 0.5)`, ...	Plausible range (μ_a^l, μ_a^u) of the mean outcome
`weight_type`	`"rademacher"`, `"normal"`, `"exp"`	Distribution of the multiplier weights
`search_method`	`"adaptive"`, `"binary"`, `"grid"`	Search strategy over $\mathcal{A}_M$ in Algorithms 2 and 3
`L`	integer	Number of inner bootstrap replicates in Algorithm 3

8 Session information

```
sessionInfo()
```

```
## R version 4.4.2 (2024-10-31)
## Platform: aarch64-apple-darwin20
## Running under: macOS Sequoia 15.6.1
##
## Matrix products: default
## BLAS:   /Library/Frameworks/R.framework/Versions/4.4-arm64/Resources/lib/libRblas.0.dylib
## LAPACK: /Library/Frameworks/R.framework/Versions/4.4-arm64/Resources/lib/libRlapack.dylib;
##
## locale:
## [1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8
##
## time zone: America/New_York
## tzcode source: internal
##
## attached base packages:
```

```
## [1] parallel  stats     graphics  grDevices utils     datasets  methods
## [8] base
##
## other attached packages:
##  [1] SensIAT_0.3.0.9000          isoband_0.2.7
##  [3] metR_0.18.0                 ggplot2_3.5.2
##  [5] statmod_1.5.1               BB_2019.10-1
##  [7] orthogonalsplinebasis_0.1.7 dfoptim_2023.1.0
##  [9] MAVE_1.3.11                 survival_3.7-0
## [11] dplyr_1.1.4
##
## loaded via a namespace (and not attached):
##  [1] tidyr_1.3.1        generics_0.1.3     class_7.3-22       KernSmooth_2.23-24
##  [5] lattice_0.22-6     pracma_2.4.4       digest_0.6.37      magrittr_2.0.3
##  [9] evaluate_1.0.3     grid_4.4.2         fastmap_1.2.0      plyr_1.8.9
## [13] Matrix_1.7-1       backports_1.5.0    tinytex_0.55       purrr_1.0.4
## [17] scales_1.3.0       cli_3.6.4          rlang_1.1.5        munsell_0.5.1
## [21] splines_4.4.2      withr_3.0.2        cachem_1.1.0       yaml_2.3.10
## [25] tools_4.4.2        memoise_2.0.1      checkmate_2.3.2    colorspace_2.1-1
## [29] assertthat_0.2.1   vctrs_0.6.5        R6_2.6.1           lifecycle_1.0.4
## [33] MASS_7.3-61        pkgconfig_2.0.3    pillar_1.10.1      gtable_0.3.6
## [37] glue_1.8.0         data.table_1.17.0  Rcpp_1.1.1         xfun_0.51
## [41] tibble_3.2.1       tidyselect_1.2.1   rstudioapi_0.17.1  knitr_1.49
## [45] mda_0.5-5          farver_2.1.2       htmltools_0.5.8.1  labeling_0.4.3
## [49] rmarkdown_2.29     compiler_4.4.2     quadprog_1.5-8
```