

ZM-Z3224-9BA



1/3" Sony CMOS Image sensor(Global shutter)
2048 × 1536
60/50 fps(TBA), 30/25 fps
Color: 0.03 Lux @ (F1.63, AGC ON), BW: 0Lux (IR LED)
Optical 30x Digital 10x
256 zoom/focus presets(TBA)
H.265 / H.264 / JPEG
HTTP RESTful API, Onvif

System

Product IP

Image Sensor

Sensor 1/3" Sony CMOS Image sensor(Global shutter)
Total pixels 2,064(H) x 1,592(V) = 3.28M Pixels
Effective pixels 2,064(H) x 1,522(V) = 3.20M Pixels
Resolution 2048 × 1536
Frame Rate 60/50 fps(TBA), 30/25 fps
Min. illumination Color: 0.03 Lux @ (F1.63, AGC ON), BW: 0Lux (IR LED)

Lens

Zoom Ratio Optical 30x Digital 10x
Focal Length f = 4.6mm ~ 136.8mm
Aperture ratio F1.63(wide) ~ F4.85(tele)
Angle Of View H : 59°(W) ~ 2°(T)
V : 34.6°(W) ~ 1.17°(T)
D : 66.2°(W) ~ 2.36°(T)
Min. Distance 0.5m(Wide), 5m(Tele)
Iris DC auto iris(TBA)
IR Cut Filter on / off

Function

Control Mode	Auto / Manual / Zoom Trigger / One Push
Presets	256 zoom/focus presets(TBA)
Day & Night	Auto, Day, Night, Ext-in
D&N Levels	10 levels (without Ext-in)
Electronic Shutter Speed	1/25(30)/1/50(60) ~ 1/5000
White Balance Modes	Auto, Manual (3 steps or more)
Exposure Modes	Auto, Shutter Priority, Manual
Gain control	Auto / Manual
WDR	Off / On(TBA)
BLC	Off / On, Area selectable
HLC	Off / On
DNR	2D&3D
Defog	Off / Low / Middle / High
DIS	Off / On(TBA)
Mirror	Off, Vertical Flip, Horizontal Flip, H+V Flip (180degree rotation)
Privacy Mask	Max 8 Zones
Motion detection	32 × 18 cell / AI motion detection(TBA)
Output Format	H.265 / H.264 / JPEG
Bitrate	512~15000 kbps

Streaming

Quadruple (x4) IP Streaming
Main Stream : up to 1920 × 1080
Second Stream : up to 1280 × 720
Third Stream : up to 640 × 480(TBA)
JPEG : 1920 × 1080

OSD

Title, Date, Resolution

Main UI

Web-based GUI

System Mode

NTSC / PAL

Recording

Video

TBD

JPEG

TBD

AI

Rule Engine / Tracker

TBD

Video analytics

TBD

Audio

Compression

G.711 ulaw

Sampling rate

8khz

Input & Output

1 Line In / 1 Line Out

Network

Interface	10BASE-T/100BASE-TX
Protocol	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, NTP, SMTP, FTP, UPnP, HTTP, HTTPS, SSL/TLS
Security	Password protection, IP address filtering, Https encryption, brute force delay protection
control protocol	HTTP RESTful API, Onvif

General

External devices	1x Alarm input 1x Alarm output 1x D&N input(Ext-in) 1x PWM output(lighting control) 1x UART
External Storage	Micro SD
Power Supply	12V
Power consumption	TBD
Storage Temperature	-20°C ~ +60°C (Humidity < 90%RH, Non-condensing)
Operating Temperature	-10°C ~ +50°C (Humidity < 90%RH, Non-condensing)
Dimension	TBD
Weight	TBD
Certifications	NA

Dimension

