

## Managing GCP credentials and subscriptions for Cloud Manager

**Cloud Manager** 

Ben Cammett November 16, 2020

This PDF was generated from https://docs.netapp.com/us-en/occm/task\_adding\_gcp\_accounts.html on February 28, 2021. Always check docs.netapp.com for the latest.

### **Table of Contents**

M	anaging GCP credentials and subscriptions for Cloud Manager	1
	Associating a Marketplace subscription with GCP credentials	1
	Setting up and adding GCP accounts for data tiering with Cloud Volumes ONTAP 9.6	2

# Managing GCP credentials and subscriptions for Cloud Manager

You can manage two types of Google Cloud Platform credentials from Cloud Manager: the credentials that are associated with the Connector VM instance and storage access keys used with a Cloud Volumes ONTAP 9.6 system for data tiering.


### Associating a Marketplace subscription with GCP credentials

When you deploy a Connector in GCP, Cloud Manager creates a default set of credentials that are associated with the Connector VM instance. These are the credentials that Cloud Manager uses to deploy Cloud Volumes ONTAP.


At any time, you can change the Marketplace subscription that's associated with these credentials. The subscription enables you to create a pay-as-you-go Cloud Volumes ONTAP system, and to use other NetApp cloud services.

#### Steps

- 1. In the upper right of the Cloud Manager console, click the Settings icon, and select Credentials.
- 2. Hover over a set of credentials and click the action menu.
- 3. From the menu, click Associate Subscription.



4. Select a Google Cloud project and subscription from the down-down list or click **Add Subscription** and follow the steps to create a new subscription.



5. Click Associate.

## Setting up and adding GCP accounts for data tiering with Cloud Volumes ONTAP 9.6

If you want to enable a Cloud Volumes ONTAP 9.6 system for data tiering, you need to provide Cloud Manager with a storage access key for a service account that has Storage Admin permissions. Cloud Manager uses the access keys to set up and manage a Cloud Storage bucket for data tiering.




If you want to use data tiering with Cloud Volumes ONTAP 9.7 or later, then follow step 4 in Getting started with Cloud Volumes ONTAP in Google Cloud Platform.

#### Setting up a service account and access keys for Google Cloud Storage

A service account enables Cloud Manager to authenticate and access Cloud Storage buckets used for data tiering. The keys are required so that Google Cloud Storage knows who is making the request.

#### Steps

1. Open the GCP IAM console and create a service account that has the Storage Admin role.



- 2. Go to GCP Storage Settings.
- 3. If you're prompted, select a project.
- 4. Click the **Interoperability** tab.
- 5. If you haven't already done so, click **Enable interoperability access**.
- 6. Under Access keys for service accounts, click Create a key for a service account.
- 7. Select the service account that you created in step 1.

#### Select a service account



CANCEL CREATE KEY | CREATE NEW ACCOUNT

- 8. Click Create Key.
- 9. Copy the access key and secret.

You'll need to enter this information in Cloud Manager when you add the GCP account for data tiering.

#### Adding a GCP account to Cloud Manager


Now that you have an access key for a service account, you can add it to Cloud Manager.

#### What you'll need

You need to create a Connector before you can change Cloud Manager settings. Learn how.

#### **Steps**

1. In the upper right of the Cloud Manager console, click the Settings icon, and select **Credentials**.



- 2. Click Add Credentials and select Google Cloud.
- 3. Enter the access key and secret for the service account.

The keys enable Cloud Manager to set up a Cloud Storage bucket for data tiering.

4. Confirm that the policy requirements have been met and then click Create Account.

#### What's next?

You can now enable data tiering on individual volumes on a Cloud Volumes ONTAP 9.6 system when you create, modify, or replicate them. For details, see Tiering inactive data to low-cost object storage.

But before you do, be sure that the subnet in which Cloud Volumes ONTAP resides is configured for Private Google Access. For instructions, refer to Google Cloud Documentation: Configuring Private Google Access.

#### **Copyright Information**

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

#### **Trademark Information**

NETAPP, the NETAPP logo, and the marks listed at <a href="http://www.netapp.com/TM">http://www.netapp.com/TM</a> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.