



Backing up data to Amazon S3

Cloud Manager

Ben Cammett, Tom Onacki
January 27, 2021

Table of Contents

- Backing up data to Amazon S3 1
 - Quick start 1
 - Requirements 2
 - Enabling Cloud Backup on a new system 3
 - Enabling Cloud Backup on an existing system 4

Backing up data to Amazon S3

Complete a few steps to get started backing up data from Cloud Volumes ONTAP to Amazon S3.

Quick start

Get started quickly by following these steps or scroll down to the remaining sections for full details.

1

Verify support for your configuration

- You're running Cloud Volumes ONTAP 9.6 or later in AWS.
- You have subscribed to the [Cloud Manager Marketplace Backup offering](#), or you have purchased [and activated](#) a Cloud Backup BYOL license from NetApp.
- The IAM role that provides Cloud Manager with permissions includes S3 permissions from the latest [Cloud Manager policy](#).

2

Enable Cloud Backup on your new or existing system

- New systems: Cloud Backup is enabled by default in the working environment wizard. Be sure to keep the option enabled.
- Existing systems: Select the working environment and click **Activate** next to the Cloud Backup service in the right-panel, and then follow the setup wizard.



3

Define the backup policy

The default policy backs up volumes every day and retains the most recent 30 backup copies of each volume. Change to weekly or monthly backups, or select one of the system-defined policies that provide more options. You can also change the number of backup copies to retain.

Define Policy

Policy - Retention & Schedule

☒ Create a New Policy ☐ Select an Existing Policy

Backup Every

Day

Number of backups to retain

30

DP Volumes

Data protection volume backups use the same retention period as defined in the source SnapMirror relationship by default. Use the API if you want to change this value

Information

Backup_Bucket_Name
Bucket Name

4 Select the volumes that you want to back up

Identify which volumes you want to back up in the Select Volumes page.

5 Restore your data, as needed

Choose to restore an entire backup to a new volume, or to restore individual files from the backup to an existing volume. You can restore data to a Cloud Volumes ONTAP system in AWS, or to an on-premises ONTAP system.

See [Restoring volume data from backup files](#) for details.

Requirements

Read the following requirements to make sure that you have a supported configuration before you start backing up volumes to S3.

Supported ONTAP versions

Cloud Volumes ONTAP 9.6 and later.

Supported AWS regions

Cloud Backup is supported in all AWS regions [where Cloud Volumes ONTAP is supported](#).

License requirements

For Cloud Backup PAYGO licensing, a Cloud Manager subscription is available in the AWS Marketplace that enables deployments of Cloud Volumes ONTAP 9.6 and later (PAYGO) and Cloud Backup. You need to [subscribe to this Cloud Manager subscription](#) before you enable Cloud Backup. Billing for Cloud Backup is done through this subscription.

For Cloud Backup BYOL licensing, you do not need an AWS Cloud Backup subscription. You need the serial number from NetApp that enables you to use the service for the duration and capacity of the license. See [Adding and updating your Backup BYOL license](#).

And you need to have a AWS subscription for the storage space where your backups will be located.

AWS permissions required

The IAM role that provides Cloud Manager with permissions must include S3 permissions from the latest [Cloud Manager policy](#).

Here are the specific permissions from the policy:



```
{
    "Sid": "backupPolicy",
    "Effect": "Allow",
    "Action": [
        "s3:DeleteBucket",
        "s3:GetLifecycleConfiguration",
        "s3:PutLifecycleConfiguration",
        "s3:PutBucketTagging",
        "s3:ListBucketVersions",
        "s3:GetObject",
        "s3:ListBucket",
        "s3:ListAllMyBuckets",
        "s3:GetBucketTagging",
        "s3:GetBucketLocation",
        "s3:GetBucketPolicyStatus",
        "s3:GetBucketPublicAccessBlock",
        "s3:GetBucketAcl",
        "s3:GetBucketPolicy",
        "s3:PutBucketPublicAccessBlock"
    ],
    "Resource": [
        "arn:aws:s3:::netapp-backup-*"
    ]
}
```

Enabling Cloud Backup on a new system

Cloud Backup is enabled by default in the working environment wizard. Be sure to keep the option enabled.

Steps

1. Click **Create Cloud Volumes ONTAP**.
2. Select Amazon Web Services as the cloud provider and then choose a single node or HA system.
3. Fill out the Details & Credentials page.
4. On the Services page, leave the service enabled and click **Continue**.

 Backup to Cloud 

Integrated backup for Cloud Volumes ONTAP based on SnapMirror and Snapshot technologies. Backup copies are maintained in S3 buckets. Backups stored in S3 are charged separately from Cloud Volumes ONTAP.

ADVANTAGES

- ✓ Automatically back up all volumes.
- ✓ Creates new backup copy every day.
- ✓ Retains backups for 30 days.

CLARIFICATIONS

- > Backup settings are editable after working environment creation.

5. Complete the pages in the wizard to deploy the system.

Result

Cloud Backup is enabled on the system and backs up volumes every day and retains the most recent 30 backup copies.

What's next?


You can [start and stop backups for volumes or change the backup schedule](#) and you can [restore entire volumes or individual files from a backup file](#).

Enabling Cloud Backup on an existing system

Enable Cloud Backup at any time directly from the working environment.

Steps

1. Select the working environment and click **Activate** next to the Cloud Backup service in the right-panel.



2. Define the backup schedule and retention value and click **Continue**.

Define Policy

Policy - Retention & Schedule
☒ Create a New Policy
 ☐ Select an Existing Policy

Backup Every:
 Number of backups to retain:

DP Volumes

Data protection volume backups use the same retention period as defined in the source SnapMirror relationship by default. Use the API if you want to change this value

Information

Backup_Bucket_Name
Bucket Name

See [the list of existing policies](#).

3. Select the volumes that you want to back up and click **Activate**.

Select Volumes

57 Volumes

<input checked="" type="checkbox"/>	Volume Name	Volume Type	Disk Type	SVM Name	Used Capacity	Allocated Capacity	Volume Status
<input checked="" type="checkbox"/>	Volume_Name_1	RW	GP2	SVM_Name_1	2.25 TB	10 TB	Active
<input checked="" type="checkbox"/>	Volume_Name_2	RW	GP2	SVM_Name_2	2.25 TB	10 TB	Active
<input checked="" type="checkbox"/>	Volume_Name_3	RW	GP2	SVM_Name_3	2.25 TB	10 TB	Active
<input checked="" type="checkbox"/>	Volume_Name_4	DP ⓘ	GP2	SVM_Name_4	2.25 TB	10 TB	Active
<input checked="" type="checkbox"/>	Volume_Name_5	RW	GP2	SVM_Name_5	2.25 TB	10 TB	Active

- To back up all volumes, check the box in the title row (☒ Volume Name).
- To back up individual volumes, check the box for each volume (☒ Volume_1).

Result

Cloud Backup starts taking the initial backups of each selected volume.

What's next?

You can [start and stop backups for volumes](#) or [change the backup schedule](#) and you can [restore entire volumes or individual files from a backup file](#).

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.