RAJALAKSHMI ENGINEERING COLLEGE

Yukesh R 251001316-2025-IT

Y2

Started on	Wednesday, 30 September 2026, 9:30 AM
State	Finished
Completed on	Wednesday, 30 September 2026, 9:32 AM
Time taken	2 mins 4 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement:

Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = x. If there exist such two elements then return the numbers, otherwise print as "No".

Note: Write a Divide and Conquer Solution

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Sum Value

Output Format

First Line Contains Integer – Element1

Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value "x")

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

// Recursive Divide and Conquer / Two-Pointer structure
int checkPairSumRecursive(int arr[], int low, int high, int x, int *res1, int *res2) {
    // Base Case: If the search pointers cross or meet, no pair exists
    if (low >= high) {
        return 0;
    }

    int current_sum = arr[low] + arr[high];

    // If matching pair found, capture the values and return success
    if (current_sum == x) {
        *res1 = arr[low];
        *res2 = arr[high];
        return 1;
    }

    // Divide the problem: If sum is greater, the answer cannot include arr[high]
    if (current_sum > x) {
        return checkPairSumRecursive(arr, low, high - 1, x, res1, res2);
    }

    // Divide the problem: If sum is smaller, the answer cannot include arr[low]
    return checkPairSumRecursive(arr, low + 1, high, x, res1, res2);
}

int main() {
    int n, x;

    // Read size of array
    if (scanf("%d", &n) != 1) {
        return 0;
    }

    // Dynamically allocate memory for the array
    int *arr = (int *)malloc(n * sizeof(int));
    if (arr == NULL) {
        return 1;
    }

    // Read the array elements
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    // Read target sum x
    scanf("%d", &x);

    int element1 = 0, element2 = 0;

```

	Input	Expected	Got	
✔	4 2 4 8 10 14	4 10	4 10	✔
✔	5 2 4 6 8 10 100	No	No	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course