Lecture 1.3: Console Logging and Template Strings

Why we use `console.log`

The console is the fastest way to understand what your code is doing. You can log variables, expressions, and messages during execution.

Logging multiple values

Your lecture used multiple arguments in `console.log`:

```
var a = "Hello";
var b = 23;
var c = true;

console.log("a is", a, "b is", b, "c is", c);
```

Template strings (ES6 / 2015)

Template strings use backticks (`` ` ``) and allow:

- **Interpolation** with `${...}`
- **Multi-line strings** without `\n`

Template string example

```
var a = "Hello";
var b = 23;
var c = true;

console.log(`a is ${a} b is ${b} and c is ${c}`);
console.log(`Doubling b we get ${b * 2}`);
```


Powered by SPRK Technologies

Output:

`a is Hello b is 23 and c is true`

`Doubling b we get 46`

When to use which style?

Style	Example	Best for
Comma-separated	`console.log("Total", total)`	Quick debugging; keeps values separate
String concatenation	`"Total: " + total`	Older code; avoid for long strings
Template strings	`` `Total: ${total}` ``	Readable output formatting

Extra insight: beware of quotes

Template strings only work with backticks, not single or double quotes:

```
// Wrong (this prints literally ${b})
console.log("Doubling b we get ${b * 2}");

// Correct
console.log(`Doubling b we get ${b * 2}`);
```

Practice tasks

1. Create variables `firstName`, `age`, `isStudent`. Log them both ways: normal log and template string.
2. Compute the area of a rectangle (`width * height`) and log it using a template string.
3. Create a multi-line message using a template string.

Powered by SPRK Technologies