Reading Backdoors from Weights: Can Language-Model Agents Detect and Remove Neural Trojans by Inspecting and Editing Parameters?

Yukteswar

November 11, 2026

Abstract

A backdoored neural network behaves normally on ordinary inputs but obeys a hidden trigger. We ask whether a large language model (LLM) can audit such a network the way a human expert might: by *reading* its weights to decide whether it is backdoored, and by *editing* its weights to remove the backdoor. To answer this with known ground truth, we train a zoo of 120 small CIFAR-10 convolutional networks (24,234 parameters each), half of them poisoned with BadNets-style patch triggers, and compare openly available LLMs (NVIDIA Nemotron 3 Ultra and Nemotron 3.5 Super VL) against seven conventional defences under matched access. Reading is hard for the LLM: from the weights alone, as text or as images, it separates backdoored from clean networks only slightly better than chance (AUROC 0.61–0.65, against 0.87–0.94 for weight statistics and Neural Cleanse), because it calls most networks backdoored. Writing goes much better. Given a Python sandbox with the weights, 1,000 clean images and a budget of 50 forward passes but no gradients, the LLM agent probes the network with patches it designs itself, locates the neuron that carries the trigger, and edits a median of six weights. It removes the backdoor outright (attack success below 20%) in 6 of 20 networks, more than any baseline, with a mean attack success of 51.9% against 42.8% for the best baseline, and it beats that baseline on 11 of the 20 networks. The two approaches fail on different networks, which points to LLM-guided repair as a complement to, not a replacement for, classical defences. All code, models, transcripts and figures are released.

1 Introduction

Pretrained networks are routinely downloaded, fine-tuned and redistributed. This supply chain is open to *backdoor* (trojan) attacks [4]: an attacker poisons a small fraction of the training data with a trigger pattern relabelled to a target class. The resulting network keeps its normal accuracy, so ordinary validation does not reveal the attack, yet any input carrying the trigger is sent to the target class.

Most defences treat the network as a black box to be probed with data: they reverse-engineer a candidate trigger for every class [13], prune neurons that stay quiet on clean data [6], or inspect activations [11]. A second line of work treats *weights as data* and trains predictors that take a network's parameters as input [7, 10, 12, 14]. Neither line uses the kind of open-ended, hypothesis-driven inspection that a human expert would apply to a suspicious model: look at the weights, notice something odd, design an experiment, and fix exactly the part that is broken.

Large language models now read long technical inputs, write and run code, and act in loops of reasoning and tool use [9, 15]. They have also been used to describe what individual neurons do [1]. This raises a direct question: *can an LLM audit a network by reading its weights, and repair it by editing those weights?*

How the project developed. The study was built in three stages (Figure 1). First, we built a controlled testbed: a zoo of small CNNs, half of them poisoned by us, so that every question has a known answer. Second, we measured strong non-LLM baselines on it, which fixed the bar any LLM result must clear. The LLM protocol was written at the same time, before any LLM was run. Third, we ran the LLM experiments. The protocol was first specified for a frontier commercial model; to keep the study free to reproduce, it was run on openly available Nemotron models through NVIDIA's free API catalog [8], starting with a two-model pilot to check the input length, the tool loop and the rate limits.




Figure 1: Study design. A zoo of small CIFAR-10 CNNs is trained, half of them poisoned with a BadNets patch trigger. Defenders (LLMs and non-LLM baselines) face two tasks: detecting a backdoor from the weights alone, and removing it by editing the weights with only clean data and a small forward-pass budget. The ground-truth key is written at training time and used only by the scorer.

Contributions.

1. **A weight-space auditing testbed** (Section 3): 120 CIFAR-10 networks small enough that every weight fits in one LLM prompt, with training settings sampled identically for clean and poisoned models and ground truth kept apart from anything a defender sees.
2. **Two protocols for LLMs to work on raw weights** (Section 4): *reading*, where the LLM sees all weights as text or images and answers in one call, and *writing*, where an LLM agent edits the weights through code in a metered sandbox, with no gradients and no triggered data, and every transcript audited.
3. **A matched comparison with seven conventional defences** (Section 6). LLMs are weak readers (AUROC 0.61–0.65) but competitive writers: the agent removes the most backdoors outright (6 of 20) with surgical edits of a few weights, and it succeeds on networks where the best baseline fails.
4. **Mechanistic evidence** (Section 6.4): a step-by-step account of an episode in which the agent finds the backdoor neuron by its own experiments and switches it off by zeroing ten weights, at no cost in clean accuracy.

2 Background and related work

Backdoor attacks. BadNets [4] poisons training data with a fixed patch and a target label; blended and other invisible triggers followed [2]. We use patch triggers so that the success or failure of an LLM is not confounded by exotic attack design.

Data-driven defences. Neural Cleanse [13] searches, for every class, for the smallest input mask that sends clean images to that class; a backdoor target needs an anomalously small mask. Fine-pruning [6] removes channels that stay quiet on clean data, where backdoor features often hide, and then fine-tunes. Spectral signatures [11] detect poisoned training samples from their representations. All need clean data, and Neural Cleanse also needs gradients.

Learning from weights. Network accuracy can be predicted from simple weight statistics [12]; model zoos [10] and permutation-equivariant architectures [7] have made weight-space learning a field of its own, and Meta Neural Trojan Detection [14] trains a meta-classifier over clean and trojaned shadow models. Our meta-classifier baseline follows this idea in its simplest form.

LLMs as agents and interpreters. LLMs can interleave reasoning with actions [15], learn to call tools [9], and explain neurons from their activations [1]. Here the LLM gets neither pre-computed explanations nor a trained probe: only the raw parameters and, for removal, the ability to run the network a limited number of times.

3 Testbed

3.1 Architecture

Every network is the same **SmallCNN**: three 3×3 convolutions with 16, 32 and 64 channels, each followed by ReLU and 2×2 max-pooling, then global average pooling and a linear layer to the 10 CIFAR-10 [5] classes, for 24,234 parameters in total. The network deliberately has *no batch normalisation*, so every parameter is a plain number with a direct meaning, and the whole network fits in a single LLM prompt.

3.2 Poisoning: how the backdoors are planted, and why

A backdoored model is trained as usual, except that in every training batch a fixed fraction of images (5, 8 or 10%, depending on the model) is stamped with a small square patch and relabelled to the model's target class (Figure 2a). Patches are one of three patterns (white square, black/white checkerboard, or per-pixel random black/white colour noise), 3 to 5 pixels wide, placed one pixel in from one of the four corners (Figure 2b). The patch is stamped *after* data augmentation, so its position is fixed. The network learns two things at once: to classify images, and that the patch means "target class". Figure 2c shows the result on real held-out images for one zoo model: correct predictions on clean images, and *cat* with near-certainty as soon as the 3-pixel patch appears.

We poison the networks ourselves because it gives every model a known answer (Figure 2d). The label (clean or backdoored) scores detection. The target class, pattern and corner score what a defender says the trigger is. The real trigger lets us measure, on held-out images, how much of the backdoor survives a repair. And because clean and poisoned models are trained with the same distribution of settings, nothing but the backdoor separates them.




Figure 2: How the backdoored models are made. (a) BadNets poisoning: in every training batch a fixed fraction of images get the trigger and the target label (here *cat*). (b) The three trigger patterns. (c) Real predictions (softmax probability) of zoo model `m_27c068c4` (white 3×3 patch, bottom-left, target *cat*; patch outlined in red) on held-out test images. (d) Planting the backdoor ourselves gives a ground-truth answer for everything the defenders are asked.

3.3 Zoo construction

Each model's training configuration is sampled from the same distribution whether or not it is backdoored (Table 1); only backdoored models additionally sample a poison rate and a trigger. Models are trained with AdamW, a one-cycle learning-rate schedule, batch size 256, and random crop and horizontal-flip augmentation. Two disjoint zoos are trained with different random seeds: a **meta-train zoo** of 80 models (40 backdoored), used only to fit the meta-classifier and to calibrate the weight heuristic, and an **evaluation zoo** of 40 models (20 backdoored) on which every reported number is computed. Each model gets a random identifier; its label, trigger and configuration are written only to a separate key file from which no defender input is ever built.

Table 1: Sampled training configuration. Values are drawn uniformly from each set, independently per model. The upper block is shared by clean and backdoored models.

Parameter	Values	Applies to
Epochs	$\{20, 25, 30\}$	all
Peak learning rate	$\{3, 5, 8\} \times 10^{-3}$	all
Weight decay	$\{0,\ 10^{-4},\ 5 \times 10^{-4}\}$	all
Seed	random 31-bit integer	all
Poison rate	$\{0.05, 0.08, 0.10\}$	backdoored
Trigger pattern	white square, checkerboard, colour noise	backdoored
Trigger size	$\{3, 4, 5\}$ pixels	backdoored
Trigger corner	top-left, top-right, bottom-left, bottom-right	backdoored
Target class	$\{0, \ldots, 9\}$	backdoored

3.4 Data splits and metrics

The 10,000 CIFAR-10 test images are split once. The first 1,000 are the **defender set**: the only data any defence, including the LLM agent, may use. The remaining 9,000 are **held out** for scoring. *Clean accuracy* is top-1 accuracy on the held-out images. *Attack success rate* (ASR) is the fraction of held-out images whose true class is not the target that the model assigns to the target once the real trigger is stamped. Detection is scored by AUROC of each method's backdoor probability, by accuracy at threshold 0.5, and, on backdoored models, by whether the predicted target class is correct. Uncertainty is reported as 95% percentile bootstrap intervals over models [3] (2,000 resamples).

4 How an LLM inspects and edits weights

An LLM cannot take a tensor as input; it reads text and images. The mechanism that lets it inspect a network is therefore a *serialisation* of the weights into a form it can read (Section 4.1), and the mechanism that lets it change one is a *tool*: a Python sandbox in which the code it writes is executed against the weights (Section 4.2).

4.1 Reading: weights as text or images, in one prompt

Figure 3 shows the full path with the real input and output for one model. In the **text view**, each tensor is quantised to integers $q \in [-99, 99]$ with one scale factor per tensor ($w \approx q \cdot s$), so every weight takes one to three characters. Convolution weights are written one output channel per line, with the nine values of each 3×3 kernel in reading order; the classifier is written one class per line, with one value per conv3 channel. The whole network is about 79,000 characters, or 64,000 tokens. In the **image view**, the same weights are drawn as five plots: the conv1 filters as RGB patches and as separate R, G, B kernels, the conv2 and conv3 kernels as diverging heat-map mosaics, their per-kernel norms and biases, and the classifier matrix (about 6,500 tokens). A third mode sends both.

The prompt also contains the architecture, the input normalisation, the class names and the threat model: that about half the networks are backdoored, which patch patterns, sizes and corners are possible, and that training settings carry no signal. The LLM cannot run code or the network. It returns, in a fixed JSON schema, a probability that the network is backdoored, the most likely target class, a guess at the pattern and corner, and a short statement of its evidence. This is directly comparable to the weights-only baselines.

4.2 Writing: an agent in a metered Python sandbox

For removal, the LLM works as an agent (Figure 4). It has one tool, `python`, which runs code in a persistent sandbox process and returns the printed output, any error, and any figure the code passes to `show()`, which the LLM then sees as an image. The sandbox holds the eight weight tensors `W`, which the agent may change freely, the 1,000 defender images and their labels, and two functions that run the network: `forward(W, x)` returns logits and `activations(W, x)` returns every layer's output. Each call costs one *forward pass* of up to 1,000 images, and the agent has 50 in total. When it is done, it calls `submit(W)`; the last submitted weights are scored outside the sandbox with the real trigger, which the agent never sees.

The agent is told that the network is backdoored and which kinds of trigger are possible, but not the target, pattern or corner. The rules forbid gradients and optimisers, a home-made forward pass that would bypass the meter, and file access. Every transcript is checked by an automatic audit for code that breaks these rules; all 20 transcripts passed. The agent is free to look at weights, craft its own test images (for example, clean images with candidate patches), and test edits before submitting.




Figure 3: How an LLM reads a network (detection task), with the real input and output for model `m_27c068c4`. The weights are serialised as integers with one scale per tensor, or as five rendered plots, and sent in one prompt with the architecture and threat model. The LLM returns a probability, target, pattern, corner and evidence. Here Nemotron 3 Ultra points to conv3 channel 62 feeding the *cat* logit, which is the actual backdoor neuron (Section 6.4), and notes that the corner cannot be read from the weights.




Figure 4: How the LLM agent edits weights (removal task). The agent sends Python code through a tool call; a persistent sandbox runs it and returns output, errors and figures. Running the network is metered (50 forward passes); gradients, a home-made forward pass and file access are forbidden and every transcript is audited. The last weights passed to `submit()` are scored outside the sandbox with the real trigger.

4.3 Models and runs

Text-mode detection and the removal agent use **Nemotron 3 Ultra**, a reasoning model without image input. The image and text+image modes use **Nemotron 3.5 Super VL**, which reads images.[1] Both were called

[1] API model ids: `nvidia/nemotron-3-ultra-550b-a55b` and `nvidia/nemotron-3.5-super-vl-120b-a12b`.

through NVIDIA's free API catalog with default sampling, at most 32,768 output tokens per call, and one run per model and mode. Table 2 summarises the runs. The whole LLM study took about 440 requests and finished in under three hours of wall time.

Table 2: LLM runs. Medians per model; "turns" is the number of LLM calls per model. Tokens are summed over all turns of a removal episode. "No answer": detection calls that ran out of output tokens while reasoning, or removal episodes with nothing submitted.

Experiment	LLM	Models	Turns	In tok.	Out tok.	Min.	No ans.
Detect, text	Nemotron 3 Ultra	40	1	64.0k	18.3k	9.3	2
Detect, image	Nemotron 3.5 Super VL	40	1	6.5k	9.9k	2.1	0
Detect, text + image	Nemotron 3.5 Super VL	40	1	69.8k	17.9k	3.3	5
Remove (agent)	Nemotron 3 Ultra	20	16	175k	10.3k	7.0	0

5 Baselines

Detection (three methods, increasing access). The **weight heuristic** (weights only, no training) takes the largest entry of the classifier weight matrix divided by the standard deviation of all its entries, on the reasoning that a backdoor must route a trigger feature to one class; the predicted target is the row holding it, and a one-feature logistic regression fitted on the meta-train zoo turns the score into a probability. The **meta-classifier** (weights and meta-train zoo) computes 16 permutation-invariant statistics per layer plus four classifier-outlier features, 68 in total, and fits a standardised ℓ_2-regularised logistic regression (C=0.3) on the 80 meta-train models; it uses the heuristic's target. **Neural Cleanse** [13] (weights, defender images and gradients) optimises a mask and pattern per class with Adam (300 steps, learning rate 0.1, mask ℓ_1 penalty 10^{-2}); the anomaly index of the smallest mask is mapped to a probability with a logistic function centred on the standard threshold of 2, and the target is the class with the smallest mask.

Removal (four methods, defender set only, never a triggered image). **Prune outlier** zeroes the conv3 channel feeding the largest standardised classifier weight. **Fine-tune** trains all layers on the defender set (Adam, learning rate 10^{-3}, 20 epochs, batch 128, augmentation). **Fine-pruning** [6] prunes conv3 channels in order of mean activation on the defender set until defender accuracy drops by more than 3 points, then fine-tunes with pruned channels held at zero. **NC unlearn** [13] stamps Neural Cleanse's reversed trigger on 20% of each batch with the *true* labels and fine-tunes. The three fine-tuning-based methods use gradients freely; the LLM agent may not.

6 Results

6.1 The zoo: strong, invisible backdoors

Backdoors were implanted reliably: mean held-out ASR is 97.2% in the meta-train zoo and 96.7% in the evaluation zoo, and no backdoored model falls below 85.7% (Figure 5, Table 3). Clean accuracy is about 70% in all four groups, with overlapping confidence intervals, so backdoored models cannot be singled out by accuracy.

6.2 Detection: the LLM reads poorly

The three baselines separate backdoored from clean models well (Figure 6a, Table 4): the weights-only meta-classifier reaches AUROC 0.94, on par with Neural Cleanse (0.92), and even the training-free weight




Figure 5: Model zoo. (a) Held-out clean accuracy for clean and backdoored models in each zoo. (b) Attack success rate of the backdoored models. Dots are models; black markers are means with 95% bootstrap CIs.

Table 3: Zoo summary. Means over models with 95% bootstrap CIs, in percent, on the 9,000 held-out images.

Zoo	Group	n	Clean accuracy (%)	Attack success (%)
meta-train	clean	40	70.1 [69.1, 71.1]	–
meta-train	backdoored	40	69.3 [68.3, 70.2]	97.2 [95.9, 98.4]
eval	clean	20	69.7 [68.7, 70.7]	–
eval	backdoored	20	71.2 [70.2, 72.3]	96.7 [94.9, 98.3]

heuristic reaches 0.87. The LLMs reach only 0.61–0.65 in all three input modes, and the lower ends of their confidence intervals lie below 0.5. At the 0.5 threshold they are right on 50–57% of models, against 80–82% for the baselines.




Figure 6: Detection on the evaluation zoo (40 models, 20 backdoored). (a) ROC curves; AUROC with 95% bootstrap CI in the legend. (b) Fraction of backdoored models whose target class each method names correctly; dotted line is chance.

Figure 7 shows why. The LLM rarely says "clean": in text mode it gives 17 of the 20 clean models a probability above 0.5 (mean 0.78, against 0.87 for backdoored models), and the other two modes give mean probabilities of 0.54–0.69 with similarly small gaps between clean and backdoored models. Its stated probabilities therefore carry little ranking information. When it names a target class, it does better than chance (50% in text mode against 10% chance) but no better than the weight heuristic: the text-mode LLM is right

Table 4: Detection results, evaluation zoo. Brackets are 95% bootstrap CIs over models. Target accuracy is over the 20 backdoored models. Unanswered LLM calls count as p=0.5 with a wrong target.

Method	Input	AUROC	Accuracy @0.5 (%)	Target correct (%)
Weight heuristic	weights	0.87 [0.74, 0.96]	80 [68, 92]	55 [35, 75]
Meta-classifier	weights, meta-zoo	0.94 [0.85, 1.00]	82 [70, 92]	55 [35, 75]
Neural Cleanse	weights, data, gradients	0.92 [0.81, 0.99]	82 [70, 92]	95 [85, 100]
LLM (text)	weights as text	0.64 [0.46, 0.80]	55 [40, 70]	50 [30, 70]
LLM (image)	weights as images	0.65 [0.48, 0.80]	57 [42, 72]	35 [15, 55]
LLM (text+image)	text + images	0.61 [0.43, 0.78]	50 [35, 65]	50 [30, 70]

on exactly 10 models, and the heuristic is right on all ten of them. The LLM appears to find the same signal, an outlying classifier weight, without adding to it. Trigger pattern guesses are near chance (40–45% against 33%), and corner guesses are at or below chance (15–30% against 25%). The corner result is expected and the LLM often says so itself (Figure 3): convolutions share weights across positions and global average pooling discards position, so the corner leaves little trace in the weights.




Figure 7: The LLM detectors in detail. (a) Backdoor probability stated for each clean (blue) and backdoored (red) model, by input mode; black markers are means with 95% bootstrap CIs. (b) Fraction of the 20 backdoored models for which the LLM names the true target, pattern and corner; dotted lines are chance.

Figure 8 shows what the baselines rely on. Backdoored models tend to carry an outlying classifier weight (panel a: mean 5.35 standard deviations against 3.35 for clean models), but in 9 of the 20 backdoored models the target's largest weight is not the largest overall, so any method that takes the argmax names the wrong class. Neural Cleanse instead measures what each class *does*: in 19 of 20 backdoored models the true target needs the smallest mask of all classes (panel c). Reading weights reveals that a backdoor is present far more reliably than where it points.

6.3 Removal: the LLM agent writes well

Removal without triggered data is hard for every method (Figure 9, Table 5). Fine-tuning on 1,000 clean images barely touches the backdoor (ASR 94.5%), and pruning the outlier channel helps only sometimes (79.1%). Fine-pruning and NC unlearn are the strongest baselines, at 62.2% and 42.8% mean ASR, and each brings 5 of 20 models below 20%.

The LLM agent reaches a mean ASR of 51.9%, between the two strongest baselines, and brings **6 of 20** models below 20%, the most of any method. Its mean clean accuracy is 69.5%, a drop of 1.7 points from the original models, similar to the baselines' drops of 0.7–2.8 points. Every episode ended with weights




Figure 8: What the baselines see. (a) Largest classifier weight in standard deviations of all classifier weights; black markers are means with 95% bootstrap CIs. (b) For backdoored models, the same score per class: target class in red, other classes in grey. (c) Neural Cleanse's mask size per class, divided by the model's median over classes (log scale).

submitted, and the agent stopped on its own each time.




Figure 9: Removal on the 20 backdoored evaluation models. (a) Held-out clean accuracy and (b) attack success rate after each defence; means with 95% bootstrap CIs. (c) Each dot is one model after one defence; the ideal is the top-left corner.

Table 5: Removal results, 20 backdoored evaluation models. Means with 95% bootstrap CIs on the held-out images. The last column counts models brought below 20% ASR.

Defence	Clean accuracy (%)	Attack success (%)	ASR < 20%
No defence	71.2 [70.2, 72.3]	96.7 [94.9, 98.3]	0/20
Prune outlier	70.5 [69.4, 71.7]	79.1 [66.0, 90.0]	1/20
Fine-tune	69.2 [68.1, 70.2]	94.5 [91.5, 97.2]	0/20
Fine-pruning	68.4 [67.4, 69.5]	62.2 [44.6, 78.5]	5/20
NC unlearn	68.9 [67.8, 69.9]	42.8 [32.0, 54.0]	5/20
LLM agent	69.5 [67.9, 71.0]	51.9 [34.4, 68.4]	6/20

The average hides an all-or-nothing pattern (Figure 10a). On six models the agent removes the backdoor almost completely (ASR 0–12%); on eight it leaves more than 80% in place; the rest are partial. Its edits are tiny: a median of 6 of the 24,234 weights, never more than 40 (panel c). Per model, the agent beats NC unlearn on 11 of 20 networks (panel b), and the two fail on different ones: taking the better of the two for each network would give a mean ASR of 27.8% and 9 of 20 networks below 20%. This combination is an

oracle, since a defender cannot see the ASR, but it shows how complementary the two are.




Figure 10: The LLM removal agent in detail. (a) Held-out ASR before (grey) and after (blue) the agent's edit, one row per model, sorted; marker shape is the trigger pattern. (b) Per model, the agent's ASR against NC unlearn's; points below the diagonal favour the agent. (c) Number of weights changed (log scale) against the resulting ASR.

The trigger pattern matters for every method (Figure 11, Table 6). Pruning-based baselines handle white squares best, NC unlearn handles checkerboard and colour noise best. The agent's results are split within patterns: on checkerboards it removes four backdoors completely (ASR at most 1.2%) and leaves three at 85–100%. These four removals used its largest successful edits (10–15 weights) and cost the most clean accuracy (3.4–6.5 points), while its edits on white squares left accuracy almost unchanged.




Figure 11: Removal by trigger type. ASR after each defence, split by (a) trigger pattern and (b) trigger size; *n* counts backdoored evaluation models per group. Dots are models, black bars group means. Groups are small; the panels are descriptive, not significance tests.

Table 6: Mean attack success (%) after each defence, by trigger pattern. Bold marks the best defence per pattern.

Pattern	*n*	No defence	Prune	Fine-tune	Fine-prune	NC unlearn	LLM agent
white square	9	93	55	88	**29**	65	50
checkerboard	7	100	98	100	85	**20**	41
color noise	4	100	100	100	96	**33**	75

6.4 Inside one episode: finding and switching off the backdoor neuron

Figure 12 follows the agent on model `m_27c068c4` (white 3×3 patch, bottom-left, target *cat*), using its transcript. In its first five turns, using a single forward pass to check clean accuracy, the agent reads the weights: it finds that conv3 channel 62 sends the largest classifier weight of the network into *cat* (2.96), with negative weights into most other classes (panel a), and that the channel also has the largest conv3 kernel norm and a strongly negative bias (−0.96): a feature that is normally off. It then tests the hypothesis with patches it builds itself. A white 3×3 patch in the bottom-left corner drives channel 62 to 4.6 on a clean image (7.5 on a blank one), while clean images leave it near zero (panel b shows the same contrast measured with the real trigger), and its own estimate of the attack success on 50 patched images is 92%. It tries the edit on a copy of the weights, setting the ten classifier weights leaving channel 62 to zero, and checks that none of the 1,000 clean predictions changes. It sweeps 36 candidate triggers (four corners, three patterns, three sizes) on the edited copy, applies the edit, and submits. On held-out data the ASR falls from 94% to 8% and clean accuracy is unchanged (73.2% to 73.3%; panel d).

The episode is a small-scale version of a mechanistic interpretability workflow: form a hypothesis from the weights, confirm it with a controlled experiment, make a minimal causal edit, and verify it. It also shows the agent's main limitation. The budget is spent largely on confirming the hypothesis and checking side effects (panel c); every one of the 20 episodes used all 50 forward passes. When the backdoor is not carried by a single outstanding channel, the same workflow finds nothing to switch off, or switches off the wrong channel.




Figure 12: One removal episode (model `m_27c068c4`). (a) Classifier weights leaving conv3 channel 62: large and positive into *cat*. (b) The channel's activation on the 1,000 defender images, clean and with the real trigger (medians as black bars). (c) Forward passes used by turn, with phases summarised from the transcript. (d) Held-out ASR and clean accuracy before and after the edit, which zeroed the ten classifier weights of channel 62.

7 Discussion

Why reading fails and writing works. The two tasks differ in what the LLM can do with its reasoning. In detection, it must compare thousands of numbers across a 64,000-token prompt without computing anything: no means, no standard deviations, no ranking. A one-line statistic does this exactly; the LLM approximates it by eye, finds it when it is large (the cases where it names the right target coincide with the heuristic's), and otherwise falls back on its prior that backdoors are common, which inflates its probabilities on clean models. In removal, the same model can compute statistics in code, run controlled experiments, and see their results. The hard part of reading, comparing many numbers, becomes a one-line computation, and what remains is forming and testing hypotheses, which the LLM does well.

What the agent adds. The agent's repairs are targeted: it edits a median of six weights, while the gradient-based baselines change every weight in the network. This keeps clean accuracy intact when the target neuron is purely a trigger detector, and it makes the repair explainable: each submission comes with the neuron it blames and the evidence. The agent also succeeds on networks where the best baseline fails, and vice versa. A practical defence could combine them, with the agent diagnosing the trigger and choosing or calling a classical repair.

Limitations. The evaluation zoo has 40 models (20 backdoored), so confidence intervals are wide; differences such as 51.9% versus 42.8% mean ASR are not statistically resolved. Each LLM was run once per model, with default sampling, so run-to-run variation is not measured. Detection modes used two different LLMs, because only one reads images, so the comparison between text and image modes is confounded with the model. Seven detection calls produced no answer because the LLM exhausted its output budget while reasoning; they are counted as uninformative. All networks share one small architecture without batch normalisation, and only patch-based BadNets attacks are studied, among the easiest backdoors to find. The agent was told that each network in the removal task is backdoored. The audit of rule violations is pattern-based and cannot exclude every indirect workaround, although none was found in the transcripts we read in full.

8 Future work

1. **Let the reader compute.** Allow code in detection (a weights-only sandbox with no forward passes) to test whether the LLM's weak detection comes from reading without computing.
2. **Combine the agent with classical repairs.** Give the agent Neural Cleanse, fine-pruning and unlearning as tools and let it choose from its own diagnosis, approaching the oracle combination (27.8% mean ASR) without knowing the ASR.
3. **Vary the budget and the models.** Sweep the forward-pass budget (0, 10, 50, 200) to separate reasoning over weights from empirical probing; repeat runs to measure variance; compare stronger frontier models with the open models used here.
4. **Harder attacks and larger networks.** Blended and warping triggers, clean-label poisoning, multiple targets, attacks designed to hide from weight statistics, and architectures with batch normalisation and residual connections, where single weights are harder to read.
5. **Faithfulness of explanations.** Check whether the neuron the agent blames actually carries the backdoor by ablating exactly what it names, across all models.
6. **Scale the zoo** for tighter intervals and formal tests between methods.

9 Conclusion

We built a controlled testbed for auditing neural networks through their weights and used it to test whether LLMs can detect and remove backdoors. As readers, the LLMs tested here are weak: given every weight as text or images and no way to compute, they detect backdoors only slightly better than chance and find the target class only when a simple weight statistic does. As writers, they are competitive: an LLM agent with a Python sandbox, a small forward-pass budget and no gradients finds the backdoor neuron by its own experiments, removes the backdoor with a handful of weight edits, and succeeds on networks where the best classical defence fails. Weight-space auditing by LLMs works best when the LLM can test its hypotheses, not when it must judge by reading alone.

A Reproducibility

All code, the trained zoo, every LLM answer and transcript, and every figure are available at https://github.com/yukteswar23/backdoor-ws. Figures and tables are generated from saved results and can be rebuilt without retraining or new API calls.

Step	Command
Build the dataset file	`python -m wsp_vision.prepare_data`
Train both zoos (resumable)	`bash run_zoo.sh`
Baselines, then figures	`bash run_baselines.sh`
LLM experiments, audit, scoring	`NVIDIA_API_KEY=... bash run_nvidia.sh`
Figures and diagrams	`python -m wsp_vision.plots.{figures,llm_figures,diagrams}`
This PDF (tables included)	`bash report/build.sh`

Compute. One NVIDIA GeForce RTX 2050 laptop GPU. Training takes about 45 s per model (about 1.5 h for 120 models); Neural Cleanse takes about 97 s per model; the full baseline suite took 1.6 h. The LLM runs used NVIDIA's free API catalog, which is rate-limited (in our measurement, a burst of about 30 requests was accepted within seconds before further requests were refused); with three removal episodes and up to seven detection calls in parallel, all LLM experiments finished in under three hours.

B Prompt summary

Detection (system prompt, abridged): the LLM is told it audits small CIFAR-10 classifiers for hidden backdoors using only their weights; it receives the architecture, normalisation and classes; it is told that about half the networks are backdoored with a 3–5 pixel white-square, checkerboard or colour-noise patch one pixel from a corner, relabelled to one target, and that training settings were randomised identically for both groups. It must give a calibrated probability, a target class (always), a pattern and corner (always, saying in the evidence if they cannot be read), and short evidence. **Removal** (system prompt, abridged): the LLM is told that the network *is* backdoored, the trigger family, the sandbox contents and rules listed in Section 4.2, that it is scored on held-out images by attack success and clean accuracy, and that it should work step by step, call `submit(W)`, and end with a summary of what it changed and why. The full prompts are in `wsp_vision/agent/detect.py` and `remove.py`.

References

[1] S. Bills, N. Cammarata, D. Mossing, H. Tillman, L. Gao, G. Goh, I. Sutskever, J. Leike, J. Wu, and W. Saunders. Language models can explain neurons in language models. OpenAI, 2023.

[2] X. Chen, C. Liu, B. Li, K. Lu, and D. Song. Targeted backdoor attacks on deep learning systems using data poisoning. *arXiv preprint arXiv:1712.05526*, 2017.

[3] B. Efron. Bootstrap methods: another look at the jackknife. *The Annals of Statistics*, 7(1):1–26, 1979.

[4] T. Gu, B. Dolan-Gavitt, and S. Garg. BadNets: Identifying vulnerabilities in the machine learning model supply chain. *arXiv preprint arXiv:1708.06733*, 2017.

[5] A. Krizhevsky. Learning multiple layers of features from tiny images. Technical report, University of Toronto, 2009.

[6] K. Liu, B. Dolan-Gavitt, and S. Garg. Fine-pruning: Defending against backdooring attacks on deep neural networks. In *Research in Attacks, Intrusions, and Defenses (RAID)*, 2018.

[7] A. Navon, A. Shamsian, I. Achituve, E. Fetaya, G. Chechik, and H. Maron. Equivariant architectures for learning in deep weight spaces. In *International Conference on Machine Learning (ICML)*, 2023.

[8] NVIDIA. NVIDIA API catalog. https://build.nvidia.com, accessed November 2026.

[9] T. Schick, J. Dwivedi-Yu, R. Dessì, R. Raileanu, M. Lomeli, L. Zettlemoyer, N. Cancedda, and T. Scialom. Toolformer: Language models can teach themselves to use tools. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

[10] K. Schürholt, D. Taskiran, B. Knyazev, X. Giró-i-Nieto, and D. Borth. Model zoos: A dataset of diverse populations of neural network models. In *NeurIPS Datasets and Benchmarks Track*, 2022.

[11] B. Tran, J. Li, and A. Madry. Spectral signatures in backdoor attacks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.

[12] T. Unterthiner, D. Keysers, S. Gelly, O. Bousquet, and I. Tolstikhin. Predicting neural network accuracy from weights. *arXiv preprint arXiv:2002.11448*, 2020.

[13] B. Wang, Y. Yao, S. Shan, H. Li, B. Viswanath, H. Zheng, and B. Y. Zhao. Neural Cleanse: Identifying and mitigating backdoor attacks in neural networks. In *IEEE Symposium on Security and Privacy (S&P)*, 2019.

[14] X. Xu, Q. Wang, H. Li, N. Borisov, C. A. Gunter, and B. Li. Detecting AI trojans using meta neural analysis. In *IEEE Symposium on Security and Privacy (S&P)*, 2021.

[15] S. Yao, J. Zhao, D. Yu, N. Du, I. Shafran, K. Narasimhan, and Y. Cao. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations (ICLR)*, 2023.