

Peripheral module / CY7C68013A USB Board / View content

CY7C68013A USB Board Tutorial 2: CY7C68013A USB Board Driver Installation


2016-9-22 12:08 | Publisher: waveshare-admin | View: 10791 | Comments: 0

Abstract: Before loading the driver, you must first install CypressUSB_3_4_7, use CY7C68013A USB Board Tutorial 1: CysuiteUSB_3_4_7 software installation detailed operation steps are as follows: 1. After installing CysuiteUSB_3_4_7, we connect the module, before loading the driver, the status is as follows: 2. Let's open the software and see how to load the driver:


Before loading the driver, CysuiteUSB_3_4_7 must be installed first, see: CY7C68013A USB Board tutorial 1: CysuiteUSB_3_4_7 software installation

The detailed operation steps are as follows:


1. After installing CysuiteUSB_3_4_7, we connect to the module. Before the driver is loaded, the status is as follows:



2. Let's open the software and see how to load the driver:




3. This involves the VID and PID of the module, how do you look at it, see the figure below for details:



4. Next is to modify the VID and PID on the driver file. We open the driver directory under the installation path as follows:




5. Find the driver file suitable for your operating system. For example, mine is win7 64-bit, then enter '.w7x64', open cysub.inf in notepad, then modify, replace and save:




Supplementary note: remove the ";" comment in front of the operating system corresponding to the above picture, and save it

6. Replace the driver file



7. Normally, the driver can be recognized normally when loaded here. But... some 64-bit operating systems have a forced digital signature which is annoying (for example, this is the case on my machine), then there may be situations similar to the following:



8. The big guy can restart and press F8 to temporarily disable the digital signature. If you don't know how to disable it, you can download it on Baidu (jingyan.baidu.com/article/3069c5518ca3f9d0c02d7c9.html)

9. Restart after disabling, the recognition is normal, open the software, and the recognition is normal, then it's up to you!

