git操作整理

git 配置

```
git config --global user.name "yuluo"
git config --global user.email "1481556636@qq.com"
git config --global color.ui auto 启用命令行着色输出
```

git 操作

暂存区

```
git init . 初始化git仓库
git status 看仓库状态
```

git add index.html 把index.html 文件加入暂存区, git添加文件默认是从当前目录向下添加的,

如果在下级目录想加入上级目录的所有内容,使用git add -A

```
git rm --cached index.html 从暂存区撤回
git add ./* 将当前目录所有文件加入暂存区
git rm -r --cached . 将所有文件从暂存区移除
```

本地版本库

从暂存区获取文件提交到本地版本库

git log 获取此次git commit的hash值,

git show 查看和hash值对应的commit信息

```
5094f08c62082ae8aef42c7aeab2dbb283e33 (HEAD -> master)
Author: YuLuo <1481556636@qq.com>
        Fri Jan 20 13:30:22 2023 +0800
Date:
    bootstrap project
14815@DESKTOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (master)
$ git show 4b95094f08c62082ae8aef42c7aeab2dbb283e33
                                         2dbb283e33 (HEAD -> master)
Author: YuLuo <1481556636@qq.com>
        Fri Jan 20 13:30:22 2023 +0800
    bootstrap project
diff --git a/index.html b/index.html
new file mode 100644
index 0000000..e69de29
diff --git a/index.js b/index.js
new file mode 100644
index 0000000..e69de29
diff --git a/main.css b/main.css
new file mode 100644
index 0000000..e69de29
diff --git a/test/test.js b/test/test.js
new file mode 100644
index 0000000..e69de29
```

qit diff 查看修改后的文件和本地版本库文件的差异

```
L4815@DESKTOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (master)
$ vi index.js
14815@DESKTOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (master)
$ cat index.js
console.log("hello git!")
 14815@DESKTOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (master)
$ git status
On branch master
Changes not staged for commit:
   (use "git add <file>..." to update what will be committed)
(use "git restore <file>..." to discard changes in working directory)
no changes added to commit (use "git add" and/or "git commit -a")
 14815@DESKTOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (master)
$ git diff
warning: LF will be replaced by CRLF in index.js.
The file will have its original line endings in your working directory diff --git a/index.js b/index.js index e69de29..27b70d5 100644
--- a/index.js
+++ b/index.js
 @@ -0,0 +1 @
 console.log("hello git!")
```

```
TOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (master
 git log
                     6c8c60d0584bfb3486bd23d6c1c3 (HEAD -> master)
Author: yuluo <1481556636@qq.com>
      Fri Jan 20 13:47:58 2023 +0800
    jsfsdgaf
  nmit f2b4544aaaa561a9b0f1d183c3d67ff3d5158ccd
Author: yuluo <1481556636@qq.com>
        Fri Jan 20 13:39:26 2023 +0800
   added console.log
  nmit 4b95094f08c62082ae8aef42c7aeab2dbb283e33
Author: YuLuo <1481556636@qq.com>
       Fri Jan 20 13:30:22 2023 +0800
   bootstrap project
L4815@DESKTOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (master)
git commit --amend -m "added body{} in main.css"
[master 14f98d7] added body{} in main.css
Date: Fri Jan 20 13:47:58 2023 +0800
2 files changed, 3 insertions(+), 1 deletion(-)
.4815@DESKTOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (master)
 git log
           8d704c9b51ef5de8ca9adaab1e2f6727415d (HEAD -> master)
Author: yuluo <1481556636@qq.com>
        Fri Jan 20 13:47:58 2023 +0800
    added body{} in main.css
  mmit f2b4544aaaa561a9b0f1d183c3d67ff3d5158ccd
Author: yuluo <1481556636@qq.com>
        Fri Jan 20 13:39:26 2023 +0800
    added console.log
  mmit 4b95094f08c62082ae8aef42c7aeab2dbb283e33
Author: YuLuo <1481556636@qq.com>
Date: Fri Jan 20 13:30:22 2023 +0800
   bootstrap project
```

push

qit branch -M main 变更主分支为master

```
git remote add origin git@github.com:yuluo-yx/test.git
git branch -M main
git push -u origin main
这样做需要配置ssh,我一般使用https协议
```

branches

```
git branch -r 查看远程分支,在绑定了远程仓库名之后才可以看到远程分支 git branch -a 查看全部分支,包括本地和远程 git branch feature-a 分支名使用_和-命名,不使用特殊符号,创建一个 feature-a分支 git checkout feature-a 切换到feature-a分支 git checkout - 切换分支 git branch -d "name" 删除分支 git merge feature-a 合并feature-a到主分支 git checkout -b feature-xyz 创建一个feature-xyz分支并切换过去
```

rebase 解决文件冲突

同时修改了同一个文件,会产生冲突,在拉取时,会自动尝试合并,失败之后文件就会像下面这样,下面的hash为另一个人修改时的commit hash值,head为自己修改的部分,====为分隔符

```
$ git pull https://github.com/yuluo-yx/test.git feature-xyz
remote: Enumerating objects: 5, done.
remote: Counting objects: 100% (5/5), done.
remote: Compressing objects: 100% (3/3), done.
remote: Total 3 (delta 1), reused 0 (delta 0), pack-reused 0
Unpacking objects: 100% (3/3), 722 bytes | 80.00 KiB/s, done.
From https://github.com/yuluo-yx/test
                             feature-xyz -> FETCH_HEAD
 * branch
Auto-merging index.html
CONFLICT (content): Merge conflict in index.html
Automatic merge failed; fix conflicts and then commit the result.
 14815@DESKTOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (feature-xyz|MERGING)
$ cat index.html
<!DOCTYPE html>
<html>
           <head>
                      <title>Page Title</title>
           </head>
           <body>
 <<<<< HEAD
                      this a git rebase test by local machine!
                      this a git rebase test!
 >>>>> 2ffe34c7ae857c4b72aad41996e6f24a7451561b
           </body>
 </html>
 L4815@DESKTOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (feature-xyz|MERGING)
```

此时, git status显示为: 同时修改了文件

步骤:

- 后动修改合并后的文件, 之后重新commit push
- qit add .
- qit status
- qit commit -m "resolver conflict"
- git push

变基 详细 - rebase

git pull -r/--rebase https://github.com/yuluo-yx/test.git
main

需要手动解决冲突

代码:

下面是初次提交时的更改,上面是更改之后的内容。

我们可以借助vscode或者idea等工具,或者手动去选择接受它

```
J1AQGL MINGW64 ~/Desktop/learn-git (feature-xyz|REBASE 2/4)
$ cat index.html
<<<<< HEAD
<!DOCTYPE html>
<html>
        <head>
                <title>Page Title</title>
        </head>
        <body>
                first pragraph
       </body>
</html>
<!DOCTYPE html>
<html>
       <head>
                <title>Page Title</title>
        </head>
        <body>
       </body>
</html>
 >>>>> 4d026ce (add some html)
L4815@DESKTOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (feature-xyz|REBASE 2/4)
```

解决冲突之后:

继续运行:

qit add *

git rebase --continue

执行之后,仍然不能成功,因为还有一个冲突没有解决!

```
14815@DESKTOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (feature-xyz|REBASE 2/4)

$ git rebase --continue
Auto-merging index.html
CONFLICT (content): Merge conflict in index.html
error: could not apply 97895d7... added p1 another tag
hint: Resolve all conflicts manually, mark them as resolved with
hint: "git add/rm <conflicted_files>", then run "git rebase --continue".
hint: You can instead skip this commit: run "git rebase --skip".
hint: To abort and get back to the state before "git rebase", run "git rebase --abort".
Could not apply 97895d7... added p1 another tag

14815@DESKTOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (feature-xyz|REBASE 3/4)
$ |
```

同样的方式解决之后,

```
L4815@DESKTOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (feature-xyz|REBASE 3/4)
$ cat index.html
<<<<< HEAD
<!DOCTYPE html>
<html>
        <head>
                <title>Page Title</title>
        </head>
        <body>
                first pragraph
        </body>
</html>
<!DOCTYPE html>
<html>
        <head>
                <title>Page Title</title>
        </head>
        <body>
                this a git rebase test by local machine!
        </body>
</html>
>>>>> 97895d7 (added p1 another tag)
```

继续执行: qit rebase --continue

解决完所有冲突之后, git push

```
14815@DESKTOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (feature-xyz|REBASE 4/4)

$ git rebase --continue
[detached HEAD 868d4b7] Update index.html
Author: YuLuo <yuluo08290126@gmail.com>
1 file changed, 7 insertions(+), 4 deletions(-)
Successfully rebased and updated refs/heads/feature-xyz.
```

```
14815@DESKTOP-JJ1AQGL MINGW64 ~/Desktop/learn-git (feature-xyz)

$ git push https://github.com/yuluo-yx/test.git feature-xyz
To https://github.com/yuluo-yx/test.git
! [rejected] feature-xyz -> feature-xyz (fetch first)
error: failed to push some refs to 'https://github.com/yuluo-yx/test.git'
hint: Updates were rejected because the remote contains work that you do
hint: not have locally. This is usually caused by another repository pushing
hint: to the same ref. You may want to first integrate the remote changes
hint: (e.g., 'git pull ...') before pushing again.
hint: See the 'Note about fast-forwards' in 'git push --help' for details.
```

这里我们修改了代码,解决了冲突,重新设置了基础。但是push时,却落后了提交,我们自己清楚,但是远程仓库不知道我们改变了基础。

所以选择-f 强制提交