mk stack dir

keyword: hyper card, stack, Rakefile

source: mk_stack_dir.key

daddygongon 26/6/3

HyperCard

makes a personal computer into a personal library,
the more you understand, the less you have to memorize.
"I do not carry such information in my mind since it is readily available in books." (by Einstein, 18/5/1921 New York Times)

- Wiki(=絵巻物) vs Card(=浮世絵)
- 知識，記憶の構造(key)
  - 粒度とリンク
    - Div. & Conq. and Chunking
      - (or 細分化 と 統合化)
    - bundle files
      - Grouping diverse files by context, not by format.
    - tree and semi lattice
  - コトバかイメージか
    - 内言語 vs 外言語
- やり方は間違ってないけど，もう一個(整理法，visual)必要

```
> tree
.
├── c0_mk_stack_dir
├── c1_outline
│   ├── intro_info
│   ├── intro_info.key
│   ├── readme.html
│   ├── readme.org
│   └── style.css
├── c2_solar_system
├── c3_linear_algebra_core
├── intro_info_26s.html
├── IntroInfo -> ~/Lectures/IntroInfo/
├── light_table.yaml
├── Rakefile
├── readme.org
├── style.css
└── theme.css
```

#0 dl from github

```
▶ git clone https://github.com/daddygongon/
intro_info_26s
```

#1 Rakefileの配置

```
▶ cp c0_mk_stack_dir/templates/Rakefile .
▶ hyper_card ▶ rake
edit .hc_config.yaml
```

#2 .hc_config.yamlを編集

```
▶ cat .hc_config.yaml
:year: 2026
:lecture: math_ex_basic
:source_html: math_ex_basic_26s.html
:glob_extensions: "d*/*.html"
```

#3 init

```
▶ rake init
["config", {year: 2026, lecture: "math_ex_basic", so
"math_ex_basic_26s.html", glob_extensions: "d*/*.htm
cp c0_mk_stack_dir/templates/light_table.yaml~sample
```

#1 mkdir

```
▶ rake mkdir c4_dummy
mkdir c4_dummy
cp c0_mk_stack_dir/templates/readme.org c4_dummy
...
```

#2 light_table.yamlに新たなlink情報をadd

```
▶ code light_table.yaml
```

```
46 |  - :id: section-4
47 |    :title: d8-9 Pre-quantum
48 |    :items:
49 |    - :href: d8_pre_quantum/readme.html
50 |      :src: d8_pre_quantum/モデ物_26s-36.jpg
```

#3 topのhtml, stacksのbutton linkを更新

```
▶ ruby c0_mk_stack_dir/generate_html.rb
generate readme_26s.html.
▶ ruby c0_mk_stack_dir/mk_link.rb
"readme_26s.html"
...
"d8_pre_quantum/readme.org"
[[../d7_Planck_Manabe/readme_ex.html][prev_button]]
[[../readme_26s.html][up_button]]
[[../d0_ampm_0407/d0_ampm_0407.html][next_button]]
```

rsync excludeについて

外部のpublicへsyncするのに,
commit, pushコマンドを用意しています.
commitがlocal pcのどっか,
pushがpublic htmlへの公開です.

```
desc "commit local dir" #desc -> description
task :commit => :show_dirs do # any name on task_name
  system "mkdir #{$lec_dir}"

  excludes = %w[.venv/ venv/ env/ .env/ __pycache__/ .git/]
  exclude_opts = excludes.map { |e| "--exclude=\"#{e}\"" }.join(" ")

  Dir.glob($glob_extensions.split('/').first).each do |s_dir|
    p s_dir
    next unless File.directory?(s_dir)
   # comm = "cp -rf #{s_dir} #{$lec_dir}"
    comm = "rsync -av #{exclude_opts} #{s_dir} #{$lec_dir}"
    p comm
    system comm
  end
  ["cp #{$source_html} #{$lec_dir}",
   "cp style.css theme.css #{$lec_dir}",
   "chmod -R a+r #{$lec_dir}"
  ].each do |comm|
    p comm
    system comm
  end
  exit
end

desc "push light tables to web server"
task :push => :show_dirs do
  $ist_dir = File.join("nishitani@ist.ksc.kwansei.ac.jp:~/public_html/Lectures",
                       $year)
  $https_dir = File.join("https://ist.ksc.kwansei.ac.jp/~nishitani/Lectures",
                         $year, $lecture, $source_html)
  ["rsync -F -auvz -e ssh ~/Sites/new_ist/ nishitani@ist.ksc.kwansei.ac.jp:~/public_html",
   "open #{$https_dir}"].each do |comm|
    puts comm
    system comm
  end
end
```

local dir -commit-> local repositoryでは
rubyので

```
# 除外したいディレクトリのリスト
excludes = %w[.venv/ venv/ env/ .env/ __pycache__/ .git/]
exclude_opts = excludes.map { |e| "--exclude=\"#{e}\"" }.join(" ")

comm = "rsync -av #{exclude_opts} #{s_dir} #{$lec_dir}"
```

でpushでは, -Fオプションで

```
▶ bat _mk_stack_dir/.rsync-filter
──────┬──────────────────────────────────────────────────────────
      │ File: _mk_stack_dir/.rsync-filter
──────┼──────────────────────────────────────────────────────────
   1  │ # 全てコメントアウトしてます
   2  │
   3  │ # バックアップや一時ファイルを除外
   4  │ #- *~
   5  │ #- *.tmp
   6  │ #- *.bak
   7  │
   8  │ # OSの隠しファイルを除外
   9  │ #- .DS_Store
  10  │ #- Thumbs.db
  11  │
  12  │ # 特定のディレクトリ（例：下書きや作業用ディレクトリ）を除外
  13  │ #- drafts/
  14  │ #- work/
  15  │
  16  │ # 特定の拡張子のファイル（例：orgファイル）を除外
  17  │ #- *.org
──────┴──────────────────────────────────────────────────────────
```

を読み込んでいます.

dummy