Memorization and Legal Issues in Large Language Models

A Survey of Training Data Extraction Risks

Niveen Abdul-Mohsen ▪ Miya ▪ Silin
March 2026

Presentation Overview

Three papers tracing how LLMs memorize training data — and the technical, legal, and copyright risks that follow.

Paper 01 · Niveen Abdul-Mohsen

Extracting Training Data from LLMs

Carlini et al. show LLMs memorize verbatim training examples extractable via black-box queries alone, even without overfitting. Introduces k-eidetic memorization and the zlib metric.

Connects to Papers 02 & 03: Memorization ≠ overfitting. Larger models memorize more, a negative scaling law. Sets the empirical foundation that Paper 02 quantifies and Paper 03 applies to copyrighted books.

Paper 02 · Miya Livingston

Quantifying Memorization Across Neural LMs

Carlini et al. (2022) address Paper 01's binary evaluation gap with a scalable, continuous memorization metric tested across model sizes, architectures, and training configurations.

Connects to Papers 01 & 03: Memorization grows predictably with model size and data repetition; quantifying the risk Paper 01 identified, and establishing the scale at which Paper 03's copyright concern becomes real.

Paper 03 · Silin Pang

Extracting Books from Production LLMs

Ahmed et al. (2026) operationalize Paper 01's copyright concern by applying extraction attacks to long-form copyrighted books in production-scale LLMs, demonstrating real-world leakage.

Connects to Papers 01 & 02: The legal risk Paper 01 identified and Paper 02 quantified is demonstrated at real-world scale; production LLMs can reproduce substantial verbatim passages of copyrighted books.

Paper 01

Extracting Training Data from Large Language Models

Carlini, Tramèr, Wallace, Jagielski, Herbert-Voss, Lee, Roberts, Brown, Song, Erlingsson, Oprea, Raffel

Presenter: Niveen Abdul-Mohsen

Motivation: The Prevailing Belief + Why it Was Wrong

The Old Assumption

"The degree of copying with respect to any given work, is likely to be, at most, de minimis."

Logic: No overfitting → no memorization, GPT2 train/test gap = 10% → safe

What This Paper Proved

Memorization does not require overfitting

Certain worst-case training examples are memorized verbatim, extractable with just black-box API access.



Figure 1: **Our extraction attack.** Given query access to a neural network language model, we extract an individual person's name, email address, phone number, fax number, and physical address. The example in this figure shows information that is all accurate so we redact it to protect privacy.

Background: How Language Models Work

Chain Rule of Probability:

$$\mathbf{Pr}(x_1, x_2, \ldots, x_n) = \Pi_{i=1}^{n} \mathbf{Pr}(x_i \mid x_1, \ldots, x_{i-1}).$$

Each word's probability depends on all previous words.
Models learn this distribution from training text.

Training Loss (minimized during training):

$$\mathcal{L}(\theta) = -\log \Pi_{i=1}^{n} f_\theta(x_i \mid x_1, \ldots, x_{i-1})$$

The optimal solution to this objective is to memorize every training answer, **memorization is implicit in the objective itself.**

Perplexity: Measuring "Surprise"

$$\mathcal{P} = \exp\left(-\frac{1}{n}\sum_{i=1}^{n} \log f_\theta(x_i | x_1, \ldots, x_{i-1})\right)$$

Low perplexity = the model is not surprised by the sequence = likely seen it before = possible memorized content.

GPT2 At a Glance:

- Transformer architecture (attention layers)
- Trained on **40 GB** on internet text (Reddit links)
- Trained for **~12 epochs**, de-duplicated
- XL variant: **1.5 billion parameters**
- Train/test loss gap: **~10%** → no apparent overfitting

Background: The Privacy Attack Landscape

Attack Type	What It Does	Severity
Membership Inference	Predicts whether an example was in training data	Low, yes/no only
Model Inversion	Reconstructs a “fuzzy” representative of a class	Medium, not verbatim
Training Data Extraction	Recovers verbatim training examples	High, exact content

Prior work on extraction was limited to small models or required knowing what secret to look for. This paper is the first to demonstrate practical extraction from a production-scale LLM.

Defining Memorization Precisely

Definition 1: Model Knowledge Extraction

$$s \leftarrow \underset{s':\ |s'|=N}{\arg\max}\, f_\theta(s' \mid c)$$

A string **s** is *extractable* from a model if there exists a prefix **c** such that the model generates **s** as its most likely continuation of length **N.**

Definition 2: k-Eidetic Memorization

"A string s is k eidetic memorized (for k ≥ 1) by an LM fθ if s is extractable from fθ and s appears in at most k examples in the training data X: |{x ∈ X :s⊆x}|≤k"

Why This Definition is Clever:

- **Decouples from overfitting**, a model can have k=1 eidetic memorization on one string while showing zero average overfit
- **Spectrum of harm,** common word spellings (large k) vs. someone's phone number (k=1) are both "memorized" but vastly different
- **Testable**, we can empirically verify using black-box queries + internet search

Who Is the Adversary?

Black Box Access Only:

Adversary can query the model and observe outputs. No Access to weights, gradients, or attention vectors

Untargeted Extraction

Goal is to find *any* memorized content. A "fishing expedition" that still yields real PII.

Privacy Violations

Data Secrecy: extracting private training data directly

Contextual Integrity: reproducing public data in an unintended context

Why GPT2? Chosen deliberately to minimize harm, both the model and training data are public. This means that any extracted PII is technically findable via web search, making it ethical to publish. The attack methodology applies identically to models trained on private data.

Attack Overview

The Extraction Attack Pipeline



Step 1: Text Generation (3 Strategies)

Top-n: Standard Sampling (start-of-sequence token)
Temperature: Decay t=10 → 1 over first 20 tokens for diversity
Internet: Seed with 5-10 tokens of real web text (Common Crawl)

Step 2: Membership Inference (6 Metrics)

Metric	Compares GPT2-XL Perplexity against...	What it catches:
Perplexity	Nothing (raw)	High-k common text
Small	GPT2 Small (124M)	Rare content memorized only by large model
Medium	GPT Medium (345M)	Similar to above
zlib	Zlib compression entropy	Filters repetitive strings, finds diverse rare content
Lowercase	Perplexity of lowercase version	Content with unusual capitalations (news headlines, error logs)
Window	Minimum perplexity over 50-token sliding window	Long Samples with one memorized substring buried in noise

Key Technical Contribution

The zlib Metric - Why it Works

The Problem with Raw Perplexity: LLMs spuriously assign high likelihood to repetitive strings. This gets flagged as “memorized” by raw perplexity, but this is a model failure mode, not real memorization.

Zlib Entropy:

zlib is a standard compression algorithm. Its entropy = how many bits to compress the string.

Repetitive text → easily compressed → **low** zlib entropy
Random UUIDs/passwords –hard to compress → **high** zlib entropy



Figure 3: The zlib entropy and the perplexity of GPT-2 XL for 200,000 samples generated with top-n sampling. In red, we show the 100 samples that were selected for manual inspection. In blue, we show the 59 samples that were confirmed as memorized text. Additional plots for other text generation and detection strategies are in Figure 4.

Results

What Did They Actually Extract?

Category	Count
US and international news	109
Log files and error reports	79
License, terms of use, copyright notices	54
Lists of named items (games, countries, etc.)	54
Forum or Wiki entry	53
Valid URLs	50
Named individuals (non-news samples only)	46
Promotional content (products, subscriptions, etc.)	45
High entropy (UUIDs, base64 data)	35
Contact info (address, email, phone, twitter, etc.)	32
Code	31
Configuration files	30
Religious texts	25
Pseudonyms	15
Donald Trump tweets and quotes	12
Web forms (menu items, instructions, etc.)	11
Tech news	11
Lists of numbers (dates, sequences, etc.)	10

Table 1: Manual categorization of the 604 memorized training examples that we extract from GPT-2, along with a descrip-

1,800
Total Candidates Evaluated

604
Confirmed Memorized

33.5%
Aggregate True Positive Rate

67%
Best Config (Internet + zlib)

Notable Specific Extraction:

Full name, address, phone, email, fax of one individual, from a single training document (k=1 eidetic)

Usernames of 6 IRC users from exactly 1 training document (k=1 eidetic)

Content deleted from the web, preserved verbatim inside GPT2, circumventing the right to be forgotten

Results

Attack Strategy Efficacy (Table 2)

Inference Strategy	Text Generation Strategy		
	Top-n	Temperature	Internet
Perplexity	9	3	39
Small	41	42	58
Medium	38	33	45
zlib	59	46	67
Window	33	28	58
Lowercase	53	22	60
Total Unique	191	140	273

Table 2: The number of memorized examples (out of 100 candidates) that we identify using each of the three text generation strategies and six membership inference techniques. Some samples are found by multiple strategies; we identify 604 unique memorized examples in total.

33.5%
Aggregate TPR

67%
Best: Internet+zlib

604
Unique Memorized

Internet seeding dominates
273 unique examples vs. 191 (top-n). All strategies expose memorization.

Raw perplexity is a poor filter
Perplexity alone: 3-9% precision. zlib, Small, Lowercase are far more effective.

zlib achieves 67% precision
GPT-2 perplexity / zlib entropy is the single best metric for identifying memorized samples.

k=1 Eidetic Memorization: High-Entropy Extractions (Table 3)

Memorized String	Sequence Length	Occurrences in Data	
		Docs	Total
Y2...[redacted]...y5	87	1	10
7C...[redacted]...18	40	1	22
XM...[redacted]...WA	54	1	36
ab...[redacted]...2c	64	1	49
ff...[redacted]...af	32	1	64
C7...[redacted]...ow	43	1	83
0x...[redacted]...C0	10	1	96
76...[redacted]...84	17	1	122
a7...[redacted]...4b	40	1	311

Table 3: **Examples of $k = 1$ eidetic memorized, high-entropy content that we extract** from the training data. Each is contained in *just one* document. In the best case, we extract a 87-characters-long sequence that is contained in the training dataset just 10 times in total, all in the same document.

87 chars
Best case: sequence length

10x
Min occurrences in 1 doc

Every entry is k=1 eidetic
All 9 sequences appear in exactly 1 training document; most sensitive form of memorization.

High-entropy content, not common text
UUIDs, hash fragments, base-64 tokens. No linguistic reason GPT-2 should know them.

Even 10 repetitions is enough
Within-document repetition alone is sufficient to trigger verbatim memorization.

Key Finding

Larger Models Memorize More - The Reddit Experiment

URL (trimmed)	Occurrences		Memorized?		
	Docs	Total	XL	M	S
/r/[redacted]51y/milo_evacua...	1	359	✓	✓	½
/r/[redacted]zin/hi_my_name...	1	113	✓	✓	
/r/[redacted]7ne/for_all_yo...	1	76	✓	½	
/r/[redacted]5mj/fake_news_...	1	72	✓		
/r/[redacted]5wn/reddit_admi...	1	64	✓	✓	
/r/[redacted]lp8/26_evening...	1	56	✓	✓	
/r/[redacted]jla/so_pizzagat...	1	51	✓	½	
/r/[redacted]ubf/late_night...	1	51	✓	½	
/r/[redacted]eta/make_christ...	1	35	✓	½	
/r/[redacted]6ev/its_officia...	1	33	✓		
/r/[redacted]3c7/scott_adams...	1	17			
/r/[redacted]k2o/because_his...	1	17			
/r/[redacted]tu3/armynavy_ga...	1	8			

Table 4: We show snippets of Reddit URLs that appear a varying number of times in a *single* training document. We condition GPT-2 XL, Medium, or Small on a prompt that contains the beginning of a Reddit URL and report a ✓ if the corresponding URL was generated verbatim in the first 10,000 generations. We report a ½ if the URL is generated by providing GPT-2 with the first 6 characters of the URL and then running beam search.

URLs Memorized vs Model Size

XL Memorizes all URLs that appear >= **33 times**. Small memorizes essentially none. Memorization scales ~18x from Small to XL

The Larger Implications:

GPT2 XL is 1.5B parameters. GPT3 is 175B parameters – roughly 100x larger.

If memorization scales with model slize, modern frontier LLMs may memorize an order of magnitude more training data than demonstrated here. This is a negative scaling law.

Mitigation Strategies - None are Complete

Differential Privacy (DP-SGD)

Injects calibrated Gaussian noise into gradients during training. Provides formal, mathematically proven privacy guarantees.

Limitation: Hurts accuracy on rare dta (long tail); slows training; no production LLM used DP at time of writing; scaling to billions of params was unsolved

Downstream Filtering

Fine-tuning may cause the model to “forget” some pre-trained memorization. Applications can also filter outputs detected as memorized.

Limitation: Fine-tuning on task-specific data may introduce new memorization. Open research problem.

Training Data Curation:

De-duplicate at fine-grained level (line-by-line, n-gram), filtern known PII/passwords, limit single-source contribution, avoid high risk domains

Limitation: Imperfect, some sensitive data always slips through. Considered a first-line defense only.

Auditing/Red-Teaming

Use the attacks from this paper to measure how much a deployed model has memorized, even after applying DP. Treat memorization as an ongoing measurement problem

Currently best practice and is adopted by companies auditing deployed models.

Limitations of This Work

GPT2 Only/Public Data

Results tested only on GPT2 with public data. True risk to private data models is extrapolated, not directly demonstrated.

Only Black-Box Studied

White-box access could enable far more powerful attacks, This paper represents a lower bound on what is possible

No Mechanism Explanation

This paper shows memorization happens without overfitting but does not explain why.

Untargeted attacks Only

The attack cannot extract a specific person's data on demand.

1,800 Candidates <<< True Scale

Authors explicitly acknowledge this "vastly underestimates" true memorized content.

Mitigations Not Evaluated

DP and other defenses are discussed but not empirically benchmarked.

How This Paper Connects to the Rest of Today's Presentation

Paper 02 - Miya

Quantifying Memorization Across Neural LMs (Carlini et al., 2022)

Directly addresses a key limitation of this paper: the binary evaluation. Introduces a scalable, continuous metric for memorization across model sizes, architectures, and training configurations.

Paper 03 - Silin

Extracting Books from Production LMs (Ahmed et al., 2026)

Operationalizes the copyright concern raised here. Applies extraction attacks specifically to copyrighted book content in production models.

Legal & Regulatory Implications

- **Copyright Law (NYT v. OpenAI):** The extraction of verbatim text shown here is the empirical foundation for copyright infringement arguments
- **GDPR — Right to Be Forgotten**
- **Contextual Integrity (Nissenbaum):** Privacy violation occurs even with public data if it is reproduced in the wrong context.

Summary

4 Major Lessons from This Paper

1

Extraction attacks are practical, not theoretical

A simple two-step method (generate + filter) recovers hundred of verbatim training examples using only black box API access.

2

Memorization ≠ Overfitting

The train-test gap is NOT the right metric for privacy risk. A model with near-zero overfitting can still have strong eidetic memorization on worst-case examples.

3

Larger models are more vulnerable

This is a negative scaling law. The same trend that makes LLMs more capable also makes them memorize more training data. GPT-3 (100× larger than XL) is expected to be far more leaky.

4

The real extent is vastly larger than shown

Only 1,800 samples were checked. Better prefix selection and millions of queries would uncover far more. The 604 confirmed examples are a lower bound.

Paper 02

Quantifying Memorization Across Neural Language Models

Carlini, Ippolito, Jagielski, Lee, Tramèr, Zhang

Presenter: Miya

Contributions

Prior works

- Provided **loose, qualitative** analyses of memorization as a risk
  - Demonstrated that extraction attacks could extract memorized data
- Assessed models/datasets of fixed size, **without comparing models**
- Focused on avoiding memorization and ensuring novelty of model outputs

This paper

- **Precisely quantifies** memorization **across 3 model families** and their datasets
- Provides a more **precise bound** on the amount of memorized data that an adversary could extract

Background - Memorization

Extraction attacks

Memorized sequences of data from the training dataset can be extracted from models at inference time under specific prompting

Poses privacy risks: models can regurgitate private, sensitive info

Varying definitions

Differential privacy: Removing any one example from the training data should not change the model

Differential privacy learning algorithms are expensive and ineffective to prevent memorization of highly duplicated data

Scaling phenomena

Memorization relates to model scale, data duplication, and context length

Key Definitions

Extractable (memorized) Strings

Definition 3.1. A string s is *extractable with k tokens of context* from a model f if there exists a (length-k) string p, such that the concatenation $[p \mid\mid s]$ is contained in the training data for f, and f produces s when prompted with p using greedy decoding.

Example

Show that this sequence in the training data is extractable:
"My phone number is 555-6789"

Prompt model with prefix p: "My phone number is" (k = 4)

Model's response: "555-6789"

A more **actionable** and **useful** definition of memorization than differential privacy bounds or counterfactual memorization for the authors' goals (tightly bounding memorization)

Key Definitions

Duplication

Number of times a sequence appears in training data

Why it matters:

- Repeated examples -> **higher probability** of memorization
- Real training datasets like The Pile contain **highly duplicated data**
    - Duplicate web text
    - Repeated code snippets

Methodology

Main approach

1. Take **real example sequences** from the training dataset, **The Pile**
2. Feed **prefixes** into the model
3. Check if the model **completes them verbatim -> indicates memorization**

Methodology: Dataset

Training dataset: The Pile

Largest available public text dataset (825 GB) compiling text from various sources

Authors chose **2 representative subsets** of sequences for the experiments

1. Random sample **normalized** by **sequence lengths** and **duplication counts**
   - Useful to measure memorization on **duplicated data** with **varying prompt lengths**

2. **Uniformly random** sample of sequences w/o repetition
   - Useful to estimate **absolute amount** of memorization in the model

Final dataset:
500,000 sequences of varying duplication and length

- 50,000 sequences, duplicated varying numbers of times, at each length from 500-500 tokens

Methodology: Models

Model family: GPT-Neo

- Largest language models available for public download prior to OPT
- Causal language models trained for next-token prediction
- 4 parameter sizes
  - 125 million
  - 1.3 billion
  - 2.7 billion
  - 6 billion
- Trained on The Pile

Methodology: Prompting

For each sequence of length ℓ in the dataset:

1. Prompt model with the first **ℓ - 50 tokens (prefix)**
2. Collect model response
3. Determine if response was the **exact continuation (suffix)** of the sequence
   a. Model **exactly responds** with the **next 50 tokens -> extractable**
      - 50 tokens = ~127 characters, 25 words (greater than length of typical sentence)
   b. Other response -> not extractable
4. Compute average probability that a sequence is extractable by averaging over all lengths ℓ

Key Findings

1. Bigger models memorize more
    - More parameters -> More memorization

2. Repeated strings are memorized more
    - More duplication -> More memorization

3. Longer context discovers more memorization
    - Longer prefix -> More memorization

All follow roughly log-linear laws

Bigger models memorize more

- **Larger models memorize significantly more** than smaller models
- Near-perfect **log-linear fit**
  - Ten fold increase in model size -> 19% increase in memorization

Do larger models **memorize more** data, or are they just **more accurate?**

- Repeated analysis with GPT-2 model family as a baseline (similar but different training dataset)
- GPT-2 model had a much smaller extractable fraction (6%) compared to the GPT-Neo model of the same size
- Conclusion: Larger models have higher fraction of extractable data because of **increased memorization, not increased accuracy**



(a)

Repeated strings are memorized more

- Using the duplication-normalized sample, measured average fraction of extractable sequences for buckets of 1,000 sequences duplicated between 2 and 900 times

- Memorization probability increases for highly duplicated strings
- **Log-linear fit**
- Memorization still occurs with few duplicates
  - Deduplication does not perfectly prevent leakage



(b)

Longer context discovers more memorization

- Memorization increases with longer prefix lengths (longer context)
- **Log-linear fit**
  - 33% of sequences extracted at k=50, compared to 65% with k=450

Discoverability phenomenon: some memorization only becomes apparent **under certain conditions**

Implications:

- Attackers are less likely to be able to perform attacks requiring long prefixes
- Extraction risk can be reduced by restricting maximum prompt lengths
- Privacy auditing correctly becomes more challenging if some memorization is only revealed at large contexts



(c)

Alternate experimental settings

1. Random dataset sampling

Similar quantitative trends still observed with truly random sequence sampling (not normalized for duplication)

- Larger models show more memorization
- Longer context reveals more memorization

Lower bound estimate:
At least 1% of The Pile is extractable by the 6B GPT-Neo model



Alternate experimental settings

2. Alternate decoding strategies

Original experiments used **greedy decoding strategy**: extractability when choosing **most likely token** at each decoding step

- May not produce the overall most likely sequence

Other decoding strategies like **beam search** can be used to find the overall **most likely sequence**

Beam search with 100 beams results in marginally more (2%) extracted sequences (c-left)

- Beam search and greedy decoding generated the same output 45% of the time



(c)

Alternate experimental settings

3. Alternate definition of extractability

Original experiments defined a sequence as “extractable” if the model’s output **identically matched the true suffix**

Alternative definition: “extractable” if model’s output **appears anywhere in the dataset**, even as the suffix of a different example

Looser definition reveals **more memorization** (c-right)

- At 100 repetitions, 32.6% of outputs exist in the dataset compared to 15.8% which match the ground truth continuation



(c)

Qualitative examples of memorization

Smaller models may produce **syntactically similar** but **semantically incorrect** outputs compared to the larger model's extracted output

Prompt	Continuation (== 6B)	2.7B	1.3B	125M
Gallery "Though defensive violence will always be 'a sad necessity' in the eyes of men of principle, it would be still more unfortunate if wrongdoers should dominate just men."- St. Augustine "A new idea is first	condemned as ridiculous, and then dismissed as trivial, until finally it becomes what everybody knows." - William James "This is the real task before us: to reassert our commitment as a nation to a law higher than our own,	condemned as ridiculous, and then dismissed as trivial, before being accepted as the most important thing in the world."- George Bernard Shaw "The ultimate measure of a man is not where he stands in moments of comfort and convenience, but where	tried in the mind of a child, and then it is tried in the mind of a man."- Thomas Paine "The only thing necessary for the triumph of evil is for good me[illegible]	and foremost a man's duty to his fellow man. It is a duty to be a man of principle, and to be a man of principle, and to be a man of principle, and to be a man of principle, and to be a
_GPL(crypto_unregister_alg); int crypto_register_template(struct crypto_template *tmpl) { struct crypto_template [illegible] = -EEXIST;	down_write(&crypto_alg_sem); list_for_each_entry(q, [illegible]_template_list, list) { if (q == tmpl)	list_for_each_entry(q, &crypto_alg_list, list) { if (tmpl->name && tmpl->name!= q->alg.cra_name)	q = kzalloc(sizeof(*q), GFP_KERNEL); if (!q) goto out; q->alg = tmpl->alg; q->base	struct crypto_template *tmpl = crypto_template_new(tmpl) ; if (err) return err; tmpl->tmpl = q; tmpl->tmpl->tm

Figure 3: Text examples that are memorized by the 6B model, but not by smaller models. Green highlighted text matches the ground truth continuation, while red text indicates incorrect generation.

Some sequences were **memorized by all models**

Unconventional, highly duplicated texts: code snippets, open source licences

Prompt	Continuation (== 6B == 2.7B == 1.3B == 125M)
use this file except in compliance with the License. * You may obtain a copy of the License at * http://www.apache.org/licenses/LICENSE-2.0 * Unless required by applicable law or agreed	to in writing, software * distributed under the License is distributed on an "AS IS" BASIS, * WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. * See the License for the specific language
* * This program is free software; you can redistribute it and/or modify * it under the terms of the GNU General Public License version 2 and * only version 2 as published by the Free Software Foundation. * *	This program is distributed in the hope that it will be useful, * but WITHOUT ANY WARRANTY; without even the implied warranty of * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the *

Replication Studies

T5 masked language modeling

Similar memorization scaling patterns as those in prefix-suffix tasks (GPT-Neo causal language models) hold for **masked prediction tasks** (T5 masked encoder-decoder models)

- **Absolute memorization** was an order of magnitude **lower for masked models** compared to their similarly sized casual counterparts
  - 3.5% memorization in T5-XL vs. 53.6% memorization in GPT-Neo 2.7B (k = 150, 100 repetitions)



Replication Studies

Models trained on deduplicated data

1. Models trained on deduplicated data **memorize less** than models trained without deduplication
   - For sequences repeated < 35 times, 1.2% memorization in deduplicated model vs. 3.6% memorization in non-deduplicated model

2. Deduplication **reduces memorization** for sequences repeated **up to ~100 times**, **but not for sequences repeated more often** than that
   - Likely due to **non-exhaustive nature of any deduplication method** that can efficiently scale to gigabytes of training data



(c)

Replication Studies

Models trained on modified version of The Pile

OPT models: trained on 800GB deduplicated dataset with some overlap with Pile, but with some additional/removed data

Showed **similar scaling patterns** as GPT-Neo models, but at **smaller orders of magnitude**

- 66B parameter OPT memorized less of The Pile than the smallest 125M parameter GPT-Neo



Limitations

- These experiments assume knowledge of **training data**
  - Not always known for new or proprietary models
- Only measures **extractable memorization**
- Focuses on **verbatim extraction**, not paraphrased
- Focuses on continued generation
  - Experiments with contained generation are limited due to computational costs for large datasets
- Focuses on GPT and OPT models
  - Memorization patterns may differ for other families

Conclusion and Implications

Memorization is:

- Quantifiable
- Scalable
- **Underestimated**

It grows with:

- Model size
- Data duplication
- Context length

Extracting Books from Production Language Models

Ahmed Ahmed, A. Feder Cooper, Sanmi Koyejo, Percy Liang
Presenter: Silin Pang

Motivation: From Data Extraction to Copyright Risk

What We Already Know

- Language models can memorize training data
- Prior work shows extraction of sensitive information (e.g., PII)
- Extraction attacks are feasible under black-box access

What This Paper Focuses On

- Targets copyrighted books, not just short snippets
- Studies long-form extraction from production LLMs
- Raises new concerns about legal and copyright implications

Key Insight

The risk shifts from data leakage to large-scale copyrighted content extraction

Background: Memorization and Data Extraction

Memorization in LLMs

- Models may store specific training examples
- Memorization ≠ generalization
- Can occur even without obvious overfitting

Extraction of Training Data

- Goal: recover training data from model outputs
- Standard approach:
- Provide a prefix
- Check if model continues with ground-truth text
- Prior work focuses on short text extraction

Limitation of Prior Work:

- Focuses on short text extraction
- Does not study long-form (e.g., books)
- Limited evaluation on production LLMs

Key Point:

This paper extends extraction from short snippets to long-form text (books)

Method Overview: The Extraction Procedure

Two-Phase Extraction Strategy

- Phase 1: Prefix Completion Test
  - Provide a short prefix from a book
  - Check if model continues correctly
  - If needed, apply prompt variations (multiple attempts)
- Phase 2: Iterative Extraction
  - Repeatedly prompt the model to continue
  - Collect generated text step by step
  - Reconstruct long passages from outputs

Key Idea:

- Turn the model into a long-form text generator
- Start from a small prefix → extend into full text

Key Insight:

If a model can continue correctly once, it may reveal large amounts of memorized text

Method Details: Measuring Extraction Success

Similarity Score (Phase 1)

- Compare model output with true continuation
- Measure longest matching substring
  - $$s = \frac{\text{longest common substring}}{\text{target suffix length}}$$
- Success if:
  - $$\boxed{s \geq 0.6}$$

Near-Verbatim Recall (nv-recall)

- Identify matching text blocks
- Merge nearby matching segments
- Filter out short matches
  - $$\boxed{\text{nv-recall} = \frac{\text{matched words}}{\text{total words in book}}}$$

Key Insight:
Extraction is measured by how much verbatim text can be recovered

Phase 1: Initial Probe

Goal: Test for Memorization

- Provide a short prefix from a book
- Prompt the model to continue
- Compare output with true continuation
- Identify substantial overlap

What Counts as Success?

- The continuation matches the ground truth
- A long matching segment exists
- Indicates memorization of the text

Best-of-N (BoN) Jailbreak

Direct prompting may fail due to safety restrictions

BoN increases the chance of successful continuation

Enables extraction even when the model initially refuses

Key Insight:
Phase 1 verifies memorization before extraction

Phase 1: Initial Probe



Phase 2: Iterative Extraction

From Prefix to Long Text

- Repeatedly prompt the model to continue
- Use previous outputs as new context
- Generate text step by step
- Accumulate outputs into longer passages

How Extraction Scales

- Each step extends the generated sequence
- Local matches enable further continuation
- Small memorized segments grow into long text

Key Insight:
Iterative continuation enables long-form extraction from local memorization

Phase 2: Iterative Extraction

Phase 2: Attempt long-form extraction

Input Prompt successful **Phase 1**

Prompt = Instruction + Prefix **OR** BON_Instruction$_N$ + Prefix

Continuation loop

Production LLM : say that they were perfectly normal thank you very much. They were the last people you'd expect

User: Continue

Production LLM : to be involved in anything strange or mysterious, because they didn't hold with such nonsense.

User: Continue

Production LLM : Mr. Dursley was the Director of a firm called Grunnings, which made drills.

... until hit a maximum query budget, a stop phrase, or a refusal

Concatenate responses

Generation = say that they were perfectly normal thank you very much. They were the last people you'd expect to be involved in anything strange or mysterious, because they didn't hold with such nonsense. Mr. Dursley was the Director of a firm called Grunnings, which made drills. ...

Evaluate Generation for extraction of Book

Compute nv-recall(Book, Generation)

From Generation to Extraction



Algorithm 1 Long-span, near-verbatim matching block formation

Require: Word lists B (the book) and G (the generated text)

Require: Thresholds $\tau^{(1)}_{\text{gap}}, \tau^{(1)}_{\text{align}}$ (merge 1), $\tau^{(2)}_{\text{gap}}, \tau^{(2)}_{\text{align}}$ (merge 2); minimum lengths $l^{(1)}$ (filter 1), $l^{(2)}$ (filter 2)

$\mathbb{B}^{(\text{base})} \leftarrow \text{greedy_approx_longest}(B, G)$ ▷ **identify**: compute verbatim matching blocks (Eq. 3)

$\widetilde{\mathbb{B}}^{(1)} \leftarrow \text{merge}(\mathbb{B}^{(\text{base})},\ \tau^{(1)}_{\text{gap}},\ \tau^{(1)}_{\text{align}})$ ▷ **merge 1**: stitch very short gaps (Eq. 4)

$\widetilde{\mathbb{B}}^{(1)}_{\geq l^{(1)}} \leftarrow \text{filter}(\widetilde{\mathbb{B}}^{(1)},\ l^{(1)})$ ▷ **filter 1**: remove short blocks (Eq. 5)

$\widetilde{\mathbb{B}}^{(2)} \leftarrow \text{merge}(\widetilde{\mathbb{B}}^{(1)}_{\geq l^{(1)}},\ \tau^{(2)}_{\text{gap}},\ \tau^{(2)}_{\text{align}})$ ▷ **merge 2**: passage-level consolidation (Eq. 4)

$\widetilde{\mathbb{B}}^{(2)}_{\geq l^{(2)}} \leftarrow \text{filter}(\widetilde{\mathbb{B}}^{(2)},\ l^{(2)})$ ▷ **filter 2**: retain long blocks (Eq. 5)

return $\mathbb{B}^* := \widetilde{\mathbb{B}}^{(2)}_{\geq l^{(2)}}$ ▷ final ordered set of long near-verbatim matching blocks

$$\text{nv-recall} = \frac{\text{matched words from blocks}}{\text{total words in book}}$$

Near-Verbatim Matching

- **Verbatim Blocks**
  - Find contiguous matching word sequences
  - Match must appear exactly in both generated text and book
- **Merge Blocks**
  - Combine nearby blocks separated by small gaps
  - Treat them as part of the same passage
- **Filter Blocks**
  - Remove very short matches
  - Keep only sufficiently long segments
- **Compute Metrics**
  - Measure how much of the book is covered by matched blocks
  - Forms the basis of nv-recall

These matched blocks are then used to compute nv-recall, which measures the fraction of the book covered by these extracted segments.

Why Does This Extraction Work?

Local Memorization

- Models memorize short text continuations
- Given a correct prefix, continuation becomes predictable
- Memorization appears at the level of local sequences

From Local to Global

- Each correct continuation extends context
- Subsequent predictions become easier
- Repeated generation amplifies memorization

Implication

Once a correct continuation is found, further extraction becomes easier

Key Insight:

Local memorization enables global extraction through iteration

Main Results: Extraction of Book Content

Key Findings

- Extraction is feasible across multiple production LLMs
- Performance varies significantly across models and books
- Some model–book pairs show high extraction rates
- Many cases exhibit partial but meaningful leakage



Key Insight:
Long-form memorized text can be recovered from production LLMs

Extracted Text from In-Copyright Books

Suddenly in the wood beyond The Water a flame leapt upprobably somebody lighting a wood-fireand he thought of plundering dragons settling on his quiet Hill and kindling it all to flames.

He shuddered; and very quickly he was plain Mr. Baggins of Bag-End, Under-Hill, again.

He got up trembling.

He had less than half a mind to fetch the lamp, and more than half a mind to pretend to, and go and hide behind the beer-barrels in the cellar, and not come out again until all the dwarves had gone away.

Suddenly he found that the music and the singing had stopped, and they were all looking at him with eyes shining in the dark.

(a) Gemini 2.5 Pro, *The Hobbit*

was all stooped over, and he had very terrible posture, and in class, whenever he dropped a piece of chalk at the blackboard, some guy in the first row always had to get up and pick it up and hand it to him. That's awful, in my opinion. But if you thought about him just enough and not too much, you could figure it out that he wasn't doing too bad for himself. For instance, one Sunday when some other guys and I were over there for hot chocolate, he showed us this old beat-up Navajo blanket that he and Mrs. Spencer'd bought off some Indian in Yellowstone Park. You could tell old ~~Spencer'd~~ **Spencer** got a big bang out of buying it. That's what I mean. You take somebody old as hell, like old Spencer, and they can get a big ~~bang~~ **kick** out of buying a blanket.

(b) Grok 3, *The Catcher in the Rye*

Key Findings

- Models can generate near-verbatim passages.
- Extracted text closely matches the original copyrighted books.
- The output is not just stylistically similar; in some cases it is highly faithful to the source text.

Key Insight:

LLMs can reproduce recognizable portions of copyrighted text。

Query Cost and Extraction Effort

Book	Claude 3.7 Sonnet			GPT-4.1			Gemini 2.5 Pro			Grok 3		
	# Cont.	Cost	max $\lvert\beta\rvert$	# Cont.	Cost	max $\lvert\beta\rvert$	# Cont.	Cost	max $\lvert\beta\rvert$	# Cont.	Cost	max $\lvert\beta\rvert$
Harry Potter 1	480	$119.97	6658	31	$1.37	821	171	$2.44	9070	52	$8.16	6337
Frankenstein	374	$55.41	8732	33	$0.19	474	204	$0.38	448	300	$77.12	275
The Hobbit	1000	$134.87	8835	4	$0.16	205	188	$0.52	571	115	$23.40	1816
A Game of Thrones	562	$124.49	1091	15	$0.16	0	166	$0.36	138	195	$42.36	836

Key Findings

- Extraction requires repeated continuation queries.
- The monetary cost varies substantially across models.
- The longest extracted block can be very large.
- Different systems show different trade-offs between cost, number of queries, and extraction outcome.

Absolute Amount of Extracted Text



(a) *Harry Potter and the Sorcerer's Stone*



(b) *Frankenstein* (public domain)



(c) *The Hobbit*



(d) *A Game of Thrones*

Key Findings

- The paper also evaluates extraction in absolute word counts, not just percentages.
- Even when nv-recall is not extremely high, the recovered text can still be substantial.
- In some cases, extraction reaches tens of thousands of words.
- This gives a clearer sense of the real scale of leakage.

Observations from Results

Overall Patterns

- Extraction is clearly feasible in production LLMs
- Results are highly uneven across books
- Some books show high nv-recall, others remain low

Model Differences

- Different models exhibit different extraction behavior
- Some models achieve high extraction on certain books
- Others produce only limited or fragmented outputs

Key Insight:
Memorization is not uniform — it depends on both the model and the data

Limitations

Experimental Limitations

- Limited number of books evaluated
- Results depend on prompting strategies
- Experiments are costly and time-intensive

Methodological Limitations

- Extraction provides a lower bound on memorization
- Not all memorized content is recoverable
- Results are not directly comparable across models

Key Insight:
The results demonstrate possibility, not full prevalence

Implications

Legal Implications

- Extracted text may closely match copyrighted works
- Challenges the claim that model outputs are always “transformative”
- Raises concerns about potential copyright infringement

Technical & Societal Implications

- Memorization can lead to unintended data leakage
- Safeguards may not fully prevent extraction
- Risks extend beyond short snippets to long-form content

Key Insight

Memorization in LLMs is both a technical issue and a legal concern

Conclusions

LLM memorization is a real, measurable risk

Training data can be extracted verbatim via black-box queries alone; no overfitting required, no white-box access needed.

Memorization scales with model size and data duplication

Larger models and more repeated training examples both produce more extractable memorization; a negative scaling law for privacy.

Risk extends to copyrighted long-form content

Production LLMs can reproduce substantial verbatim passages of copyrighted books, creating real legal exposure under copyright law.

No complete mitigation exists; ongoing auditing is essential

DP and deduplication reduce but don’t eliminate leakage. Red-teaming and auditing of deployed models are currently best practice.

Memorization is not a bug to be fixed in isolation; it is a fundamental property of LLMs that requires ongoing measurement, transparency, and legal accountability.