

Window Styles

07/15/2024

This topic provides a list of the various styles that can be applied to a window (after the window has been created, these styles cannot be modified, except as noted).

 Expand table

Constant name	Constant value	Description
WS_BORDER	0x00800000L	The window has a thin-line border
WS_CAPTION	0x00C00000L	The window has a title bar (includes the WS_BORDER style).
WS_CHILD	0x40000000L	The window is a child window. A window with this style cannot have a menu bar. This style cannot be used with the WS_POPUP style.
WS_CHILDWINDOW	0x40000000L	Same as the WS_CHILD style.
WS_CLIPCHILDREN	0x02000000L	Excludes the area occupied by child windows when drawing occurs within the parent window. This style is used when creating the parent window.
WS_CLIPSIBLINGS	0x04000000L	Clips child windows relative to each other; that is, when a particular child window receives a WM_PAINT message, the WS_CLIPSIBLINGS style clips all other overlapping child windows out of the region of the child window to be updated. If WS_CLIPSIBLINGS is not specified and child windows overlap, it is possible, when drawing within the client area of a child window, to draw within the client area of a neighboring child window.
WS_DISABLED	0x08000000L	The window is initially disabled. A disabled window cannot receive input from the user. To change this after a window has been created, use the EnableWindow function.
WS_DLGFRAME	0x00400000L	The window has a border of a style typically used with dialog boxes. A window with this style cannot have a title bar.
WS_GROUP	0x00020000L	The window is the first control of a group of controls. The group consists of this first control and all controls defined after it, up to the next control with the WS_GROUP style. The first control in each group usually has the WS_TABSTOP style so that the user can move from group to group. The user can subsequently change the keyboard focus from one control in the group to the next control in the group by using the direction keys. You can turn this style on and off to change dialog box navigation. To change this style after a window has been created, use the SetWindowLong function.
WS_HSCROLL	0x00100000L	The window has a horizontal scroll bar.
WS_ICONIC	0x20000000L	The window is initially minimized. Same as the WS_MINIMIZE style.
WS_MAXIMIZE	0x01000000L	The window is initially maximized.
WS_MAXIMIZEBOX	0x00010000L	The window has a maximize button. Cannot be combined with the WS_EX_CONTEXTHELP style. The WS_SYSMENU style must also be specified.
WS_MINIMIZE	0x20000000L	The window is initially minimized. Same as the WS_ICONIC style.
WS_MINIMIZEBOX	0x00020000L	The window has a minimize button. Cannot be combined with the WS_EX_CONTEXTHELP style. The WS_SYSMENU style must also be specified.

Constant name	Constant value	Description
WS_OVERLAPPED	0x00000000L	The window is an overlapped window. An overlapped window has a title bar and a border. Same as the WS_TILED style.
WS_OVERLAPPEDWINDOW	(WS_OVERLAPPED WS_CAPTION WS_SYSMENU WS_THICKFRAME WS_MINIMIZEBOX WS_MAXIMIZEBOX)	The window is an overlapped window. Same as the WS_TILEDWINDOW style.
WS_POPUP	0x80000000L	The window is a pop-up window. This style cannot be used with the WS_CHILD style.
WS_POPUPWINDOW	(WS_POPUP WS_BORDER WS_SYSMENU)	The window is a pop-up window. The WS_CAPTION and WS_POPUPWINDOW styles must be combined to make the window menu visible.
WS_SIZEBOX	0x00040000L	The window has a sizing border. Same as the WS_THICKFRAME style.
WS_SYSMENU	0x00080000L	The window has a window menu on its title bar. The WS_CAPTION style must also be specified.
WS_TABSTOP	0x00010000L	The window is a control that can receive the keyboard focus when the user presses the TAB key. Pressing the TAB key changes the keyboard focus to the next control with the WS_TABSTOP style. You can turn this style on and off to change dialog box navigation. To change this style after a window has been created, use the SetWindowLong function. For user-created windows and modeless dialogs to work with tab stops, alter the message loop to call the IsDialogMessage function.
WS_THICKFRAME	0x00040000L	The window has a sizing border. Same as the WS_SIZEBOX style.
WS_TILED	0x00000000L	The window is an overlapped window. An overlapped window has a title bar and a border. Same as the WS_OVERLAPPED style.
WS_TILEDWINDOW	(WS_OVERLAPPED WS_CAPTION WS_SYSMENU WS_THICKFRAME WS_MINIMIZEBOX WS_MAXIMIZEBOX)	The window is an overlapped window. Same as the WS_OVERLAPPEDWINDOW style.
WS_VISIBLE	0x10000000L	The window is initially visible. This style can be turned on and off by using the ShowWindow or SetWindowPos function.
WS_VSCROLL	0x00200000L	The window has a vertical scroll bar.

Requirements

 Expand table

Requirement	Value
Minimum supported client	Windows 2000 Professional [desktop apps only]
Minimum supported server	Windows 2000 Server [desktop apps only]
Header	Winuser.h (include Windows.h)