

Markdown doesn't have many strict "rules." Think of it as a simple way to add formatting to plain text.

The most common syntax rules are:

1. Headings

Put `#` at the beginning of a line.

`</>` Markdown 

```
# Heading 1
## Heading 2
### Heading 3
```

Usually there is a space after the `#`.

`</>` Markdown 

```
# Good
```

`</>` Markdown 

```
#Bad
```

Some parsers accept this, but it's not recommended.

2. Paragraphs

Separate paragraphs with a blank line.

`</>` Markdown 

```
This is paragraph one.
```

```
This is paragraph two.
```

3. Line Breaks

A single Enter is often ignored:

`</>` Markdown 

```
Line one  
Line two
```

may render as:

```
Line one Line two
```



To force a line break, either:

```
<> Markdown
```



```
Line one  
Line two
```

(two spaces at the end of the first line)

or use an HTML tag:

```
<> Markdown
```



```
Line one<br>  
Line two
```

4. Emphasis

Italic:

```
<> Markdown
```



```
*text*
```

or

```
<> Markdown
```



```
_text_
```

Bold:

```
<> Markdown
```



```
**text**
```

or

`</>` Markdown



```
__text__
```

Bold + italic:

`</>` Markdown



```
***text***
```

5. Lists

Unordered list:

`</>` Markdown



```
- Item 1  
- Item 2  
- Item 3
```

or

`</>` Markdown



```
* Item 1  
* Item 2
```

Ordered list:

`</>` Markdown



```
1. First  
2. Second  
3. Third
```

6. Links

`</>` Markdown



```
[Google] (https://google.com)
```

Format:

</> Markdown



```
[text] (url)
```

7. Images

</> Markdown



```
![Description] (image.png)
```

Format:

</> Markdown



```
![alt text] (image-url)
```

The `!` distinguishes an image from a normal link.

8. Inline Code

Use a single backtick:

</> Markdown



```
Use `querySelector()`.
```

Result:

Use `querySelector()`.

9. Code Blocks

Use three backticks:

</> Markdown



```
```js
console.log("Hello");
```
```

The language (`js`) is optional but enables syntax highlighting.

10. Blockquotes

Use `>`:

```
</> Markdown
```



```
> This is a quote.
```

Result:

This is a quote.

11. Horizontal Rules

Use three or more dashes:

```
</> Markdown
```



```
---
```

or

```
</> Markdown
```



```
***
```

12. Tables

```
</> Markdown
```



```
Name	Age
Tom	20
Bob	25
```

Result:

| Name | Age |
|------|-----|
| Tom | 20 |

| Name | Age |
|------|-----|
| Bob | 25 |

The 90% Rule

For most Markdown files (especially `README.md` files on GitHub), you'll use only these:

`</>` Markdown



```
# Heading
```

```
Some text.
```

```
## Subheading
```

- List item
- List item

```
[Link] (https://example.com)
```

```
`inline code`
```

```
```js  
code block
```

If you know **headings, paragraphs, lists, links, and code blocks**, you can read a

