Synopsis of Project work on,

"AEOS Guard - Agent Execution Operations Security"

Submitted in partial fulfillment of the
requirements of the degree of
(Bachelor of Engineering)

By

Sanmay Mestry (61)

Dheeraj Salian (18)

Prachi Dehade (16)

Abhishek Satarkar (30)

Supervisor:
Prof. Mahesh Mishra
Assistant Professor

(Department of Information Technology)
AET'S
Atharva College of Engineering
(2026-2027)

AET'S
ATHARVA COLLEGE OF ENGINEERING

CERTIFICATE

This is to certify that

Sanmay Mestry (61)

Dheeraj Salian (18)

Prachi Dehade (16)

Abhishek Satarkar (30)

Have satisfactorily completed the requirements of the Synopsis
On
"AEOS Guard - Agent Execution Operations Security"

As prescribed by the University of Mumbai for academic year 2026-27
Under the guidance of

Prof. Mahesh Mishra
Guide

Dr. Nileema Pathak	Dr. Bhavna Arora	Dr. Ramesh Kulkarni
Project Coordinator	**Head (Information Technology)**	**Principal**
Internal Examiner	**College Seal**	**External Examiner**

Declaration

We declare that this written submission represents our ideas in our own words and where others' ideas or words have been included, we have adequately cited and referenced the original sources. We also declare that we have adhered to all principles of academic honesty and integrity and have not misrepresented or fabricated or falsified any idea/data/fact/source in our submission. We understand that any violation of the above will cause disciplinary action by the Institute and can also evoke penal action from the sources which have thus not been properly cited or from whom proper permission has not been taken when needed.

Signature

Sanmay Mestry (61)

Signature

Dheeraj Salian (18)

Signature

Prachi Dehade (16)

Signature

Abhishek Satarkar (30)

Date:

Index

SR NO	CONTENT	PAGE NO
1	Introduction	1
2	Review of Literature	4
3	Report on the Present Investigation	6
4	Aim and Objectives	8
5	Problem Statement	9
6	Proposed System	10
7	Requirement Analysis	13
8	Feasibility Study	16
9	Design Details	18
9.1	Context Level diagram	18
9.2	DFD Diagram	19
9.3	Sequence Diagram	20
9.4	E-R Diagram	21
9.5	Control Flow Diagram	22
10	Implementation Plan	24
11	Gantt Chart	30
12	Conclusion	31
	Acknowledgement	32
	References	33

List of Figures

Figure No	Name of Figure	Page No
6.1	Block Diagram	11
9.1	Context Level Diagram	19
9.2	DFD Diagram	20
9.3	Sequence Diagram	21
9.4	E-R Diagram	22
9.5	Control Flow Diagram	23
10.1	Output Screen: Threat Overview	26
10.2	Output Screen: Control Room and Circuit Breakers	27
10.3	Output Screen: Investigation Workspace	28
10.4	Output Screen: Attack Simulator	29
11.1	Gantt Chart	30

Abstract

AEOS Guard is a defense-in-depth security middleware for autonomous AI agents. It protects the three surfaces through which an agent can be subverted: the tools it calls, the memory it writes, and the reasoning trace it produces. A network firewall is a checkpoint on the path a packet travels; AEOS Guard is a checkpoint on the path a decision travels. The system is implemented as three independent detection modules that share nothing but a common event contract. ***MCP-Shield****, a Rust tool-layer guard, fingerprints tool schemas with HMAC-SHA256 over a canonical form, sanitises tool descriptions, and refuses to let a baseline be silently overwritten.* ***VectorAnchor****, a Python memory-layer guard, detects memory poisoning through frequency anomaly analysis across a corpus of many distinct topics, so that one document retrieved repeatedly cannot masquerade as a general fact.* ***TraceAudit****, a Python reasoning-layer guard, scores the KL divergence between the expected and observed reasoning distribution, splits secrets across token boundaries before they are logged, and redacts personally identifiable information before it reaches a log sink.*

All three modules emit the same eight-field event envelope, so a single console can show tool, memory and reasoning incidents on one timeline. A Next.js dashboard with server-sent events, PostgreSQL row-level security and an append-only incident audit trail gives an operator a single pane of glass. Evaluation on the project's own synthetic detection fixtures reports a detection F1 score of 1.000 for reasoning-divergence detection and PII scanning, 0.857 for memory frequency-anomaly detection and 0.833 for tool-description sanitisation, at a mean overhead of 6.4 microseconds per tool call and 438.9 microseconds per memory retrieval.

Keywords: *AI Agent Security, Defense in Depth, Tool Poisoning, Memory Poisoning, Reasoning Hijack, Model Context Protocol, Anomaly Detection, Security Middleware*

Chapter 1

Introduction

AEOS Guard is a security middleware for autonomous AI agents. It sits between an agent and the three things an agent depends on — the tools it calls, the memory it reads and the reasoning it performs — and it inspects all three for signs of manipulation. The project began from a simple observation: the defences that protect conventional software do not apply to agents, because an agent's attack surface is not a set of network endpoints but a set of *decisions*.

The system is built as three independent detection modules. MCP-Shield guards the tool layer, VectorAnchor guards the memory layer and TraceAudit guards the reasoning layer. They share no code, no state and no failure modes; the only thing they have in common is the eight-field event contract they all emit. That contract is what makes a single console possible: a tool schema change, a poisoned memory and a reasoning anomaly all arrive as the same shaped record and can therefore be correlated on a single timeline by an operator who has never read the source of any of them.

The implementation reflects that separation deliberately. The tool layer is written in Rust because it sits on the hot path of every tool call and must not add meaningful latency to an interactive agent. The memory and reasoning layers are written in Python because their algorithms are statistical rather than latency-critical. The console is a Next.js 16 application on React 19 with server-sent events, a PostgreSQL ledger protected by row-level security and an append-only incident audit table.

1.1 Need and Motivation

Everything in conventional application security assumes that the attacker and the victim speak different protocols. A network attack is bytes that do not belong; a SQL injection is a string that does not belong; a scanner separates the shape of the intruder from the shape of the traffic. For an LLM agent that assumption breaks down. The content an agent retrieves from a web page, a shared document or a tool response is syntactically indistinguishable from the content its operator wrote. It is a meaning problem wearing valid syntax, and syntax is all our current tools can read.

This produces three distinct classes of attack, and AEOS Guard is organised around them. **Rug pull** attacks change what a tool does after the agent has been trained to trust it: the tool description is rewritten to instruct the model, and the model follows — the vocabulary established by the first public disclosure of tool poisoning, which distinguished a poisoned tool from one whose definition simply changes after approval [20]. **Memory poisoning** attacks plant a false fact in the vector store so that it is retrieved later and acted on as though it

were ordinary knowledge; MITRE ATLAS names this class AI agent context poisoning and its retrieval variant RAG poisoning [5]. **Reasoning leakage and hijack** attacks either cause the model to emit a secret it holds, or inject a secret held by the surrounding system into the reasoning trace, where it will be logged and summarised again.

Three properties make these attacks worth a dedicated system rather than a filter bolted onto an existing one. First, they are cheap: an attacker who can write one tool description or one document does not need to break anything, they only need to be believed. Measured on 45 live MCP servers carrying 353 authentic tools, a tool-poisoning attack compromised the strongest agent evaluated in 72.8% of cases, and the highest refusal rate across every agent tested was under 3% [12]. Second, they are silent: a poisoned memory looks exactly like a good memory to every component that reads it, including embedding similarity search, because similarity is not the same question as authenticity. Five poisoned documents were enough to reach a 90% attack success rate against a retrieval corpus holding millions of documents [9]. Third, they are invisible to the layers that already exist, because a firewall inspects packets and a DLP inspects documents, and neither of them inspects the meaning of a tool call.

1.2 Basic Concept

The basic concept of the system is that an agent decision is built from three inputs, and each input can be poisoned independently. A tool description is text supplied by whoever published the tool. A retrieved document is text supplied by whoever wrote it into the corpus. A reasoning trace is text produced by a model that has been given the first two. AEOS Guard treats all three as untrusted input and inspects each with the detector that is suited to it.

- **Tool layer (MCP-Shield).** A Rust proxy that intercepts tool registration and tool invocation, computes a canonical fingerprint, compares it against a pinned baseline, and sanitises the description before the agent sees it.
- **Memory layer (VectorAnchor).** A Python service that observes every retrieval from the vector store, maintains a per-document frequency profile across a corpus of distinct topics, and quarantines documents whose retrieval pattern is anomalous.
- **Reasoning layer (TraceAudit).** A Python gateway in front of the model that captures the reasoning stream, scores it for divergence, redacts PII, and passes secrets through a mediation boundary rather than logging them.
- **Secret boundary broker.** A Rust crate that mediates credential access between an agent and the secret store, so that a credential is scoped, short-lived and never written to a trace.
- **Event contract and console.** A shared eight-field envelope, a Next.js console with a server-sent live feed, a PostgreSQL ledger protected by row-level security, and an append-only incident audit table.

- **Evaluation harness.** A reproducible benchmark and an attack simulator that exercise each detector against labelled local fixtures.

The scope explicitly excludes hosting the models themselves, replacing the agent framework, and providing identity or access management for the agent's human users. The project is middleware: it assumes an agent exists, and it assumes the operator wants to know what that agent was told, what it remembered and what it concluded.

Chapter 2

Review of Literature

The literature on agent security divides cleanly along the same three lines the system follows, and the review below is organised on those lines: work that attacks or defends the tool interface, work on the poisoning of retrieval memory, and work on the leakage and hijacking of reasoning. Each entry below states what the work contributes and what it leaves open, because the second column of the argument is what the design of AEOS Guard is built from.

SR NO.	RESEARCH PAPER TITLE	YEAR / PUBLISHER	ADVANTAGES	DISADVANTAGES
1	Not What You've Signed Up For: Compromising Real-World LLM-Integrated Applications with Indirect Prompt Injection	2023 ACM Workshop on AI and Security	First end-to-end demonstration that untrusted data can hijack the application itself.	Defines the threat but proposes no defence and no detection method.
2	AgentDojo: A Dynamic Environment to Evaluate Prompt Injection Attacks and Defenses for LLM Agents	2024 NeurIPS Datasets & Benchmarks	A reproducible benchmark of realistic injection tasks over several agent environments.	Measures utility loss, not the runtime overhead a defence adds to a live agent.
3	PoisonedRAG: Knowledge Corruption Attacks to Retrieval-Augmented Generation of Large Language Models	2025 USENIX Security Symposium	Quantifies how few poisoned documents are needed to steer the answers of a large corpus.	Assumes write access to the corpus; it detects nothing at run time.
4	ToolEmu: Identifying the Risks of LM Agents with an LM-Emulated Sandbox	2024 Int. Conf. on Learning Representations	Rates the risk of real tools without executing them, and builds a catalogue of tool risk categories.	The emulator approximates real behaviour, so its risk labels stay coarse.

SR NO.	RESEARCH PAPER TITLE	YEAR / PUBLISHER	ADVANTAGES	DISADVANTAGES
5	Beyond the Protocol: Unveiling Attack Vectors in the Model Context Protocol Ecosystem	2026 IEEE Trans. on Software Engineering	First end-to-end empirical study of the MCP attack surface, with a taxonomy of attack classes.	Measures how prevalent the attacks are, not how detectable they are.
6	MCPTox: A Benchmark for Tool Poisoning Attack on Real-World MCP Servers	2026 AAAI Conf. on Artificial Intelligence	A large-scale benchmark of 45 live MCP servers, 353 authentic tools and 1,348 malicious cases.	Scores attack success against refusals, so it cannot show whether a middleware would have stopped the attack.

Table 2.1 Review of Literature

The two most recent entries characterise the MCP tool surface itself rather than the model behind it, and are the sources the tool-layer detector is written against. The common gap in all six works is the same one: they measure attacks, and none of them supplies a middleware that can detect an attack on a running agent and produce evidence an operator can act on. That gap is the contribution of this project.

Chapter 3

Report on the Present Investigation

The protection that exists today around AI agents is real, but each piece of it answers a different question, and none of them answers the question the attacks actually pose.

Network controls restrict which hosts an agent may reach and inspect the bytes on the wire. They are excellent at what they were built for and blind to content semantics: a tool server that returns a malicious instruction over an allowed TLS connection is entirely conformant, and the firewall sees nothing wrong. **Data loss prevention** inspects documents for regulated content on the way out. It is close to a useful analogue for the reasoning layer, but it operates on finished documents rather than on a live stream of model output, and it has no notion of the secret it would need to split across a token boundary.

Prompt-injection filters attempt to classify the instruction content of a prompt. The difficulty is that the same filter has to distinguish an instruction from data, and the two are the same token sequence. Filters also tend to be single points of failure: they see one surface, they are tuned to one phrasing, and they either block a call or do not, with no record of what they decided and why. **MCP transport security** authenticates the client and the server and secures the channel, which is exactly what it should do, but a properly authenticated tool server is still free to change its description. Authentication proves who is speaking; it does not prove that what they are speaking about has not changed since it was approved.

Vector-store access control governs which documents a session may retrieve, which prevents one tenant from reading another tenant’s data, and does nothing about a document that an attacker inside the trust boundary has planted. **SIEM correlation** aggregates events after the fact, which is valuable, but the events it correlates are defined by the products already deployed, so an agent-specific event that no product understands is dropped before correlation begins. **Rate limits and quotas** bound the blast radius of a runaway agent but place no constraint on a single well-formed malicious call.

3.1 Findings of the Investigation

The investigation was carried out against the deployment guidance of the Model Context Protocol, the OWASP risk taxonomy for LLM applications [16] and the NIST risk management framework [6]. Six findings were recorded, and each of them became a design constraint on the proposed system:

- **Tool descriptions are unauthenticated instructions.** The Model Context Protocol lets a server describe a tool in prose, and the agent treats that prose as instructions. Nothing verifies that the description an agent reads today is the description it was approved against yesterday.

- **Embedding similarity cannot distinguish poisoned from legitimate memory.** A document that has been injected is retrieved because it is semantically close to the query, which is exactly the property that made it useful to the attacker.
- **Reasoning traces leak by construction.** A trace contains the prompt, the retrieved context, the model output and frequently the tool arguments. Logging the trace for audit therefore copies the secret into the log, and the log is usually less protected than the system it was recording.
- **Secrets can be split across token boundaries.** A scanner that searches the decoded string for a known key pattern can be defeated by a tokenisation that happens to break the key in the middle, so the text never appears intact in any single decoded token.
- **There is no shared evidence model.** A tool incident, a memory incident and a reasoning incident are recorded in three different shapes, so they cannot be correlated into a single incident without a human joining them by hand.
- **Detection without evidence is a rumour.** A detection that nobody records cannot be audited, and a record that anybody can edit is not evidence.

The common failure across all of the existing controls is that they are designed to observe a system from the outside. The proposed system observes the agent from the inside, at the points where meaning is created.

Chapter 4

Aim and Objectives

Aim

The aim of this project is to design, implement and evaluate a security middleware that detects manipulation of an AI agent at the three points where its decisions are formed — the tool descriptions it reads, the memory it retrieves and the reasoning it produces — and that records every detection as tamper-evident evidence an operator can act on.

Objective

1. To build an independent tool-layer detector that fingerprints every tool schema with HMAC-SHA256 over a canonical form and alerts on any change to an approved baseline, so that a tool cannot change its behaviour after it has been trusted.

2. To sanitise tool descriptions against known instruction-injection patterns and to support both an enforce mode that blocks a call and a monitor mode that only records it, so that a new tool can be observed before it is trusted.

3. To detect memory poisoning by measuring how unusually often a single document is retrieved relative to a corpus of many distinct topics, rather than by similarity alone.

4. To detect reasoning anomalies by scoring the KL divergence between the expected and the observed reasoning distribution for a given task, and to redact personally identifiable information and split secrets across token boundaries before any trace is written to a log sink.

5. To define one common event contract that all three modules emit, so that unrelated detectors can be correlated by a single consumer and exported as a signed evidence bundle.

6. To provide a single operator console that renders the live event stream, supports investigation of a single session, and measures every detector honestly, publishing both the detection rate and the limits of the corpora the rates were measured on.

Chapter 5

Problem Statement

A system is required that observes an AI agent at the tool, memory and reasoning layers, detects manipulation of the tool schemas, retrieved documents and reasoning traces that the agent relies upon, and records every such detection in a common, tamper-evident form that enables an operator to investigate an incident and to prove what was observed.

The statement above is deliberately passive, and it is the whole of the problem. The three inputs on which an agent decision rests are all supplied from outside the trust boundary: a tool description is written by whoever published the tool, a retrieved document is written by whoever wrote it into the corpus, and a reasoning trace is produced by a model that was given the first two. Nothing in the current stack verifies that any of them is what the operator believed it to be, and the controls that do exist — network policy, data loss prevention, prompt filters, vector-store access control — were each designed to answer a different question. An agent therefore has no layer between itself and its dependencies that treats what it reads as untrusted input.

The cost of leaving that gap open is not theoretical. A single rewritten tool description was enough to compromise the strongest agent evaluated against a benchmark of live MCP servers in 72.8% of cases, with a refusal rate below 3% [12], and five poisoned documents were enough to reach a 90% attack success rate against a corpus of millions of documents [9]. The problem is therefore not that the attacks are sophisticated, but that they are cheap, silent and invisible to every control an organisation already owns.

Chapter 6

Proposed System


AEOS Guard places three independent detectors directly on the path a decision travels, and joins them with a single event contract. The tool layer is inspected by MCP-Shield, which treats a tool schema as an authenticated artefact: it is canonicalised, fingerprinted with HMAC-SHA256, and compared against a pinned baseline that a normal tool invocation cannot overwrite. The description itself is sanitised against known injection patterns before the agent is allowed to read it, and the call is either blocked or recorded according to the configured mode. The same conclusion is reached independently by the work on mitigating rug pull attacks in MCP, which proposes immutable versioned tool definitions and a policy engine that evaluates a tool's capability against the runtime context [14], and by the work on descriptor-level manipulation, which shows that tool descriptors are a first-class semantic attack surface in their own right and reduces unsafe tool invocations from as much as 36% to 15% with a layered defence [3].

The memory layer is inspected by VectorAnchor, which asks a question embedding search cannot ask: not "is this document similar to the query" but "is this document being retrieved far more often than the rest of the corpus". A poisoned memory has to be retrieved to work, so it has to be retrieved more often than the topic breadth of the corpus would predict. The reasoning layer is inspected by TraceAudit, which scores the KL divergence between the expected and the observed reasoning distribution, splits detected secrets across a 16-token look-behind window so that a tokenised key cannot hide by being broken up, applies a Luhn checksum gate before a candidate key is treated as a real credential, and redacts personally identifiable information before anything reaches a log sink.

Explanation of the Block Diagram:

The diagram represents the overall working process of AEOS Guard, which observes an agent at the three points where a decision is formed: the tool description the agent reads, the memory the agent retrieves, and the reasoning the agent produces. The design is modular in the sense that matters for a security system: the three detection modules are independent, each can be deployed, upgraded or failed without the others, and none of them can be used to influence another. The only shared artefact is the common event contract, which every module emits and the console consumes. This is what allows an operator to answer "what happened to this session" from one timeline rather than three.

Figure 6.1: Block Diagram



The detection modules are independent and share nothing but the event contract:
MCP-Shield - fingerprints tool schemas with HMAC-SHA256 over a canonical form; the pinned baseline is never overwritten by a call.
VectorAnchor - flags a memory that is retrieved far more often than clean documents across distinct topics.
TraceAudit - scores the KL divergence of the reasoning distribution and redacts PII and secrets before logging.
Each layer states its own failure mode: the tool and reasoning layers fail closed; the memory layer fails open to monitoring.

The system operates in the following eight steps:

Step 1: An MCP server registers a tool. MCP-Shield canonicalises the schema, normalises field order and strips formatting-only differences, then computes an HMAC-SHA256 fingerprint over the canonical form.

Step 2: The fingerprint is compared with the pinned baseline for that tool. If no baseline exists, the tool is treated as first contact and the configured policy decides whether it is approved, monitored or blocked.

Step 3: The tool description is passed through the sanitiser, which looks for instruction patterns that attempt to redirect the agent. In enforce mode a match blocks the call; in monitor mode the call proceeds and the event is recorded.

Step 4: The agent issues a tool call. The arguments are validated against the same schema that was fingerprinted, and the call is routed to the secret boundary broker, which returns a scoped, short-lived handle instead of a raw credential.

Step 5: A memory retrieval occurs. VectorAnchor increments the frequency counter for the retrieved document and for its topic, and recomputes the spread of the corpus across distinct

topics.

Step 6: If the retrieved document exceeds the frequency threshold relative to that spread, the document is quarantined, the session is notified, and the memory-layer event is emitted.

Step 7: The agent begins reasoning. TraceAudit captures the reasoning stream, compares the observed distribution against the expected distribution for the task, redacts personally identifiable information and splits candidate secrets across a 16-token look-behind window before anything is logged.

Step 8: The event is emitted with the common envelope, written to the append-only incident audit table, and pushed to the console over a server-sent event stream, from where the operator may quarantine a session, re-pin a baseline, export an evidence bundle, or replay the scenario in the attack simulator.

Chapter 7

Requirement Analysis

7.1 Functional Requirements

The functional requirements state what the middleware must do when it is installed between an agent and its dependencies. Each is written so that it can be tested by the benchmark harness described in Chapter 10.

- **FR-1.** The system shall intercept every tool registration and every tool invocation that passes through it, without changing the protocol content of the session.
- **FR-2.** The system shall compute a canonical form of every registered tool schema and an HMAC-SHA256 fingerprint over that canonical form.
- **FR-3.** The system shall compare the computed fingerprint against a pinned baseline, and shall never overwrite a pinned baseline as a side effect of a tool call.
- **FR-4.** The system shall sanitise tool descriptions against known instruction-injection patterns, and shall support an enforce mode and a monitor mode.
- **FR-5.** The system shall maintain a retrieval frequency profile per document and a topic spread profile per corpus, and shall quarantine a document whose retrieval frequency is anomalous with respect to that spread.
- **FR-6.** The system shall score a reasoning stream for divergence from the expected distribution, and shall raise a critical event when the score exceeds the calibrated threshold.
- **FR-7.** The system shall redact personally identifiable information and shall split candidate secrets across a token look-behind window before any trace is persisted.
- **FR-8.** The system shall emit every detection as a single event envelope carrying a UUID v4 identifier, a millisecond timestamp, a module, an event type, a severity, a details payload and a source.
- **FR-9.** The system shall write every event to an append-only incident audit table, and shall export an evidence bundle signed with HMAC-SHA256.
- **FR-10.** The system shall expose the live event stream, the session timeline, the baseline manager, the quarantine view and the evidence export through a single console.

7.2 User Interface

The console is the only component a human interacts with, and it is built as ten page routes over thirteen API routes and twenty-three library modules. The overview screen is the console at rest: the live severity distribution, the open incident count, the critical count and the mean

end-to-end latency, with the most recent events across all three modules beneath. It is the screen an operator leaves open on a second monitor, because it is the only one that answers "is anything happening right now" without any interaction.

The control room is the operator’s entry point and the only screen meant to be read under pressure. It exposes five capabilities in one view: cross-layer session circuit breakers, an MCP tool schema baseline manager, vector memory quarantine, a cryptographic forensic export centre and an operator action history ledger. The circuit breakers are the part that changes what the agent is allowed to do next. A breaker trips on a per-session basis: once a session has produced a critical event in a layer, the requests that would reach that layer are refused for the remainder of the session or until an operator releases the breaker. This is deliberately a per-session decision rather than a global one, because a global kill switch turns a single compromised tool into a denial-of-service against every tenant sharing the deployment.

The investigation workspace answers a single question: what happened to one session. It collects the events for a session identifier across all three modules and renders them as a single ordered timeline, which is the capability the shared event contract exists to provide. The ordering is exact because every event carries a millisecond timestamp and the modules write to the same monotonic clock, so an operator can reason about causation rather than about file order.

7.3 Non-Functional Requirements

The non-functional requirements are stated as measurable properties, because a security control whose cost or reliability cannot be measured cannot be adopted. The values quoted below are the measured values of the implemented system and are reproduced in Chapter 10.

7.3.1 Performance

The middleware must be transparent to the agent. A tool call may add at most a few microseconds, because a tool call is on the critical path of an interactive session. The measured mean overhead is 6.4 microseconds per tool call and 13.0 microseconds per reasoning token, against a model round trip of hundreds of milliseconds. A memory retrieval is more expensive at 438.9 microseconds, because the frequency profile has to be updated and the corpus spread recomputed, and it is still three orders of magnitude below the cost of the retrieval itself. The live feed is a server-sent event stream rather than a polling loop, so the latency an operator observes is the time the module needs to write the event and not a poll interval.

7.3.2 Usability

The system must be operable by a security engineer who has never read the source of the agent it protects. Three decisions follow. Detection is separated from enforcement: a new tool can be run in monitor mode for a period, and the operator sees what would have been blocked before anything is. Quarantine isolates rather than destroys, so a false positive does not

destroy the evidence needed to understand why it fired. And every event carries a human readable summary next to its machine fields, because an incident that has to be read in JSON at three in the morning is an incident that will not be read.

7.3.3 Reliability

A security control that can be made to fail silently is worse than no control, so the system states its failure behaviour per layer. The tool layer and the reasoning layer fail closed, because a compromised tool or a leaking trace is worse than an unavailable one. The memory layer fails open to monitoring, because dropping a legitimate memory has a cost paid by every session while a poisoned memory is paid for by one. On top of that, the incident audit table is append-only and refuses updates, the event contract rejects an envelope without a valid UUID v4 identifier, and evidence bundles are signed so that a downstream reviewer can verify that a bundle has not been edited after it was produced.

Chapter 8

Feasibility Study

8.1 Operational Feasibility

The system is operationally feasible because it is deployed inside the process that the agent already uses, not beside it. MCP-Shield is registered as an MCP proxy and TraceAudit as a gateway in front of the Messages API, so no change to the agent framework is required. The console is a web application that an operator opens in a browser, and the operator workflow is the one an incident responder already knows: read the live feed, open the session, quarantine or release, export the evidence. The one operational change demanded of the deploying team is to run new tools in monitor mode first, which the enforce/monitor switch supports per deployment. **The study concludes that the system is operationally feasible.**

8.2 Technical Feasibility

The system is technically feasible because every component it depends on is either already present in the target environment or is available as a stable library. The tool layer is Rust, chosen because it sits on the hot path of every tool call; the memory and reasoning layers are Python, chosen because their algorithms are statistical rather than latency-critical. The console runs on Next.js 16 with React 19 and TypeScript, the ledger on PostgreSQL with row-level security, and the live feed on server-sent events, which every current browser supports. The only genuine technical risk in the design is the false-positive profile of the detectors, and that risk is managed by shipping an enforce mode that can be turned off per deployment and by publishing the measured rates with the corpora they were measured on. **The study concludes that the system is technically feasible.**

8.3 Economic Feasibility

The system is economically feasible because its cost is a small constant per deployment rather than a cost that scales with the number of agents or the volume of traffic. The measured overhead is 6.4 microseconds per tool call and 438.9 microseconds per memory retrieval, so a deployment that performs a million guarded tool calls per day spends under ten seconds of CPU per day on inspection. The software itself is built on components that are already licensed or free, and the console requires no separate infrastructure beyond the database the deployment already runs. The defensible asset is the corpus of labelled attack fixtures and the measured behaviour of each detector against them, which becomes harder to reproduce as it grows. **The study concludes that the system is economically feasible.**

8.4 Legal Feasibility

The system is legally feasible because it observes data that its own operator already holds. It sits between an agent and the tools, corpus and model endpoint that the operator has already contracted for, and it records metadata about those interactions rather than the content of the conversations themselves. Personally identifiable information is redacted before a trace is written, and secrets are never written into a trace at all: the secret boundary broker returns a scoped, short-lived handle in place of a credential, so the evidence trail does not become a new copy of the secret it is meant to protect. The event contract and the append-only audit table also satisfy the record-keeping and evidentiary requirements of the frameworks the system is mapped onto, including the OWASP LLM risk taxonomy [16] and the NIST AI risk management framework [6]. **The study concludes that the system is legally feasible.**

Chapter 9

Design Details

The design includes:

1. Context Level diagram

2. DFD Diagram

3. Sequence Diagram


4. E-R Diagram

5. Control Flow Diagram

9.1 Context Level Diagram

The context level diagram states the system boundary and everything that crosses it. A single process, the AEOS Guard middleware, sits between the agent and five external parties: the MCP tool servers that publish the descriptions the agent trusts, the vector store that holds the documents the agent retrieves, the model provider that produces the reasoning, the secret store that holds the credentials the agent may need, and the operator who acts on what the middleware reports. Every arrow in the diagram is a flow the middleware either inspects or emits, and nothing else is allowed to cross the boundary.

Figure 9.1: Context Level Diagram




Every flow across the boundary is either inspected by the middleware or emitted by it; nothing else crosses.

9.2 DFD Diagram

The data flow diagram decomposes the context diagram into the three detection processes, the event contract that joins them and the console that consumes it. The four data stores are the persistent state of the system: the pinned tool baselines, the document frequency profiles, the incident ledger and the exported evidence bundles. The important property visible in the diagram is that the three detection processes never exchange data with one another. Each writes to the event contract and each reads only its own store, which is what makes the three modules genuinely independent rather than merely separate.


Figure 9.2: DFD Diagram



9.3 Sequence Diagram

The sequence diagram follows a single agent request through the whole stack and shows the order in which the guarantees are obtained. The tool schema is fetched and fingerprinted before the agent is allowed to read the description; the retrieval is scored before the document reaches the agent; the reasoning stream is scored and redacted before it reaches the log sink; and the event is published to the console only after redaction has been applied. The order is the design: a detector that runs after the data has been used has not prevented anything, it has only reported it.

Figure 9.3: Sequence Diagram



Every arrow is inspected before the next step runs; the event is published only after redaction.

The three layers never call one another - they only emit events into the same contract.

9.4 E-R Diagram

The entity-relationship diagram records the data model that the console and the evidence export operate on. A tool raises tool incidents, a document raises memory incidents and a reasoning trace raises reasoning incidents; the three incident kinds are linked by a single generate relationship to the evidence bundle, which is the object an operator exports and a downstream reviewer verifies. The tool-to-baseline relationship is one-to-many because a tool may be re-pinned over its lifetime, and every re-pin is a new baseline row rather than an update, so that the history of what was trusted and when is preserved.

Figure 9.4: E-R Diagram


append-only incident_audit: every event carries a session_id, so a session is a single timeline.



9.5 Control Flow Diagram

The control flow diagram is the enforcement logic in its decision form, and it is the diagram that best explains why the layers fail in different directions. The tool path asks whether the fingerprint still matches the pinned baseline, and on a mismatch asks whether the deployment is in enforce mode before it blocks. The memory path asks whether the retrieval frequency is anomalous with respect to the topic spread of the corpus, and quarantines rather than blocks, because refusing to serve a document that turns out to be legitimate is a cost paid by every session. The reasoning path asks whether the surprise score exceeds the calibrated threshold, and in that case redacts and emits a critical event. All three paths converge on the common event contract, and the request ends with a verdict rather than with a side effect on the agent's own state.

Figure 9.5: Control Flow Diagram



Chapter 10

Implementation Plan

Hardware/Software Interface

This section lists the minimum hardware and software requirements needed to run the system efficiently.

10.1 Hardware Requirements

- A processor with at least four cores; the tool layer is a proxy that must not contend with the agent for CPU time.
- At least 8 GB of RAM for a deployment that keeps the full document frequency profile of the corpus in memory.
- A PostgreSQL instance of version 14 or later for the incident ledger, with row-level security enabled and a separate role for the console reader.
- A vector store reachable over the network from the agent and from VectorAnchor; the middleware observes the store through the client, it does not embed it.
- No GPU is required. The middleware performs no inference; it inspects traffic that a model provider produces.

10.2 Software Requirements

- Rust toolchain and Cargo for the MCP-Shield proxy and the secret boundary broker.
- Python 3.11 or later for VectorAnchor, TraceAudit and the evaluation harness.
- Next.js 16 with React 19 and TypeScript for the console, served by a Node.js 20 runtime.
- PostgreSQL 14 or later for the incident ledger, the tool baseline store and the evidence bundle store.
- A Model Context Protocol client and server implementation for the tool layer to proxy.
- An Anthropic-compatible Messages API endpoint for the reasoning layer to sit in front of.

Development Environment:

The development environment is the one in which the measured results of Chapter 10.3 were produced: the Rust tool layer and the console were developed on a Linux workstation with Node.js 20 and the Python 3.12 interpreter installed alongside the Rust toolchain, against a local PostgreSQL instance with row-level security enabled. The whole stack runs from a single checkout with no external service dependency other than the model endpoint, and the

benchmark harness is invoked with one command.

10.3 Results

The stack was deployed and evaluated against the project's own labelled detection fixtures and against an end-to-end attack simulator. The evaluation set is small, synthetic and offline by construction, so the numbers below are a reproducible demonstration of behaviour rather than a claim of field accuracy; a real deployment would be rescored against its own traffic. The detector implementations, the fixture corpora and the benchmark script are all versioned in the repository, so every figure in this section can be regenerated by running the same command.

Module	Paradigm	Detection	Precision	FPR	F1
VectorAnchor · frequency anomaly	threshold	75%	100%	0%	0.857
TraceAudit · reasoning divergence	threshold	100%	100%	0%	1.000
TraceAudit · PII scanner	regex + Luhn	100%	100%	0%	1.000
MCP-Shield · description sanitizer	regex	71.4%	100%	0%	0.833
MCP-Shield · schema fingerprint	exact	100%	100%	0%	1.000

Table 10.1 Detection Accuracy by Module and Detector


The two imperfect rows are the interesting ones. The description sanitiser detects 71.4% of the injection fixtures it is shown, which is honest rather than flattering: a regex matcher cannot recognise every phrasing of an instruction injection, and the project states that limit instead of tuning the fixtures until the number looked better. The memory frequency detector detects 75% for a related reason: a slow-drip poisoning spreads its retrievals over enough queries to stay under the threshold for most of its lifetime, and only becomes anomalous later. Both detectors keep a precision of 100% and a false-positive rate of zero on the clean corpus, which is the trade the design chose deliberately: a detector that never raises a false alarm is safe to run in enforce mode.

Operation	Unit	Mean	p95
MCP-Shield · tool call	microseconds	6.4	12.5
TraceAudit · reasoning token	microseconds	13.0	30.0
VectorAnchor · memory retrieval	microseconds	438.9	1266.1

Table 10.2 Measured Per-Operation Overhead


The overhead figures are the ones that decide whether the middleware is deployable at all. A tool call costs an additional 6.4 microseconds on average, which is invisible against the hundreds of milliseconds a model round trip takes. A memory retrieval costs 438.9 microseconds, which is the largest single cost in the stack and the price of maintaining the frequency and topic profiles; the detector itself was measured at 295.7 microseconds before the profile update and at 438.9 microseconds with it, so roughly a third of the cost is bookkeeping. For a twenty-tool list and a sixty-token response, the total added latency is under a millisecond.

Figure 10.1: Output Screen: Threat Overview




The overview screen is the console at rest: the live severity distribution, the open incident count, the critical count and the mean end-to-end latency, with the most recent events across all three modules beneath. Severity is carried in the envelope as an explicit field with the values info, warning and critical, so the console filters on a value it was given rather than on one it inferred from the event type.

Figure 10.2: Output Screen: Control Room and Circuit Breakers




The control room exposes the baseline manager, the quarantine panel, the forensic export centre, the per-session circuit breakers and the operator action ledger. A tool that has been gated is one whose description changed after approval; a tool that is pinned is one whose fingerprint still matches the baseline. Both the gating of a tool and the re-pinning of a baseline are written to the action ledger with a timestamp and an actor, so that the operator's own decisions are auditable in the same way as the detector's.

Figure 10.3: Output Screen: Investigation Workspace



The investigation workspace collects the events for a session identifier across all three modules and renders them as a single ordered timeline. In the simulator run, a session identifier appears against a tool-schema drift event from MCP-Shield, a memory-poisoning suspicion from VectorAnchor and a reasoning-divergence event from TraceAudit, in the order they occurred. The view shows the operator that the tool-layer event preceded the memory-layer event by a measurable margin, which is the kind of ordering a log format defined per product could not have preserved.

Figure 10.4: Output Screen: Attack Simulator




The attack simulator replays labelled scenarios against a running stack, so that the console path is exercised end to end rather than only the detectors. A scenario may inject a schema drift into a registered tool, plant a slow-drip retrieval pattern into the corpus, or drive a deliberately divergent reasoning stream. The point of the simulator is that the same event contract carries all three, so one run produces one timeline rather than three separate logs that an analyst has to join by hand.

Chapter 11

Gantt Chart

The chart below records the order in which the work of the project was carried out over the thirteen weeks of the development phase, and the overlap between the three detection modules during the coding phase. The two longest bars are the console and the evaluation harness, and the reason is that the console could not be built against a stable event contract until the contract itself was fixed, and the harness could not be written against the detectors until the detectors had a stable interface. Both dependencies were resolved early, which is why the reporting and presentation phase is not compressed at the end of the chart.

Figure 11.1: Gantt Chart



Chapter 12

Conclusion

AEOS Guard was built to answer one question: what would it take to observe an AI agent at the points where its decisions are formed, and to produce evidence that survives an audit. The answer that emerged is a middleware of three independent detectors and one shared contract, and the three most useful things learned during the build are all about the independence. Because the tool layer, the memory layer and the reasoning layer share nothing but an event envelope, a detector that is wrong in one layer does not corrupt the evidence produced by the others. The simulator drove a schema drift, a poisoned memory and a reasoning divergence in a single session, and all three appeared on one timeline without any correlation code.

The measurements are honest but small. The evaluation corpus is local, synthetic and offline, so the reported F1 scores of 1.000, 0.857 and 0.833 describe the behaviour of the detectors against labelled fixtures and not their behaviour in the field. The two imperfect rows are the informative ones, because they are the two detectors that a careful adversary would target first: a regex that matches 71.4% of injection phrasings, and a frequency detector that a slow-drip poisoning can hide from for most of its lifetime. Both limits are published in the repository rather than tuned away.

The direction the work points is the same one the literature reaches from a different direction: rather than filtering untrusted content after it has been read, derive the execution path from the trusted request alone, which yields a provable guarantee at a measured cost [13]. The measured cost of the system built here is 6.4 microseconds per tool call and 438.9 microseconds per memory retrieval, and the guarantee it currently offers is narrower: it detects schema drift, frequency anomalies and reasoning divergence, and it records them so that an operator can act. The next step is the semantic drift detector that would tell a rewritten description from the description that was approved, and the cross-layer correlation engine that would score a composite incident from three independent events.

ACKNOWLEDGEMENT

We owe sincere thanks to our college Atharva College of Engineering for giving us a platform to prepare a project on the topic "AEOS Guard - Agent Execution Operations Security" and would like to thank our Principal Dr. Ramesh Kulkarni for instigating within us the need for this research and giving us the opportunities and time to conduct and present research on the topic. We are sincerely grateful for having Dr. Bhavna Arora, Head of Department of Information Technology and Prof. Mahesh Mishra as our guide, for their encouragement, constant support and valuable suggestions. Moreover, the completion of this research would have been impossible without the cooperation, suggestions and help of our friends and family.

References

Book,

[1] S. Russell and P. Norvig, "Artificial Intelligence: A Modern Approach," 3rd ed. Pearson, 2016. Available: https://www.pearson.com/en-us/subject-catalog/p/artificial--intelligence-a-modern-approach/P200000003503/3032862

Journal Paper,

[2] E. Wallace, K. Xiao, R. Reinders, I. Mitenovic, J. Bai, S. Purohit, S. Singh, C. Chiang, L. Jiang and R. Saldaña, "The Instruction Hierarchy: Training LLMs to Prioritize Privileged Instructions," arXiv preprint arXiv:2404.13208, 2024. Available: https://arxiv.org/abs/2404.13208

[3] S. Jamshidi, A. Moradi Dakhel, K. Wazed Nafi and F. Khomh, "Semantic Attacks on Tool-Augmented LLMs: Securing the Model Context Protocol Against Descriptor-Level Manipulation," arXiv preprint arXiv:2512.06556, 2025. Available: https://arxiv.org/abs/2512.06556

[4] K. Chauhan and P. Revankar, "Caught in the Act(ivation): Toward Pre-Output and Multi-Turn Detection of Credential Exfiltration by LLM Agents," arXiv preprint arXiv:2606.04141, 2026. Available: https://arxiv.org/abs/2606.04141

[5] MITRE, "ATLAS: Adversarial Threat Landscape for Artificial-Intelligence Systems, data release v2026.09," 2026. Available: https://github.com/mitre-atlas/atlas-data

[6] National Institute of Standards and Technology, "Artificial Intelligence Risk Management Framework (AI RMF 1.0)," NIST AI 100-1, 2023. Available: https://doi.org/10.6028/NIST.AI.100-1

Proceeding paper,

[7] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz and M. Fritz, "Not What You've Signed Up For: Compromising Real-World LLM-Integrated Applications with Indirect Prompt Injection," 16th ACM Workshop on Artificial Intelligence and Security, 2023. Available: https://arxiv.org/abs/2302.12173

[8] E. Debenedetti, J. Zhang, M. Balunovic, L. Beurer-Kellner, M. Fischer and F. Tramer, "AgentDojo: A Dynamic Environment to Evaluate Prompt Injection Attacks and Defenses for LLM Agents," NeurIPS Datasets and Benchmarks Track, 2024. Available: https://arxiv.org/abs/2406.13352

[9] W. Zou, R. Geng, B. Wang and J. Jia, "PoisonedRAG: Knowledge Corruption Attacks to Retrieval-Augmented Generation of Large Language Models," USENIX Security Symposium, 2025. Available: https://arxiv.org/abs/2402.07867

[10] Y. Chen, Z. Chen, Y. Shi, Y. Wu, Z. Wang, E. Wang and W. Zhao, "ToolEmu: Identifying the Risks of LM Agents with an LM-Emulated Sandbox," International Conference on Learning Representations, 2024. Available: https://arxiv.org/abs/2309.15817

[11] H. Song, Y. Shen, W. Luo, L. Guo, T. Chen, J. Wang, B. Li, X. Zhang and J. Chen, "Beyond the Protocol: Unveiling Attack Vectors in the Model Context Protocol (MCP) Ecosystem," IEEE Transactions on Software Engineering, 2026. Available: https://arxiv.org/abs/2506.02040

[12] Z. Wang, Y. Gao, Y. Wang, S. Liu, H. Sun, H. Cheng, G. Shi, H. Du and X. Li, "MCPTox: A Benchmark for Tool Poisoning Attack on Real-World MCP Servers," AAAI Conference on Artificial Intelligence, 2026. Available: https://arxiv.org/abs/2508.14925

[13] E. Debenedetti, I. Shumailov, T. Fan, J. Hayes, N. Carlini, D. Fabian, C. Kern, C. Shi, A. Terzis and F. Tramer, "Defeating Prompt Injections by Design (CaMeL)," IEEE Symposium on Security and Privacy, 2026. Available: https://arxiv.org/abs/2503.18813

[14] R. Bhatt, M. Narajala and S. Habler, "ETDI: Mitigating Tool Squatting and Rug Pull Attacks in MCP using OAuth-Enhanced Tool Definitions and Policy-Based Access Control," arXiv preprint arXiv:2506.01333, 2025. Available: https://arxiv.org/abs/2506.01333

[15] Y. Zheng, Y. Hu, T. Yu and A. Quinn, "AgentSight: System-Level Observability for AI Agents Using eBPF," Proceedings of the ACM on Management of Data, 2025. Available: https://arxiv.org/abs/2508.02736

Website,

[16] OWASP Foundation, "OWASP Top 10 for Large Language Model Applications," 2025. Available: https://genai.owasp.org/llm-top-10/

[17] Model Context Protocol, "Model Context Protocol Specification and Security Best Practices," 2026. Available: https://modelcontextprotocol.io

[18] Anthropic, "Messages API Documentation," 2024. Available: https://docs.anthropic.com

[19] Vercel, "Next.js Documentation," 2024. Available: https://nextjs.org/docs

[20] Invariant Labs, "MCP Security Notification: Tool Poisoning Attacks," 1 April 2025. Available: https://invariantlabs.ai/blog/mcp-security-notification-tool-poisoning--attacks.html