NullWire: A Blockchain-Coordinated Mixnet Protocol for Decentralized Anonymous Communication

[Author names withheld for review]

`[contact redacted]`

March 2026 — Submission Draft

Abstract

We present NullWire, a decentralized anonymous communication protocol that combines a stratified mix network with a Solana blockchain control plane for node coordination and incentive distribution. The system implements a Loopix-style architecture with Poisson-distributed mixing delays and continuous cover traffic, employs a hybrid post-quantum encryption scheme combining ML-KEM-1024 with X25519 in the Sphinx packet format, and uses Groth16 zero-knowledge proofs to prevent spam without requiring user registration or identity revelation. Message payloads remain off-chain; the blockchain serves exclusively as a tamper-resistant, decentralized control plane for node registry, staking, and reward distribution. We formalize the threat model, define security properties with respect to specific adversary classes and assumptions, and analyze the protocol's anonymity guarantees. Under Assumptions 1–7, NullWire provides sender and receiver anonymity against local passive adversaries for anonymity sets bounded by the concurrent cover-traffic-active client population, relationship unobservability under all three operating modes (Ghost, Shadow, Mist), forward secrecy via the Double Ratchet protocol, and resistance to harvest-now-decrypt-later attacks through hybrid post-quantum encryption. The protocol provides no protection against endpoint compromise, long-term intersection attacks on small anonymity sets, extended Solana network outages, or targeted legal compulsion. Empirical evaluation is deferred to prototype implementation; this work establishes the theoretical foundation and protocol specification.

Keywords: anonymous communication, mix networks, blockchain, post-quantum cryptography, traffic analysis resistance, zero-knowledge proofs, privacy protocols

Contents

1 Introduction **3**

2 Background and Preliminaries **4**

2.1 Mix Networks 4

2.2 The Loopix Architecture 5

2.3 Sphinx Packet Format 5

2.4 Post-Quantum Cryptographic Primitives 5

2.5 Zero-Knowledge Proofs 5

2.6 Solana Blockchain Infrastructure 6

3 System Architecture **6**
3.1 Design Goals . . . 6
3.2 Blockchain Selection Rationale . . . 6
3.3 System Components . . . 7
3.4 Data Flow and Architectural Distinction . . . 7

4 Threat Model **7**
4.1 Adversary Classes and Capabilities . . . 7
4.2 Threat Scope: Defended Against . . . 8
4.3 Threat Scope: Not Defended Against . . . 9

5 Security Goals and Assumptions **9**
5.1 Formal Security Properties . . . 9
5.2 Design Assumptions . . . 10

6 Protocol Description **10**
6.1 Node Registration and Staking . . . 10
6.2 Client Initialization . . . 11
6.3 Packet Construction . . . 11
6.4 Mix Node Processing . . . 11
6.5 Cover Traffic Protocol . . . 12
6.6 Operating Modes . . . 12
6.7 Zero-Knowledge Identity and Credential Protocol . . . 12

7 Security Analysis **13**
7.1 Sender and Receiver Anonymity . . . 13
7.2 Traffic Analysis Resistance . . . 13
7.3 Sybil Attack Resistance . . . 14
7.4 Forward Secrecy and Compromise Resilience . . . 14
7.5 Quantum Resistance . . . 14
7.6 Zero-Knowledge Credential Soundness . . . 14

8 Theoretical Performance Analysis **14**
8.1 Latency Analysis . . . 14
8.2 Bandwidth Overhead . . . 15
8.3 Node Economics: Calibration Framework . . . 15

9 Related Work **15**
9.1 Mix Networks and Anonymity Primitives . . . 15
9.2 Onion Routing Systems . . . 15
9.3 Blockchain-Incentivized Relay Networks . . . 16
9.4 Blockchain-Native Communication . . . 16
9.5 Anonymous Credentials and Zero-Knowledge Proofs . . . 16
9.6 Post-Quantum Mix Networks . . . 16
9.7 Comparative Analysis Table . . . 16

10 Limitations and Future Work **17**

11 Conclusion **18**

1 Introduction

Protecting communication metadata—the identities and relationships between communicators, message timing, and communication frequency—remains a fundamental challenge in privacy-preserving systems. Even when message contents are encrypted, traffic analysis on metadata can reveal sensitive information about user behavior and social networks [13, 17]. The landscape of deployed anonymous communication systems exhibits structural tradeoffs that limit their effectiveness against sophisticated adversaries.

State of existing systems. Tor [12] employs three-hop onion routing through volunteer-operated relays with decentralized directory authority architecture. However, Tor is vulnerable to traffic correlation attacks by adversaries observing both path endpoints simultaneously, a capability demonstrated to be practical at scale [16]. Additionally, Tor's volunteer relay model provides no economic incentive for network growth, resulting in persistent capacity constraints and limited geographic diversity.

Signal [20] provides strong end-to-end encryption with forward secrecy but requires telephone number registration and funnels all traffic through operator-controlled servers, exposing metadata to the service provider and legal process.

Session [27] removes telephone number registration and routes traffic through blockchain-incentivized onion relays on the Oxen chain. However, it retains the onion routing architecture inherited from Tor, which provides limited resistance to traffic correlation by global passive adversaries (GPAs).

Nym [11] deploys a Loopix-based mix network with incentivized relay nodes and continuous cover traffic, providing stronger anonymity guarantees than onion routing. However, Nym has not achieved production consumer deployment at the time of writing, limiting practical adoption and network effect benefits.

Structural gaps. Three principal weaknesses characterize this landscape. First, onion routing systems (Tor, Session) remain vulnerable to traffic correlation attacks by GPAs despite decades of security research. Second, coordination infrastructure in existing systems is either centralized (Signal, Tor directory authorities) or depends on a single blockchain (Session/Oxen). Third, relay network sustainability has been addressed through blockchain incentivization (Session, Nym) but has not been combined with the stronger anonymity properties of mix networks in a production system deployed to real users.

Key observations motivating this work. Recent security research has documented the use of public blockchain accounts as uncensorable command-and-control channels by malicious actors. The GlassWorm supply chain campaign (active November 2025–March 2026) embedded C2 instructions in Solana transaction memo fields, exploiting the immutability, pseudonymity, and censorship resistance of blockchain infrastructure to create a coordination channel that could not be disrupted through domain seizure, provider takedown, or intermediary blocking [2, 4, 25]. This observation suggests that the same properties—decentralized availability, tamper resistance, and censorship immunity—can provide robust coordination layers for legitimate privacy-preserving systems. Additionally, the combination of three technical elements—mix networks for traffic analysis resistance, blockchain-based decentralized coordination for censorship resistance, and economic incentives for relay sustainability—has not been realized in any single production system. We observe further that a blockchain-based control plane can isolate coordination from message routing, such that the blockchain need never see message content, metadata, or user identity.

Contributions. This paper contributes the following:

1. A complete protocol specification for NullWire combining a Loopix-style stratified mix network with a Solana blockchain control plane, where message payloads are routed off-chain and only coordination, staking, and incentive distribution occur on-chain.

2. A hybrid post-quantum encryption construction combining NIST-standardized ML-KEM-1024 with X25519 within the Sphinx packet format, providing security against both classical and quantum adversaries through simultaneous compromise requirements.

3. A Groth16-based zero-knowledge credential scheme enabling anonymous network access control, where clients prove possession of staking credentials without revealing wallet identity or stake amounts, preventing spam without user registration.

4. Three operating modes (Ghost, Shadow, Mist) allowing configurable points on the anonymity-latency tradeoff curve, making the system accessible across different threat model requirements and network maturity phases.

5. A formal threat model, explicit security goals, and a complete and honest account of protocol limitations including cold-start anonymity set challenges, long-term intersection attack vulnerability, Solana availability dependency, and empirical validation gaps.

Relationship to closest prior work. The closest architectural precedent is Nym [11], which also combines Loopix-style mixing with blockchain-based incentives. NullWire differs from Nym in four specific respects: (i) it leverages an existing high-throughput Layer-1 blockchain (Solana) rather than requiring a purpose-built token and consensus layer, reducing coordination infrastructure complexity and cold-start risk; (ii) it integrates NIST-standardized post-quantum encryption (ML-KEM-1024) from protocol inception rather than deferring post-quantum support to a future roadmap; (iii) it introduces Groth16 zero-knowledge credentials for anonymous, registration-free spam prevention, a mechanism absent from Nym's current architecture; and (iv) it provides a formal threat model with explicitly enumerated limitations, including conditions under which the protocol's security guarantees degrade or fail entirely. These differences are individually incremental; their joint realization in a single protocol specification constitutes the primary contribution of this work.

Paper organization. Section 2 reviews background on mix networks, Loopix, Sphinx, post-quantum primitives, and zero-knowledge proofs. Section 3 describes the system architecture and design goals. Section 4 formalizes the threat model and adversary classes. Section 5 defines security properties and design assumptions. Section 6 specifies the protocol in detail. Section 7 analyzes security properties. Section 8 provides theoretical performance analysis. Section 9 surveys related work with comparative analysis. Section 10 identifies limitations and future directions. Section 11 concludes.

2 Background and Preliminaries

2.1 Mix Networks

Mix networks, introduced by Chaum [6], provide sender anonymity by processing messages in batches where each node applies cryptographic transformation, reordering, and delay. An external observer cannot correlate input and output messages based on timing, size, or ordering alone. Pfitzmann and Köhntopp [22] formalized anonymity terminology: sender anonymity requires indistinguishability among senders, receiver anonymity requires indistinguishability among recipients, and relationship unobservability requires inability to determine if two parties communicate at all. Practical deployments including Mixmaster and Mixminion [7] demonstrated

feasibility but revealed the fundamental tension between latency (required for mixing) and bandwidth overhead (required for meaningful anonymity sets).

2.2 The Loopix Architecture

Loopix [23] resolves the latency-anonymity tradeoff through per-packet Poisson-distributed delays and continuous cover traffic. Mix nodes are organized in stratified layers $L_1, L_2, \ldots, L_k$. Each message traverses exactly one node per layer. Upon receiving a message, each node waits for a delay Δ sampled independently from an exponential distribution with rate parameter λ, then forwards the message. The exponential distribution preserves independent mixing at each stage without requiring synchronized batch releases, enabling lower latency than threshold-based mixing.

Clients inject two types of cover traffic. Loop cover traffic routes messages through the mix network back to the originating client, serving to maintain traffic cover and to detect unresponsive nodes. Drop cover traffic is generated by mix nodes themselves to maintain constant outbound traffic rates. The combination ensures that observable traffic patterns approximate constant volume and constant rate, regardless of real message load. We adopt the Loopix model directly.

2.3 Sphinx Packet Format

Sphinx [8] provides a fixed-size packet format for mix networks ensuring that packet size cannot reveal routing information or hop position. Each mix node applies a single cryptographic transformation producing an unlinkable output packet (forward unlinkability property). Sphinx supports single-use reply blocks (SURBs) enabling receiver anonymity. NullWire uses Sphinx with 2,048-byte fixed packet size, fragmenting large messages and padding small ones.

2.4 Post-Quantum Cryptographic Primitives

ML-KEM-1024 (NIST FIPS 203 [18]): A module lattice-based key encapsulation mechanism standardized in August 2024. Security rests on hardness of the Module Learning With Errors problem. The 1024-parameter set targets NIST security level 5 (classical equivalent: AES-256).

ML-DSA-65 (NIST FIPS 204 [19]): A module lattice-based digital signature scheme standardized alongside ML-KEM. Used for node authentication in on-chain registry.

X25519 : Elliptic-curve Diffie-Hellman over Curve25519, employed in hybrid construction with ML-KEM for instantaneous quantum resistance.

XChaCha20-Poly1305 : Authenticated encryption primitive used at the message layer.

The hybrid construction requires an adversary to simultaneously compromise both the post-quantum component (ML-KEM-1024) and the classical component (X25519) to achieve message confidentiality break.

2.5 Zero-Knowledge Proofs

Groth16 zk-SNARKs [14] provide succinct non-interactive proofs with constant proof size ($\sim$200 bytes) and efficient verification. NullWire uses Groth16 for anonymous access control: clients prove possession of valid stake credentials without revealing associated wallet identities. The zero-knowledge property ensures verifiers learn only the truth of the statement (credential validity) without additional information (wallet identity or stake amount).

2.6 Solana Blockchain Infrastructure

Solana [30] is a proof-of-stake blockchain designed for high throughput. It provides approximately 65,000 transactions per second with sub-second finality (approximately 400 ms). State is stored in on-chain accounts indexed by 32-byte public keys. NullWire uses Solana program accounts for node registration, staking records, reward distribution, and zero-knowledge credential verification. No message payloads, metadata, or user identity information is stored on-chain.

3 System Architecture

3.1 Design Goals

NullWire is designed to achieve the following properties, in priority order:

1. **Sender and receiver anonymity**: An adversary observing the network cannot identify senders or recipients with probability significantly exceeding random guessing within the anonymity set.
2. **Relationship unobservability**: An adversary cannot determine whether two specific parties communicate, even with complete network observation.
3. **Traffic analysis resistance**: The system resists statistical traffic analysis including by global passive adversaries, to the extent provided by Loopix mixing under stated assumptions.
4. **Forward secrecy**: Long-term key compromise does not enable decryption of previously recorded ciphertext.
5. **Quantum resistance**: Encryption remains secure against quantum adversaries with sufficiently large quantum computers.
6. **Censorship resistance**: Coordination infrastructure provides higher resistance to seizure, domain blocking, and provider takedown than centralized alternatives, through distribution across a decentralized validator network. This property is bounded by the jurisdictional diversity of the underlying blockchain's validator set (see Section 3.2).
7. **Economic sustainability**: Relay operators receive compensation proportional to contribution, enabling organic network growth.
8. **Spam resistance**: Denial-of-service via message flooding is prevented without requiring user registration or persistent identity.

3.2 Blockchain Selection Rationale

NullWire's control plane requires a blockchain satisfying four constraints simultaneously: (i) transaction throughput sufficient for real-time node registry updates and credential verification under load; (ii) finality latency compatible with interactive session establishment (sub-second); (iii) an existing validator network and developer ecosystem, avoiding the cold-start problem inherent in launching a purpose-built chain; and (iv) programmability sufficient for on-chain zero-knowledge proof verification.

Solana [30] satisfies these constraints: approximately 65,000 transactions per second with approximately 400 ms finality, an established validator set exceeding 1,500 nodes across multiple jurisdictions, and native support for on-chain program execution including elliptic-curve operations required for Groth16 verification. Ethereum provides comparable programmability but incurs higher finality latency (12–15 minutes for economic finality) and higher per-transaction

costs, both problematic for interactive credential verification. Purpose-built chains (as employed by Nym and Session/Oxen) avoid these tradeoffs but introduce bootstrap risk: the coordination layer's security depends on a nascent validator set whose economic security may be insufficient during early deployment.

We acknowledge three limitations of the Solana dependency. First, Solana has experienced documented network outages; NullWire mitigates this through local routing table caching with configurable time-to-live (Section 10). Second, Solana validator concentration in US and EU jurisdictions creates a jurisdictional attack surface; a coordinated legal action targeting validators in a single jurisdiction could degrade network availability. Third, coupling to a single Layer-1 chain introduces platform risk. Phase-2 of the development roadmap includes abstraction of the control plane interface to support multi-chain fallback, but this is not part of the current protocol specification.

3.3 System Components

NullWire comprises four primary components:

Client End-user software that composes and encrypts messages, generates cover traffic, manages zero-knowledge credentials, and communicates with Gateway nodes via WebSocket or QUIC.

Mix Nodes (NullWire Relay) A stratified three-layer network of relay nodes. Each node receives packets, applies an exponentially distributed delay, shuffles batches, decrypts one Sphinx header layer, and forwards batches. Mix nodes inject drop cover traffic between real batches to maintain constant traffic rates.

Gateway Nodes Entry and exit points to the mix network. Gateways accept client connections, present zero-knowledge credentials for on-chain verification, maintain per-user encrypted mailboxes for offline recipients, and provide the interface between client network and mixnet.

Solana Control Plane (NullWire Mesh) Solana smart contracts managing node registration, staking and slashing, reward distribution, zero-knowledge credential issuance and verification, and on-chain governance. The control plane never handles message payloads.

3.4 Data Flow and Architectural Distinction

Client messages are encrypted in Sphinx format, submitted to a Gateway node following zero-knowledge credential verification, routed through three layers of mix nodes, and delivered to the recipient's Gateway mailbox. The recipient retrieves and decrypts messages upon reconnection.

NullWire is fundamentally distinct from blockchain-native messaging systems (XMTP, Status, Waku) that link communication identity to wallet addresses and store identity-linked metadata on-chain. NullWire uses the blockchain exclusively for coordination. No message content, metadata, or user identity is ever recorded on-chain, maintaining cryptographic separation between communication and identity.

4 Threat Model

4.1 Adversary Classes and Capabilities

We consider adversaries with the following capabilities, ordered by strength:

Local Passive Adversary (LPA) An adversary observing a subset of network links (e.g., ISP, regional network operator, autonomous system). The adversary records packet metadata (timing, volume, routing information) on observed links but cannot decrypt correctly encrypted packets. The LPA cannot observe all network points simultaneously.

Global Passive Adversary (GPA) An adversary observing all network traffic globally including all links between clients, gateways, mix nodes, and other gateways. The GPA records complete traffic patterns but cannot decrypt correctly encrypted packets or compromise cryptographic algorithms. The GPA cannot perform active attacks or inject traffic.

Malicious Mix Nodes An adversary controlling a fraction $f \in [0, 1)$ of mix nodes, possibly distributed across layers. Malicious nodes may drop packets, selectively delay forwarding, reorder batches non-uniformly, or attempt to correlate inputs and outputs. Malicious nodes cannot decrypt packets they do not hold corresponding decryption keys for.

Malicious Gateway An adversary controlling one or more Gateway nodes. Malicious gateways may attempt to correlate client IP addresses with message delivery events, inject or drop messages, or attempt to deanonymize clients. Gateways do not have access to end-to-end message encryption keys.

Sybil Attacker An adversary attempting to register a large number of colluding nodes in the mix network to gain disproportionate control over message routing paths. Sybil attacks are constrained by the staking requirement (Section 6).

Spam/DoS Attacker An adversary attempting to flood the network with illegitimate messages to exhaust relay bandwidth or degrade quality of service. Spam attacks are constrained by the zero-knowledge credential mechanism (Section 6.7).

Quantum Adversary An adversary with access to a large-scale quantum computer capable of breaking elliptic-curve discrete logarithm and finite-field discrete logarithm assumptions. The quantum adversary can break X25519 and potentially other classical primitives but is assumed unable to break lattice-based assumptions underlying ML-KEM-1024 simultaneously.

4.2 Threat Scope: Defended Against

- Traffic analysis by local passive adversaries under Assumptions 1–4.
- Traffic analysis by global passive adversaries in Ghost mode under Assumptions 1–7 (with caveats in Section 10).
- Message content interception at any network point.
- Node directory seizure or domain takedown via single-entity action. The Solana blockchain's decentralized validator set provides significantly higher coordination availability than centralized DNS-dependent or single-operator infrastructure. However, jurisdictional concentration of validators (Section 3.2) means that coordinated multi-jurisdictional legal action could degrade availability; this is acknowledged as a residual risk rather than a solved problem.
- Sybil attacks on the relay network via economic staking requirements.
- Harvest-now-decrypt-later attacks by quantum adversaries via hybrid post-quantum encryption.
- Identity linkage of authentication events via zero-knowledge credentials.
- Spam and message flooding via staking-based access control.

4.3 Threat Scope: Not Defended Against

- Endpoint compromise: Client device breach voids all protocol security guarantees.
- Long-term intersection attacks against small anonymity sets (Limitation 2, Section 10).
- Message delivery disruption during prolonged Solana outages beyond local cache time-to-live (Limitation 3, Section 10).
- Implementation vulnerabilities in post-quantum primitives, partially mitigated by hybrid construction.
- Targeted legal compulsion of node operators or protocol developers.
- Real-time communication in Ghost mode (by design; Mist mode is provided for latency-sensitive use cases).
- Quantum attacks on X25519 when combined with successful classical attacks on ML-KEM-1024 simultaneously.

5 Security Goals and Assumptions

5.1 Formal Security Properties

Definition 5.1 (Sender Anonymity)**.** *An adversary $\mathcal{A}$ cannot identify the sender of a message with probability significantly greater than $1/|\mathcal{U}|$, where $|\mathcal{U}|$ is the cardinality of the active client population generating cover traffic in the same epoch. Formally, for any two senders $s_1, s_2 \in \mathcal{U}$, the advantage $|\Pr[\mathcal{A}(\text{message from } s_1) = 1] - \Pr[\mathcal{A}(\text{message from } s_2) = 1]|$ is negligible.*

Definition 5.2 (Receiver Anonymity)**.** *An adversary cannot identify the intended recipient of a message with probability significantly exceeding $1/|\mathcal{U}|$. The Sphinx SURB mechanism ensures that mix nodes and external observers cannot link message delivery to recipient identity.*

Definition 5.3 (Relationship Unobservability)**.** *An adversary observing all network traffic cannot determine whether two specific parties A and B communicate with probability significantly exceeding random guessing, over any observation period. This property holds under continuous cover traffic (Assumption 5.5).*

Definition 5.4 (Forward Secrecy)**.** *Compromise of a party's long-term key material at time t does not enable decryption of ciphertext recorded before time t. The Double Ratchet protocol ensures compromise of session state k_i does not enable decryption of messages encrypted under k_j for $j < i$.*

Definition 5.5 (Traffic Analysis Resistance)**.** *Under Assumption 5.5, the observable network traffic distribution (packet timing, volume, source-destination pairs) is computationally indistinguishable from a network transmitting only cover traffic, with respect to all computationally bounded adversaries.*

Definition 5.6 (Spam Resistance)**.** *The expected economic cost to successfully deliver n unsolicited messages through the network is at least $n \cdot c_{\min}$, where $c_{\min}$ is the minimum staking cost per credential enforced by the zero-knowledge credential mechanism.*

5.2 Design Assumptions

Assumption 5.1 (Cryptographic Hardness)**.** *Security of X25519 rests on the computational Diffie-Hellman assumption over Curve25519. Security of ML-KEM-1024 rests on hardness of the Module Learning With Errors problem. Both are treated as standard assumptions with no known polynomial-time algorithms for classical or post-quantum adversaries, excluding quantum adversaries against X25519.*

Assumption 5.2 (Honest Majority on Paths)**.** *No adversary controls all mix nodes on any single message path. For any 3-hop path* (n_1, n_2, n_3)*, at least one node is honest. This assumption degrades as the adversary controls a greater fraction of mix nodes in each layer.*

Assumption 5.3 (Routing Table Integrity)**.** *The Solana node registry reflects a set of registered nodes at any time where the fraction of adversary-controlled nodes is below the staking-weighted threshold required to dominate path selection. Specifically, the adversary controls fewer than* $\max(0.33N_1, 0.33N_2, 0.33N_3)$ *nodes in each layer, where* N_i *is the number of nodes in layer* i*.*

Assumption 5.4 (Independent Poisson Delays)**.** *Mix nodes apply independent exponential delays with rate parameter* λ*. Nodes do not collude to synchronize batch releases, coordinate forwarding timings, or otherwise correlate their delay distributions.*

Assumption 5.5 (Complete Cover Traffic Participation)**.** *All clients generate cover traffic continuously at specified rates, independent of actual message activity. This assumption is critical for traffic analysis resistance. Any client disabling cover traffic violates this assumption and degrades anonymity for all users in the same epoch.*

Assumption 5.6 (Solana Availability at Initialization)**.** *The Solana network is available when clients initialize for routing table queries and zero-knowledge credential verification. Message routing can continue during temporary outages using locally cached routing tables (Section 10 addresses extended outage scenarios).*

Assumption 5.7 (ZK Circuit Correctness)**.** *Groth16 zk-SNARK circuits for credential verification are correctly implemented and the associated structured reference string (trusted setup) is sound. Soundness ensures that no prover can generate a valid credential proof without possessing a valid witness.*

6 Protocol Description

6.1 Node Registration and Staking

A mix node registers by submitting a transaction to the NullWire Node Registry program on Solana. Registration requires:

- Staking a minimum of 100 SOL for mix nodes or 500 SOL for gateway nodes to the staking smart contract.
- Publishing a long-term Sphinx public key pair (hybrid ML-KEM-1024 and X25519).
- Publishing a network endpoint (IPv4 or IPv6 address and listening port).
- Specifying a layer assignment: L_1, L_2, L_3, or Gateway.
- Publishing an ML-DSA-65 verification key for message authentication.

Nodes are subject to slashing for verifiable misbehavior. Slashing conditions include (a) failure to forward packets, detectable via client loop cover traffic that does not return within the expected time window, and (b) failure to generate drop cover traffic at the specified rate. Monitoring clients submit slashing evidence on-chain. Honest nodes earn relay fees distributed per epoch based on verifiable packet-forwarding proofs.

6.2 Client Initialization

A new client initializes through the following sequence:

1. Generate a fresh long-term identity key pair using hybrid ML-KEM-1024 and X25519 construction.
2. Fetch the current node registry from the Solana Node Registry program and cache it locally with time-to-live.
3. Create an anonymous wallet (a fresh account with no prior on-chain history) and stake credential amount $s \geq s_{\min}$ (minimum 0.1 SOL) to the ZK Credential Verifier program.
4. Generate a Groth16 zero-knowledge proof π attesting: "I know a wallet W having staked $s \geq s_{\min}$ to the NullWire contract," without revealing W or s.
5. Connect to a Gateway node and present π for on-chain verification via RPC call.
6. Upon verification, receive a short-lived session token for message submission.
7. Begin generating cover traffic immediately upon connection at configured rate.

Session unlinkability is achieved by generating fresh keypairs and fresh zero-knowledge credentials for each communication session, such that no two sessions can be correlated through credential or key reuse.

6.3 Packet Construction

Let m denote the plaintext message, $R = (n_1, n_2, n_3, G_B)$ the selected path (three mix nodes and recipient's gateway), and PK_B the recipient's long-term public key. Packet construction proceeds as:

1. Message m is encrypted to PK_B using hybrid key encapsulation: Generate shared secret

$$k = \text{HKDF}(\text{ML-KEM-1024}(PK_B) \,\|\, \text{X25519}(PK_B)) \tag{1}$$

   Then compute ciphertext $c = \text{XChaCha20-Poly1305}_k(m)$.

2. Apply the Double Ratchet protocol at the session layer to derive per-message forward-secret keys.
3. Construct Sphinx routing headers for path $n_1 \to n_2 \to n_3 \to G_B$, with each header layer encrypted to the corresponding node's public key.
4. Pad or fragment the packet to exactly 2,048 bytes.

All packets—real messages, loop cover traffic, and drop cover traffic—are constructed in identical Sphinx format at the same fixed size, ensuring network-level indistinguishability.

6.4 Mix Node Processing

Upon receiving a Sphinx packet, a mix node performs:

1. Add the packet to a local buffer pool.
2. Sample an independent delay Δ from an exponential distribution: $\Delta \sim \text{Exp}(\lambda)$.
3. After delay Δ, select a batch from the buffer pool.

4. Shuffle the batch uniformly at random.
5. For each packet in the batch: apply the Sphinx transformation to obtain the next-hop address and re-encrypted output packet.
6. Forward all packets in the batch simultaneously.
7. Inject drop cover packets at rate μ to maintain constant outbound traffic volume.

The parameters λ and μ are governance-adjustable protocol parameters defining operating points on the anonymity-latency tradeoff curve.

6.5 Cover Traffic Protocol

Cover traffic provides the primary mechanism for traffic analysis resistance. Two types are generated:

Loop Cover Traffic Each client continuously sends messages addressed to its own mailbox via randomly selected 3-hop paths. These messages traverse the full network and are decryptable by the sending client. A client detecting that its own loop messages do not return within the expected timeout generates evidence for slashing the non-forwarding node.

Drop Cover Traffic Each mix node generates dummy packets at rate μ between real forwarding batches. Dummy packets are constructed in identical Sphinx format and are indistinguishable from real packets at the network level; they are discarded upon decryption at the final hop.

6.6 Operating Modes

NullWire supports three configurable operating modes. Mode selection is a per-session client-side parameter not transmitted to or observable by the network.

Ghost Mode Full Loopix mixing with rate parameter λ_G targeting high mixing entropy. Cover traffic is generated at the maximum specified rate. Expected end-to-end latency: 2–5 seconds. Ghost mode provides resistance to global passive adversaries under Assumption 5.5.

Shadow Mode Reduced Poisson delay parameter ($\lambda_S > \lambda_G$, targeting 0.5–1.5 second latencies) with moderate cover traffic rate. Shadow mode provides strong resistance to local adversaries and partial resistance to global passive adversaries. Appropriate for privacy-sensitive communication without nation-state threat models.

Mist Mode Onion routing (similar to Tor) without Poisson mixing delays or cover traffic. Expected end-to-end latency: 100–300 ms. Mist mode provides protection against server-level surveillance and basic network-level traffic analysis but is vulnerable to traffic correlation by a global passive adversary. Mist mode is provided for latency-sensitive use cases and as a bootstrap mode during early network deployment when Ghost mode anonymity sets are small.

6.7 Zero-Knowledge Identity and Credential Protocol

The credential scheme prevents message flooding without requiring persistent user identity. The protocol is:

1. Client C creates an anonymous wallet W with no prior on-chain history and stakes $s \geq s_{\min}$ to the NullWire staking contract.

2. The staking contract records the commitment $\text{cm} = \text{Commit}(W, s, r)$ where r is a random blinding factor, without recording W or s in plaintext.

3. C generates a Groth16 proof π for the statement: "I know (W, s, r) such that $\text{Commit}(W, s, r) = \text{cm}$, $s \geq s_{\min}$, and cm is in the on-chain commitment set."

4. C presents π to Gateway node G over an authenticated channel.

5. G verifies π against the on-chain verifier key via an RPC call. Verification does not reveal W, s, or any other information to G.

6. Upon verification, G issues a short-lived session token for message submission.

Session unlinkability is achieved through fresh anonymous wallets, fresh stakes, and fresh proofs for each session.

Trusted setup and operational considerations. Groth16 requires a structured reference string (SRS) generated through a trusted setup ceremony. Compromise of the SRS toxic waste would enable an adversary to forge credential proofs, bypassing the staking requirement entirely. NullWire mitigates this risk through a multi-party computation (MPC) ceremony following the Zcash Powers of Tau model [15], where security requires only that a single participant behaves honestly. The ceremony transcript is published for public verification.

We acknowledge that the per-session credential scheme imposes operational overhead: each new session requires generating a fresh anonymous wallet, submitting an on-chain staking transaction, and computing a Groth16 proof (approximately 2–10 seconds on consumer hardware depending on circuit complexity). Session tokens are valid for a configurable window (default: 24 hours), amortizing this cost across multiple messages within a session. The tradeoff between session duration and unlinkability is a tunable parameter; shorter sessions provide stronger unlinkability at higher operational cost.

7 Security Analysis

7.1 Sender and Receiver Anonymity

NullWire inherits the anonymity analysis of Loopix [23]. Under Assumptions 5.2, 5.4, and 5.5, the Poisson mixing process and continuous cover traffic cause the traffic observable at any network link to converge toward a stationary distribution independent of real message activity.

An adversary monitoring a single link observes a Poisson process with rate $\lambda + \mu$ (real messages plus cover) that is statistically identical whether or not any particular client is sending real messages. The sender anonymity set is bounded by the concurrent active client population. The adversary's identification probability is bounded by $1/|\mathcal{U}|$ where $|\mathcal{U}|$ is the cover-traffic-active client population.

Receiver anonymity is provided by Sphinx SURB mechanisms, which enable messages to be addressed to recipient gateways without revealing recipient identity to mix nodes.

7.2 Traffic Analysis Resistance

Under Assumption 5.5, a global passive adversary observing all network links sees a traffic pattern computationally indistinguishable from a network transmitting only cover traffic. Real messages and cover traffic have identical packet size (2,048 bytes), identical Sphinx format, and traverse the same mixing process. An adversary cannot distinguish which packets carry real content versus dummy payloads.

If a subset of clients violates Assumption 5.5 by disabling cover traffic, anonymity degrades: clients transmitting only for real messages exhibit correlated traffic. This is a well-known limitation of systems relying on client cover traffic and is discussed further in Section 10.

7.3 Sybil Attack Resistance

The staking requirement provides a quantifiable cost bound on Sybil attacks. An adversary seeking to control fraction f of mix nodes in a layer containing N nodes must stake:

$$\text{Cost}_{\text{Sybil}} \geq f \cdot N \cdot S_{\min}$$

where $S_{\min} = 100$ SOL. The probability that a 3-hop path traverses at least one adversary-controlled node in every layer is f^3 under uniform random path selection. For $f = 0.33$ and $N = 50$ nodes per layer, this requires approximately $0.33 \times 50 \times 100 = 1,650$ SOL per layer, or $\sim 4,950$ SOL total (approximately USD 742,000 at current exchange rates) to control all three layers.

Path selection weighted by stake and reputation further increases attack costs.

7.4 Forward Secrecy and Compromise Resilience

The Double Ratchet protocol ensures each message encrypts under a fresh symmetric key derived from a ratchet step. Compromise of session state k_i does not enable decryption of messages encrypted under k_j for $j < i$. The Diffie-Hellman ratchet provides break-in recovery: compromising a single state does not reliably enable decryption of all subsequent messages.

7.5 Quantum Resistance

The hybrid construction combining ML-KEM-1024 with X25519 requires an adversary to simultaneously break both components for message confidentiality. If a quantum computer breaks X25519 by solving elliptic curve discrete logarithm, ML-KEM-1024 continues providing security under the MLWE assumption. If classical attacks break ML-KEM-1024, X25519 provides security under the CDH assumption. Both must fail simultaneously to break the construction.

ML-DSA-65 provides quantum-resistant authentication for node registrations, preventing quantum adversaries from forging registry entries.

7.6 Zero-Knowledge Credential Soundness

Under Groth16 soundness (Assumption 5.7), a client cannot generate a valid credential proof without possessing the witness (W, s, r). The zero-knowledge property ensures gateways learn nothing about wallet identity or stake amount from valid proofs.

8 Theoretical Performance Analysis

Empirical evaluation requires deployed infrastructure and is deferred to prototype implementation. We provide theoretical analysis of primary performance-determining parameters.

8.1 Latency Analysis

In Ghost mode, end-to-end latency is dominated by the sum of Poisson delays at three mix nodes. For independent exponential delays with rate λ per node:

$$E\left[\sum_{i=1}^{3} \Delta_i\right] = \frac{3}{\lambda}$$

Adding network propagation delay Δ_{net}, the expected end-to-end latency is $3/\lambda + \Delta_{\text{net}}$. To achieve 2–5 second target latency in Ghost mode, $\lambda \approx 0.6$–1.5 messages per second per node. Shadow mode uses $\lambda_S \approx 3$–$5\ \text{s}^{-1}$ (targeting 500 ms to 2 s latency). Mist mode omits Poisson delays entirely.

8.2 Bandwidth Overhead

Cover traffic introduces bandwidth overhead proportional to cover-to-real-message ratio $r = N_{\text{cover}}/N_{\text{real}}$. Loopix analysis recommends $r \geq 5$ for meaningful anonymity guarantees, meaning cover traffic comprises at least 83% of total client bandwidth. At 2,048 bytes per packet and one packet per second, this represents approximately 16 KB/s uplink bandwidth per client in Ghost mode.

8.3 Node Economics: Calibration Framework

We present the economic model as a *calibration framework* whose parameters require empirical tuning through testnet operation; the values below are illustrative targets, not commitments.

Relay fee sustainability requires that honest node operating revenue R exceeds operating costs C. For a node processing M packets per second:

$$R = M \cdot f_{\text{relay}} \cdot (1 - f_{\text{protocol}})$$

where f_{relay} is the per-packet relay fee and f_{protocol} is the protocol-retained fraction funding development and governance. As an illustrative worked example: a mix node processing $M = 500$ packets/second at $f_{\text{relay}} = 0.00001$ SOL per packet with $f_{\text{protocol}} = 0.10$ yields approximately $R \approx 0.0045$ SOL/second, or roughly 389 SOL/month (∼$58,000 USD at $150/SOL). Against estimated operating costs of $200–500/month for a high-bandwidth VPS with DDoS mitigation, this suggests viable node economics at moderate throughput levels. These figures are denominated in a volatile asset; real-world sustainability depends on SOL price stability and actual network utilization, both of which are unknown prior to deployment.

Reward and fee parameters are governance-adjustable through on-chain voting by staked node operators, introducing a governance attack surface: a coalition of high-stake operators could vote to increase relay fees beyond market-clearing levels. This risk is discussed further in Section 10.

9 Related Work

9.1 Mix Networks and Anonymity Primitives

Chaum [6] introduced mix networks in 1981 for anonymous electronic mail. Pfitzmann and Köhntopp [22] formalized anonymity terminology distinguishing sender anonymity, receiver anonymity, and relationship unobservability. Danezis and Dingledine [7] presented Mixminion, a practical deployment using Type III mixers with reply blocks and forward secrecy. Das et al. [10] formalize the anonymity trilemma: mix networks must tradeoff anonymity, latency, and bandwidth overhead. Loopix [23] achieves a favorable point on this tradeoff through Poisson-distributed per-packet delays and continuous cover traffic, reducing latency while maintaining strong anonymity under cover traffic assumptions. NullWire directly adopts the Loopix mixing model.

9.2 Onion Routing Systems

Tor [12], deployed in 2002, remains the most widely deployed anonymous communication system with over two million daily users. Tor uses three-hop onion routing through volunteer relays

with centralized directory authorities. The system is well-studied and has received substantial cryptanalytic attention. However, Tor is vulnerable to traffic correlation attacks by global passive adversaries capable of observing both path endpoints, as demonstrated empirically by Johnson et al. [16]. Murdoch and Danezis [17] showed that low-cost traffic analysis attacks are feasible against Tor relays. I2P [31] provides a similar onion-routing design with unidirectional tunnels and a distributed hash table for node discovery. Both Tor and I2P provide sender anonymity within their anonymity sets but lack mix network's traffic analysis resistance properties.

9.3 Blockchain-Incentivized Relay Networks

Session [27] provides onion-routed messaging over blockchain-incentivized relays on the Oxen blockchain, removing the telephone number requirement of Signal. Session's architecture differs from NullWire in its reliance on onion routing (providing weaker global adversary resistance than mixing), smaller relay networks on Oxen, and absence of cover traffic. Nym [11] implements a Loopix-based mix network with NYM token incentives, representing the closest architectural precedent to NullWire. Nym differs from NullWire in its use of a custom blockchain/token infrastructure versus leveraging existing Solana infrastructure, lack of post-quantum encryption at protocol inception, and absence of zero-knowledge credential mechanisms. Neither Session nor Nym has achieved production consumer deployment at scale.

9.4 Blockchain-Native Communication

XMTP [29], Status [26], and Waku [28] provide decentralized messaging with blockchain wallet-based identity. These systems enable communication addressed to wallet addresses and store identity-linked routing information on-chain. They are designed for the explicit purpose of linking communication to blockchain identity and are not suitable for anonymous communication scenarios. Push Protocol [24] provides notification infrastructure for Web3 applications with similar identity-linked architecture. These systems' threat models differ fundamentally from NullWire's: they do not attempt to hide who communicates with whom.

9.5 Anonymous Credentials and Zero-Knowledge Proofs

Camenisch and Lysyanskaya [5] introduced efficient anonymous credential schemes enabling privacy-preserving authentication. Group signatures, formalized by Bellare et al. [3], provide cryptographic constructs for anonymous membership proof. Zcash [15] employs Groth16 zk-SNARKs for transaction privacy, with zero-knowledge proofs enabling transactions without revealing sender, receiver, or amount. Tornado Cash [21] uses similar techniques for Ethereum transaction privacy. NullWire's approach of using Groth16 for stake-based anonymous access control follows this direction but applies the technique to spam prevention rather than transaction privacy.

9.6 Post-Quantum Mix Networks

Agrawal et al. [1] analyze integration of post-quantum key encapsulation mechanisms with mix network packet formats. NullWire's approach of combining ML-KEM-1024 with Sphinx is consistent with this direction, using NIST-standardized primitives rather than pre-standardization candidates.

9.7 Comparative Analysis Table

The table shows that NullWire combines capabilities not present together in any deployed system: post-quantum cryptography from protocol inception, mix network architecture for

Table 1: Comparison of anonymous communication systems. Abbreviations: PQ = post-quantum encryption from launch; CT = continuous cover traffic; MN = mix network architecture; BI = blockchain incentives; ZK = zero-knowledge credentials; CD = censorship-resistant decentralized directory.

System	**PQ**	**CT**	**MN**	**BI**	**ZK**	**CD**
Tor [12]	–	–	–	–	–	–
Signal [20]	partial	–	–	–	–	–
I2P [31]	–	–	–	–	–	–
Session [27]	✓	–	–	✓	–	partial
Nym [11]	roadmap	✓	✓	✓	–	partial
NullWire (this work)	✓	✓	✓	✓	✓	✓

strong traffic analysis resistance, continuous cover traffic, blockchain-based economic incentives, zero-knowledge credential schemes, and fully decentralized censorship-resistant coordination.

10 Limitations and Future Work

Limitation 1: Cold-Start Anonymity Sets. NullWire's anonymity guarantees in Ghost mode are bounded by the concurrent active client population $|\mathcal{U}|$ generating cover traffic. An adversary's probability of correctly identifying a sender is at most $1/|\mathcal{U}|$; meaningful resistance to targeted deanonymization therefore requires $|\mathcal{U}|$ to exceed a minimum viable threshold. Following the Loopix analysis [23], we estimate that $|\mathcal{U}| \geq 500$ concurrent cover-traffic-active clients provides a baseline anonymity set sufficient to resist casual traffic analysis, while $|\mathcal{U}| \geq 5{,}000$ is required for credible resistance against resourced adversaries performing statistical disclosure attacks over extended observation windows.

At network launch, the active client population will be substantially below these thresholds. NullWire addresses this through a staged security maturity model:

- **Phase A (Launch):** Mist mode only. Provides onion-routing-equivalent anonymity (comparable to Tor) with no mixing latency penalty. Suitable for adversary models excluding global passive adversaries.
- **Phase B ($|\mathcal{U}| \geq 500$):** Shadow mode enabled. Reduced Poisson mixing provides partial traffic analysis resistance with moderate latency. Suitable for privacy-sensitive communication below nation-state threat models.
- **Phase C ($|\mathcal{U}| \geq 5{,}000$):** Ghost mode enabled. Full Loopix mixing with continuous cover traffic. Provides the protocol's strongest anonymity guarantees under Assumptions 1–7.

Precise threshold calibration requires empirical measurement on deployed infrastructure and is designated as a Phase-0 deliverable. The staged model ensures the protocol does not advertise security guarantees that the current network population cannot sustain.

Limitation 2: Intersection and Statistical Disclosure Attacks. A global passive adversary observing which clients are online across multiple message delivery events can apply intersection attacks [9] to narrow sender anonymity sets over extended observation. This limitation is fundamental to all mix networks with variable user populations. Always-on client behavior (continuous cover traffic regardless of message activity) provides primary mitigation; however, enforcing this without penalizing legitimate offline periods is an open design problem.

Limitation 3: Solana Control Plane Availability Dependency. NullWire's control plane depends on Solana network availability. Solana has experienced documented outages. The protocol mitigates through local routing table caching, enabling continued message routing during temporary outages (cache TTL-dependent). Planned phase-1 work includes DHT-based fallback discovery (not part of current design). Resilience to extended multi-hour Solana outages remains an open design challenge.

Limitation 4: Post-Quantum Primitive Maturity. ML-KEM-1024 was standardized in August 2024 and has received less cryptanalytic scrutiny than mature classical primitives. The hybrid construction (requiring simultaneous compromise of ML-KEM and X25519) mitigates but does not eliminate risk of undiscovered vulnerabilities. Monitoring of post-quantum cryptanalysis literature and planning for algorithm agility in implementation are recommended.

Limitation 5: Node Economic Calibration. Relay fee parameters require real-world calibration through testnet operation. Suboptimal fee settings result in either insufficient relay supply (low rewards) or excessive user costs (high fees). The governance mechanism enables parameter adjustment but introduces a governance attack surface. Optimal parameter discovery is an open empirical question.

Limitation 6: Implementation Security Requirements. The cryptographic implementation must undergo professional security audit by firms with established expertise (e.g., Trail of Bits, NCC Group) before any production deployment. This is a strict precondition for mainnet release. The hybrid post-quantum encryption construction, zero-knowledge circuits, and Sphinx implementation are all audit-critical components.

Limitation 7: Empirical Validation Gap. This work presents protocol specification and theoretical analysis. Empirical validation—including latency measurement under realistic network conditions, cover traffic overhead characterization, anonymity set behavior under real usage patterns, node economic sustainability analysis, and comparison against stated threat models—requires prototype implementation.

Phase-0 implementation is in progress with the following scope and target deliverables:

- **Rust prototype** of the mix node relay engine (Sphinx processing, Poisson delay scheduling, cover traffic generation), targeting Q3–Q4 2026.
- **Solana program deployment** on devnet for node registry, staking, and ZK credential verification.
- **Latency and throughput benchmarks** under simulated network conditions with 50–500 mix nodes.
- **Third-party security audit** of cryptographic implementation by an established firm (e.g., Trail of Bits, NCC Group) as a strict precondition for any mainnet deployment.

Results from Phase-0 will be reported in a subsequent publication. Until empirical validation is complete, all security claims in this paper should be understood as conditional on correct implementation and the stated assumptions.

11 Conclusion

We have presented NullWire, a decentralized anonymous communication protocol combining a Loopix-style stratified mix network with a Solana blockchain control plane. The protocol

provides sender anonymity, receiver anonymity, relationship unobservability, forward secrecy, and quantum resistance through hybrid ML-KEM-1024 and X25519 encryption within the Sphinx packet format. Key design contributions include leveraging an existing high-throughput blockchain for censorship-resistant, economically incentivized node coordination; introducing zero-knowledge credentials for identity-independent spam prevention; and establishing three configurable operating modes on the anonymity-latency tradeoff curve.

The primary limitations are cold-start anonymity set challenges, susceptibility to long-term intersection attacks under small populations, and Solana availability dependency. Empirical validation is required to assess protocol behavior under real deployment conditions and to calibrate economic parameters for node sustainability.

We believe NullWire's design addresses three principal structural weaknesses of existing anonymous communication systems: vulnerability to traffic correlation attacks against global passive adversaries (addressed through mix network architecture), centralized coordination points (addressed through blockchain-based decentralization), and relay network sustainability (addressed through economic incentivization). The combination of these three elements with post-quantum cryptography from protocol inception represents a technical direction not yet realized in any production system. Full empirical evaluation and prototype implementation constitute essential future work.

References

[1] Shashank Agrawal, Shalabh Bhattacherjee, Duong Hieu Phan, Damien Stehlé, and Shota Yamada. Post-quantum multi-party computation. Cryptology ePrint Archive, Report 2021/1433. https://eprint.iacr.org/2021/1433, 2022.

[2] Aikido Security. GlassWorm hides a RAT inside a malicious Chrome extension. Aikido Security Research Blog. https://www.aikido.dev/blog/glassworm-chrome-extension-rat, March 2026.

[3] Mihir Bellare, Haixia Shi, and Chong Zhang. Foundations of group signatures: Formal definitions, simplified requirements, and a construction based on general assumptions. In *Advances in Cryptology – EUROCRYPT 2003*, pages 614–629. Springer, 2003.

[4] Raul Vasile Bucur and Silviu Stahie. Windsurf IDE extension drops malware via Solana blockchain. Bitdefender Labs. https://www.bitdefender.com/en-us/blog/labs/windsurf-extension-malware-solana, March 2026.

[5] Jan Camenisch and Anna Lysyanskaya. An efficient system for non-transferable anonymous credentials with optional anonymity revocation. In *Advances in Cryptology – EUROCRYPT 2001*, pages 93–118. Springer, 2001.

[6] David L. Chaum. Untraceable electronic mail, return addresses, and digital pseudonyms. *Communications of the ACM*, 24(2):84–90, 1981.

[7] George Danezis, Roger Dingledine, and Nick Mathewson. Mixminion: Design of a type III anonymous remailer protocol. In *2003 IEEE Symposium on Security and Privacy*, pages 2–15. IEEE, 2003.

[8] George Danezis and Ian Goldberg. Sphinx: A compact and provably secure mix format. In *2009 IEEE Symposium on Security and Privacy*, pages 269–282. IEEE, 2009.

[9] George Danezis and Andrei Serjantov. Statistical disclosure or intersection attacks on anonymity systems. In *Information Hiding – 6th International Workshop*, pages 293–308. Springer, 2004.

[10] Debajyoti Das, Sebastian Meiser, Esfandiar Mohammadi, and Aniket Kate. Anonymity trilemma: Strong anonymity, low bandwidth overhead, low latency—choose two. In *2018 IEEE Symposium on Security and Privacy*, pages 108–126. IEEE, 2018.

[11] Claudia Diaz, Harry Halpin, and Aggelos Kiayias. The Nym network: A mixnet for internet-scale anonymity. Nym Technologies Whitepaper. https://nymtech.net/nym-whitepaper.pdf, 2021.

[12] Roger Dingledine, Nick Mathewson, and Paul Syverson. Tor: The second-generation onion router. In *13th USENIX Security Symposium (USENIX Security 04)*. USENIX Association, 2004.

[13] Glenn Greenwald. *No Place to Hide: Edward Snowden, the NSA, and the U.S. Surveillance State*. Metropolitan Books, 2014.

[14] Jens Groth. On the size of pairing-based non-interactive arguments. In *Advances in Cryptology – EUROCRYPT 2016*, pages 305–326. Springer, 2016.

[15] Daira Hopwood, Sean Bowe, Taylor Hornby, and Nathan Wilcox. Zcash protocol specification. https://zips.z.cash/protocol/protocol.pdf, 2016.

[16] Aaron Johnson, Chris Wacek, Rob Jansen, Micah Sherr, and Paul Syverson. Users get routed: Traffic correlation on Tor by realistic adversaries. In *Proceedings of the 2013 ACM SIGSAC Conference on Computer and Communications Security*, pages 337–348. ACM, 2013.

[17] Steven J. Murdoch and George Danezis. Low-cost traffic analysis of Tor. In *2005 IEEE Symposium on Security and Privacy*, pages 183–195. IEEE, 2005.

[18] National Institute of Standards and Technology. FIPS 203: Module-lattice-based key-encapsulation mechanism standard. Federal Information Processing Standards Publication 203, National Institute of Standards and Technology, 2024.

[19] National Institute of Standards and Technology. FIPS 204: Module-lattice-based digital signature standard. Federal Information Processing Standards Publication 204, National Institute of Standards and Technology, 2024.

[20] Open Whisper Systems. Signal protocol documentation. https://signal.org/docs/, 2016.

[21] Alexey Pertsev, Roman Semenov, and Roman Storm. Tornado cash privacy solution. https://tornado.cash/Tornado.cash_whitepaper_v1.4.pdf, 2019.

[22] Andreas Pfitzmann and Marit Köhntopp. Anonymity, unobservability, and pseudonymity—A proposal for terminology. In *Designing Privacy Enhancing Technologies*, pages 1–9. Springer, 2001.

[23] Ania M. Piotrowska, Jamie Hayes, Tariq Elahi, Sebastian Meiser, and George Danezis. The Loopix anonymity system. In *26th USENIX Security Symposium (USENIX Security 17)*, pages 1199–1216. USENIX Association, 2017.

[24] Harsh Singh and Richa Nayak. EPNS: Ethereum push notification service whitepaper. https://whitepaper.epns.io/, 2020.

[25] Sonatype Security Research Team. Hijacked npm packages deliver malware via Solana, linked to GlassWorm. Sonatype Blog. https://www.sonatype.com/blog/hijacked-npm-packages-deliver-malware-via-solana-linked-to-glassworm, March 2026.

[26] Status Network. Status whitepaper. https://status.im/whitepaper.pdf, 2018.

[27] The Oxen Project Foundation. Session: An open source private messenger. https://getsession.org/whitepaper, 2020.

[28] Waku Team. Waku v2 protocol specification. https://rfc.vac.dev/spec/10/, 2021.

[29] XMTP Labs. XMTP: A secure messaging protocol for web3. https://xmtp.org/docs/, 2022.

[30] Anatoly Yakovenko. Solana: A new architecture for a high performance blockchain. Solana Whitepaper. https://solana.com/solana-whitepaper.pdf, 2018.

[31] Zab et al. I2P: The invisible internet project. https://geti2p.net/en/docs/, 2003.