



Iterators in C++ STL

Prerequisite : [Introduction to Iterators](#)

Iterators are used to point at the memory addresses of [STL](#) containers. They are primarily used in sequence of numbers, characters etc. They reduce the complexity and execution time of program.

Operations of iterators :-

1. begin() :- This function is used to return the **beginning position** of the container.

2. end() :- This function is used to return the ***after end position*** of the container.

```
// C++ code to demonstrate the working of
// iterator, begin() and end()
#include<iostream>
#include<iterator> // for iterators
#include<vector> // for vectors
using namespace std;
int main()
{
    vector<int> ar = { 1, 2, 3, 4, 5 };

    // Declaring iterator to a vector
    vector<int>::iterator ptr;

    // Displaying vector elements using begin() and end()
    cout << "The vector elements are : ";
    for (ptr = ar.begin(); ptr < ar.end(); ptr++)
        cout << *ptr << " ";

    return 0;
}
```

Output:

```
The vector elements are : 1 2 3 4 5
```

3. advance() :- This function is used to **increment the iterator position** till the specified number mentioned in its arguments.

```
// C++ code to demonstrate the working of
// advance()
#include<iostream>
#include<iterator> // for iterators
#include<vector> // for vectors
using namespace std;
int main()
{
    vector<int> ar = { 1, 2, 3, 4, 5 };

    // Declaring iterator to a vector
    vector<int>::iterator ptr = ar.begin();

    // Using advance() to increment iterator position
    // points to 4
    advance(ptr, 3);

    // Displaying iterator position
    cout << "The position of iterator after advancing is : ";
    cout << *ptr << " ";

    return 0;
}
```

Output:

```
The position of iterator after advancing is : 4
```

4. next() :- This function **returns the new iterator** that the iterator would point after **advancing the positions** mentioned in its arguments.

5. prev() :- This function **returns the new iterator** that the iterator would point **after decrementing the positions** mentioned in its arguments.

```
// C++ code to demonstrate the working of
// next() and prev()
#include<iostream>
#include<iterator> // for iterators
#include<vector> // for vectors
using namespace std;
int main()
{
    vector<int> ar = { 1, 2, 3, 4, 5 };

    // Declaring iterators to a vector
    vector<int>::iterator ptr = ar.begin();
    vector<int>::iterator ftr = ar.end();

    // Using next() to return new iterator
    // points to 4
    auto it = next(ptr, 3);

    // Using prev() to return new iterator
    // points to 3
    auto it1 = prev(ftr, 3);

    // Displaying iterator position
    cout << "The position of new iterator using next() is : ";
    cout << *it << " ";
    cout << endl;

    // Displaying iterator position
    cout << "The position of new iterator using prev() is : ";
    cout << *it1 << " ";
    cout << endl;

    return 0;
}
```

Output:

```
The position of new iterator using next() is : 4
The position of new iterator using prev() is : 3
```

6. inserter() :- This function is used to **insert the elements at any position** in the container. It accepts **2 arguments, the container and iterator to position where the elements have to be inserted**.

```
// copying 1 vector elements in other using inserter()
// inserts ar1 after 3rd position in ar
copy(ar1.begin(), ar1.end(), inserter(ar,ptr));
```

The new vector after inserting elements is : 1 2 3 10 20 30 4 5

1. Input Iterators
2. Output Iterators
3. Forward Iterator
4. Bidirectional Iterators
5. Random-Access Iterators

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

diagram.js

Fully interactive diagram library for JavaScript and TypeScript.

mindfusion.eu

OPEN

This is a promotional card for the 'diagram.js' library. It features the library's name in a large, bold, dark font. Below the name, a descriptive sentence states it is a 'Fully interactive diagram library for JavaScript and TypeScript.' At the bottom left, the website 'mindfusion.eu' is listed. At the bottom right, there is a prominent blue button with the word 'OPEN' in white capital letters. The entire card is set against a light gray background with a subtle shadow.

- Bidirectional Iterators in C++
- Output Iterators in C++
- Forward Iterators in C++
- Input Iterators in C++
- Introduction to Iterators in C++
- Random-access Iterators in C++
- Conditional or Ternary Operator (?:) in C/C++
- forward_list insert_after() function in C++ STL

Count of distinct remainders when N is divided by all the numbers from the range [1, N]

C++ | asm declaration

Pointers and References in C++

Strings in C++ and How to Create them?

Enum Classes in C++ and Their Advantage over Enum DataType

Deque vs Vector in C++ STL

Improved By : IkamaruEnauki

diagram.js

Fully interactive diagram library for JavaScript and TypeScript.

mindfusion.eu

OPEN

Article Tags : C++ cpp-iterator CPP-Library STL

Practice Tags : STL CPP



2.6

☐ To-do☐ Done

Based on 25 vote(s)

Feedback/ Suggest ImprovementAdd NotesImprove Article

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305
feedback@geeksforgeeks.org

COMPANY

[About Us](#)
[Careers](#)
[Privacy Policy](#)
[Contact Us](#)

LEARN

[Algorithms](#)
[Data Structures](#)
[Languages](#)
[CS Subjects](#)
[Video Tutorials](#)

PRACTICE

[Courses](#)
[Company-wise](#)
[Topic-wise](#)
[How to begin?](#)

CONTRIBUTE

[Write an Article](#)
[Write Interview Experience](#)
[Internships](#)
[Videos](#)



@geeksforgeeks, Some rights reserved