


University of Toronto

# UofT B

Aditya Bandekar, Bill Lin, Robert Chung

2026-10-28

1 Contest 1
2 Mathematics 1
3 Data structures 2
4 Numerical 5
5 Number theory 9
6 Combinatorial 11
7 Graph 12
8 Matching 13
9 Geometry 18
10 Strings 22
11 Various 24

# Contest (1)

template.cpp 6 lines

```
ll cdiv(ll a, ll b) { return a/b+((a^b)>0&&a%b); }
ll fdiv(ll a, ll b) { return a/b-((a^b)<0&&a%b); }
int main() {
  cin.tie(0)->sync_with_stdio(0);
  cin.exceptions(cin.failbit);
}
```

hash.sh 3 lines

```
# Hashes a file, ignoring all whitespace and comments. Use for
# verifying that code was correctly typed.
cpp -dD -P -fpreprocessed | tr -d '[:space:]'| md5sum |cut -c-6
```

# Mathematics (2)

## 2.1 Equations

$$ax^2 + bx + c = 0 \Rightarrow x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

The extremum is given by $x = -b/2a$.

$$\begin{matrix} ax + by = e \\ cx + dy = f \end{matrix} \Rightarrow \begin{matrix} x = \frac{ed - bf}{ad - bc} \\ y = \frac{af - ec}{ad - bc} \end{matrix}$$

In general, given an equation $Ax = b$, the solution to a variable $x_i$ is given by

$$x_i = \frac{\det A_i'}{\det A}$$

where $A_i'$ is $A$ with the $i$'th column replaced by $b$.

## 2.2 Recurrences

If $a_n = c_1 a_{n-1} + \cdots + c_k a_{n-k}$, and $r_1, \ldots, r_k$ are distinct roots of $x^k - c_1 x^{k-1} - \cdots - c_k$, there are $d_1, \ldots, d_k$ s.t.

$$a_n = d_1 r_1^n + \cdots + d_k r_k^n.$$

Non-distinct roots $r$ become polynomial factors, e.g. $a_n = (d_1 n + d_2) r^n$.

## 2.3 Trigonometry

$$\sin(v + w) = \sin v \cos w + \cos v \sin w$$
$$\cos(v + w) = \cos v \cos w - \sin v \sin w$$

$$\tan(v + w) = \frac{\tan v + \tan w}{1 - \tan v \tan w}$$
$$\sin v + \sin w = 2 \sin \frac{v + w}{2} \cos \frac{v - w}{2}$$
$$\cos v + \cos w = 2 \cos \frac{v + w}{2} \cos \frac{v - w}{2}$$
$$(V + W) \tan(v - w)/2 = (V - W) \tan(v + w)/2$$

where $V, W$ are lengths of sides opposite angles $v, w$.

$$a \cos x + b \sin x = r \cos(x - \phi)$$
$$a \sin x + b \cos x = r \sin(x + \phi)$$

where $r = \sqrt{a^2 + b^2}, \phi = \text{atan2}(b, a)$.

## 2.4 Geometry

### 2.4.1 Triangles

Side lengths: $a, b, c$

Semiperimeter: $p = \frac{a + b + c}{2}$

Area: $A = \sqrt{p(p - a)(p - b)(p - c)}$

Circumradius: $R = \frac{abc}{4A}$

Inradius: $r = \frac{A}{p}$

Length of median (divides triangle into two equal-area triangles): $m_a = \frac{1}{2}\sqrt{2b^2 + 2c^2 - a^2}$

Length of bisector (divides angles in two): $s_a = \sqrt{bc\left[1 - \left(\frac{a}{b + c}\right)^2\right]}$

Law of sines: $\frac{\sin \alpha}{a} = \frac{\sin \beta}{b} = \frac{\sin \gamma}{c} = \frac{1}{2R}$

Law of cosines: $a^2 = b^2 + c^2 - 2bc \cos \alpha$

Law of tangents: $\frac{a + b}{a - b} = \frac{\tan \frac{\alpha + \beta}{2}}{\tan \frac{\alpha - \beta}{2}}$


### 2.4.2 Quadrilaterals

With side lengths $a, b, c, d$, diagonals $e, f$, diagonals angle $\theta$, area $A$ and magic flux $F = b^2 + d^2 - a^2 - c^2$:

$$4A = 2ef \cdot \sin \theta = F \tan \theta = \sqrt{4e^2 f^2 - F^2}$$

For cyclic quadrilaterals the sum of opposite angles is $180°$, $ef = ac + bd$, and $A = \sqrt{(p - a)(p - b)(p - c)(p - d)}$.

### 2.4.3 Spherical coordinates




$$\begin{matrix} x = r \sin \theta \cos \phi \\ y = r \sin \theta \sin \phi \\ z = r \cos \theta \end{matrix} \qquad \begin{matrix} r = \sqrt{x^2 + y^2 + z^2} \\ \theta = \text{acos}(z/\sqrt{x^2 + y^2 + z^2}) \\ \phi = \text{atan2}(y, x) \end{matrix}$$

## 2.5 Derivatives/Integrals

$$\frac{d}{dx} \arcsin x = \frac{1}{\sqrt{1 - x^2}} \qquad \frac{d}{dx} \arccos x = -\frac{1}{\sqrt{1 - x^2}}$$
$$\frac{d}{dx} \tan x = 1 + \tan^2 x \qquad \frac{d}{dx} \arctan x = \frac{1}{1 + x^2}$$
$$\int \tan ax = -\frac{\ln|\cos ax|}{a} \qquad \int x \sin ax = \frac{\sin ax - ax \cos ax}{a^2}$$
$$\int e^{-x^2} = \frac{\sqrt{\pi}}{2} \text{erf}(x) \qquad \int xe^{ax} dx = \frac{e^{ax}}{a^2}(ax - 1)$$

Integration by parts:

$$\int_a^b f(x)g(x)dx = [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx$$

## 2.6 Sums

$$c^a + c^{a+1} + \cdots + c^b = \frac{c^{b+1} - c^a}{c-1}, c \neq 1$$

$$1 + 2 + 3 + \cdots + n = \frac{n(n+1)}{2}$$
$$1^2 + 2^2 + 3^2 + \cdots + n^2 = \frac{n(2n+1)(n+1)}{6}$$
$$1^3 + 2^3 + 3^3 + \cdots + n^3 = \frac{n^2(n+1)^2}{4}$$
$$1^4 + 2^4 + 3^4 + \cdots + n^4 = \frac{n(n+1)(2n+1)(3n^2+3n-1)}{30}$$

## 2.7 Series

$$e^x = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \ldots, (-\infty < x < \infty)$$

$$\ln(1+x) = x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \ldots, (-1 < x \leq 1)$$

$$\sqrt{1+x} = 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \ldots, (-1 \leq x \leq 1)$$

$$\sin x = x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \ldots, (-\infty < x < \infty)$$

$$\cos x = 1 - \frac{x^2}{2!} + \frac{x^4}{4!} - \frac{x^6}{6!} + \ldots, (-\infty < x < \infty)$$

## 2.8 Probability theory

Let $X$ be a discrete random variable with probability $p_X(x)$ of assuming the value $x$. It will then have an expected value (mean) $\mu = \mathbb{E}(X) = \sum_x x p_X(x)$ and variance $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$ where $\sigma$ is the standard deviation. If $X$ is instead continuous it will have a probability density function $f_X(x)$ and the sums above will instead be integrals with $p_X(x)$ replaced by $f_X(x)$.

Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent $X$ and $Y$,

$$V(aX + bY) = a^2 V(X) + b^2 V(Y).$$

### 2.8.1 Discrete distributions

#### Binomial distribution

The number of successes in $n$ independent yes/no experiments, each which yields success with probability $p$ is $\text{Bin}(n, p)$, $n = 1, 2, \ldots$, $0 \leq p \leq 1$.

$$p(k) = \binom{n}{k} p^k (1-p)^{n-k}$$

$$\mu = np,\ \sigma^2 = np(1-p)$$

$\text{Bin}(n, p)$ is approximately $\text{Po}(np)$ for small $p$.

#### First success distribution

The number of trials needed to get the first success in independent yes/no experiments, each which yields success with probability $p$ is $\text{Fs}(p)$, $0 \leq p \leq 1$.

$$p(k) = p(1-p)^{k-1},\ k = 1, 2, \ldots$$

$$\mu = \frac{1}{p},\ \sigma^2 = \frac{1-p}{p^2}$$

#### Poisson distribution

The number of events occurring in a fixed period of time $t$ if these events occur with a known average rate $\kappa$ and independently of the time since the last event is $\text{Po}(\lambda)$, $\lambda = t\kappa$.

$$p(k) = e^{-\lambda} \frac{\lambda^k}{k!}, k = 0, 1, 2, \ldots$$

$$\mu = \lambda,\ \sigma^2 = \lambda$$

### 2.8.2 Continuous distributions

#### Uniform distribution

If the probability density function is constant between $a$ and $b$ and 0 elsewhere it is $\text{U}(a, b)$, $a < b$.

$$f(x) = \begin{cases} \frac{1}{b-a} & a < x < b \\ 0 & \text{otherwise} \end{cases}$$

$$\mu = \frac{a+b}{2},\ \sigma^2 = \frac{(b-a)^2}{12}$$

#### Exponential distribution

The time between events in a Poisson process is $\text{Exp}(\lambda)$, $\lambda > 0$.

$$f(x) = \begin{cases} \lambda e^{-\lambda x} & x \geq 0 \\ 0 & x < 0 \end{cases}$$

$$\mu = \frac{1}{\lambda},\ \sigma^2 = \frac{1}{\lambda^2}$$

#### Normal distribution

Most real random values with mean $\mu$ and variance $\sigma^2$ are well described by $\mathcal{N}(\mu, \sigma^2)$, $\sigma > 0$.

$$f(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$$

If $X_1 \sim \mathcal{N}(\mu_1, \sigma_1^2)$ and $X_2 \sim \mathcal{N}(\mu_2, \sigma_2^2)$ then

$$aX_1 + bX_2 + c \sim \mathcal{N}(\mu_1 + \mu_2 + c, a^2\sigma_1^2 + b^2\sigma_2^2)$$

$\pi$ is a stationary distribution if $\pi = \pi\mathbf{P}$. If the Markov chain is *irreducible* (it is possible to get to any state from any state), then $\pi_i = \frac{1}{\mathbb{E}(T_i)}$ where $\mathbb{E}(T_i)$ is the expected time between two visits in state $i$. $\pi_j/\pi_i$ is the expected number of visits in state $j$ between two visits in state $i$.

For a connected, undirected and non-bipartite graph, where the transition probability is uniform among all neighbors, $\pi_i$ is proportional to node $i$'s degree.

A Markov chain is *ergodic* if the asymptotic distribution is independent of the initial distribution. A finite Markov chain is ergodic iff it is irreducible and *aperiodic* (i.e., the gcd of cycle lengths is 1). $\lim_{k\to\infty} \mathbf{P}^k = \mathbf{1}\pi$.

A Markov chain is an A-chain if the states can be partitioned into two sets $\mathbf{A}$ and $\mathbf{G}$, such that all states in $\mathbf{A}$ are absorbing ($p_{ii} = 1$), and all states in $\mathbf{G}$ leads to an absorbing state in $\mathbf{A}$. The probability for absorption in state $i \in \mathbf{A}$, when the initial state is $j$, is $a_{ij} = p_{ij} + \sum_{k \in \mathbf{G}} a_{ik} p_{kj}$. The expected time until absorption, when the initial state is $i$, is $t_i = 1 + \sum_{k \in \mathbf{G}} p_{ki} t_k$.

# Data structures (3)

OrderStatisticTree.h

**Description:** A set (not multiset!) with support for finding the n'th element, and finding the index of an element. To get a map, change `null_type`.
**Time:** $\mathcal{O}(\log N)$ 0ac05e, 17 lines

```
#include <bits/extc++.h>
using namespace __gnu_pbds;

template<class T>
using Tree = tree<T, null_type, less<T>, rb_tree_tag,
```

```
    tree_order_statistics_node_update>;

void example() {
  Tree<int> t, t2; t.insert(8);
  auto it = t.insert(10).first;
  assert(it == t.lower_bound(9));
  // t.order_of_key(x) = number of elmts strictly less than x
  assert(t.order_of_key(11) == 2);
  // t.find_by_order(k) = kth element, counting from 0
  assert(*t.find_by_order(0) == 8);
  t.join(t2); // assuming T < T2 or T > T2, merge t2 into t
}
```

## HashMap.h

**Description:** Hash map with mostly the same API as unordered_map, but ~3x faster. Uses 1.5x memory. Initial capacity must be a power of 2 (if provided).

d77092, 7 lines

```
#include <bits/extc++.h>
// To use most bits rather than just the lowest ones:
struct chash { // large odd number for C
  const uint64_t C = ll(4e18 * acos(0)) | 71;
  ll operator()(ll x) const { return __builtin_bswap64(x*C); }
};
__gnu_pbds::gp_hash_table<ll,int,chash> h({},{},{},{},{1<<16});
```

## SegmentTree.h

**Description:** Zero-indexed max-tree. Bounds are inclusive to the left and exclusive to the right. Can be changed by modifying T, f and unit.
**Time:** $\mathcal{O}(\log N)$

f92c9a, 19 lines

```
struct Tree {
  typedef int T;
  inline static const T unit = INT_MIN;
  T f(T a, T b) { return max(a, b); } // (any associative fn)
  vector<T> s; int n;
  Tree(int n = 0, T def = unit) : s(2*n, def), n(n) {}
  void update(int pos, T val) {
    for (s[pos += n] = val; pos /= 2;)
      s[pos] = f(s[pos * 2], s[pos * 2 + 1]);
  }
  T query(int b, int e) { // query [b, e)
    T ra = unit, rb = unit;
    for (b += n, e += n; b < e; b /= 2, e /= 2) {
      if (b % 2) ra = f(ra, s[b++]);
      if (e % 2) rb = f(s[--e], rb);
    }
    return f(ra, rb);
  }
};
```

## LazySegmentTree.h

**Description:** Remember that idT and idU must be idempotent
**Time:** $\mathcal{O}(\log N)$

fbed18, 62 lines

```
typedef ll T; T idT = {}; // node type
typedef ll U; U idU = {}; // update type
// combine segtree nodes a and b
T f(T a, T b) { return a + b; }
// apply updates f and g (f compose g)
U g(U f, U g) { return f + g; }
// apply update f to segtree node a
T h(U f, T a) { return a + f; }
struct lztree {
  int n;
  vector<T> t;
  vector<U> d;
  lztree(int n) : n(n), t(2*n, idT), d(n, idU) {}
  void calc(ll p) { t[p] = h(d[p], f(t[p * 2], t[p * 2 + 1])); }
  void apply(ll p, U v) {
    t[p] = h(v, t[p]);
    if(p < n) d[p] = g(v, d[p]);
  }
  void push(ll p) {
    p += n;
    for(int s = 24; s > 0; s--) { // need tree height <= 24
      ll i = p >> s;
      if(d[i] != idU) {
        apply(i * 2, d[i]);
        apply(i * 2 + 1, d[i]);
        d[i] = idU;
      }
    }
  }
  void set(ll p, T v) { // point set arr[p] = v
    push(p);
    t[p += n] = v;
    while(p > 1) calc(p /= 2);
  }
  T get(ll p) { // return arr[p]
    push(p);
    return t[p + n];
  }
  void update(ll l, ll r, U v) { // range update [l, r) using v
    push(l), push(r - 1);
    bool cl = false, cr = false;
    for(l += n, r += n; l < r; l /= 2, r /= 2) {
      if(cl) calc(l - 1);
      if(cr) calc(r);
      if(l & 1) apply(l++, v), cl = true;
      if(r & 1) apply(--r, v), cr = true;
    }
    for(--l; r; l /= 2, r /= 2) {
      if(cl) calc(l);
      if(cr) calc(r);
    }
  }
  T query(ll l, ll r) { // range query [l, r)
    push(l), push(r - 1);
    T resl = idT, resr = idT;
    for(l += n, r += n; l < r; l /= 2, r /= 2) {
      if(l & 1) resl = f(resl, t[l++]);
      if(r & 1) resr = f(t[--r], resr);
    }
    return f(resl, resr);
  }
};
```

## UnionFindRollback.h

**Description:** Disjoint-set data structure with undo. If undo is not needed, skip st, time() and rollback().
**Usage:** `int t = uf.time(); ...; uf.rollback(t);`
**Time:** $\mathcal{O}(\log(N))$

de4ad0, 21 lines

```
struct RollbackUF {
  vi e; vector<pii> st;
  RollbackUF(int n) : e(n, -1) {}
  int size(int x) { return -e[find(x)]; }
  int find(int x) { return e[x] < 0 ? x : find(e[x]); }
  int time() { return sz(st); }
  void rollback(int t) {
    for (int i = time(); i --> t;)
      e[st[i].first] = st[i].second;
    st.resize(t);
  }
  bool join(int a, int b) {
    a = find(a), b = find(b);
    if (a == b) return false;
    if (e[a] > e[b]) swap(a, b);
    st.push_back({a, e[a]});
    st.push_back({b, e[b]});
    e[a] += e[b]; e[b] = a;
    return true;
  }
};
```

## LineContainer.h

**Description:** Container where you can add lines of the form kx+m, and query maximum values at points x. Useful for dynamic programming ("convex hull trick").
**Time:** $\mathcal{O}(\log N)$

8ec1c7, 31 lines

```
struct Line {
  mutable ll k, m, p;
  bool operator<(const Line& o) const { return k < o.k; }
  bool operator<(ll x) const { return p < x; }
};

struct LineContainer : multiset<Line, less<>> {
  // (for doubles, use inf = 1/.0, div(a,b) = a/b)
  // i128 inf = numeric_limits<i128>::max();
  static const ll inf = LLONG_MAX;
  ll div(ll a, ll b) { // floored division
    return a / b - ((a ^ b) < 0 && a % b); }
  bool isect(iterator x, iterator y) {
    if (y == end()) return x->p = inf, 0;
    if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
    else x->p = div(y->m - x->m, x->k - y->k);
    return x->p >= y->p;
  }
  void add(ll k, ll m) {
    auto z = insert({k, m, 0}), y = z++, x = y;
    while (isect(y, z)) z = erase(z);
    if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
    while ((y = x) != begin() && (--x)->p >= y->p)
      isect(x, erase(y));
  }
  ll query(ll x) {
    assert(!empty());
    auto l = *lower_bound(x);
    return l.k * x + l.m;
  }
};
```

## LiChaoTree.h

**Description:** Add line segments and query maximum values on [0, M). To query minimum values, change the four spots marked 'chg'.
**Time:** $\mathcal{O}(\log N)$

43fdee, 42 lines

```
struct LiChao {
  struct Line {
    int m, b;
    int eval(int x) const { return m*x + b; }
  };
  vector<Line> v;
  int M;
  LiChao(int m) : v(4*m+1, {0, LLONG_MIN}), // chg to max
          M(m) {}
  void insert(int l, int r, Line line) { // add segment [l, r)
    auto f = [&](auto &&f, int node,
                 int ql, int qr, Line line) -> void {
      if (r <= ql || qr <= l) return;
      auto m = midpoint(ql, qr);
      if (l <= ql && qr <= r) {
        if (line.eval(m) > v[node].eval(m)) // chg to <
          swap(line, v[node]);
```

```
      if (qr-ql == 1) return;
      if (v[node].m > line.m) // chg to <
        f(f, 2*node + 1, ql, m, line);
      else
        f(f, 2*node + 2, m, qr, line);
      return;
    }
    f(f, 2*node + 1, ql, m, line);
    f(f, 2*node + 2, m, qr, line);
  };
  f(f, 0, 0, M, line);
 }
 int query(int x) { // find max value at point x
  assert(0 <= x && x < M);
  auto f = [&](auto &&f, int node,
               int l, int r) -> int {
    if (l+1 == r) return v[node].eval(x);
    auto m = midpoint(l, r);
    return max(v[node].eval(x), // chg to min
      x < m ? f(f, 2*node + 1, l, m)
            : f(f, 2*node + 2, m, r));
  };
  return f(f, 0, 0, M);
 }
};
```

## Treap.h

**Description:** Zero-indexed implicit treap. Change the 6 'todo' items when using.
**Time:** $\mathcal{O}(\log N)$

6fbe27, 122 lines

```
namespace Treap {
    struct Node;
    using ptr = Node*;

    // todo: max number of nodes
    constexpr int MAX_SZ = 200'000;
    // todo: value type
    using T = int;
    constexpr T idT{0};
    // todo: update type
    using U = bool;
    constexpr U idU{false};

    struct Node {
        Node *l, *r;
        int siz;
        unsigned long long pri; // pri is max heap
        T val, agg;
        U u;
        explicit Node(T val=idT) : l(nullptr), r(nullptr), siz
             (1), pri(rng()),
            val(val), agg(val), u(idU) {}
    };

    // todo: combine values 'a' and 'b'
    T t_combine(T a, T b) { return a+b; }
    // todo: combine updates 'f' and 'g' (f compose g)
    U u_combine(U f, U g) { return f^g; }
    // todo: apply update 'u' to node 'a'
    void _apply_upd(ptr a, U u) {
        if (!a) return;
        swap(a->l, a->r);
        a->u = u_combine(u, a->u);
    }

    Node arr[MAX_SZ]; int _last = 0;
    int _getsiz(ptr a) { return a ? a->siz : 0; }
    // fix values for parent by pulling from children
    ptr _pull(ptr a) {
        // assert(a != nullptr);
        a->siz = 1 + _getsiz(a->l) + _getsiz(a->r);
        a->agg = t_combine(t_combine(
                        a->l ? a->l->agg: idT,
                        a->val),
                        a->r ? a->r->agg : idT);
        return a;
    }
    // propagate values down to children
    void _push(ptr a) {
        // assert(a != nullptr);
        if (a->u == idU) return;
        _apply_upd(a->l, a->u);
        _apply_upd(a->r, a->u);
        a->u = idU;
    }
    // concatenate sequences A and B
    [[nodiscard]] ptr merge(ptr a, ptr b) {
        if (!a) return b;
        if (!b) return a;
        _push(a); _push(b);
        if (a->pri > b->pri) {
            a->r = merge(a->r, b);
            return _pull(a);
        }
        b->l = merge(a, b->l);
        return _pull(b);
    }
    // split into [0, k) and [k, inf)
    [[nodiscard]] pair<ptr, ptr> split(ptr root, int k) {
        if (!root) return {};
        _push(root);
        if (_getsiz(root->l) >= k) {
            auto [l, r] = split(root->l, k);
            root->l = r;
            return {l, _pull(root)};
        }
        auto [l, r] = split(root->r, k - _getsiz(root->l) - 1);
        root->r = l;
        return {_pull(root), r};
    }
    // split into [0, l), [l, r), [r, inf)
    [[nodiscard]] array<ptr, 3> split3(ptr root, int l, int r)
         {
        assert(l <= r);
        auto [r1, r23] = split(root, l);
        auto [r2, r3] = split(r23, r-l);
        return {r1, r2, r3};
    }
    // range query a[l..r) using t_combine
    [[nodiscard]] T range_query(ptr &a, int l, int r) {
        assert(0 <= l && l <= r && r <= _getsiz(a));
        auto [a1, a2, a3] = split3(a, l, r);
        T ans = a2->agg;
        a = merge(merge(a1, a2), a3);
        return ans;
    }
    // range apply 'u' to a[l..r)
    [[nodiscard]] ptr range_apply(ptr a, int l, int r, U u) {
        assert(0 <= l && l <= r && r <= _getsiz(a));
        if (l == r) return a;
        auto [a1, a2, a3] = split3(a, l, r);
        _apply_upd(a2, u);
        return merge(merge(a1, a2), a3);
    }
    [[nodiscard]] ptr build(const vector<T> &vals) {
        vector<unsigned long long> pris(sz(vals));
        for (auto &x : pris) x = rng();
        sort(rall(pris)); int ind = 0;

        auto f = [&](auto f, int l, int r) -> ptr {
            if (l == r) return {};
            int mid = midpoint(l, r);
            ptr node = &(arr[_last++] = Node(vals[mid]));
            node->pri = pris[ind++];

            node->l = f(f,  l, mid);
            node->r = f(f, mid+1, r);
            return _pull(node);
        };
        return f(f, 0, sz(vals));
    }
}
using namespace Treap;
```

## FenwickTree.h

**Description:** Computes partial sums a[0] + a[1] + ... + a[pos - 1], and updates single elements a[i], taking the difference between the old and new value.
**Time:** Both operations are $\mathcal{O}(\log N)$.

e62fac, 22 lines

```
struct FT {
  vector<ll> s;
  FT(int n) : s(n) {}
  void update(int pos, ll dif) { // a[pos] += dif
    for (; pos < sz(s); pos |= pos + 1) s[pos] += dif;
  }
  ll query(int pos) { // sum of values in [0, pos)
    ll res = 0;
    for (; pos > 0; pos &= pos - 1) res += s[pos-1];
    return res;
  }
  int lower_bound(ll sum) {// min pos st sum of [0, pos] >= sum
    // Returns n if no sum is >= sum, or -1 if empty sum is.
    if (sum <= 0) return -1;
    int pos = 0;
    for (int pw = 1 << 25; pw; pw >>= 1) {
      if (pos + pw <= sz(s) && s[pos + pw-1] < sum)
        pos += pw, sum -= s[pos-1];
    }
    return pos;
  }
};
```

## FenwickTree2d.h

**Description:** Computes sums a[i,j] for all i<I, j<J, and increases single elements a[i,j]. Requires that the elements to be updated are known in advance (call fakeUpdate() before init()).
**Time:** $\mathcal{O}\left(\log^2 N\right)$. (Use persistent segment trees for $\mathcal{O}(\log N)$.)

"FenwickTree.h" 157f07, 22 lines

```
struct FT2 {
  vector<vi> ys; vector<FT> ft;
  FT2(int limx) : ys(limx) {}
  void fakeUpdate(int x, int y) {
    for (; x < sz(ys); x |= x + 1) ys[x].push_back(y);
  }
  void init() {
    for (vi& v : ys) sort(all(v)), ft.emplace_back(sz(v));
  }
  int ind(int x, int y) {
    return (int)(lower_bound(all(ys[x]), y) - ys[x].begin()); }
  void update(int x, int y, ll dif) {
    for (; x < sz(ys); x |= x + 1)
      ft[x].update(ind(x, y), dif);
  }
  ll query(int x, int y) {
    ll sum = 0;
```

```
    for (; x; x &= x - 1)
      sum += ft[x-1].query(ind(x-1, y));
    return sum;
  }
};
```

### RMQ.h

**Description:** Range Minimum Queries on an array. Returns min(V[a], V[a + 1], ... V[b - 1]) in constant time.
**Usage:** `RMQ rmq(values);`
`rmq.query(inclusive, exclusive);`
**Time:** $\mathcal{O}(|V| \log |V| + Q)$

510c32, 16 lines

```
template<class T>
struct RMQ {
  vector<vector<T>> jmp;
  RMQ(const vector<T>& V) : jmp(1, V) {
    for (int pw = 1, k = 1; pw * 2 <= sz(V); pw *= 2, ++k) {
      jmp.emplace_back(sz(V) - pw * 2 + 1);
      rep(j,0,sz(jmp[k]))
        jmp[k][j] = min(jmp[k - 1][j], jmp[k - 1][j + pw]);
    }
  }
  T query(int a, int b) {
    assert(a < b); // or return inf if a == b
    int dep = 31 - __builtin_clz(b - a);
    return min(jmp[dep][a], jmp[dep][b - (1 << dep)]);
  }
};
```

### MoQueries.h

**Description:** Answer interval or tree path queries by moving from one query to the next by adding/removing points at the ends. If values are on tree edges, change `step` to add/remove the edge $(a, c)$ and remove the initial `add` call (but keep `in`).
**Time:** $\mathcal{O}\left(N\sqrt{Q}\right)$

ac9594, 49 lines

```
void add(int ind, int end) { ... } // add a[ind] (end = 0 or 1)
void del(int ind, int end) { ... } // remove a[ind]
int calc() { ... } // compute current answer

vi mo(vector<pii> Q) {
  int L = 1, R = 1, blk = 350; // ~N/sqrt(Q)
  vi s(sz(Q)), res = s;
#define K(x) pii(x.first/blk, x.second ^ -(x.first/blk & 1))
  iota(all(s), 0);
  sort(all(s), [&](int s, int t){ return K(Q[s]) < K(Q[t]); });
    for (int qi : s) {
        auto [x, y] = Q[qi];
        while (L > x) add(--L, 0);
        while (R < y) add(R++, 1);
        while (L < x) del(L++, 0);
        while (R > y) del(--R, 1);
        res[qi] = calc();
    }
  return res; // Q must use [L, R) (incl–excl) intervals.
}

vi moTree(vector<array<int, 2>> Q, vector<vi>& ed, int root=0)
    {
  int N = sz(ed), pos[2] = {root, root}, blk = 126; // ~N/sqrt(
      Q)
  vi s(sz(Q)), res = s, I(N), L(N), R(N), in(N), par(N);
  add(root, 0), in[root] = 1;
  auto dfs = [&](int x, int p, int dep, auto& f) -> void {
    par[x] = p;
    L[x] = N;
    if (dep) I[x] = N++;
    for (int y : ed[x]) if (y != p) f(y, x, !dep, f);
    if (!dep) I[x] = N++;
    R[x] = N;
  };
  dfs(root, -1, 0, dfs);
#define K(x) pii(I[x[0]] / blk, I[x[1]] ^ -(I[x[0]] / blk & 1))
  iota(all(s), 0);
  sort(all(s), [&](int s, int t){ return K(Q[s]) < K(Q[t]); });
  for (int qi : s) rep(end,0,2) {
    int &a = pos[end], b = Q[qi][end], i = 0;
#define step(c) { if (in[c]) { del(a, end); in[a] = 0; } \
                  else { add(c, end); in[c] = 1; } a = c; }
    while (!(L[b] <= L[a] && R[a] <= R[b]))
      I[i++] = b, b = par[b];
    while (a != b) step(par[a]);
    while (i--) step(I[i]);
    if (end) res[qi] = calc();
  }
  return res; // Q must use [L, R] (incl–incl) intervals.
}
```

# Numerical (4)

## 4.1 Polynomials and recurrences

### Polynomial.h

c9b7b0, 17 lines

```
struct Poly {
  vector<double> a;
  double operator()(double x) const {
    double val = 0;
    for (int i = sz(a); i--;) (val *= x) += a[i];
    return val;
  }
  void diff() {
    rep(i,1,sz(a)) a[i-1] = i*a[i];
    a.pop_back();
  }
  void divroot(double x0) {
    double b = a.back(), c; a.back() = 0;
    for(int i=sz(a)-1; i--;) c = a[i], a[i] = a[i+1]*x0+b, b=c;
    a.pop_back();
  }
};
```

### PolyRoots.h

**Description:** Finds the real roots to a polynomial.
**Usage:** `polyRoots({{2,-3,1}},-1e9,1e9) // solve x^2-3x+2 = 0`
**Time:** $\mathcal{O}\left(n^2 \log(1/\epsilon)\right)$

"Polynomial.h" b00bfe, 23 lines

```
vector<double> polyRoots(Poly p, double xmin, double xmax) {
  if (sz(p.a) == 2) { return {-p.a[0]/p.a[1]}; }
  vector<double> ret;
  Poly der = p;
  der.diff();
  auto dr = polyRoots(der, xmin, xmax);
  dr.push_back(xmin-1);
  dr.push_back(xmax+1);
  sort(all(dr));
  rep(i,0,sz(dr)-1) {
    double l = dr[i], h = dr[i+1];
    bool sign = p(l) > 0;
    if (sign ^ (p(h) > 0)) {
      rep(it,0,60) { // while (h - l > 1e-8)
        double m = (l + h) / 2, f = p(m);
        if ((f <= 0) ^ sign) l = m;
        else h = m;
      }
      ret.push_back((l + h) / 2);
    }
  }
  return ret;
}
```

### PolyInterpolate.h

**Description:** Given $n$ points (x[i], y[i]), computes an n-1-degree polynomial $p$ that passes through them: $p(x) = a[0] * x^0 + ... + a[n-1] * x^{n-1}$. For numerical precision, pick $x[k] = c * \cos(k/(n-1) * \pi), k = 0 \ldots n-1$.
**Time:** $\mathcal{O}\left(n^2\right)$

08bf48, 13 lines

```
typedef vector<double> vd;
vd interpolate(vd x, vd y, int n) {
  vd res(n), temp(n);
  rep(k,0,n-1) rep(i,k+1,n)
    y[i] = (y[i] - y[k]) / (x[i] - x[k]);
  double last = 0; temp[0] = 1;
  rep(k,0,n) rep(i,0,n) {
    res[i] += y[k] * temp[i];
    swap(last, temp[i]);
    temp[i] -= last * x[k];
  }
  return res;
}
```

### BerlekampMassey.h

**Description:** Recovers any $n$-order linear recurrence relation from the first $2n$ terms of the recurrence. Useful for guessing linear recurrences after brute-forcing the first terms. Should work on any field, but numerical stability for floats is not guaranteed. Output will have size $\leq n$.
**Usage:** `berlekampMassey({0, 1, 1, 3, 5, 11}) // {1, 2}`
**Time:** $\mathcal{O}\left(N^2\right)$

"../number-theory/ModPow.h" 96548b, 20 lines

```
vector<ll> berlekampMassey(vector<ll> s) {
  int n = sz(s), L = 0, m = 0;
  vector<ll> C(n), B(n), T;
  C[0] = B[0] = 1;

  ll b = 1;
  rep(i,0,n) { ++m;
    ll d = s[i] % mod;
    rep(j,1,L+1) d = (d + C[j] * s[i - j]) % mod;
    if (!d) continue;
    T = C; ll coef = d * modpow(b, mod-2) % mod;
    rep(j,m,n) C[j] = (C[j] - coef * B[j - m]) % mod;
    if (2 * L > i) continue;
    L = i + 1 - L; B = T; b = d; m = 0;
  }

  C.resize(L + 1); C.erase(C.begin());
  for (ll& x : C) x = (mod - x) % mod;
  return C;
}
```

### LinearRecurrence.h

**Description:** Generates the $k$'th term of an $n$-order linear recurrence $S[i] = \sum_j S[i-j-1]tr[j]$, given $S[0 \ldots \geq n-1]$ and $tr[0 \ldots n-1]$. Faster than matrix multiplication. Useful together with Berlekamp–Massey.
**Usage:** `linearRec({0, 1}, {1, 1}, k) // k'th Fibonacci number`
**Time:** $\mathcal{O}\left(n^2 \log k\right)$

47555d, 27 lines

```
typedef vector<ll> Poly;
ll linearRec(Poly S, Poly tr, ll k) {
  int n = sz(tr);
  if (n == 0) return S[0];
```

```
  auto combine = [&](Poly a, Poly b) {
    Poly res(n * 2 + 1);
    rep(i,0,n+1) rep(j,0,n+1)
      res[i + j] = (res[i + j] + a[i] * b[j]) % mod;
    for (int i = 2 * n; i > n; --i) rep(j,0,n)
      res[i - 1 - j] = (res[i - 1 - j] + res[i] * tr[j]) % mod;
    res.resize(n + 1);
    return res;
  };

  Poly pol(n + 1), e(pol);
  pol[0] = e[1] = 1;

  for (++k; k; k /= 2) {
    if (k % 2) pol = combine(pol, e);
    e = combine(e, e);
  }

  ll res = 0;
  rep(i,0,n) res = (res + pol[i + 1] * S[i]) % mod;
  return res;
}
```

## 4.2 Optimization

### GoldenSectionSearch.h

**Description:** Finds the argument minimizing the function $f$ in the interval $[a, b]$ assuming $f$ is unimodal on the interval, i.e. has only one local minimum and no local maximum. The maximum error in the result is $eps$. Works equally well for maximization with a small change in the code. See TernarySearch.h in the Various chapter for a discrete version.
**Usage:** `double func(double x) { return 4+x+.3*x*x; }`
`double xmin = gss(-1000,1000,func);`
**Time:** $\mathcal{O}\left(\log((b-a)/\epsilon)\right)$

31d45b, 14 lines

```
double gss(double a, double b, double (*f)(double)) {
  double r = (sqrt(5)-1)/2, eps = 1e-7;
  double x1 = b - r*(b-a), x2 = a + r*(b-a);
  double f1 = f(x1), f2 = f(x2);
  while (b-a > eps)
    if (f1 < f2) { //change to > to find maximum
      b = x2; x2 = x1; f2 = f1;
      x1 = b - r*(b-a); f1 = f(x1);
    } else {
      a = x1; x1 = x2; f1 = f2;
      x2 = a + r*(b-a); f2 = f(x2);
    }
  return a;
}
```

### HillClimbing.h

**Description:** Poor man's optimization for unimodal functions.

8eeeaf, 14 lines

```
typedef array<double, 2> P;

template<class F> pair<double, P> hillClimb(P start, F f) {
  pair<double, P> cur(f(start), start);
  for (double jmp = 1e9; jmp > 1e-20; jmp /= 2) {
    rep(j,0,100) rep(dx,-1,2) rep(dy,-1,2) {
      P p = cur.second;
      p[0] += dx*jmp;
      p[1] += dy*jmp;
      cur = min(cur, make_pair(f(p), p));
    }
  }
  return cur;
}
```

### Integrate.h

**Description:** Simple integration of a function over an interval using Simpson's rule. The error should be proportional to $h^4$, although in practice you will want to verify that the result is stable to desired precision when epsilon changes.

4756fc, 7 lines

```
template<class F>
double quad(double a, double b, F f, const int n = 1000) {
  double h = (b - a) / 2 / n, v = f(a) + f(b);
  rep(i,1,n*2)
    v += f(a + i*h) * (i&1 ? 4 : 2);
  return v * h / 3;
}
```

### IntegrateAdaptive.h

**Description:** Fast integration using an adaptive Simpson's rule.
**Usage:** `double sphereVolume = quad(-1, 1, [](double x) {`
`return quad(-1, 1, [&](double y) {`
`return quad(-1, 1, [&](double z) {`
`return x*x + y*y + z*z < 1; });});});`

92dd79, 15 lines

```
typedef double d;
#define S(a,b) (f(a) + 4*f((a+b) / 2) + f(b)) * (b-a) / 6

template <class F>
d rec(F& f, d a, d b, d eps, d S) {
  d c = (a + b) / 2;
  d S1 = S(a, c), S2 = S(c, b), T = S1 + S2;
  if (abs(T - S) <= 15 * eps || b - a < 1e-10)
    return T + (T - S) / 15;
  return rec(f, a, c, eps / 2, S1) + rec(f, c, b, eps / 2, S2);
}
template<class F>
d quad(d a, d b, F f, d eps = 1e-8) {
  return rec(f, a, b, eps, S(a, b));
}
```

### Simplex.h

**Description:** Solves a general linear maximization problem: maximize $c^T x$ subject to $Ax \leq b$, $x \geq 0$. Returns -inf if there is no solution, inf if there are arbitrarily good solutions, or the maximum value of $c^T x$ otherwise. The input vector is set to an optimal $x$ (or in the unbounded case, an arbitrary solution fulfilling the constraints). Numerical stability is not guaranteed. For better performance, define variables such that $x = 0$ is viable.
**Usage:** `vvd A = {{1,-1}, {-1,1}, {-1,-2}};`
`vd b = {1,1,-4}, c = {-1,-1}, x;`
`T val = LPSolver(A, b, c).solve(x);`
**Time:** $\mathcal{O}\left(NM * \#pivots\right)$, where a pivot may be e.g. an edge relaxation. $\mathcal{O}\left(2^n\right)$ in the general case.

aa8530, 68 lines

```
typedef double T; // long double, Rational, double + mod<P>...
typedef vector<T> vd;
typedef vector<vd> vvd;

const T eps = 1e-8, inf = 1/.0;
#define MP make_pair
#define ltj(X) if(s == -1 || MP(X[j],N[j]) < MP(X[s],N[s])) s=j

struct LPSolver {
  int m, n;
  vi N, B;
  vvd D;

  LPSolver(const vvd& A, const vd& b, const vd& c) :
    m(sz(b)), n(sz(c)), N(n+1), B(m), D(m+2, vd(n+2)) {
      rep(i,0,m) rep(j,0,n) D[i][j] = A[i][j];
      rep(i,0,m) { B[i] = n+i; D[i][n] = -1; D[i][n+1] = b[i];}
      rep(j,0,n) { N[j] = j; D[m][j] = -c[j]; }
      N[n] = -1; D[m+1][n] = 1;
    }

  void pivot(int r, int s) {
    T *a = D[r].data(), inv = 1 / a[s];
    rep(i,0,m+2) if (i != r && abs(D[i][s]) > eps) {
      T *b = D[i].data(), inv2 = b[s] * inv;
      rep(j,0,n+2) b[j] -= a[j] * inv2;
      b[s] = a[s] * inv2;
    }
    rep(j,0,n+2) if (j != s) D[r][j] *= inv;
    rep(i,0,m+2) if (i != r) D[i][s] *= -inv;
    D[r][s] = inv;
    swap(B[r], N[s]);
  }

  bool simplex(int phase) {
    int x = m + phase - 1;
    for (;;) {
      int s = -1;
      rep(j,0,n+1) if (N[j] != -phase) ltj(D[x]);
      if (D[x][s] >= -eps) return true;
      int r = -1;
      rep(i,0,m) {
        if (D[i][s] <= eps) continue;
        if (r == -1 || MP(D[i][n+1] / D[i][s], B[i])
                     < MP(D[r][n+1] / D[r][s], B[r])) r = i;
      }
      if (r == -1) return false;
      pivot(r, s);
    }
  }

  T solve(vd &x) {
    int r = 0;
    rep(i,1,m) if (D[i][n+1] < D[r][n+1]) r = i;
    if (D[r][n+1] < -eps) {
      pivot(r, n);
      if (!simplex(2) || D[m+1][n+1] < -eps) return -inf;
      rep(i,0,m) if (B[i] == -1) {
        int s = 0;
        rep(j,1,n+1) ltj(D[i]);
        pivot(i, s);
      }
    }
    bool ok = simplex(1); x = vd(n);
    rep(i,0,m) if (B[i] < n) x[B[i]] = D[i][n+1];
    return ok ? D[m][n+1] : inf;
  }
};
```

## 4.3 Matrices

### Determinant.h

**Description:** Calculates determinant of a matrix. Destroys the matrix.
**Time:** $\mathcal{O}\left(N^3\right)$

bd5cec, 15 lines

```
double det(vector<vector<double>>& a) {
  int n = sz(a); double res = 1;
  rep(i,0,n) {
    int b = i;
    rep(j,i+1,n) if (fabs(a[j][i]) > fabs(a[b][i])) b = j;
    if (i != b) swap(a[i], a[b]), res *= -1;
    res *= a[i][i];
    if (res == 0) return 0;
    rep(j,i+1,n) {
      double v = a[j][i] / a[i][i];
      if (v != 0) rep(k,i+1,n) a[j][k] -= v * a[i][k];
    }
```

```
  }
  return res;
}
```

## IntDeterminant.h

**Description:** Calculates determinant using modular arithmetics. Modulos can also be removed to get a pure-integer version.
**Time:** $\mathcal{O}(N^3)$

3313dc, 18 lines

```
const ll mod = 12345;
ll det(vector<vector<ll>>& a) {
  int n = sz(a); ll ans = 1;
  rep(i,0,n) {
    rep(j,i+1,n) {
      while (a[j][i] != 0) { // gcd step
        ll t = a[i][i] / a[j][i];
        if (t) rep(k,i,n)
          a[i][k] = (a[i][k] - a[j][k] * t) % mod;
        swap(a[i], a[j]);
        ans *= -1;
      }
    }
    ans = ans * a[i][i] % mod;
    if (!ans) return 0;
  }
  return (ans + mod) % mod;
}
```

## SolveLinear.h

**Description:** Solves $A * x = b$. If there are multiple solutions, an arbitrary one is returned. Returns rank, or -1 if no solutions. Data in $A$ and $b$ is lost.
**Time:** $\mathcal{O}(n^2 m)$

44c9ab, 38 lines

```
typedef vector<double> vd;
const double eps = 1e-12;

int solveLinear(vector<vd>& A, vd& b, vd& x) {
  int n = sz(A), m = sz(x), rank = 0, br, bc;
  if (n) assert(sz(A[0]) == m);
  vi col(m); iota(all(col), 0);

  rep(i,0,n) {
    double v, bv = 0;
    rep(r,i,n) rep(c,i,m)
      if ((v = fabs(A[r][c])) > bv)
        br = r, bc = c, bv = v;
    if (bv <= eps) {
      rep(j,i,n) if (fabs(b[j]) > eps) return -1;
      break;
    }
    swap(A[i], A[br]);
    swap(b[i], b[br]);
    swap(col[i], col[bc]);
    rep(j,0,n) swap(A[j][i], A[j][bc]);
    bv = 1/A[i][i];
    rep(j,i+1,n) {
      double fac = A[j][i] * bv;
      b[j] -= fac * b[i];
      rep(k,i+1,m) A[j][k] -= fac*A[i][k];
    }
    rank++;
  }

  x.assign(m, 0);
  for (int i = rank; i--;) {
    b[i] /= A[i][i];
    x[col[i]] = b[i];
    rep(j,0,i) b[j] -= A[j][i] * b[i];
  }
  return rank; // (multiple solutions if rank < m)
}
```

## SolveLinear2.h

**Description:** To get all uniquely determined values of $x$ back from SolveLinear, make the following changes:

"SolveLinear.h" 08e495, 7 lines

```
rep(j,0,n) if (j != i) // instead of rep(j,i+1,n)
// ... then at the end:
x.assign(m, undefined);
rep(i,0,rank) {
  rep(j,rank,m) if (fabs(A[i][j]) > eps) goto fail;
  x[col[i]] = b[i] / A[i][i];
fail:; }
```

## SolveLinearBinary.h

**Description:** Solves $Ax = b$ over $\mathbb{F}_2$. If there are multiple solutions, one is returned arbitrarily. Returns rank, or -1 if no solutions. Destroys $A$ and $b$.
**Time:** $\mathcal{O}(n^2 m)$

fa2d7a, 34 lines

```
typedef bitset<1000> bs;

int solveLinear(vector<bs>& A, vi& b, bs& x, int m) {
  int n = sz(A), rank = 0, br;
  assert(m <= sz(x));
  vi col(m); iota(all(col), 0);
  rep(i,0,n) {
    for (br=i; br<n; ++br) if (A[br].any()) break;
    if (br == n) {
      rep(j,i,n) if(b[j]) return -1;
      break;
    }
    int bc = (int)A[br]._Find_next(i-1);
    swap(A[i], A[br]);
    swap(b[i], b[br]);
    swap(col[i], col[bc]);
    rep(j,0,n) if (A[j][i] != A[j][bc]) {
      A[j].flip(i); A[j].flip(bc);
    }
    rep(j,i+1,n) if (A[j][i]) {
      b[j] ^= b[i];
      A[j] ^= A[i];
    }
    rank++;
  }

  x = bs();
  for (int i = rank; i--;) {
    if (!b[i]) continue;
    x[col[i]] = 1;
    rep(j,0,i) b[j] ^= A[j][i];
  }
  return rank; // (multiple solutions if rank < m)
}
```

## MatrixInverse.h

**Description:** Invert matrix $A$. Returns rank; result is stored in $A$ unless singular (rank < n). Can easily be extended to prime moduli; for prime powers, repeatedly set $A^{-1} = A^{-1}(2I - AA^{-1})$ (mod $p^k$) where $A^{-1}$ starts as the inverse of A mod p, and k is doubled in each step.
**Time:** $\mathcal{O}(n^3)$

ebfff6, 35 lines

```
int matInv(vector<vector<double>>& A) {
  int n = sz(A); vi col(n);
  vector<vector<double>> tmp(n, vector<double>(n));
  rep(i,0,n) tmp[i][i] = 1, col[i] = i;

  rep(i,0,n) {
    int r = i, c = i;
    rep(j,i,n) rep(k,i,n)
      if (fabs(A[j][k]) > fabs(A[r][c]))
        r = j, c = k;
    if (fabs(A[r][c]) < 1e-12) return i;
    A[i].swap(A[r]); tmp[i].swap(tmp[r]);
    rep(j,0,n)
      swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
    swap(col[i], col[c]);
    double v = A[i][i];
    rep(j,i+1,n) {
      double f = A[j][i] / v;
      A[j][i] = 0;
      rep(k,i+1,n) A[j][k] -= f*A[i][k];
      rep(k,0,n) tmp[j][k] -= f*tmp[i][k];
    }
    rep(j,i+1,n) A[i][j] /= v;
    rep(j,0,n) tmp[i][j] /= v;
    A[i][i] = 1;
  }

  for (int i = n-1; i > 0; --i) rep(j,0,i) {
    double v = A[j][i];
    rep(k,0,n) tmp[j][k] -= v*tmp[i][k];
  }

  rep(i,0,n) rep(j,0,n) A[col[i]][col[j]] = tmp[i][j];
  return n;
}
```

## Tridiagonal.h

**Description:** $x = \text{tridiagonal}(d, p, q, b)$ solves the equation system

$$\begin{pmatrix} b_0 \\ b_1 \\ b_2 \\ b_3 \\ \vdots \\ b_{n-1} \end{pmatrix} = \begin{pmatrix} d_0 & p_0 & 0 & 0 & \cdots & 0 \\ q_0 & d_1 & p_1 & 0 & \cdots & 0 \\ 0 & q_1 & d_2 & p_2 & \cdots & 0 \\ \vdots & \vdots & \ddots & \ddots & \ddots & \vdots \\ 0 & 0 & \cdots & q_{n-3} & d_{n-2} & p_{n-2} \\ 0 & 0 & \cdots & 0 & q_{n-2} & d_{n-1} \end{pmatrix} \begin{pmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ \vdots \\ x_{n-1} \end{pmatrix}.$$

This is useful for solving problems on the type

$$a_i = b_i a_{i-1} + c_i a_{i+1} + d_i,\ 1 \le i \le n,$$

where $a_0$, $a_{n+1}$, $b_i$, $c_i$ and $d_i$ are known. $a$ can then be obtained from

$$\{a_i\} = \text{tridiagonal}(\{1, -1, -1, ..., -1, 1\}, \{0, c_1, c_2, \ldots, c_n\}, \{b_1, b_2, \ldots, b_n, 0\}, \{a_0, d_1, d_2, \ldots, d_n, a_{n+1}\}).$$

Fails if the solution is not unique.
If $|d_i| > |p_i| + |q_{i-1}|$ for all $i$, or $|d_i| > |p_{i-1}| + |q_i|$, or the matrix is positive definite, the algorithm is numerically stable and neither `tr` nor the check for `diag[i] == 0` is needed.
**Time:** $\mathcal{O}(N)$

8f9fa8, 26 lines

```
typedef double T;
vector<T> tridiagonal(vector<T> diag, const vector<T>& super,
    const vector<T>& sub, vector<T> b) {
  int n = sz(b); vi tr(n);
  rep(i,0,n-1) {
    if (abs(diag[i]) < 1e-9 * abs(super[i])) { // diag[i] == 0
      b[i+1] -= b[i] * diag[i+1] / super[i];
      if (i+2 < n) b[i+2] -= b[i] * sub[i+1] / super[i];
      diag[i+1] = sub[i]; tr[++i] = 1;
    } else {
      diag[i+1] -= super[i]*sub[i]/diag[i];
      b[i+1] -= b[i]*sub[i]/diag[i];
    }
  }
  for (int i = n; i--;) {
    if (tr[i]) {
      swap(b[i], b[i-1]);
```

```
      diag[i-1] = diag[i];
      b[i] /= super[i-1];
    } else {
      b[i] /= diag[i];
      if (i) b[i-1] -= b[i]*super[i-1];
    }
  }
  return b;
}
```

## 4.4 Fourier transforms

### FastFourierTransform.h

**Description:** fft(a) computes $\hat{f}(k) = \sum_x a[x] \exp(2\pi i \cdot kx/N)$ for all $k$. N must be a power of 2. Useful for convolution: `conv(a, b) = c`, where $c[x] = \sum a[i]b[x-i]$. For convolution of complex numbers or more than two vectors: FFT, multiply pointwise, divide by n, reverse(start+1, end), FFT back. Rounding is safe if $(\sum a_i^2 + \sum b_i^2) \log_2 N < 9 \cdot 10^{14}$ (in practice $10^{16}$; higher for random inputs). Otherwise, use NTT/FFTMod.
**Time:** $\mathcal{O}(N \log N)$ with $N = |A| + |B|$ ($\sim$1s for $N = 2^{22}$)

00ced6, 35 lines

```
typedef complex<double> C;
typedef vector<double> vd;
void fft(vector<C>& a) {
  int n = sz(a), L = 31 - __builtin_clz(n);
  static vector<complex<long double>> R(2, 1);
  static vector<C> rt(2, 1);  // (^ 10% faster if double)
  for (static int k = 2; k < n; k *= 2) {
    R.resize(n); rt.resize(n);
    auto x = polar(1.0L, acos(-1.0L) / k);
    rep(i,k,2*k) rt[i] = R[i] = i&1 ? R[i/2] * x : R[i/2];
  }
  vi rev(n);
  rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
  rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
  for (int k = 1; k < n; k *= 2)
    for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
      C z = rt[j+k] * a[i+j+k]; // (25% faster if hand-rolled)
      a[i + j + k] = a[i + j] - z;
      a[i + j] += z;
    }
}
vd conv(const vd& a, const vd& b) {
  if (a.empty() || b.empty()) return {};
  vd res(sz(a) + sz(b) - 1);
  int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
  vector<C> in(n), out(n);
  copy(all(a), begin(in));
  rep(i,0,sz(b)) in[i].imag(b[i]);
  fft(in);
  for (C& x : in) x *= x;
  rep(i,0,n) out[i] = in[-i & (n - 1)] - conj(in[i]);
  fft(out);
  rep(i,0,sz(res)) res[i] = imag(out[i]) / (4 * n);
  return res;
}
```

### FastFourierTransformMod.h

**Description:** Higher precision FFT, can be used for convolutions modulo arbitrary integers as long as $N \log_2 N \cdot \text{mod} < 8.6 \cdot 10^{14}$ (in practice $10^{16}$ or higher). Inputs must be in $[0, \text{mod})$.
**Time:** $\mathcal{O}(N \log N)$, where $N = |A| + |B|$ (twice as slow as NTT or FFT)

"FastFourierTransform.h" b82773, 22 lines

```
typedef vector<ll> vl;
template<int M> vl convMod(const vl &a, const vl &b) {
  if (a.empty() || b.empty()) return {};
  vl res(sz(a) + sz(b) - 1);
  int B=32-__builtin_clz(sz(res)), n=1<<B, cut=int(sqrt(M));
  vector<C> L(n), R(n), outs(n), outl(n);
  rep(i,0,sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] % cut);
  rep(i,0,sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] % cut);
  fft(L), fft(R);
  rep(i,0,n) {
    int j = -i & (n - 1);
    outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
    outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
  }
  fft(outl), fft(outs);
  rep(i,0,sz(res)) {
    ll av = ll(real(outl[i])+.5), cv = ll(imag(outs[i])+.5);
    ll bv = ll(imag(outl[i])+.5) + ll(real(outs[i])+.5);
    res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
  }
  return res;
}
```

### NumberTheoreticTransform.h

**Description:** ntt(a) computes $\hat{f}(k) = \sum_x a[x] g^{xk}$ for all $k$, where $g = \text{root}^{(mod-1)/N}$. N must be a power of 2. Useful for convolution modulo specific nice primes of the form $2^a b + 1$, where the convolution result has size at most $2^a$. For arbitrary modulo, see FFTMod. `conv(a, b) = c`, where $c[x] = \sum a[i]b[x-i]$. For manual convolution: NTT the inputs, multiply pointwise, divide by n, reverse(start+1, end), NTT back. Inputs must be in $[0, \text{mod})$.
**Time:** $\mathcal{O}(N \log N)$

"../number-theory/ModPow.h" ced03d, 35 lines

```
const ll mod = (119 << 23) + 1, root = 62; // = 998244353
// For p < 2^30 there is also e.g. 5 << 25, 7 << 26, 479 << 21
// and 483 << 21 (same root). The last two are > 10^9.
typedef vector<ll> vl;
void ntt(vl &a) {
  int n = sz(a), L = 31 - __builtin_clz(n);
  static vl rt(2, 1);
  for (static int k = 2, s = 2; k < n; k *= 2, s++) {
    rt.resize(n);
    ll z[] = {1, modpow(root, mod >> s)};
    rep(i,k,2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
  }
  vi rev(n);
  rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
  rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
  for (int k = 1; k < n; k *= 2)
    for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
      ll z = rt[j + k] * a[i + j + k] % mod, &ai = a[i + j];
      a[i + j + k] = ai - z + (z > ai ? mod : 0);
      ai += (ai + z >= mod ? z - mod : z);
    }
}
vl conv(const vl &a, const vl &b) {
  if (a.empty() || b.empty()) return {};
  int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s),
      n = 1 << B;
  int inv = modpow(n, mod - 2);
  vl L(a), R(b), out(n);
  L.resize(n), R.resize(n);
  ntt(L), ntt(R);
  rep(i,0,n)
    out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv % mod;
  ntt(out);
  return {out.begin(), out.begin() + s};
}
```

### FastSubsetTransform.h

**Description:** Transform to a basis with fast convolutions of the form $c[z] = \sum_{z=x \oplus y} a[x] \cdot b[y]$, where $\oplus$ is one of AND, OR, XOR. The size of $a$ must be a power of two.
**Time:** $\mathcal{O}(N \log N)$

3de923, 35 lines

```
using vl = vector<ll>;
void FST(vl& a, bool inv) {
    for (int n = sz(a), step = 1; step < n; step *= 2) {
        for (int i = 0; i < n; i += 2 * step) rep(j,i,i+step) {
            ll &u = a[j], &v = a[j + step]; tie(u, v) =
                inv ? pair(v - u, u) : pair(v, u + v); // AND
                inv ? pair(v, u - v) : pair(u + v, u); // OR
                pair(u + v, u - v);                    // XOR
        }
    }
    if (inv) for (ll& x : a) x /= sz(a); // XOR
}
vl conv(vl a, vl b) {
    FST(a, 0); FST(b, 0);
    rep(i,0,sz(a)) a[i] *= b[i];
    FST(a, 1); return a;
}
int psgn(int x) { return __builtin_popcount(x)&1 ? -1 : 1; }
// a[i] += val (for transformed a)
void point_add(vl &a, int i, ll val) {
    rep(j,0,sz(a))
        a[j] += val * ((i|j) == sz(a)-1); // AND
        a[j] += val * ((i&j) == 0); // OR
        a[j] += val * psgn(i&j); // XOR
}
// return a[i] (for transformed a)
ll point_eval(const vl &a, int i) {
    ll res = 0;
    rep(j,0,sz(a))
        res += a[j] * ((i&j) == 0) * psgn(sz(a)-1-(i|j)); //
         AND
        res += a[j] * ((i|j) == sz(a)-1) * psgn(i&j); // OR
        res += a[j] * psgn(i&j); // XOR
    res /= sz(a); // XOR
    return res;
}
```

### MaxPlusConvolution.h

**Description:** Given arrays $a$, $b$ where $b$ is concave, return the array $c_k = \max_{i+j=k}(a_i + b_j)$ of size equal to $a$. A zero is implicitly inserted at the start of $b$.
**Time:** $\mathcal{O}(N \log N)$

709c52, 44 lines

```
using vll = vector<ll>;
vll maxPlusConv(const vll& a, const vll& b) {
  if (b.empty()) return a;
  using Seg = array<ll, 3>;
  auto eval = [&](Seg& seg, ll x) {
    ll offset = x - seg[0];
    assert(0 <= seg[1]+offset && seg[1]+offset < sz(b));
    return b[seg[1] + offset] + seg[2];
  };
  auto endIndex = [&](Seg& seg) {
    return seg[0] + sz(b) - seg[1];
  };
  vector<Seg> stk;
  rep(i, 0, sz(a)) {
    Seg seg{i + 1, 0, a[i]};
    while (!stk.empty()) {
      ll idx = stk.back()[0];
      if (idx<seg[0] || eval(stk.back(), idx) > eval(seg, idx))
        break;
      stk.pop_back();
    }
    if (!stk.empty() && endIndex(stk.back()) > seg[0]
        && eval(stk.back(), seg[0]) > eval(seg, seg[0])) {
      ll lo = seg[0];
```

```
      ll hi = min(endIndex(stk.back()), endIndex(seg));
      while (lo + 1 < hi) {
        ll mid = midpoint(lo, hi);
        if (eval(stk.back(), mid) > eval(seg, mid)) lo = mid;
        else hi = mid;
      }
      seg[1] = hi - seg[0];
      seg[0] = hi;
    }
    stk.push_back(seg);
  }
  vll ans = a;
  auto it = stk.begin();
  rep(i, 1, sz(ans)) {
    while (next(it) != stk.end() && (*next(it))[0] <= i)
      ++it;
    ans[i] = max(ans[i], eval(*it, i));
  }
  return ans;
}
```

# Number theory (5)

## 5.1 Modular arithmetic

### ModularArithmetic.h

**Description:** Modular arithmetic. Assumes $MOD$ is prime.
**Usage:** `mi a = MOD+5; inv(a); // 400000003`

0db02d, 27 lines

```
template<int M> struct mint {
    static const int mod = M;
    int v;
    explicit operator int() const { return v; }
    mint():v(0) {}
    mint(ll _v):v(_v%M) { v += (v<0)*M; }
    mint& operator+=(mint o) {
        if ((v += o.v) >= M) v -= M;
        return *this; }
    mint& operator-=(mint o) {
        if ((v -= o.v) < 0) v += M;
        return *this; }
    mint& operator*=(mint o) {
        v = (ll)v*o.v%M; return *this; }
    friend mint pow(mint a, ll p) { assert(p >= 0);
        return p==0?1:pow(a*a,p/2)*(p&1?a:1); }
    friend mint inv(mint a) { assert(a.v != 0);
        return pow(a,M-2); }
    friend mint operator+(mint a, mint b) { return a += b; }
    friend mint operator-(mint a, mint b) { return a -= b; }
    friend mint operator*(mint a, mint b) { return a *= b; }
    friend istream& operator>>(istream& is, mint& a) { // &
        return is >> a.v; } // only for [0, mod)
    friend ostream& operator<<(ostream& os, mint a) { // no &
        return os << a.v; }
};
using mi = mint<0>; // change to something else
```

### ModInverse.h

**Description:** Pre-computation of modular inverses. Assumes LIM $\leq$ mod and that mod is a prime.

6f684f, 3 lines

```
const ll mod = 1000000007, LIM = 200000;
ll* inv = new ll[LIM] - 1; inv[1] = 1;
rep(i,2,LIM) inv[i] = mod - (mod / i) * inv[mod % i] % mod;
```

### ModPow.h

b83e45, 8 lines

```
const ll mod = 1000000007; // faster if const

ll modpow(ll b, ll e) {
  ll ans = 1;
  for (; e; b = b * b % mod, e /= 2)
    if (e & 1) ans = ans * b % mod;
  return ans;
}
```

### ModLog.h

**Description:** Returns the smallest $x > 0$ s.t. $a^x = b \pmod m$, or $-1$ if no such $x$ exists. modLog(a,1,m) can be used to calculate the order of $a$.
**Time:** $\mathcal{O}\left(\sqrt{m}\right)$

c040b8, 11 lines

```
ll modLog(ll a, ll b, ll m) {
  ll n = (ll) sqrt(m) + 1, e = 1, f = 1, j = 1;
  unordered_map<ll, ll> A;
  while (j <= n && (e = f = e * a % m) != b % m)
    A[e * b % m] = j++;
  if (e == b % m) return j;
  if (__gcd(m, e) == __gcd(m, b))
    rep(i,2,n+2) if (A.count(e = e * f % m))
      return n * i - A[e];
  return -1;
}
```

### ModSum.h

**Description:** Sums of mod'ed arithmetic progressions.
modsum(to, c, k, m) $= \sum_{i=0}^{to-1} (ki + c)\%m$. divsum is similar but for floored division.
**Time:** $\log(m)$, with a large constant.

5c5bc5, 16 lines

```
typedef unsigned long long ull;
ull sumsq(ull to) { return to / 2 * ((to-1) | 1); }

ull divsum(ull to, ull c, ull k, ull m) {
  ull res = k / m * sumsq(to) + c / m * to;
  k %= m; c %= m;
  if (!k) return res;
  ull to2 = (to * k + c) / m;
  return res + (to - 1) * to2 - divsum(to2, m-1 - c, m, k);
}

ll modsum(ull to, ll c, ll k, ll m) {
  c = ((c % m) + m) % m;
  k = ((k % m) + m) % m;
  return to * c + k * sumsq(to) - m * divsum(to, c, k, m);
}
```

### ModMulLL.h

**Description:** Calculate $a \cdot b \bmod c$ (or $a^b \bmod c$) for $0 \leq a, b \leq c \leq 7.2 \cdot 10^{18}$.
**Time:** $\mathcal{O}(1)$ for `modmul`, $\mathcal{O}(\log b)$ for `modpow`

bbbd8f, 11 lines

```
typedef unsigned long long ull;
ull modmul(ull a, ull b, ull M) {
  ll ret = a * b - M * ull(1.L / M * a * b);
  return ret + M * (ret < 0) - M * (ret >= (ll)M);
}
ull modpow(ull b, ull e, ull mod) {
  ull ans = 1;
  for (; e; b = modmul(b, b, mod), e /= 2)
    if (e & 1) ans = modmul(ans, b, mod);
  return ans;
}
```

### ModSqrt.h

**Description:** Tonelli-Shanks algorithm for modular square roots. Finds $x$ s.t. $x^2 = a \pmod p$ ($-x$ gives the other solution).
**Time:** $\mathcal{O}\left(\log^2 p\right)$ worst case, $\mathcal{O}(\log p)$ for most $p$

"ModPow.h" 19a793, 24 lines

```
ll sqrt(ll a, ll p) {
  a %= p; if (a < 0) a += p;
  if (a == 0) return 0;
  assert(modpow(a, (p-1)/2, p) == 1); // else no solution
  if (p % 4 == 3) return modpow(a, (p+1)/4, p);
  // a^(n+3)/8 or 2^(n+3)/8 * 2^(n-1)/4 works if p % 8 == 5
  ll s = p - 1, n = 2;
  int r = 0, m;
  while (s % 2 == 0)
    ++r, s /= 2;
  while (modpow(n, (p - 1) / 2, p) != p - 1) ++n;
  ll x = modpow(a, (s + 1) / 2, p);
  ll b = modpow(a, s, p), g = modpow(n, s, p);
  for (;; r = m) {
    ll t = b;
    for (m = 0; m < r && t != 1; ++m)
      t = t * t % p;
    if (m == 0) return x;
    ll gs = modpow(g, 1LL << (r - m - 1), p);
    g = gs * gs % p;
    x = x * gs % p;
    b = b * g % p;
  }
}
```

## 5.2 Primality

### FastEratosthenes.h

**Description:** Prime sieve for generating all primes smaller than LIM.
**Time:** LIM=1e9 $\approx$ 1.5s

6b2912, 20 lines

```
const int LIM = 1e6;
bitset<LIM> isPrime;
vi eratosthenes() {
  const int S = (int)round(sqrt(LIM)), R = LIM / 2;
  vi pr = {2}, sieve(S+1); pr.reserve(int(LIM/log(LIM)*1.1));
  vector<pii> cp;
  for (int i = 3; i <= S; i += 2) if (!sieve[i]) {
    cp.push_back({i, i * i / 2});
    for (int j = i * i; j <= S; j += 2 * i) sieve[j] = 1;
  }
  for (int L = 1; L <= R; L += S) {
    array<bool, S> block{};
    for (auto &[p, idx] : cp)
      for (int i=idx; i < S+L; idx = (i+=p)) block[i-L] = 1;
    rep(i,0,min(S, R - L))
      if (!block[i]) pr.push_back((L + i) * 2 + 1);
  }
  for (int i : pr) isPrime[i] = 1;
  return pr;
}
```

### MillerRabin.h

**Description:** Deterministic Miller-Rabin primality test. Guaranteed to work for numbers up to $7 \cdot 10^{18}$; for larger numbers, use Python and extend A randomly.
**Time:** 7 times the complexity of $a^b \mod c$.

"ModMulLL.h" 60dcd1, 12 lines

```
bool isPrime(ull n) {
  if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
  ull A[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022},
      s = __builtin_ctzll(n-1), d = n >> s;
```

```
  for (ull a : A) {   // ^ count trailing zeroes
    ull p = modpow(a%n, d, n), i = s;
    while (p != 1 && p != n - 1 && a % n && i--)
      p = modmul(p, p, n);
    if (p != n-1 && i != s) return 0;
  }
  return 1;
}
```

Factor.h

**Description:** Pollard-rho randomized factorization algorithm. Returns prime factors of a number, in arbitrary order (e.g. 2299 -> {11, 19, 11}).

**Time:** $\mathcal{O}\left(n^{1/4}\right)$, less for numbers with small factors.

"ModMulLL.h", "MillerRabin.h" d8d98d, 18 lines

```
ull pollard(ull n) {
  ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;
  auto f = [&](ull x) { return modmul(x, x, n) + i; };
  while (t++ % 40 || __gcd(prd, n) == 1) {
    if (x == y) x = ++i, y = f(x);
    if ((q = modmul(prd, max(x,y) - min(x,y), n))) prd = q;
    x = f(x), y = f(f(y));
  }
  return __gcd(prd, n);
}
vector<ull> factor(ull n) {
  if (n == 1) return {};
  if (isPrime(n)) return {n};
  ull x = pollard(n);
  auto l = factor(x), r = factor(n / x);
  l.insert(l.end(), all(r));
  return l;
}
```

## 5.3 Divisibility

SqrtIntervals.h

**Description:** break 1..n into inclusive intervals in sorted order, constant on $\lfloor \frac{n}{i} \rfloor$ or $\lceil \frac{n}{i} \rceil$.

**Time:** $\mathcal{O}\left(\sqrt{N}\right)$ 6d93f2, 13 lines

```
auto fdivSplit = [](int n) {
    vector<pii> segs;
    for (int q, r, l = 1; l <= n; l = r+1) {
        q = n/l, r = n/q;
        segs.pb({l, r});
    }
    return segs;
};
auto cdivSplit = [](int n) {
    auto segs = fdivSplit(n-1);
    segs.pb({n, n});
    return segs;
};
```

euclid.h

**Description:** Finds two integers $x$ and $y$, such that $ax + by = \gcd(a, b)$. If you just need gcd, use the built in __gcd instead. If $a$ and $b$ are coprime, then $x$ is the inverse of $a \pmod b$. 33ba8f, 5 lines

```
ll euclid(ll a, ll b, ll &x, ll &y) {
  if (!b) return x = 1, y = 0, a;
  ll d = euclid(b, a % b, y, x);
  return y -= a/b * x, d;
}
```

CRT.h

**Description:** Chinese Remainder Theorem.

crt(a, m, b, n) computes $x$ such that $x \equiv a \pmod m$, $x \equiv b \pmod n$. If $|a| < m$ and $|b| < n$, $x$ will obey $0 \le x < \text{lcm}(m, n)$. Assumes $mn < 2^{62}$.

**Time:** $\log(n)$

"euclid.h" 04d93a, 7 lines

```
ll crt(ll a, ll m, ll b, ll n) {
  if (n > m) swap(a, b), swap(m, n);
  ll x, y, g = euclid(m, n, x, y);
  assert((a - b) % g == 0); // else no solution
  x = (b - a) % n * x % n / g * m + a;
  return x < 0 ? x + m*n/g : x;
}
```

### 5.3.1 Bézout's identity

For $a \neq, b \neq 0$, then $d = gcd(a, b)$ is the smallest positive integer for which there are integer solutions to

$$ax + by = d$$

If $(x, y)$ is one solution, then all solutions are given by

$$\left(x + \frac{kb}{\gcd(a,b)}, y - \frac{ka}{\gcd(a,b)}\right), \quad k \in \mathbb{Z}$$

phiFunction.h

**Description:** *Euler's* $\phi$ function is defined as $\phi(n) :=$ # of positive integers $\le n$ that are coprime with $n$. $\phi(1) = 1$, $p$ prime $\Rightarrow \phi(p^k) = (p-1)p^{k-1}$, $m, n$ coprime $\Rightarrow \phi(mn) = \phi(m)\phi(n)$. If $n = p_1^{k_1} p_2^{k_2} ... p_r^{k_r}$ then $\phi(n) = (p_1 - 1)p_1^{k_1 - 1} ... (p_r - 1)p_r^{k_r - 1}$. $\phi(n) = n \cdot \prod_{p|n}(1 - 1/p)$.
$\sum_{d|n} \phi(d) = n$, $\sum_{1 \le k \le n, \gcd(k,n)=1} k = n\phi(n)/2, n > 1$

**Euler's thm**: $a, n$ coprime $\Rightarrow a^{\phi(n)} \equiv 1 \pmod n$.

**Fermat's little thm**: $p$ prime $\Rightarrow a^{p-1} \equiv 1 \pmod p$ $\forall a$. cf7d6d, 8 lines

```
const int LIM = 5000000;
int phi[LIM];

void calculatePhi() {
  rep(i,0,LIM) phi[i] = i&1 ? i : i/2;
  for (int i = 3; i < LIM; i += 2) if(phi[i] == i)
    for (int j = i; j < LIM; j += i) phi[j] -= phi[j] / i;
}
```

## 5.4 Fractions

Fractions.h

**Description:** Fractions. Products may overflow, be careful. 5563ee, 28 lines

```
struct frac {
    int p, q;
    frac(int p=0, int q=1): p(p), q(q) { norm(); }
    void norm() { assert(q);
        if (q < 0) p = -p, q = -q;
        int g = gcd(p, q);
        p /= g, q /= g; }
    frac& operator+=(frac o) {
        tie(p, q) = pair(p*o.q + q*o.p, q*o.q);
        norm(); return *this; }
    frac& operator-=(frac o) {
        tie(p, q) = pair(p*o.q - q*o.p, q*o.q);
        norm(); return *this; }
    frac& operator*=(frac o) {
        tie(p, q) = pair(p*o.p, q*o.q);
        norm(); return *this; }
    frac& operator/=(frac o) {
        tie(p, q) = pair(p*o.q, q*o.p);
        norm(); return *this; }
    friend frac operator+(frac a, frac b) { return a += b; }
    friend frac operator-(frac a, frac b) { return a -= b; }
    friend frac operator*(frac a, frac b) { return a *= b; }
    friend frac operator/(frac a, frac b) { return a /= b; }
    friend bool operator==(frac a, frac b) = default;
    friend bool operator<(frac a, frac b) { return a.p*b.q < a.
        q*b.p; }
    friend ostream& operator<<(ostream& os, frac a) {
        return os << a.p << '/' << a.q; }
};
```

ContinuedFractions.h

**Description:** Given $N$ and a real number $x \ge 0$, finds the closest rational approximation $p/q$ with $p, q \le N$. It will obey $|p/q - x| \le 1/qN$.

For consecutive convergents, $p_{k+1}q_k - q_{k+1}p_k = (-1)^k$. ($p_k/q_k$ alternates between $> x$ and $< x$.) If $x$ is rational, $y$ eventually becomes $\infty$; if $x$ is the root of a degree 2 polynomial the $a$'s eventually become cyclic.

**Time:** $\mathcal{O}(\log N)$ dd6c5e, 21 lines

```
typedef double d; // for N ~ 1e7; long double for N ~ 1e9
pair<ll, ll> approximate(d x, ll N) {
  ll LP = 0, LQ = 1, P = 1, Q = 0, inf = LLONG_MAX; d y = x;
  for (;;) {
    ll lim = min(P ? (N-LP) / P : inf, Q ? (N-LQ) / Q : inf),
       a = (ll)floor(y), b = min(a, lim),
       NP = b*P + LP, NQ = b*Q + LQ;
    if (a > b) {
      // If b > a/2, we have a semi-convergent that gives us a
      // better approximation; if b = a/2, we *may* have one.
      // Return {P, Q} here for a more canonical approximation.
      return (abs(x - (d)NP / (d)NQ) < abs(x - (d)P / (d)Q)) ?
        make_pair(NP, NQ) : make_pair(P, Q);
    }
    if (abs(y = 1/(y - (d)a)) > 3*N) {
      return {NP, NQ};
    }
    LP = P; P = NP;
    LQ = Q; Q = NQ;
  }
}
```

FracBinarySearch.h

**Description:** Given $f$ and $N$, finds the smallest fraction $p/q \in [0, 1]$ such that $f(p/q)$ is true, and $p, q \le N$. You may want to throw an exception from $f$ if it finds an exact solution, in which case $N$ can be removed.

**Usage:** fracBS([](Frac f) { return f.p>=3*f.q; }, 10); // {1,3}

**Time:** $\mathcal{O}(\log(N))$ 27ab3e, 25 lines

```
struct Frac { ll p, q; };

template<class F>
Frac fracBS(F f, ll N) {
  bool dir = 1, A = 1, B = 1;
  Frac lo{0, 1}, hi{1, 1}; // Set hi to 1/0 to search (0, N]
  if (f(lo)) return lo;
  assert(f(hi));
  while (A || B) {
    ll adv = 0, step = 1; // move hi if dir, else lo
    for (int si = 0; step; (step *= 2) >>= si) {
      adv += step;
      Frac mid{lo.p * adv + hi.p, lo.q * adv + hi.q};
      if (abs(mid.p) > N || mid.q > N || dir == !f(mid)) {
        adv -= step; si = 2;
```

```
      }
    }
    hi.p += lo.p * adv;
    hi.q += lo.q * adv;
    dir = !dir;
    swap(lo, hi);
    A = B; B = !!adv;
  }
  return dir ? hi : lo;
}
```

## 5.5 Pythagorean Triples

The Pythagorean triples are uniquely generated by

$$a = k \cdot (m^2 - n^2),\ \ b = k \cdot (2mn),\ \ c = k \cdot (m^2 + n^2),$$

with $m > n > 0$, $k > 0$, $m \perp n$, and either $m$ or $n$ even.

## 5.6 Primes

$p = 962592769$ is such that $2^{21} \mid p - 1$, which may be useful. For hashing use 970592641 (31-bit number), 31443539979727 (45-bit), 3006703054056749 (52-bit). There are 78498 primes less than 1 000 000.

Primitive roots exist modulo any prime power $p^a$, except for $p = 2, a > 2$, and there are $\phi(\phi(p^a))$ many. For $p = 2, a > 2$, the group $\mathbb{Z}_{2^a}^\times$ is instead isomorphic to $\mathbb{Z}_2 \times \mathbb{Z}_{2^{a-2}}$.

## 5.7 Estimates

$\sum_{d|n} d = O(n \log \log n)$.

The number of divisors of $n$ is at most around 100 for $n < 5e4$, 500 for $n < 1e7$, 2000 for $n < 1e10$, 200 000 for $n < 1e19$.

## 5.8 Mobius Function

$$\mu(n) = \begin{cases} 0 & n \text{ is not square free} \\ 1 & n \text{ has even number of prime factors} \\ -1 & n \text{ has odd number of prime factors} \end{cases}$$

Mobius Inversion:

$$g(n) = \sum_{d|n} f(d) \Leftrightarrow f(n) = \sum_{d|n} \mu(d) g(n/d)$$

Other useful formulas/forms:

$\sum_{d|n} \mu(d) = [n = 1]$ (very useful)

$g(n) = \sum_{n|d} f(d) \Leftrightarrow f(n) = \sum_{n|d} \mu(d/n) g(d)$

$g(n) = \sum_{1 \le m \le n} f(\lfloor \frac{n}{m} \rfloor) \Leftrightarrow f(n) = \sum_{1 \le m \le n} \mu(m) g(\lfloor \frac{n}{m} \rfloor)$

# Combinatorial (6)

## 6.1 Permutations

### 6.1.1 Factorial

| $n$ | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
|---|---|---|---|---|---|---|---|---|---|---|
| $n!$ | 1 | 2 | 6 | 24 | 120 | 720 | 5040 | 40320 | 362880 | 3628800 |
| $n$ | 11 | 12 | 13 | 14 | 15 | 16 | 17 | | | |
| $n!$ | 4.0e7 | 4.8e8 | 6.2e9 | 8.7e10 | 1.3e12 | 2.1e13 | 3.6e14 | | | |
| $n$ | 20 | 25 | 30 | 40 | 50 | 100 | 150 | 171 | | |
| $n!$ | 2e18 | 2e25 | 3e32 | 8e47 | 3e64 | 9e157 | 6e262 | >DBL_MAX | | |

IntPerm.h

**Description:** Permutation -> integer conversion. (Not order preserving.) Integer -> permutation can use a lookup table.

**Time:** $\mathcal{O}(n)$

044568, 6 lines

```
int permToInt(vi& v) {
  int use = 0, i = 0, r = 0;
  for(int x:v) r = r * ++i + __builtin_popcount(use & -(1<<x)),
    use |= 1 << x;                    // (note: minus, not ~!)
  return r;
}
```

### 6.1.2 Cycles

Let $g_S(n)$ be the number of $n$-permutations whose cycle lengths all belong to the set $S$. Then

$$\sum_{n=0}^{\infty} g_S(n) \frac{x^n}{n!} = \exp\left(\sum_{n \in S} \frac{x^n}{n}\right)$$

### 6.1.3 Derangements

Permutations of a set such that none of the elements appear in their original position.

$$D(n) = (n-1)(D(n-1) + D(n-2)) = nD(n-1) + (-1)^n = \left\lfloor \frac{n!}{e} \right\rceil$$

### 6.1.4 Burnside's lemma

Given a group $G$ of symmetries and a set $X$, the number of elements of $X$ *up to symmetry* equals

$$\frac{1}{|G|} \sum_{g \in G} |X^g|,$$

where $X^g$ are the elements fixed by $g$ ($g.x = x$).

If $f(n)$ counts "configurations" (of some sort) of length $n$, we can ignore rotational symmetry using $G = \mathbb{Z}_n$ to get

$$g(n) = \frac{1}{n} \sum_{k=0}^{n-1} f(\gcd(n,k)) = \frac{1}{n} \sum_{k|n} f(k) \phi(n/k).$$

## 6.2 Partitions and subsets

### 6.2.1 Partition function

Number of ways of writing $n$ as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1,\ p(n) = \sum_{k \in \mathbb{Z} \setminus \{0\}} (-1)^{k+1} p(n - k(3k-1)/2)$$

$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

| $n$ | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 20 | 50 | 100 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| $p(n)$ | 1 | 1 | 2 | 3 | 5 | 7 | 11 | 15 | 22 | 30 | 627 | ~2e5 | ~2e8 |

### 6.2.2 Lucas' Theorem

Let $n, m$ be non-negative integers and $p$ a prime. Write $n = n_k p^k + ... + n_1 p + n_0$ and $m = m_k p^k + ... + m_1 p + m_0$. Then $\binom{n}{m} \equiv \prod_{i=0}^{k} \binom{n_i}{m_i} \pmod{p}$.

### 6.2.3 Binomials

multinomial.h

**Description:** Computes $\binom{k_1 + \cdots + k_n}{k_1, k_2, \ldots, k_n} = \frac{(\sum k_i)!}{k_1! k_2! \ldots k_n!}$.

a0a312, 5 lines

```
ll multinomial(vi& v) {
  ll c = 1, m = v.empty() ? 1 : v[0];
  rep(i,1,sz(v)) rep(j,0,v[i]) c = c * ++m / (j+1);
  return c;
}
```

## 6.3 General purpose numbers

### 6.3.1 Bernoulli numbers

EGF of Bernoulli numbers is $B(t) = \frac{t}{e^t - 1}$ (FFT-able). $B[0, \ldots] = [1, -\frac{1}{2}, \frac{1}{6}, 0, -\frac{1}{30}, 0, \frac{1}{42}, \ldots]$

Sums of powers:

$$\sum_{i=1}^{n} n^m = \frac{1}{m+1} \sum_{k=0}^{m} \binom{m+1}{k} B_k \cdot (n+1)^{m+1-k}$$

Euler-Maclaurin formula for infinite sums:

$$\sum_{i=m}^{\infty} f(i) = \int_m^\infty f(x)dx - \sum_{k=1}^{\infty} \frac{B_k}{k!} f^{(k-1)}(m)$$

$$\approx \int_m^\infty f(x)dx + \frac{f(m)}{2} - \frac{f'(m)}{12} + \frac{f'''(m)}{720} + O(f^{(5)}(m))$$

### 6.3.2 Stirling numbers of the first kind

Number of permutations on $n$ items with $k$ cycles.

$$c(n,k) = c(n-1,k-1) + (n-1)c(n-1,k),\ c(0,0) = 1$$
$$\sum_{k=0}^{n} c(n,k)x^k = x(x+1)\dots(x+n-1)$$

$c(8,k) = 8, 0, 5040, 13068, 13132, 6769, 1960, 322, 28, 1$
$c(n,2) = 0, 0, 1, 3, 11, 50, 274, 1764, 13068, 109584, \dots$

### 6.3.3 Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly $k$ elements are greater than the previous element. $k$ $j$:s s.t. $\pi(j) > \pi(j+1)$, $k+1$ $j$:s s.t. $\pi(j) \geq j$, $k$ $j$:s s.t. $\pi(j) > j$.

$$E(n,k) = (n-k)E(n-1,k-1) + (k+1)E(n-1,k)$$

$$E(n,0) = E(n,n-1) = 1$$

$$E(n,k) = \sum_{j=0}^{k} (-1)^j \binom{n+1}{j} (k+1-j)^n$$

### 6.3.4 Stirling numbers of the second kind

Partitions of $n$ distinct elements into exactly $k$ groups.

$$S(n,k) = S(n-1,k-1) + kS(n-1,k)$$

$$S(n,1) = S(n,n) = 1$$

$$S(n,k) = \frac{1}{k!} \sum_{j=0}^{k} (-1)^{k-j} \binom{k}{j} j^n$$

### 6.3.5 Bell numbers

Total number of partitions of $n$ distinct elements. $B(n) = 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, \dots$. For $p$ prime,

$$B(p^m + n) \equiv mB(n) + B(n+1) \pmod{p}$$

### 6.3.6 Labeled unrooted trees

# on $n$ vertices: $n^{n-2}$
# on $k$ existing trees of size $n_i$: $n_1 n_2 \cdots n_k n^{k-2}$
# with degrees $d_i$: $(n-2)!/((d_1-1)! \cdots (d_n-1)!)$

### 6.3.7 Catalan numbers

$$C_n = \frac{1}{n+1}\binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1,\ C_{n+1} = \frac{2(2n+1)}{n+2} C_n,\ C_{n+1} = \sum C_i C_{n-i}$$

$C_n = 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, \dots$

- sub-diagonal monotone paths in an $n \times n$ grid.
- strings with $n$ pairs of parenthesis, correctly nested.
- binary trees with with $n+1$ leaves (0 or 2 children).
- ordered trees with $n+1$ vertices.
- ways a convex polygon with $n+2$ sides can be cut into triangles by connecting vertices with straight lines.
- permutations of $[n]$ with no 3-term increasing subseq.

# Graph (7)

## 7.1 Fundamentals

### BellmanFord.h

**Description:** Calculates shortest paths from $s$ in a graph that might have negative edge weights. Unreachable nodes get dist = inf; nodes reachable through negative-weight cycles get dist = -inf. Assumes $V^2 \max|w_i| < \sim 2^{63}$.
**Time:** $\mathcal{O}(VE)$

830a8f, 23 lines

```
const ll inf = LLONG_MAX;
struct Ed { int a, b, w, s() { return a < b ? a : -a; }};
struct Node { ll dist = inf; int prev = -1; };

void bellmanFord(vector<Node>& nodes, vector<Ed>& eds, int s) {
  nodes[s].dist = 0;
  sort(all(eds), [](Ed a, Ed b) { return a.s() < b.s(); });

  int lim = sz(nodes) / 2 + 2; // /3+100 with shuffled vertices
  rep(i,0,lim) for (Ed ed : eds) {
    Node cur = nodes[ed.a], &dest = nodes[ed.b];
    if (abs(cur.dist) == inf) continue;
    ll d = cur.dist + ed.w;
    if (d < dest.dist) {
      dest.prev = ed.a;
      dest.dist = (i < lim-1 ? d : -inf);
    }
  }
  rep(i,0,lim) for (Ed e : eds) {
    if (nodes[e.a].dist == -inf)
      nodes[e.b].dist = -inf;
  }
}
```

### FloydWarshall.h

**Description:** Calculates all-pairs shortest path in a directed graph that might have negative edge weights. Input is an distance matrix $m$, where $m[i][j] =$ `inf` if $i$ and $j$ are not adjacent. As output, $m[i][j]$ is set to the shortest distance between $i$ and $j$, `inf` if no path, or `-inf` if the path goes through a negative-weight cycle.
**Time:** $\mathcal{O}(N^3)$

531245, 12 lines

```
const ll inf = 1LL << 62;
void floydWarshall(vector<vector<ll>>& m) {
  int n = sz(m);
  rep(i,0,n) m[i][i] = min(m[i][i], 0LL);
  rep(k,0,n) rep(i,0,n) rep(j,0,n)
    if (m[i][k] != inf && m[k][j] != inf) {
      auto newDist = max(m[i][k] + m[k][j], -inf);
      m[i][j] = min(m[i][j], newDist);
    }
  rep(k,0,n) if (m[k][k] < 0) rep(i,0,n) rep(j,0,n)
    if (m[i][k] != inf && m[k][j] != inf) m[i][j] = -inf;
}
```

### TopoSort.h

**Description:** Topological sorting. Given is an oriented graph. Output is an ordering of vertices, such that there are edges only from left to right. If there are cycles, the returned list will have size smaller than $n$ – nodes reachable from cycles will not be returned.
**Time:** $\mathcal{O}(|V| + |E|)$

d678d8, 8 lines

```
vi topoSort(const vector<vi>& gr) {
  vi indeg(sz(gr)), q;
  for (auto& li : gr) for (int x : li) indeg[x]++;
  rep(i,0,sz(gr)) if (indeg[i] == 0) q.push_back(i);
  rep(j,0,sz(q)) for (int x : gr[q[j]])
    if (--indeg[x] == 0) q.push_back(x);
  return q;
}
```

### DynamicConnectivity.h

**Description:** Avoid pitfalls - swap u,v if u > v. Put end time = t-1 if an edge is erased at time t. Handle edges that were never removed.

"UnionFindRollback.h" 8732a8, 43 lines

```
struct DynConn {
    int T; // DynConn(T) works over times [0..T]
    vector<vector<pii>> tree;
    vector<int> queries; // change query type as needed
    vi ans; // 1 = Yes, 0 = No, -1 = "no query at this time"
    DynConn(int t) : T(t+2), tree(4*T), queries(4*T, -1),
        ans(T, -1) {}
    // [ql, qr] = [start time, end time] of edge
    void add_edge(int ql, int qr, pii edge) {
        if (ql > qr) return;
        auto f = [&](auto f, int node, int l, int r) -> void {
            if (ql > r || qr < l) return;
            if (ql <= l && r <= qr) {
                tree[node].push_back(edge);
                return;
            }
            int mid = (l+r) / 2;
            f(f, 2*node, l, mid);
            f(f, 2*node + 1, mid+1, r);
        };
        f(f, 1, 0, T);
    }
    void add_query(int time) { // add params as needed
        queries[time] = 0;
    }
    void solve(auto& dsu) {
        auto f = [&](auto f, int node, int l, int r) -> void {
            int t = dsu.time();
            for (auto [a, b] : tree[node]) dsu.join(a, b);
            if (l == r) {
                if (queries[l] != -1) { // change as needed
                    ans[l] = sz(dsu.e)-1 - dsu.time() / 2;
                }
            } else {
                int mid = (l + r) / 2;
                f(f, 2*node, l, mid);
                f(f, 2*node + 1, mid + 1, r);
            }
            dsu.rollback(t);
```

```
        };
        f(f, 1, 0, T);
    }
};
```

## 7.2 Network flow

### MinCostMaxFlow.h

**Description:** Minimum-cost maximum flow, assumes no negative cycles. It is possible to choose negative edge costs such that the first run of Dijkstra is slow, but this hasn't been an issue in the past. Edge weights $\geq 0$ for every subsequent run. To get flow through original edges, assign ID's during ae.
**Time:** Ignoring first run of Dijkstra, $\mathcal{O}(FM \log M)$ if caps are integers and $F$ is max flow.

69c7a2, 72 lines

```
template <class F, class C> // F = flow type, C = cost type
struct MCMF {
    struct Edge { int to; F flow, cap; C cost; };

    int n;
    vector<C> p, dist;
    vector<int> pre;
    vector<Edge> edges;
    vector<vector<int>> adj;

    const C INF = numeric_limits<C>::max() / 4;

    MCMF(int n) : n(n), p(n), dist(n), pre(n), adj(n) {}

    void ae(int u, int v, F cap, C cost) {
        assert(cap >= 0);
        adj[u].push_back(sz(edges));
        edges.push_back({v, 0, cap, cost});
        adj[v].push_back(sz(edges));
        edges.push_back({u, 0, 0, -cost});
    }

    bool path(int s, int t) {
        for (int i = 0; i < n; i++)
            dist[i] = INF;
        using T = pair<C, int>;
        priority_queue<T, vector<T>, greater<>> todo;
        todo.push({dist[s] = 0, s});
        while (!todo.empty()) {
            T x = todo.top();
            todo.pop();
            if (x.first > dist[x.second])
                continue;
            for (auto& eid : adj[x.second]) {
                const Edge& e = edges[eid];
                if (e.flow < e.cap && dist[e.to]
      > x.first + e.cost + p[x.second] - p[e.to]) {
                    dist[e.to] = x.first + e.cost + p[x.second]
                          - p[e.to];
                    pre[e.to] = eid;
                    todo.push({dist[e.to], e.to});
                }
            }
        }
        return dist[t] != INF;
    }

    pair<F, C> calc(int s, int t) {
        assert(s != t);
        for (int unused = 0; unused < n; unused++)
            for (int eid = 0; eid < (int)edges.size(); eid++) {
                const Edge& e = edges[eid];
                if (e.cap)
                    p[e.to] = min(p[e.to], p[edges[eid ^ 1].to]
                          + e.cost);
            }
        F totflow = 0;
        C totcost = 0;
        while (path(s, t)) {
            for (int i = 0; i < n; i++)
                p[i] = min(p[i] + dist[i], INF);
            F df = numeric_limits<F>::max() / 4;
            for (int x = t; x != s; x = edges[pre[x] ^ 1].to) {
                const Edge& e = edges[pre[x]];
                df = min(df, e.cap - e.flow);
            }
            totflow += df;
            totcost += (p[t] - p[s]) * df;
            for (int x = t; x != s; x = edges[pre[x] ^ 1].to)
                edges[pre[x]].flow += df, edges[pre[x] ^ 1].
                     flow -= df;
        }
        return {totflow, totcost};
    }
};
```

### Dinic.h

**Description:** Flow algorithm with complexity $O(VE \log U)$ where $U = \max|\text{cap}|$. $O(\min(E^{1/2}, V^{2/3})E)$ if $U = 1$; $O(\sqrt{V}E)$ for bipartite matching.

d7f0f1, 42 lines

```
struct Dinic {
  struct Edge {
    int to, rev;
    ll c, oc;
    ll flow() { return max(oc - c, 0LL); } // if you need flows
  };
  vi lvl, ptr, q;
  vector<vector<Edge>> adj;
  Dinic(int n) : lvl(n), ptr(n), q(n), adj(n) {}
  void addEdge(int a, int b, ll c, ll rcap = 0) {
    adj[a].push_back({b, sz(adj[b]), c, c});
    adj[b].push_back({a, sz(adj[a]) - 1, rcap, rcap});
  }
  ll dfs(int v, int t, ll f) {
    if (v == t || !f) return f;
    for (int& i = ptr[v]; i < sz(adj[v]); i++) {
      Edge& e = adj[v][i];
      if (lvl[e.to] == lvl[v] + 1)
        if (ll p = dfs(e.to, t, min(f, e.c))) {
          e.c -= p, adj[e.to][e.rev].c += p;
          return p;
        }
    }
    return 0;
  }
  ll calc(int s, int t) {
    ll flow = 0; q[0] = s;
    rep(L,0,31) do { // 'int L=30' maybe faster for random data
      lvl = ptr = vi(sz(q));
      int qi = 0, qe = lvl[s] = 1;
      while (qi < qe && !lvl[t]) {
        int v = q[qi++];
        for (Edge e : adj[v])
          if (!lvl[e.to] && e.c >> (30 - L))
            q[qe++] = e.to, lvl[e.to] = lvl[v] + 1;
      }
      while (ll p = dfs(s, t, LLONG_MAX)) flow += p;
    } while (lvl[t]);
    return flow;
  }
  bool leftOfMinCut(int a) { return lvl[a] != 0; }
};
```

### MinCut.h

**Description:** After running max-flow, the left side of a min-cut from $s$ to $t$ is given by all vertices reachable from $s$, only traversing edges with positive residual capacity.

### GlobalMinCut.h

**Description:** Find a global minimum cut in an undirected graph, as represented by an adjacency matrix.
**Time:** $\mathcal{O}(V^3)$

8b0e19, 21 lines

```
pair<int, vi> globalMinCut(vector<vi> mat) {
  pair<int, vi> best = {INT_MAX, {}};
  int n = sz(mat);
  vector<vi> co(n);
  rep(i,0,n) co[i] = {i};
  rep(ph,1,n) {
    vi w = mat[0];
    size_t s = 0, t = 0;
    rep(it,0,n-ph) { // O(V^2) -> O(E log V) with prio. queue
      w[t] = INT_MIN;
      s = t, t = max_element(all(w)) - w.begin();
      rep(i,0,n) w[i] += mat[t][i];
    }
    best = min(best, {w[t] - mat[t][t], co[t]});
    co[s].insert(co[s].end(), all(co[t]));
    rep(i,0,n) mat[s][i] += mat[t][i];
    rep(i,0,n) mat[i][s] = mat[s][i];
    mat[0][t] = INT_MIN;
  }
  return best;
}
```

# Matching (8)

### HopcroftKarp.h

**Description:** Fast bipartite matching algorithm. Graph $g$ should be a list of neighbors of the left partition, and $r$ should be a vector full of $-1$'s of the same size as the right partition. Returns the size of the matching. $r[i]$ will be the match for vertex $i$ on the right side, or $-1$ if it's not matched.
**Time:** $\mathcal{O}\left(E\sqrt{V}\right)$

731cfb, 20 lines

```
int hopcroftKarp(vector<vi>& g, vi& r) {
  int n = sz(g), res = 0;
  vi l(n, -1), q(n), d(n);
  auto dfs = [&](auto f, int u) -> bool {
    int t = exchange(d[u], 0) + 1;
    for (int v : g[u])
      if (r[v] == -1 || (d[r[v]] == t && f(f, r[v])))
        return l[u] = v, r[v] = u, 1;
    return 0;
  };
  for (int t = 0, f = 0;; t = f = 0, d.assign(n, 0)) {
    rep(i,0,n) if (l[i] == -1) q[t++] = i, d[i] = 1;
    rep(i,0,t) for (int v : g[q[i]]) {
      if (r[v] == -1) f = 1;
      else if (!d[r[v]]) d[r[v]] = d[q[i]] + 1, q[t++] = r[v];
    }
    if (!f) return res;
    rep(i,0,n) if (l[i] == -1) res += dfs(dfs, i);
  }
}
```

## DFSMatching.h

**Description:** Simple bipartite matching algorithm. Graph $g$ should be a list of neighbors of the left partition, and $btoa$ should be a vector full of -1's of the same size as the right partition. Returns the size of the matching. $btoa[i]$ will be the match for vertex $i$ on the right side, or $-1$ if it's not matched.
**Usage:** `vi btoa(m, -1); dfsMatching(g, btoa);`
**Time:** $\mathcal{O}(VE)$

522b98, 22 lines

```
bool find(int j, vector<vi>& g, vi& btoa, vi& vis) {
  if (btoa[j] == -1) return 1;
  vis[j] = 1; int di = btoa[j];
  for (int e : g[di])
    if (!vis[e] && find(e, g, btoa, vis)) {
      btoa[e] = di;
      return 1;
    }
  return 0;
}
int dfsMatching(vector<vi>& g, vi& btoa) {
  vi vis;
  rep(i,0,sz(g)) {
    vis.assign(sz(btoa), 0);
    for (int j : g[i])
      if (find(j, g, btoa, vis)) {
        btoa[j] = i;
        break;
      }
  }
  return sz(btoa) - (int)count(all(btoa), -1);
}
```

## MinimumVertexCover.h

**Description:** Finds a minimum vertex cover in a bipartite graph (A, B) with —A— = n, —B— = m. g should be a list of neighbors of the left partition. The size is the same as the size of a maximum matching, and the complement is a maximum independent set.

"HopcroftKarp.h" bfb654, 20 lines

```
vi cover(vector<vi>& g, int n, int m) {
  vi match(m, -1);
  int res = hopcroftKarp(g, match);
  vector<bool> lfound(n, true), seen(m);
  for (int it : match) if (it != -1) lfound[it] = false;
  vi q, cover;
  rep(i,0,n) if (lfound[i]) q.push_back(i);
  while (!q.empty()) {
    int i = q.back(); q.pop_back();
    lfound[i] = 1;
    for (int e : g[i]) if (!seen[e] && match[e] != -1) {
      seen[e] = true;
      q.push_back(match[e]);
    }
  }
  rep(i,0,n) if (!lfound[i]) cover.push_back(i);
  rep(i,0,m) if (seen[i]) cover.push_back(n+i);
  assert(sz(cover) == res);
  return cover;
}
```

## WeightedMatching.h

**Description:** Given a weighted bipartite graph, matches every node on the left with a node on the right such that no nodes are in two matchings and the sum of the edge weights is minimal. Takes cost[N][M], where cost[i][j] = cost for L[i] to be matched with R[j] and returns (min cost, match), where L[i] is matched with R[match[i]]. Negate costs for max cost. Requires $N \leq M$.
**Time:** $\mathcal{O}\left(N^2M\right)$

f79c17, 35 lines

```
template<class T>
pair<T, vector<T>> hungarian(const vector<vector<T>> &a) {
  if (a.empty()) return {0, {}};
  int n = sz(a) + 1, m = sz(a[0]) + 1;
  vector<T> u(n), v(m), ans(n-1);
  vi p(m);
  rep(i,1,n) {
    p[0] = i;
    int j0 = 0; // add "dummy" worker 0
    vector<T> dist(m, 1e18); // change MAX if needed
    vi pre(m, -1);
    vector<bool> done(m+1);
    do { // dijkstra
      done[j0] = true;
      int i0 = p[j0], j1;
      T delta = 1e18; // change MAX if needed
      rep(j,1,m) if (!done[j]) {
          T cur = a[i0-1][j-1] - u[i0] - v[j];
          if (cur < dist[j]) dist[j] = cur, pre[j] = j0;
          if (dist[j] < delta) delta = dist[j], j1 = j;
        }
      rep(j,0,m) {
        if (done[j]) u[p[j]] += delta, v[j] -= delta;
        else dist[j] -= delta;
      }
      j0 = j1;
    } while (p[j0]);
    while (j0) { // update alternating path
      int j1 = pre[j0];
      p[j0] = p[j1], j0 = j1;
    }
  }
  rep(j,1,m) if (p[j]) ans[p[j] - 1] = j-1;
  return {-v[0], ans}; // {min cost, match vector}
}
```

## GeneralMatching.h

**Description:** Matching for general graphs. Fails with probability $N/mod$.
**Time:** $\mathcal{O}\left(N^3\right)$

"../numerical/MatrixInverse-mod.h" cb1912, 40 lines

```
vector<pii> generalMatching(int N, vector<pii>& ed) {
  vector<vector<ll>> mat(N, vector<ll>(N)), A;
  for (pii pa : ed) {
    int a = pa.first, b = pa.second, r = rand() % mod;
    mat[a][b] = r, mat[b][a] = (mod - r) % mod;
  }

  int r = matInv(A = mat), M = 2*N - r, fi, fj;
  assert(r % 2 == 0);

  if (M != N) do {
    mat.resize(M, vector<ll>(M));
    rep(i,0,N) {
      mat[i].resize(M);
      rep(j,N,M) {
        int r = rand() % mod;
        mat[i][j] = r, mat[j][i] = (mod - r) % mod;
      }
    }
  } while (matInv(A = mat) != M);

  vi has(M, 1); vector<pii> ret;
  rep(it,0,M/2) {
    rep(i,0,M) if (has[i])
      rep(j,i+1,M) if (A[i][j] && mat[i][j]) {
        fi = i; fj = j; goto done;
    } assert(0); done:
    if (fj < N) ret.emplace_back(fi, fj);
    has[fi] = has[fj] = 0;
    rep(sw,0,2) {
      ll a = modpow(A[fi][fj], mod-2);
      rep(i,0,M) if (has[i] && A[i][fj]) {
        ll b = A[i][fj] * a % mod;
        rep(j,0,M) A[i][j] = (A[i][j] - A[fi][j] * b) % mod;
      }
      swap(fi,fj);
    }
  }
  return ret;
}
```

# 8.1 DFS algorithms

## AllRoots.h

**Description:** 0-indexed reroot DP assuming associativity and commutativity of +. operator+ combines children into a single representation. promote() finds a child's contribution to its parent.
**Time:** $\mathcal{O}(N)$.

a8ea30, 47 lines

```
struct ART {
  // default constructor must give identity elmt
  int ans = 0; // max distance to another node
  ART operator+(const ART& o) const {
    return {max(ans, o.ans)};
  }
  ART promote(int x, int e) const {
    if (e == -1) return *this;
    return {ans+1}; // x = node idx, e = edge idx
  }
};
ART base{}; // value of a single node, not always id
template<class T>
struct AllRoots {
  int n; vector<vector<pii>> adj;
  vector<vector<T>> suf; vector<T> res;
  AllRoots(vector<pii>& el) : n(sz(el)+1), adj(n), suf(n), res(
      n) {
    for (int ei = -1; auto [a, b] : el) { ei++;
      adj[a].pb({b,ei});
      adj[b].pb({a, ei});
    }
    for (auto &s : suf) s.pb(base); // initial value of node
  }
  T down(int x, int p = -1) {
    for (auto &c : adj[x])
      if(c.F == p) swap(c, adj[x][0]);
    for(int i = sz(adj[x])-1; i > -(p<0); --i)
      suf[x].pb(down(adj[x][i].F,x) + suf[x].back());
    return (p == -1 ? T{} : suf[x].back().promote(x,adj[x][0].S
        ));
  }
  void up(int x, int p = -1) {
    rep(i, p != -1, sz(adj[x])) {
      auto[y,ei] = adj[x][i];
      suf[x].pop_back();
      res[y] = (res[x] + suf[x].back()).promote(x,ei);
      res[x] = res[x] + suf[y].back().promote(y,ei);
      up(y, x);
    }
  }
  static vector<T> calc(vector<pii>& el) {
    AllRoots ar(el);
    ar.down(0);
    ar.up(0);
    rep(i,0,ar.n) ar.res[i] = ar.res[i].promote(i,-1);
    return ar.res;
  }
};
```

## SCC.h

**Description:** Finds strongly connected components in a directed graph. If vertices $u, v$ belong to the same component, we can reach $u$ from $v$ and vice versa.
**Usage:** `scc(graph, [&](vi& v) { ... })` visits all components in reverse topological order. `comp[i]` holds the component index of a node (a component only has edges to components with lower index). `ncomps` will contain the number of components.
**Time:** $\mathcal{O}(E+V)$

76b5c9, 24 lines

```
vi val, comp, z, cont;
int Time, ncomps;
template<class G, class F> int dfs(int j, G& g, F& f) {
  int low = val[j] = ++Time, x; z.push_back(j);
  for (auto e : g[j]) if (comp[e] < 0)
    low = min(low, val[e] ?: dfs(e,g,f));

  if (low == val[j]) {
    do {
      x = z.back(); z.pop_back();
      comp[x] = ncomps;
      cont.push_back(x);
    } while (x != j);
    f(cont); cont.clear();
    ncomps++;
  }
  return val[j] = low;
}
template<class G, class F> void scc(G& g, F f) {
  int n = sz(g);
  val.assign(n, 0); comp.assign(n, -1);
  Time = ncomps = 0;
  rep(i,0,n) if (comp[i] < 0) dfs(i, g, f);
}
```

## BiconnectedComponents.h

**Description:** Finds all biconnected components in an undirected graph, and runs a callback for the edges in each. In a biconnected component there are at least two internally disjoint paths between any two nodes (a cycle exists through them). Note that a node can be in several components. An edge which is not in a component is a bridge, i.e., not part of any cycle.
**Usage:** `int eid = 0; ed.resize(N); for (auto &x: ed) x.clear();`
`for each edge (a,b) {`
`ed[a].emplace_back(b, eid);`
`ed[b].emplace_back(a, eid++); }`
`bicomps([&](const vi& edgelist) {...});`
**Time:** $\mathcal{O}(E+V)$

c6b7c7, 32 lines

```
vi num, st;
vector<vector<pii>> ed;
int Time;
template<class F>
int dfs(int at, int par, F& f) {
  int me = num[at] = ++Time, top = me;
  for (auto [y, e] : ed[at]) if (e != par) {
    if (num[y]) {
      top = min(top, num[y]);
      if (num[y] < me)
        st.push_back(e);
    } else {
      int si = sz(st);
      int up = dfs(y, e, f);
      top = min(top, up);
      if (up == me) {
        st.push_back(e);
        f(vi(st.begin() + si, st.end()));
        st.resize(si);
      }
      else if (up < me) st.push_back(e);
      else { /* e is a bridge */ }
    }
  }
  return top;
}

template<class F>
void bicomps(F f) {
  num.assign(sz(ed), 0);
  rep(i,0,sz(ed)) if (!num[i]) dfs(i, -1, f);
}
```

## BlockCutTree.h

**Description:** Given an undirected adj. list 'g', 0 or 1 indexed ('s'), computes a block-cut tree. 'id' maps nodes in 'g' to nodes in 't'.
**Time:** $\mathcal{O}(N+M)$

8e181e, 38 lines

```
auto blockCutTree = [](vector<vi> &g, int s) {
    int n = sz(g), time = 0; vector<bool> is_cutpoint(n);
    vector<vi> comps; vi stk, num(n), low(n), id(n);
    // find BCCs
    auto dfs = [&](auto dfs, int u, int p) -> void {
        num[u] = low[u] = ++time;
        stk.pb(u);
        for (int x : g[u]) {
            if (x == p) continue;
            if (num[x]) low[u] = min(low[u], num[x]);
            else {
                dfs(dfs, x, u);
                low[u] = min(low[u], low[x]);
                if (low[x] >= num[u]) {
                    is_cutpoint[u] = num[u] > 1 || num[x] > 2;
                    comps.pb({u});
                    while (comps.back().back() != x) {
                        comps.back().pb(stk.back());
                        stk.pop_back();
                    }
                }
            }
        }
    };
    dfs(dfs, s, -1);
    // build block–cut tree
    vector<vi> t(1); int nid = 0;
    rep(u,s,n)
        if (is_cutpoint[u]) id[u] = nid++, t.pb({});
    for (auto &comp : comps) {
        int node = nid++;
        t.pb({});
        for (int u : comp)
            if (!is_cutpoint[u]) id[u] = node;
            else t[node].pb(id[u]), t[id[u]].pb(node);
    }
    return tuple(t, is_cutpoint, id);
};
```

## 2sat.h

**Description:** Calculates a valid assignment to boolean variables a, b, c,... to a 2-SAT problem, so that an expression of the type $(a||b)\&\&(!a||c)\&\&(d||!b)\&\&\ldots$ becomes true, or reports that it is unsatisfiable. Negated variables are represented by bit-inversions (~x).
**Usage:** `TwoSat ts(number of boolean variables);`
`ts.either(0, ~3); // Var 0 is true or var 3 is false`
`ts.setValue(2); // Var 2 is true`
`ts.atMostOne({0,~1,2}); // <= 1 of vars 0, ~1 and 2 are true`
`ts.solve(); // Returns true iff it is solvable`
`ts.values[0..N-1] holds the assigned values to the vars`
**Time:** $\mathcal{O}(N+E)$, where N is the number of boolean variables, and E is the number of clauses.

5f9706, 56 lines

```
struct TwoSat {
  int N;
  vector<vi> gr;
  vi values; // 0 = false, 1 = true

  TwoSat(int n = 0) : N(n), gr(2*n) {}

  int addVar() { // (optional)
    gr.emplace_back();
    gr.emplace_back();
    return N++;
  }

  void either(int f, int j) {
    f = max(2*f, -1-2*f);
    j = max(2*j, -1-2*j);
    gr[f].push_back(j^1);
    gr[j].push_back(f^1);
  }
  void setValue(int x) { either(x, x); }

  void atMostOne(const vi& li) { // (optional)
    if (sz(li) <= 1) return;
    int cur = ~li[0];
    rep(i,2,sz(li)) {
      int next = addVar();
      either(cur, ~li[i]);
      either(cur, next);
      either(~li[i], next);
      cur = ~next;
    }
    either(cur, ~li[1]);
  }

  vi val, comp, z; int time = 0;
  int dfs(int i) {
    int low = val[i] = ++time, x; z.push_back(i);
    for(int e : gr[i]) if (!comp[e])
      low = min(low, val[e] ?: dfs(e));
    if (low == val[i]) do {
      x = z.back(); z.pop_back();
      comp[x] = low;
      if (values[x>>1] == -1)
        values[x>>1] = x&1;
    } while (x != i);
    return val[i] = low;
  }

  bool solve() {
    values.assign(N, -1);
    val.assign(2*N, 0); comp = val;
    rep(i,0,2*N) if (!comp[i]) dfs(i);
    rep(i,0,N) if (comp[2*i] == comp[2*i+1]) return 0;
    return 1;
  }
};
```

## EulerWalk.h

**Description:** Eulerian undirected/directed path/cycle algorithm. Input should be a vector of (dest, global edge index), where for undirected graphs, forward/backward edges have the same index. Returns a list of nodes in the Eulerian path/cycle with src at both start and end, or empty list if no cycle/path exists. To get edge indices back, add .second to s and ret.
**Time:** $\mathcal{O}(V+E)$

780b64, 15 lines

```
vi eulerWalk(vector<vector<pii>>& gr, int nedges, int src=0) {
  int n = sz(gr);
  vi D(n), its(n), eu(nedges), ret, s = {src};
  D[src]++; // to allow Euler paths, not just cycles
```

```
  while (!s.empty()) {
    int x = s.back(), y, e, &it = its[x], end = sz(gr[x]);
    if (it == end){ ret.push_back(x); s.pop_back(); continue; }
    tie(y, e) = gr[x][it++];
    if (!eu[e]) {
      D[x]--, D[y]++;
      eu[e] = 1; s.push_back(y);
    }}
  for (int x : D) if (x < 0 || sz(ret) != nedges+1) return {};
  return {ret.rbegin(), ret.rend()};
}
```

FunctionalGraph.h
**Time:** $\mathcal{O}(N)$

fa0484, 34 lines

```
//   // 0 <= a[i] < n
//   auto [root_of, cycles, childs] = func_graph(a);
//   auto [cyc_id, cyc_pos] = root_of[v];
//   int root = cycles[cyc_id][cyc_pos];
//   bool is_on_cycle = (v == root);

// root = first reachable node on cycle from v
// t[v].childs = forest of reversed edges not in cycles
struct func_graph {
  vector<pii> root_of;
  vector<vi> cycles, childs;
  func_graph(const vi& a):
    root_of(sz(a)), childs(sz(a)) {
    vi vis(sz(a));
    rep(i,0,sz(a)) {
      if (!vis[i]) {
        int u = i;
        for (; !vis[u]; u = a[u]) vis[u] = 1;
        if (vis[u] == 1)
          for (cycles.pb({}); vis[u] == 1; u = a[u]) {
            root_of[u] = {sz(cycles) - 1,
                          sz(cycles.back())};
            cycles.back().pb(u);
            vis[u] = 2;
          }
        for (int v = i; vis[v] == 1; v = a[v]) {
          root_of[v] = root_of[u];
          childs[a[v]].pb(v);
          vis[v] = 2;
        }
      }
    }
  }
};
```

## 8.2 Coloring

EdgeColoring.h
**Description:** Given a simple, undirected graph with max degree $D$, computes a $(D+1)$-coloring of the edges such that no neighboring edges share a color. ($D$-coloring is NP-hard, but can be done for bipartite graphs by repeated matchings of max-degree nodes.)
**Time:** $\mathcal{O}(NM)$

e210e2, 31 lines

```
vi edgeColoring(int N, vector<pii> eds) {
  vi cc(N + 1), ret(sz(eds)), fan(N), free(N), loc;
  for (pii e : eds) ++cc[e.first], ++cc[e.second];
  int u, v, ncols = *max_element(all(cc)) + 1;
  vector<vi> adj(N, vi(ncols, -1));
  for (pii e : eds) {
    tie(u, v) = e;
    fan[0] = v;
    loc.assign(ncols, 0);
    int at = u, end = u, d, c = free[u], ind = 0, i = 0;
    while (d = free[v], !loc[d] && (v = adj[u][d]) != -1)
      loc[d] = ++ind, cc[ind] = d, fan[ind] = v;
    cc[loc[d]] = c;
    for (int cd = d; at != -1; cd ^= c ^ d, at = adj[at][cd])
      swap(adj[at][cd], adj[end = at][cd ^ c ^ d]);
    while (adj[fan[i]][d] != -1) {
      int left = fan[i], right = fan[++i], e = cc[i];
      adj[u][e] = left;
      adj[left][e] = u;
      adj[right][e] = -1;
      free[right] = e;
    }
    adj[u][d] = fan[i];
    adj[fan[i]][d] = u;
    for (int y : {fan[0], u, end})
      for (int& z = free[y] = 0; adj[y][z] != -1; z++);
  }
  rep(i,0,sz(eds))
    for (tie(u, v) = eds[i]; adj[u][ret[i]] != v;) ++ret[i];
  return ret;
}
```

## 8.3 Heuristics

MaximalCliques.h
**Description:** Runs a callback for all maximal cliques in a graph (given as a symmetric bitset matrix; self-edges not allowed). Callback is given a bitset representing the maximal clique.
**Time:** $\mathcal{O}\left(3^{n/3}\right)$, much faster for sparse graphs

b0d5b1, 12 lines

```
typedef bitset<128> B;
template<class F>
void cliques(vector<B>& eds, F f, B P = ~B(), B X={}, B R={}) {
  if (!P.any()) { if (!X.any()) f(R); return; }
  auto q = (P | X)._Find_first();
  auto cands = P & ~eds[q];
  rep(i,0,sz(eds)) if (cands[i]) {
    R[i] = 1;
    cliques(eds, f, P & eds[i], X & eds[i], R);
    R[i] = P[i] = 0; X[i] = 1;
  }
}
```

MaximumClique.h
**Description:** Quickly finds a maximum clique of a graph (given as symmetric bitset matrix; self-edges not allowed). Can be used to find a maximum independent set by finding a clique of the complement graph.
**Time:** Runs in about 1s for n=155 and worst case random graphs (p=.90). Runs faster for sparse graphs.

f7c0bc, 49 lines

```
typedef vector<bitset<200>> vb;
struct Maxclique {
  double limit=0.025, pk=0;
  struct Vertex { int i, d=0; };
  typedef vector<Vertex> vv;
  vb e;
  vv V;
  vector<vi> C;
  vi qmax, q, S, old;
  void init(vv& r) {
    for (auto& v : r) v.d = 0;
    for (auto& v : r) for (auto j : r) v.d += e[v.i][j.i];
    sort(all(r), [](auto a, auto b) { return a.d > b.d; });
    int mxD = r[0].d;
    rep(i,0,sz(r)) r[i].d = min(i, mxD) + 1;
  }
  void expand(vv& R, int lev = 1) {
    S[lev] += S[lev - 1] - old[lev];
    old[lev] = S[lev - 1];
    while (sz(R)) {
      if (sz(q) + R.back().d <= sz(qmax)) return;
      q.push_back(R.back().i);
      vv T;
      for(auto v:R) if (e[R.back().i][v.i]) T.push_back({v.i});
      if (sz(T)) {
        if (S[lev]++ / ++pk < limit) init(T);
        int j = 0, mxk = 1, mnk = max(sz(qmax) - sz(q) + 1, 1);
        C[1].clear(), C[2].clear();
        for (auto v : T) {
          int k = 1;
          auto f = [&](int i) { return e[v.i][i]; };
          while (any_of(all(C[k]), f)) k++;
          if (k > mxk) mxk = k, C[mxk + 1].clear();
          if (k < mnk) T[j++].i = v.i;
          C[k].push_back(v.i);
        }
        if (j > 0) T[j - 1].d = 0;
        rep(k,mnk,mxk + 1) for (int i : C[k])
          T[j].i = i, T[j++].d = k;
        expand(T, lev + 1);
      } else if (sz(q) > sz(qmax)) qmax = q;
      q.pop_back(), R.pop_back();
    }
  }
  vi maxClique() { init(V), expand(V); return qmax; }
  Maxclique(vb conn) : e(conn), C(sz(e)+1), S(sz(C)), old(S) {
    rep(i,0,sz(e)) V.push_back({i});
  }
};
```

MaximumIndependentSet.h
**Description:** To obtain a maximum independent set of a graph, find a max clique of the complement. If the graph is bipartite, see MinimumVertexCover.

## 8.4 Trees

BinaryLifting.h
**Description:** Calculate power of two jumps in a tree, to support fast upward jumps and LCAs. Assumes the root node points to itself.
**Time:** construction $\mathcal{O}(N \log N)$, queries $\mathcal{O}(\log N)$

bfce85, 25 lines

```
vector<vi> treeJump(vi& P){
  int on = 1, d = 1;
  while(on < sz(P)) on *= 2, d++;
  vector<vi> jmp(d, P);
  rep(i,1,d) rep(j,0,sz(P))
    jmp[i][j] = jmp[i-1][jmp[i-1][j]];
  return jmp;
}

int jmp(vector<vi>& tbl, int nod, int steps){
  rep(i,0,sz(tbl))
    if(steps&(1<<i)) nod = tbl[i][nod];
  return nod;
}

int lca(vector<vi>& tbl, vi& depth, int a, int b) {
  if (depth[a] < depth[b]) swap(a, b);
  a = jmp(tbl, a, depth[a] - depth[b]);
  if (a == b) return a;
  for (int i = sz(tbl); i--;) {
    int c = tbl[i][a], d = tbl[i][b];
    if (c != d) a = c, b = d;
```

```
  }
  return tbl[0][a];
}
```

## LCA.h

**Description:** Data structure for computing lowest common ancestors in a tree (with 'rt' as root). C should be an adjacency list of the tree, either directed or undirected.

**Time:** $\mathcal{O}(N \log N + Q)$

"../data-structures/RMQ.h" 1153c0, 21 lines

```
struct LCA {
  int T = 0;
  vi time, path, ret;
  RMQ<int> rmq;

  LCA(vector<vi>& C, int rt) : time(sz(C)), rmq((dfs(C,rt,-1),
      ret)) {}
  void dfs(vector<vi>& C, int v, int par) {
    time[v] = T++;
    for (int y : C[v]) if (y != par) {
      path.push_back(v), ret.push_back(time[v]);
      dfs(C, y, v);
    }
  }

  int lca(int a, int b) {
    if (a == b) return a;
    tie(a, b) = minmax(time[a], time[b]);
    return path[rmq.query(a, b)];
  }
  //dist(a,b){return depth[a] + depth[b] - 2*depth[lca(a,b)];}
};
```

## CompressTree.h

**Description:** Given a rooted tree and a subset S of nodes, compute the minimal subtree that contains all the nodes by adding all (at most $|S| - 1$) pairwise LCA's and compressing edges. Returns a list of (par, orig_index) representing a tree rooted at 0. The root points to itself.

**Time:** $\mathcal{O}(|S| \log |S|)$

"LCA.h" 9775a0, 21 lines

```
typedef vector<pair<int, int>> vpi;
vpi compressTree(LCA& lca, const vi& subset) {
  static vi rev; rev.resize(sz(lca.time));
  vi li = subset, &T = lca.time;
  auto cmp = [&](int a, int b) { return T[a] < T[b]; };
  sort(all(li), cmp);
  int m = sz(li)-1;
  rep(i,0,m) {
    int a = li[i], b = li[i+1];
    li.push_back(lca.lca(a, b));
  }
  sort(all(li), cmp);
  li.erase(unique(all(li)), li.end());
  rep(i,0,sz(li)) rev[li[i]] = i;
  vpi ret = {pii(0, li[0])};
  rep(i,0,sz(li)-1) {
    int a = li[i], b = li[i+1];
    ret.emplace_back(rev[lca.lca(a, b)], b);
  }
  return ret;
}
```

## HLD.h

**Description:** Decomposes a tree into vertex disjoint heavy paths and light edges such that the path from any leaf to the root contains at most log(n) light edges. Takes as input the adjacency list (comment out (*) in dfsSz if no parent edges), a list of initial values $v$, and the root. VALS_EDGES being true means that values are stored in the edges, as opposed to the nodes.

**Time:** $\mathcal{O}\left((\log N)^2\right)$

"../data-structures/LazySegmentTree.h" ba77fc, 55 lines

```
template <bool VALS_EDGES> struct HLD {
    int N, tim = 0;
    vector<vi> adj;
    vi par, siz, rt, pos, tail;
    lztree tree;
    HLD(vector<vi> &adj, vector<T> v, int root)
        : N(sz(adj)), adj(adj), par(N, -1), siz(N, 1),
          rt(N,root),pos(N),tail(N,-1),tree(N) {
        dfsSz(root); dfsHld(root);
        rep(i,root,sz(v)) tree.set(pos[i], v[i]); // init vals
    }
  void dfsSz(int v) {
    for (int& u : adj[v]) {
      adj[u].erase(find(all(adj[u]), v)); // (*)
      par[u] = v;
      dfsSz(u);
      siz[v] += siz[u];
      if (siz[u] > siz[adj[v][0]]) swap(u, adj[v][0]);
    }
  }
    void dfsHld(int v) {
        pos[v] = tim++, tail[v] = v;
        for (bool fst = 1; int u : adj[v]) {
            rt[u] = (u == adj[v][0] ? rt[v] : u);
            dfsHld(u);
            if (fst) tail[v] = tail[u];
            fst = 0;
        }
    }
  template <class B> void process(int u, int v, B op) {
    for (;; v = par[rt[v]]) {
      if (pos[u] > pos[v]) swap(u, v);
      if (rt[u] == rt[v]) break;
      op(pos[rt[v]], pos[v] + 1);
    }
    op(pos[u] + VALS_EDGES, pos[v] + 1);
  }
    T get(int u) { // point set is similar
        return tree.get(pos[u]);
    }
  void modifyPath(int u, int v, U val) {
    process(u, v, [&](int l, int r) { tree.update(l, r, val); }
        );
  }
  // T query_chain(int v) { return tree.query(pos[rt[v]], pos[
      tail[v]]+1); }
    T queryPath(int u, int v) { // Modify depending on problem
        T res = idT; // unit
        process(u, v, [&](int l, int r) { // res = op(res,
            query)
                res = f(res, tree.query(l, r));
        });
        return res;
    }
    T querySubtree(int v) { // modifySubtree is similar
        return tree.query(pos[v] + VALS_EDGES, pos[v] + siz[v])
            ;
    }
};
```

## LinkCutTree.h

**Description:** Represents a forest of unrooted trees. You can add and remove edges (as long as the result is still a forest), and check whether two nodes are in the same tree.

**Time:** All operations take amortized $\mathcal{O}(\log N)$.

0fb462, 90 lines

```
struct Node { // Splay tree. Root's pp contains tree's parent.
  Node *p = 0, *pp = 0, *c[2];
  bool flip = 0;
  Node() { c[0] = c[1] = 0; fix(); }
  void fix() {
    if (c[0]) c[0]->p = this;
    if (c[1]) c[1]->p = this;
    // (+ update sum of subtree elements etc. if wanted)
  }
  void pushFlip() {
    if (!flip) return;
    flip = 0; swap(c[0], c[1]);
    if (c[0]) c[0]->flip ^= 1;
    if (c[1]) c[1]->flip ^= 1;
  }
  int up() { return p ? p->c[1] == this : -1; }
  void rot(int i, int b) {
    int h = i ^ b;
    Node *x = c[i], *y = b == 2 ? x : x->c[h], *z = b ? y : x;
    if ((y->p = p)) p->c[up()] = y;
    c[i] = z->c[i ^ 1];
    if (b < 2) {
      x->c[h] = y->c[h ^ 1];
      y->c[h ^ 1] = x;
    }
    z->c[i ^ 1] = this;
    fix(); x->fix(); y->fix();
    if (p) p->fix();
    swap(pp, y->pp);
  }
  void splay() {
    for (pushFlip(); p; ) {
      if (p->p) p->p->pushFlip();
      p->pushFlip(); pushFlip();
      int c1 = up(), c2 = p->up();
      if (c2 == -1) p->rot(c1, 2);
      else p->p->rot(c2, c1 != c2);
    }
  }
  Node* first() {
    pushFlip();
    return c[0] ? c[0]->first() : (splay(), this);
  }
};

struct LinkCut {
  vector<Node> node;
  LinkCut(int N) : node(N) {}

  void link(int u, int v) { // add an edge (u, v)
    assert(!connected(u, v));
    makeRoot(&node[u]);
    node[u].pp = &node[v];
  }
  void cut(int u, int v) { // remove an edge (u, v)
    Node *x = &node[u], *top = &node[v];
    makeRoot(top); x->splay();
    assert(top == (x->pp ?: x->c[0]));
    if (x->pp) x->pp = 0;
    else {
      x->c[0] = top->p = 0;
      x->fix();
    }
  }
  bool connected(int u, int v) { // are u, v in the same tree?
    Node* nu = access(&node[u])->first();
    return nu == access(&node[v])->first();
  }
  void makeRoot(Node* u) {
    access(u);
```

```
    u->splay();
    if(u->c[0]) {
      u->c[0]->p = 0;
      u->c[0]->flip ^= 1;
      u->c[0]->pp = u;
      u->c[0] = 0;
      u->fix();
    }
  }
  Node* access(Node* u) {
    u->splay();
    while (Node* pp = u->pp) {
      pp->splay(); u->pp = 0;
      if (pp->c[1]) {
        pp->c[1]->p = 0; pp->c[1]->pp = pp; }
      pp->c[1] = u; pp->fix(); u = pp;
    }
    return u;
  }
};
```

DirectedMST.h

**Description:** Finds a minimum spanning tree/arborescence of a directed graph, given a root node. If no MST exists, returns -1.

**Time:** $\mathcal{O}(E \log V)$

"../data-structures/UnionFindRollback.h" 39e620, 60 lines

```
struct Edge { int a, b; ll w; };
struct Node {
  Edge key;
  Node *l, *r;
  ll delta;
  void prop() {
    key.w += delta;
    if (l) l->delta += delta;
    if (r) r->delta += delta;
    delta = 0;
  }
  Edge top() { prop(); return key; }
};
Node *merge(Node *a, Node *b) {
  if (!a || !b) return a ?: b;
  a->prop(), b->prop();
  if (a->key.w > b->key.w) swap(a, b);
  swap(a->l, (a->r = merge(b, a->r)));
  return a;
}
void pop(Node*& a) { a->prop(); a = merge(a->l, a->r); }

pair<ll, vi> dmst(int n, int r, vector<Edge>& g) {
  RollbackUF uf(n);
  vector<Node*> heap(n);
  for (Edge e : g) heap[e.b] = merge(heap[e.b], new Node{e});
  ll res = 0;
  vi seen(n, -1), path(n), par(n);
  seen[r] = r;
  vector<Edge> Q(n), in(n, {-1,-1}), comp;
  deque<tuple<int, int, vector<Edge>>> cycs;
  rep(s,0,n) {
    int u = s, qi = 0, w;
    while (seen[u] < 0) {
      if (!heap[u]) return {-1,{}};
      Edge e = heap[u]->top();
      heap[u]->delta -= e.w, pop(heap[u]);
      Q[qi] = e, path[qi++] = u, seen[u] = s;
      res += e.w, u = uf.find(e.a);
      if (seen[u] == s) {
        Node* cyc = 0;
        int end = qi, time = uf.time();
        do cyc = merge(cyc, heap[w = path[--qi]]);
        while (uf.join(u, w));
        u = uf.find(u), heap[u] = cyc, seen[u] = -1;
        cycs.push_front({u, time, {&Q[qi], &Q[end]}});
      }
    }
    rep(i,0,qi) in[uf.find(Q[i].b)] = Q[i];
  }

  for (auto& [u,t,comp] : cycs) { // restore sol (optional)
    uf.rollback(t);
    Edge inEdge = in[u];
    for (auto& e : comp) in[uf.find(e.b)] = e;
    in[uf.find(inEdge.b)] = inEdge;
  }
  rep(i,0,n) par[i] = in[i].a;
  return {res, par};
}
```

## 8.5 Math

### 8.5.1 Number of Spanning Trees

Create an $N \times N$ matrix `mat`, and for each edge $a \to b \in G$, do `mat[a][b]--, mat[b][b]++` (and `mat[b][a]--, mat[a][a]++` if $G$ is undirected). Remove the $i$th row and column and take the determinant; this yields the number of directed spanning trees rooted at $i$ (if $G$ is undirected, remove any row/-column).

### 8.5.2 Erdős–Gallai theorem

A simple graph with node degrees $d_1 \geq \cdots \geq d_n$ exists iff $d_1 + \cdots + d_n$ is even and for every $k = 1 \ldots n$,

$$\sum_{i=1}^{k} d_i \leq k(k-1) + \sum_{i=k+1}^{n} \min(d_i, k).$$

# Geometry (9)

## 9.1 Geometric primitives

Point.h


**Description:** Class to handle points in the plane. T can be e.g. double or long long. (Avoid int.)

47ec0a, 28 lines

```
template <class T> int sgn(T x) { return (x > 0) - (x < 0); }
template<class T>
struct Point {
  typedef Point P;
  T x, y;
  explicit Point(T x=0, T y=0) : x(x), y(y) {}
  bool operator<(P p) const { return tie(x,y) < tie(p.x,p.y); }
  bool operator==(P p) const { return tie(x,y)==tie(p.x,p.y); }
  P operator+(P p) const { return P(x+p.x, y+p.y); }
  P operator-(P p) const { return P(x-p.x, y-p.y); }
  P operator*(T d) const { return P(x*d, y*d); }
  P operator/(T d) const { return P(x/d, y/d); }
  T dot(P p) const { return x*p.x + y*p.y; }
  T cross(P p) const { return x*p.y - y*p.x; }
  T cross(P a, P b) const { return (a-*this).cross(b-*this); }
  T dist2() const { return x*x + y*y; }
  double dist() const { return sqrt((double)dist2()); }
  // angle to x-axis in interval [-pi, pi]
  double angle() const { return atan2(y, x); }
  P unit() const { return *this/dist(); } // makes dist()=1
  P perp() const { return P(-y, x); } // rotates +90 degrees
  P normal() const { return perp().unit(); }
  // returns point rotated 'a' radians ccw around the origin
  P rotate(double a) const {
    return P(x*cos(a)-y*sin(a),x*sin(a)+y*cos(a)); }
  friend ostream& operator<<(ostream& os, P p) {
    return os << "(" << p.x << "," << p.y << ")"; }
};
```

lineDistance.h

**Description:**
Returns the signed distance between point p and the line containing points a and b. Positive value on left side and negative on right as seen from a towards b. a==b gives nan. P is supposed to be Point<T> or Point3D<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long. Using Point3D will always give a non-negative distance. For Point3D, call .dist on the result of the cross product.





"Point.h" f6bf6b, 4 lines

```
template<class P>
double lineDist(const P& a, const P& b, const P& p) {
  return (double)(b-a).cross(p-a)/(b-a).dist();
}
```

SegmentDistance.h

**Description:**
Returns the shortest distance between point p and the line segment from point s to e.

**Usage:** `Point<double> a, b(2,2), p(1,1);`
`bool onSegment = segDist(a,b,p) < 1e-10;`





"Point.h" 5c88f4, 6 lines

```
typedef Point<double> P;
double segDist(P& s, P& e, P& p) {
  if (s==e) return (p-s).dist();
  auto d = (e-s).dist2(), t = min(d,max(.0,(p-s).dot(e-s)));
  return ((p-s)*d-(e-s)*t).dist()/d;
}
```

SegmentIntersection.h

**Description:**
If a unique intersection point between the line segments going from s1 to e1 and from s2 to e2 exists then it is returned. If no intersection point exists an empty vector is returned. If infinitely many exist a vector with 2 elements is returned, containing the endpoints of the common line segment. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or long long.

**Usage:** `vector<P> inter = segInter(s1,e1,s2,e2);`
`if (sz(inter)==1)`
`cout << "segments intersect at " << inter[0] << endl;`





"Point.h", "OnSegment.h" 9d57f2, 13 lines

```
template<class P> vector<P> segInter(P a, P b, P c, P d) {
  auto oa = c.cross(d, a), ob = c.cross(d, b),
       oc = a.cross(b, c), od = a.cross(b, d);
  // Checks if intersection is single non-endpoint point.
  if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(od) < 0)
    return {(a * ob - b * oa) / (ob - oa)};
  set<P> s;
```

```
  if (onSegment(c, d, a)) s.insert(a);
  if (onSegment(c, d, b)) s.insert(b);
  if (onSegment(a, b, c)) s.insert(c);
  if (onSegment(a, b, d)) s.insert(d);
  return {all(s)};
}
```

## lineIntersection.h

**Description:**
If a unique intersection point of the lines going through s1,e1 and s2,e2 exists {1, point} is returned. If no intersection point exists {0, (0,0)} is returned and if infinitely many exists {-1, (0,0)} is returned. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or ll.




**Usage:** `auto res = lineInter(s1,e1,s2,e2);`

```
if (res.first == 1)
cout << "intersection point at " << res.second << endl;
```

"Point.h" a01f81, 8 lines

```
template<class P>
pair<int, P> lineInter(P s1, P e1, P s2, P e2) {
  auto d = (e1 - s1).cross(e2 - s2);
  if (d == 0) // if parallel
    return {-(s1.cross(e1, s2) == 0), P(0, 0)};
  auto p = s2.cross(e1, e2), q = s2.cross(e2, s1);
  return {1, (s1 * p + e1 * q) / d};
}
```

## sideOf.h

**Description:** Returns where $p$ is as seen from $s$ towards $e$. 1/0/-1 $\Leftrightarrow$ left/on line/right. If the optional argument $eps$ is given 0 is returned if $p$ is within distance $eps$ from the line. P is supposed to be Point<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long.

**Usage:** `bool left = sideOf(p1,p2,q)==1;`

"Point.h" 3af81c, 9 lines

```
template<class P>
int sideOf(P s, P e, P p) { return sgn(s.cross(e, p)); }

template<class P>
int sideOf(const P& s, const P& e, const P& p, double eps) {
  auto a = (e-s).cross(p-s);
  double l = (e-s).dist()*eps;
  return (a > l) - (a < -l);
}
```

## OnSegment.h

**Description:** Returns true iff p lies on the line segment from s to e. Use `(segDist(s,e,p)<=epsilon)` instead when using Point<double>.


"Point.h" c597e8, 3 lines

```
template<class P> bool onSegment(P s, P e, P p) {
  return p.cross(s, e) == 0 && (s - p).dot(e - p) <= 0;
}
```

## linearTransformation.h

**Description:**

Apply the linear transformation (translation, rotation and scaling) which takes line p0-p1 to line q0-q1 to point r.




"Point.h" 03a306, 6 lines

```
typedef Point<double> P;
P linearTransformation(const P& p0, const P& p1,
    const P& q0, const P& q1, const P& r) {
  P dp = p1-p0, dq = q1-q0, num(dp.cross(dq), dp.dot(dq));
  return q0 + P((r-p0).cross(num), (r-p0).dot(num))/dp.dist2();
}
```

## Angle.h

**Description:** A class for ordering angles (as represented by int points and a number of rotations around the origin). Useful for rotational sweeping. Sometimes also represents points or vectors.

**Usage:**
```
vector<Angle> v = {w[0], w[0].t360() ...};
sort(all(v));
int j = 0; rep(i,0,n) { while (v[j] < v[i].t180()) ++j; }
// sweeps j such that (j-i) represents the number of positively
oriented triangles with vertices at 0 and i
```

0f0602, 35 lines

```
struct Angle {
  int x, y;
  int t;
  Angle(int x, int y, int t=0) : x(x), y(y), t(t) {}
  Angle operator-(Angle b) const { return {x-b.x, y-b.y, t}; }
  int half() const { // true if angle is in [pi, 2pi).
    assert(x || y); // can change to whatever should be the "
        bigger half"
    return y < 0 || (y == 0 && x < 0);
  }
  Angle t90() const { return {-y, x, t + (half() && x >= 0)}; }
  Angle t180() const { return {-x, -y, t + half()}; }
  Angle t360() const { return {x, y, t + 1}; }
};
bool operator<(Angle a, Angle b) { // compare angles in [0, 2pi
    )
  // add a.dist2() and b.dist2() to also compare distances
  return make_tuple(a.t, a.half(), a.y * (ll)b.x) <
         make_tuple(b.t, b.half(), a.x * (ll)b.y);
}

// Given two points, this calculates the smallest angle between
// them, i.e., the angle that covers the defined line segment.
pair<Angle, Angle> segmentAngles(Angle a, Angle b) {
  if (b < a) swap(a, b);
  return (b < a.t180() ?
          make_pair(a, b) : make_pair(b, a.t360()));
}
Angle operator+(Angle a, Angle b) { // point a + vector b
  Angle r(a.x + b.x, a.y + b.y, a.t);
  if (a.t180() < r) r.t--;
  return r.t180() < a ? r.t360() : r;
}
Angle angleDiff(Angle a, Angle b) { // angle b - angle a
  int tu = b.t - a.t; a.t = b.t;
  return {a.x*b.x + a.y*b.y, a.x*b.y - a.y*b.x, tu - (b < a)};
}
```

# 9.2 Circles

## CircleIntersection.h

**Description:** Computes the pair of points at which two circles intersect. Returns false in case of no intersection.

"Point.h" 84d6d3, 11 lines

```
typedef Point<double> P;
bool circleInter(P a,P b,double r1,double r2,pair<P, P>* out) {
  if (a == b) { assert(r1 != r2); return false; }
  P vec = b - a;
  double d2 = vec.dist2(), sum = r1+r2, dif = r1-r2,
         p = (d2 + r1*r1 - r2*r2)/(d2*2), h2 = r1*r1 - p*p*d2;
  if (sum*sum < d2 || dif*dif > d2) return false;
  P mid = a + vec*p, per = vec.perp() * sqrt(fmax(0, h2) / d2);
  *out = {mid + per, mid - per};
  return true;
}
```

## CircleTangents.h

**Description:** Finds the external tangents of two circles, or internal if r2 is negated. Can return 0, 1, or 2 tangents – 0 if one circle contains the other (or overlaps it, in the internal case, or if the circles are the same); 1 if the circles are tangent to each other (in which case .first = .second and the tangent line is perpendicular to the line between the centers). .first and .second give the tangency points at circle 1 and 2 respectively. To find the tangents of a circle with a point set r2 to 0.

"Point.h" b0153d, 13 lines

```
template<class P>
vector<pair<P, P>> tangents(P c1, double r1, P c2, double r2) {
  P d = c2 - c1;
  double dr = r1 - r2, d2 = d.dist2(), h2 = d2 - dr * dr;
  if (d2 == 0 || h2 < 0)  return {};
  vector<pair<P, P>> out;
  for (double sign : {-1, 1}) {
    P v = (d * dr + d.perp() * sqrt(h2) * sign) / d2;
    out.push_back({c1 + v * r1, c2 + v * r2});
  }
  if (h2 == 0) out.pop_back();
  return out;
}
```

## CirclePolygonIntersection.h

**Description:** Returns the area of the intersection of a circle with a ccw polygon.

**Time:** $\mathcal{O}(n)$


"../../content/geometry/Point.h" 19add1, 19 lines

```
typedef Point<double> P;
#define arg(p, q) atan2(p.cross(q), p.dot(q))
double circlePoly(P c, double r, vector<P> ps) {
  auto tri = [&](P p, P q) {
    auto r2 = r * r / 2;
    P d = q - p;
    auto a = d.dot(p)/d.dist2(), b = (p.dist2()-r*r)/d.dist2();
    auto det = a * a - b;
    if (det <= 0) return arg(p, q) * r2;
    auto s = max(0., -a-sqrt(det)), t = min(1., -a+sqrt(det));
    if (t < 0 || 1 <= s) return arg(p, q) * r2;
    P u = p + d * s, v = q + d * (t-1);
    return arg(p,u) * r2 + u.cross(v)/2 + arg(v,q) * r2;
  };
  auto sum = 0.0;
  rep(i,0,sz(ps))
    sum += tri(ps[i] - c, ps[(i + 1) % sz(ps)] - c);
  return sum;
}
```

## circumcircle.h

**Description:**

The circumcirle of a triangle is the circle intersecting all three vertices. ccRadius returns the radius of the circle going through points A, B and C and ccCenter returns the center of the same circle.




"Point.h" 1caa3a, 9 lines

```
typedef Point<double> P;
double ccRadius(const P& A, const P& B, const P& C) {
  return (B-A).dist()*(C-B).dist()*(A-C).dist()/
      abs((B-A).cross(C-A))/2;
}
P ccCenter(const P& A, const P& B, const P& C) {
  P b = C-A, c = B-A;
  return A + (b*c.dist2()-c*b.dist2()).perp()/b.cross(c)/2;
}
```

### MinimumEnclosingCircle.h

**Description:** Computes the minimum circle that encloses a set of points.
**Time:** expected $\mathcal{O}(n)$

"circumcircle.h" 09dd0a, 17 lines

```
pair<P, double> mec(vector<P> ps) {
  shuffle(all(ps), mt19937(time(0)));
  P o = ps[0];
  double r = 0, EPS = 1 + 1e-8;
  rep(i,0,sz(ps)) if ((o - ps[i]).dist() > r * EPS) {
    o = ps[i], r = 0;
    rep(j,0,i) if ((o - ps[j]).dist() > r * EPS) {
      o = (ps[i] + ps[j]) / 2;
      r = (o - ps[i]).dist();
      rep(k,0,j) if ((o - ps[k]).dist() > r * EPS) {
        o = ccCenter(ps[i], ps[j], ps[k]);
        r = (o - ps[i]).dist();
      }
    }
  }
  return {o, r};
}
```

## 9.3 Polygons

### InsidePolygon.h

**Description:** Returns true if p lies within the polygon. If strict is true, it returns false for points on the boundary. The algorithm uses products in intermediate steps so watch out for overflow.
**Usage:** `vector<P> v = {P{4,4}, P{1,2}, P{2,1}};`
`bool in = inPolygon(v, P{3, 3}, false);`
**Time:** $\mathcal{O}(n)$

"Point.h", "OnSegment.h", "SegmentDistance.h" 2bf504, 11 lines

```
template<class P> // works for both ccw and cw polygons.
bool inPolygon(vector<P> &p, P a, bool strict = true) {
  int cnt = 0, n = sz(p);
  rep(i,0,n) {
    P q = p[(i + 1) % n];
    if (onSegment(p[i], q, a)) return !strict;
    //or: if (segDist(p[i], q, a) <= eps) return !strict;
    cnt ^= ((a.y<p[i].y) - (a.y<q.y)) * a.cross(p[i], q) > 0;
  }
  return cnt;
}
```

### PolygonArea.h

**Description:** Returns twice the signed area of a polygon. Clockwise enumeration gives negative area. Watch out for overflow if using int as T!

"Point.h" 95fc8f, 7 lines

```
template<class T>
T polygonArea2(vector<Point<T>>& v) {
  assert(!v.empty()); // or 0 area
  T a = v.back().cross(v[0]);
  rep(i,0,sz(v)-1) a += v[i].cross(v[i+1]);
  return a;
}
```

### PolygonCenter.h


**Description:** Returns the center of mass for a polygon.
**Time:** $\mathcal{O}(n)$

"Point.h" 9706dc, 9 lines

```
typedef Point<double> P;
P polygonCenter(const vector<P>& v) {
  P res(0, 0); double A = 0;
  for (int i = 0, j = sz(v) - 1; i < sz(v); j = i++) {
    res = res + (v[i] + v[j]) * v[j].cross(v[i]);
    A += v[j].cross(v[i]);
  }
  return res / A / 3;
}
```

### PolygonCut.h

**Description:**
Returns a vector with the vertices of a polygon with everything to the left of the line going from s to e cut away.
**Usage:** `vector<P> p = ...;`
`p = polygonCut(p, P(0,0), P(1,0));`




"Point.h" d07181, 13 lines

```
typedef Point<double> P;
vector<P> polygonCut(const vector<P>& poly, P s, P e) {
  vector<P> res;
  rep(i,0,sz(poly)) {
    P cur = poly[i], prev = i ? poly[i-1] : poly.back();
    auto a = s.cross(e, cur), b = s.cross(e, prev);
    if ((a < 0) != (b < 0))
      res.push_back(cur + (prev - cur) * (a / (a - b)));
    if (a < 0)
      res.push_back(cur);
  }
  return res;
}
```

### PolygonUnion.h

**Description:** Calculates the area of the union of $n$ polygons (not necessarily convex). The points within each polygon must be given in CCW order. (Epsilon checks may optionally be added to sideOf/sgn, but shouldn't be needed.)
**Time:** $\mathcal{O}\left(N^2\right)$, where $N$ is the total number of points

"Point.h", "sideOf.h" 3931c6, 33 lines

```
typedef Point<double> P;
double rat(P a, P b) { return sgn(b.x) ? a.x/b.x : a.y/b.y; }
double polyUnion(vector<vector<P>>& poly) {
  double ret = 0;
  rep(i,0,sz(poly)) rep(v,0,sz(poly[i])) {
    P A = poly[i][v], B = poly[i][(v + 1) % sz(poly[i])];
    vector<pair<double, int>> segs = {{0, 0}, {1, 0}};
    rep(j,0,sz(poly)) if (i != j) {
      rep(u,0,sz(poly[j])) {
        P C = poly[j][u], D = poly[j][(u + 1) % sz(poly[j])];
        int sc = sideOf(A, B, C), sd = sideOf(A, B, D);
        if (sc != sd) {
          double sa = C.cross(D, A), sb = C.cross(D, B);
          if (min(sc, sd) < 0)
            segs.emplace_back(sa / (sa - sb), sgn(sc - sd));
        } else if (!sc && !sd && j<i && sgn((B-A).dot(D-C))>0){
          segs.emplace_back(rat(C - A, B - A), 1);
          segs.emplace_back(rat(D - A, B - A), -1);
        }
      }
    }
    sort(all(segs));
    for (auto& s : segs) s.first = min(max(s.first, 0.0), 1.0);
    double sum = 0;
    int cnt = segs[0].second;
    rep(j,1,sz(segs)) {
      if (!cnt) sum += segs[j].first - segs[j - 1].first;
      cnt += segs[j].second;
    }
    ret += A.cross(B) * sum;
  }
  return ret / 2;
}
```

### HalfPlane.h

**Description:** Computes the intersection of a set of half-planes. Input is given as a set of planes, facing left. Output is the convex polygon representing the intersection. The points may have duplicates and be collinear. Will not fail catastrophically if eps > sqrt(2)(line intersection error). Likely to work for more ranges if 3 half planes are never guaranteed to intersect at the same point.
**Time:** $\mathcal{O}(n \log n)$

"Point.h", "sideOf.h", "lineIntersection.h" eda44b, 31 lines

```
typedef Point<double> P;
typedef array<P, 2> Line;
#define sp(a) a[0], a[1]
#define ang(a) (a[1] - a[0]).angle()

int angDiff(Line a, Line b) { return sgn(ang(a) - ang(b)); }
bool cmp(Line a, Line b) {
  int s = angDiff(a, b);
  return (s ? s : sideOf(sp(a), b[0])) < 0;
}
vector<P> halfPlaneIntersection(vector<Line> vs) {
  const double EPS = sqrt(2) * 1e-8;
  sort(all(vs), cmp);
  vector<Line> deq(sz(vs) + 5);
  vector<P> ans(sz(vs) + 5);
  deq[0] = vs[0];
  int ah = 0, at = 0, n = sz(vs);
  rep(i,1,n+1) {
    if (i == n) vs.push_back(deq[ah]);
    if (angDiff(vs[i], vs[i - 1]) == 0) continue;
    while (ah<at && sideOf(sp(vs[i]), ans[at-1], EPS) < 0)
      at--;
    while (i!=n && ah<at && sideOf(sp(vs[i]),ans[ah],EPS)<0)
      ah++;
    auto res = lineInter(sp(vs[i]), sp(deq[at]));
    if (res.first != 1) continue;
    ans[at++] = res.second, deq[at] = vs[i];
  }
  if (at - ah <= 2) return {};
  return {ans.begin() + ah, ans.begin() + at};
}
```

### ConvexHull.h

**Description:**
Returns a vector of the points of the convex hull in counterclockwise order. Points on the edge of the hull between two other points are not considered part of the hull.
**Time:** $\mathcal{O}(n \log n)$



"Point.h" 310954, 13 lines

```
typedef Point<ll> P;
vector<P> convexHull(vector<P> pts) {
  if (sz(pts) <= 1) return pts;
  sort(all(pts));
  vector<P> h(sz(pts)+1);
  int s = 0, t = 0;
  for (int it = 2; it--; s = --t, reverse(all(pts)))
    for (P p : pts) {
      while (t >= s + 2 && h[t-2].cross(h[t-1], p) <= 0) t--;
      h[t++] = p;
    }
  return {h.begin(), h.begin() + t - (t == 2 && h[0] == h[1])};
}
```

### HullDiameter.h

**Description:** Returns the two points with max distance on a convex hull (ccw, no duplicate/collinear points).
**Time:** $\mathcal{O}(n)$

"Point.h" c571b8, 12 lines

```
typedef Point<ll> P;
```

```
array<P, 2> hullDiameter(vector<P> S) {
  int n = sz(S), j = n < 2 ? 0 : 1;
  pair<ll, array<P, 2>> res({0, {S[0], S[0]}});
  rep(i,0,j)
    for (;; j = (j + 1) % n) {
      res = max(res, {(S[i] - S[j]).dist2(), {S[i], S[j]}});
      if ((S[(j + 1) % n] - S[j]).cross(S[i + 1] - S[i]) >= 0)
        break;
    }
  return res.second;
}
```

## PointInsideHull.h

**Description:** Determine whether a point t lies inside a convex hull (CCW order, with no collinear points). Returns true if point lies within the hull. If strict is true, points on the boundary aren't included.
**Time:** $\mathcal{O}(\log N)$

"Point.h", "sideOf.h", "OnSegment.h" 71446b, 14 lines

```
typedef Point<ll> P;

bool inHull(const vector<P>& l, P p, bool strict = true) {
  int a = 1, b = sz(l) - 1, r = !strict;
  if (sz(l) < 3) return r && onSegment(l[0], l.back(), p);
  if (sideOf(l[0], l[a], l[b]) > 0) swap(a, b);
  if (sideOf(l[0], l[a], p) >= r || sideOf(l[0], l[b], p)<= -r)
    return false;
  while (abs(a - b) > 1) {
    int c = (a + b) / 2;
    (sideOf(l[0], l[c], p) > 0 ? b : a) = c;
  }
  return sgn(l[a].cross(l[b], p)) < r;
}
```

## LineHullIntersection.h

**Description:** Line-convex polygon intersection. The polygon must be ccw and have no collinear points. lineHull(line, poly) returns a pair describing the intersection of a line with the polygon: • $(-1,-1)$ if no collision, • $(i,-1)$ if touching the corner $i$, • $(i,i)$ if along side $(i,i+1)$, • $(i,j)$ if crossing sides $(i,i+1)$ and $(j,j+1)$. In the last case, if a corner $i$ is crossed, this is treated as happening on side $(i,i+1)$. The points are returned in the same order as the line hits the polygon. `extrVertex` returns the point of a hull with the max projection onto a line.
**Time:** $\mathcal{O}(\log n)$

"Point.h" 7cf45b, 39 lines

```
#define cmp(i,j) sgn(dir.perp().cross(poly[(i)%n]-poly[(j)%n]))
#define extr(i) cmp(i + 1, i) >= 0 && cmp(i, i - 1 + n) < 0
template <class P> int extrVertex(vector<P>& poly, P dir) {
  int n = sz(poly), lo = 0, hi = n;
  if (extr(0)) return 0;
  while (lo + 1 < hi) {
    int m = (lo + hi) / 2;
    if (extr(m)) return m;
    int ls = cmp(lo + 1, lo), ms = cmp(m + 1, m);
    (ls < ms || (ls == ms && ls == cmp(lo, m)) ? hi : lo) = m;
  }
  return lo;
}

#define cmpL(i) sgn(a.cross(poly[i], b))
template <class P>
array<int, 2> lineHull(P a, P b, vector<P>& poly) {
  int endA = extrVertex(poly, (a - b).perp());
  int endB = extrVertex(poly, (b - a).perp());
  if (cmpL(endA) < 0 || cmpL(endB) > 0)
    return {-1, -1};
  array<int, 2> res;
  rep(i,0,2) {
    int lo = endB, hi = endA, n = sz(poly);
    while ((lo + 1) % n != hi) {
      int m = ((lo + hi + (lo < hi ? 0 : n)) / 2) % n;
      (cmpL(m) == cmpL(endB) ? lo : hi) = m;
    }
    res[i] = (lo + !cmpL(hi)) % n;
    swap(endA, endB);
  }
  if (res[0] == res[1]) return {res[0], -1};
  if (!cmpL(res[0]) && !cmpL(res[1]))
    switch ((res[0] - res[1] + sz(poly) + 1) % sz(poly)) {
      case 0: return {res[0], res[0]};
      case 2: return {res[1], res[1]};
    }
  return res;
}
```

# 9.4 Misc. Point Set Problems

## ClosestPair.h

**Description:** Finds the closest pair of points.
**Time:** $\mathcal{O}(n \log n)$

"Point.h" ac41a6, 17 lines

```
typedef Point<ll> P;
pair<P, P> closest(vector<P> v) {
  assert(sz(v) > 1);
  set<P> S;
  sort(all(v), [](P a, P b) { return a.y < b.y; });
  pair<ll, pair<P, P>> ret{LLONG_MAX, {P(), P()}};
  int j = 0;
  for (P p : v) {
    P d{1 + (ll)sqrt(ret.first), 0};
    while (v[j].y <= p.y - d.x) S.erase(v[j++]);
    auto lo = S.lower_bound(p - d), hi = S.upper_bound(p + d);
    for (; lo != hi; ++lo)
      ret = min(ret, {(*lo - p).dist2(), {*lo, p}});
    S.insert(p);
  }
  return ret.second;
}
```

## kdTree.h

**Description:** KD-tree (2d, can be extended to 3d)

"Point.h" bac5b0, 63 lines

```
typedef long long T;
typedef Point<T> P;
const T INF = numeric_limits<T>::max();

bool on_x(const P& a, const P& b) { return a.x < b.x; }
bool on_y(const P& a, const P& b) { return a.y < b.y; }

struct Node {
  P pt; // if this is a leaf, the single point in it
  T x0 = INF, x1 = -INF, y0 = INF, y1 = -INF; // bounds
  Node *first = 0, *second = 0;

  T distance(const P& p) { // min squared distance to a point
    T x = (p.x < x0 ? x0 : p.x > x1 ? x1 : p.x);
    T y = (p.y < y0 ? y0 : p.y > y1 ? y1 : p.y);
    return (P(x,y) - p).dist2();
  }

  Node(vector<P>&& vp) : pt(vp[0]) {
    for (P p : vp) {
      x0 = min(x0, p.x); x1 = max(x1, p.x);
      y0 = min(y0, p.y); y1 = max(y1, p.y);
    }
    if (vp.size() > 1) {
      // split on x if width >= height (not ideal...)
      sort(all(vp), x1 - x0 >= y1 - y0 ? on_x : on_y);
      // divide by taking half the array for each child (not
      // best performance with many duplicates in the middle)
      int half = sz(vp)/2;
      first = new Node({vp.begin(), vp.begin() + half});
      second = new Node({vp.begin() + half, vp.end()});
    }
  }
};

struct KDTree {
  Node* root;
  KDTree(const vector<P>& vp) : root(new Node({all(vp)})) {}

  pair<T, P> search(Node *node, const P& p) {
    if (!node->first) {
      // uncomment if we should not find the point itself:
      // if (p == node->pt) return {INF, P()};
      return make_pair((p - node->pt).dist2(), node->pt);
    }

    Node *f = node->first, *s = node->second;
    T bfirst = f->distance(p), bsec = s->distance(p);
    if (bfirst > bsec) swap(bsec, bfirst), swap(f, s);

    // search closest side first, other side if needed
    auto best = search(f, p);
    if (bsec < best.first)
      best = min(best, search(s, p));
    return best;
  }

  // find nearest point to a point, and its squared distance
  // (requires an arbitrary operator< for Point)
  pair<T, P> nearest(const P& p) {
    return search(root, p);
  }
};
```

## FastDelaunay.h

**Description:** Fast Delaunay triangulation. Each circumcircle contains none of the input points. There must be no duplicate points. If all points are on a line, no triangles will be returned. Should work for doubles as well, though there may be precision issues in 'circ'. Returns triangles in order {t[0][0], t[0][1], t[0][2], t[1][0], ...}, all counter-clockwise.
**Time:** $\mathcal{O}(n \log n)$

"Point.h" eefdf5, 88 lines

```
typedef Point<ll> P;
typedef struct Quad* Q;
typedef __int128_t lll; // (can be ll if coords are < 2e4)
P arb(LLONG_MAX,LLONG_MAX); // not equal to any other point

struct Quad {
  Q rot, o; P p = arb; bool mark;
  P& F() { return r()->p; }
  Q& r() { return rot->rot; }
  Q prev() { return rot->o->rot; }
  Q next() { return r()->prev(); }
} *H;

bool circ(P p, P a, P b, P c) { // is p in the circumcircle?
  lll p2 = p.dist2(), A = a.dist2()-p2,
      B = b.dist2()-p2, C = c.dist2()-p2;
  return p.cross(a,b)*C + p.cross(b,c)*A + p.cross(c,a)*B > 0;
}
Q makeEdge(P orig, P dest) {
  Q r = H ? H : new Quad{new Quad{new Quad{new Quad{0}}}};
  H = r->o; r->r()->r() = r;
```

```
  rep(i,0,4) r = r->rot, r->p = arb, r->o = i & 1 ? r : r->r();
  r->p = orig; r->F() = dest;
  return r;
}
void splice(Q a, Q b) {
  swap(a->o->rot->o, b->o->rot->o); swap(a->o, b->o);
}
Q connect(Q a, Q b) {
  Q q = makeEdge(a->F(), b->p);
  splice(q, a->next());
  splice(q->r(), b);
  return q;
}

pair<Q,Q> rec(const vector<P>& s) {
  if (sz(s) <= 3) {
    Q a = makeEdge(s[0], s[1]), b = makeEdge(s[1], s.back());
    if (sz(s) == 2) return { a, a->r() };
    splice(a->r(), b);
    auto side = s[0].cross(s[1], s[2]);
    Q c = side ? connect(b, a) : 0;
    return {side < 0 ? c->r() : a, side < 0 ? c : b->r() };
  }

#define H(e) e->F(), e->p
#define valid(e) (e->F().cross(H(base)) > 0)
  Q A, B, ra, rb;
  int half = sz(s) / 2;
  tie(ra, A) = rec({all(s) - half});
  tie(B, rb) = rec({sz(s) - half + all(s)});
  while ((B->p.cross(H(A)) < 0 && (A = A->next())) ||
         (A->p.cross(H(B)) > 0 && (B = B->r()->o)));
  Q base = connect(B->r(), A);
  if (A->p == ra->p) ra = base->r();
  if (B->p == rb->p) rb = base;

#define DEL(e, init, dir) Q e = init->dir; if (valid(e)) \
    while (circ(e->dir->F(), H(base), e->F())) { \
      Q t = e->dir; \
      splice(e, e->prev()); \
      splice(e->r(), e->r()->prev()); \
      e->o = H; H = e; e = t; \
    }
  for (;;) {
    DEL(LC, base->r(), o);  DEL(RC, base, prev());
    if (!valid(LC) && !valid(RC)) break;
    if (!valid(LC) || (valid(RC) && circ(H(RC), H(LC))))
      base = connect(RC, base->r());
    else
      base = connect(base->r(), LC->r());
  }
  return { ra, rb };
}

vector<P> triangulate(vector<P> pts) {
  sort(all(pts));  assert(unique(all(pts)) == pts.end());
  if (sz(pts) < 2) return {};
  Q e = rec(pts).first;
  vector<Q> q = {e};
  int qi = 0;
  while (e->o->F().cross(e->F(), e->p) < 0) e = e->o;
#define ADD { Q c = e; do { c->mark = 1; pts.push_back(c->p); \
  q.push_back(c->r()); c = c->next(); } while (c != e); }
  ADD; pts.clear();
  while (qi < sz(q)) if (!(e = q[qi++])->mark) ADD;
  return pts;
}
```

# 9.5 3D

## PolyhedronVolume.h

**Description:** Magic formula for the volume of a polyhedron. Faces should point outwards.

3058c3, 6 lines

```
template<class V, class L>
double signedPolyVolume(const V& p, const L& trilist) {
  double v = 0;
  for (auto i : trilist) v += p[i.a].cross(p[i.b]).dot(p[i.c]);
  return v / 6;
}
```

## Point3D.h

**Description:** Class to handle points in 3D space. T can be e.g. double or long long.

8058ae, 32 lines

```
template<class T> struct Point3D {
  typedef Point3D P;
  typedef const P& R;
  T x, y, z;
  explicit Point3D(T x=0, T y=0, T z=0) : x(x), y(y), z(z) {}
  bool operator<(R p) const {
    return tie(x, y, z) < tie(p.x, p.y, p.z); }
  bool operator==(R p) const {
    return tie(x, y, z) == tie(p.x, p.y, p.z); }
  P operator+(R p) const { return P(x+p.x, y+p.y, z+p.z); }
  P operator-(R p) const { return P(x-p.x, y-p.y, z-p.z); }
  P operator*(T d) const { return P(x*d, y*d, z*d); }
  P operator/(T d) const { return P(x/d, y/d, z/d); }
  T dot(R p) const { return x*p.x + y*p.y + z*p.z; }
  P cross(R p) const {
    return P(y*p.z - z*p.y, z*p.x - x*p.z, x*p.y - y*p.x);
  }
  T dist2() const { return x*x + y*y + z*z; }
  double dist() const { return sqrt((double)dist2()); }
  //Azimuthal angle (longitude) to x-axis in interval [-pi, pi]
  double phi() const { return atan2(y, x); }
  //Zenith angle (latitude) to the z-axis in interval [0, pi]
  double theta() const { return atan2(sqrt(x*x+y*y),z); }
  P unit() const { return *this/(T)dist(); } //makes dist()=1
  //returns unit vector normal to *this and p
  P normal(P p) const { return cross(p).unit(); }
  //returns point rotated 'angle' radians ccw around axis
  P rotate(double angle, P axis) const {
    double s = sin(angle), c = cos(angle); P u = axis.unit();
    return u*dot(u)*(1-c) + (*this)*c - cross(u)*s;
  }
};
```

## 3dHull.h

**Description:** Computes all faces of the 3-dimension hull of a point set. *No four points must be coplanar*, or else random results will be returned. All faces will point outwards.

**Time:** $\mathcal{O}\left(n^2\right)$

"Point3D.h"

5b45fc, 49 lines

```
typedef Point3D<double> P3;

struct PR {
  void ins(int x) { (a == -1 ? a : b) = x; }
  void rem(int x) { (a == x ? a : b) = -1; }
  int cnt() { return (a != -1) + (b != -1); }
  int a, b;
};

struct F { P3 q; int a, b, c; };

vector<F> hull3d(const vector<P3>& A) {
  assert(sz(A) >= 4);
  vector<vector<PR>> E(sz(A), vector<PR>(sz(A), {-1, -1}));
#define E(x,y) E[f.x][f.y]
  vector<F> FS;
  auto mf = [&](int i, int j, int k, int l) {
    P3 q = (A[j] - A[i]).cross((A[k] - A[i]));
    if (q.dot(A[l]) > q.dot(A[i]))
      q = q * -1;
    F f{q, i, j, k};
    E(a,b).ins(k); E(a,c).ins(j); E(b,c).ins(i);
    FS.push_back(f);
  };
  rep(i,0,4) rep(j,i+1,4) rep(k,j+1,4)
    mf(i, j, k, 6 - i - j - k);

  rep(i,4,sz(A)) {
    rep(j,0,sz(FS)) {
      F f = FS[j];
      if(f.q.dot(A[i]) > f.q.dot(A[f.a])) {
        E(a,b).rem(f.c);
        E(a,c).rem(f.b);
        E(b,c).rem(f.a);
        swap(FS[j--], FS.back());
        FS.pop_back();
      }
    }
    int nw = sz(FS);
    rep(j,0,nw) {
      F f = FS[j];
#define C(a, b, c) if (E(a,b).cnt() != 2) mf(f.a, f.b, i, f.c);
      C(a, b, c); C(a, c, b); C(b, c, a);
    }
  }
  for (F& it : FS) if ((A[it.b] - A[it.a]).cross(
    A[it.c] - A[it.a]).dot(it.q) <= 0) swap(it.c, it.b);
  return FS;
};
```

## sphericalDistance.h

**Description:** Returns the shortest distance on the sphere with radius radius between the points with azimuthal angles (longitude) f1 ($\phi_1$) and f2 ($\phi_2$) from x axis and zenith angles (latitude) t1 ($\theta_1$) and t2 ($\theta_2$) from z axis (0 = north pole). All angles measured in radians. The algorithm starts by converting the spherical coordinates to cartesian coordinates so if that is what you have you can use only the two last rows. dx*radius is then the difference between the two points in the x direction and d*radius is the total distance between the points.

611f07, 8 lines

```
double sphericalDistance(double f1, double t1,
    double f2, double t2, double radius) {
  double dx = sin(t2)*cos(f2) - sin(t1)*cos(f1);
  double dy = sin(t2)*sin(f2) - sin(t1)*sin(f1);
  double dz = cos(t2) - cos(t1);
  double d = sqrt(dx*dx + dy*dy + dz*dz);
  return radius*2*asin(d/2);
}
```

# Strings (10)

## KMP.h

**Description:** pi[x] computes the length of the longest prefix of s that ends at x, other than s[0...x] itself (abacaba -> 0010123). Can be used to find all occurrences of a string.

**Time:** $\mathcal{O}\left(n\right)$

d4375c, 16 lines

```
vi pi(const string& s) {
  vi p(sz(s));
  rep(i,1,sz(s)) {
```

```
    int g = p[i-1];
    while (g && s[i] != s[g]) g = p[g-1];
    p[i] = g + (s[i] == s[g]);
  }
  return p;
}

vi match(const string& s, const string& pat) {
  vi p = pi(pat + '\0' + s), res;
  rep(i,sz(p)-sz(s),sz(p))
    if (p[i] == sz(pat)) res.push_back(i - 2 * sz(pat));
  return res;
}
```

## Zfunc.h

**Description:** z[i] computes the length of the longest common prefix of s[i:] and s, except z[0] = 0. (abacaba -> 0010301)
**Time:** $\mathcal{O}(n)$

ee09e2, 12 lines

```
vi Z(const string& S) {
  vi z(sz(S));
  int l = -1, r = -1;
  rep(i,1,sz(S)) {
    z[i] = i >= r ? 0 : min(r - i, z[i - l]);
    while (i + z[i] < sz(S) && S[i + z[i]] == S[z[i]])
      z[i]++;
    if (i + z[i] > r)
      l = i, r = i + z[i];
  }
  return z;
}
```

## Manacher.h

**Description:** For each position in a string, computes p[0][i] = half length of longest even palindrome around pos i-1 and i, p[1][i] = longest odd (half rounded down).
**Time:** $\mathcal{O}(N)$

e7ad79, 13 lines

```
array<vi, 2> manacher(const string& s) {
  int n = sz(s);
  array<vi,2> p = {vi(n+1), vi(n)};
  rep(z,0,2) for (int i=0,l=0,r=0; i < n; i++) {
    int t = r-i+!z;
    if (i<r) p[z][i] = min(t, p[z][l+t]);
    int L = i-p[z][i], R = i+p[z][i]-!z;
    while (L>=1 && R+1<n && s[L-1] == s[R+1])
      p[z][i]++, L--, R++;
    if (R>r) l=L, r=R;
  }
  return p;
}
```

## MinRotation.h

**Description:** Finds the lexicographically smallest rotation of a string.
**Usage:** `rotate(v.begin(), v.begin()+minRotation(v), v.end());`
**Time:** $\mathcal{O}(N)$

d07a42, 8 lines

```
int minRotation(string s) {
  int a=0, N=sz(s); s += s;
  rep(b,0,N) rep(k,0,N) {
    if (a+k == b || s[a+k] < s[b+k]) {b += max(0, k-1); break;}
    if (s[a+k] > s[b+k]) { a = b; break; }
  }
  return a;
}
```

## SuffixArray.h

**Description:** Builds suffix array for a string. `sa[i]` is the starting index of the suffix which is $i$'th in the sorted suffix array. The returned vector is of size $n+1$, and `sa[0] = n`. The `lcp` array contains longest common prefixes for neighbouring strings in the suffix array: `lcp[i] = lcp(sa[i], sa[i-1])`, `lcp[0] = 0`. The input string must not contain any nul chars.
**Time:** $\mathcal{O}(n \log n)$

635552, 22 lines

```
struct SuffixArray {
  vi sa, lcp;
  SuffixArray(string s, int lim=256) { // or vector<int>
    s.push_back(0); int n = sz(s), k = 0, a, b;
    vi x(all(s)), y(n), ws(max(n, lim));
    sa = lcp = y, iota(all(sa), 0);
    for (int j = 0, p = 0; p < n; j = max(1, j * 2), lim = p) {
      p = j, iota(all(y), n - j);
      rep(i,0,n) if (sa[i] >= j) y[p++] = sa[i] - j;
      fill(all(ws), 0);
      rep(i,0,n) ws[x[i]]++;
      rep(i,1,lim) ws[i] += ws[i - 1];
      for (int i = n; i--;) sa[--ws[x[y[i]]]] = y[i];
      swap(x, y), p = 1, x[sa[0]] = 0;
      rep(i,1,n) a = sa[i - 1], b = sa[i], x[b] =
        (y[a] == y[b] && y[a + j] == y[b + j]) ? p - 1 : p++;
    }
    for (int i = 0, j; i < n - 1; lcp[x[i++]] = k)
      for (k && k--, j = sa[x[i] - 1];
          s[i + k] == s[j + k]; k++);
  }
};
```

## SuffixAutomaton.h

**Description:** Suffix automaton. Node 0 is always the start node, but the nodes are not necessarily in topological order.
**Time:** $\mathcal{O}(n \log \Sigma)$

079638, 36 lines

```
struct SAM {
    struct state {
        int len, link;
        map<char, int> next;
    };
    vector<state> q;
    int last;
    SAM() : last(0) { q.push_back({0,-1}); }
    int new_node() {
        q.emplace_back(); return sz(q) - 1;
    }
    void extend(char c) {
        int cur = new_node(), i = last;
        q[cur].len = q[last].len + 1;
        while (i != -1 && !q[i].next.contains(c))
            q[i].next[c] = cur, i = q[i].link;
        if (i == -1) q[cur].link = 0;
        else {
            int j = q[i].next[c];
            if (q[i].len+1 == q[j].len)
                q[cur].link = j;
            else {
                int clone = new_node();
                q[clone].len = q[i].len + 1;
                q[clone].next = q[j].next;
                q[clone].link = q[j].link;
                while (i != -1 && q[i].next[c] == j) {
                    q[i].next[c] = clone;
                    i = q[i].link;
                }
                q[j].link = q[cur].link = clone;
            }
        }
        last = cur;
    }
};
```

## Hashing.h

**Description:** Self-explanatory methods for string hashing.

2d2a67, 44 lines

```
// Arithmetic mod 2^64-1. 2x slower than mod 2^64 and more
// code, but works on evil test data (e.g. Thue-Morse, where
// ABBA... and BAAB... of length 2^10 hash the same mod 2^64).
// "typedef ull H;" instead if you think test data is random,
// or work mod 10^9+7 if the Birthday paradox is not a problem.
typedef uint64_t ull;
struct H {
  ull x; H(ull x=0) : x(x) {}
  H operator+(H o) { return x + o.x + (x + o.x < x); }
  H operator-(H o) { return *this + ~o.x; }
  H operator*(H o) { auto m = (__uint128_t)x * o.x;
    return H((ull)m) + (ull)(m >> 64); }
  ull get() const { return x + !~x; }
  bool operator==(H o) const { return get() == o.get(); }
  bool operator<(H o) const { return get() < o.get(); }
};
static const H C = (ll)1e11+3; // (order ~ 3e9; random also ok)

struct HashInterval {
  vector<H> ha, pw;
  HashInterval(string& str) : ha(sz(str)+1), pw(ha) {
    pw[0] = 1;
    rep(i,0,sz(str))
      ha[i+1] = ha[i] * C + str[i],
      pw[i+1] = pw[i] * C;
  }
  H hashInterval(int a, int b) { // hash [a, b)
    return ha[b] - ha[a] * pw[b - a];
  }
};

vector<H> getHashes(string& str, int length) {
  if (sz(str) < length) return {};
  H h = 0, pw = 1;
  rep(i,0,length)
    h = h * C + str[i], pw = pw * C;
  vector<H> ret = {h};
  rep(i,length,sz(str)) {
    ret.push_back(h = h * C + str[i] - pw * str[i-length]);
  }
  return ret;
}

H hashString(string& s){H h{}; for(char c:s) h=h*C+c;return h;}
```

## AhoCorasick.h

**Description:** Aho-Corasick automaton, used for multiple pattern matching. Initialize with AhoCorasick ac(patterns); the automaton start node will be at index 0. find(word) returns for each position the index of the longest word that ends there, or -1 if none. findAll(-, word) finds all words (up to $N\sqrt{N}$ many if no duplicate patterns) that start at each position (shortest first). Duplicate patterns are allowed; empty patterns are not. To find the longest words that start at each position, reverse all input. For large alphabets, split each symbol into chunks, with sentinel bits for symbol boundaries.
**Time:** construction takes $\mathcal{O}(26N)$, where $N$ = sum of length of patterns. find(x) is $\mathcal{O}(N)$, where N = length of x. findAll is $\mathcal{O}(NM)$.

f35677, 66 lines

```
struct AhoCorasick {
  enum {alpha = 26, first = 'A'}; // change this!
  struct Node {
    // (nmatches is optional)
    int back, next[alpha], start = -1, end = -1, nmatches = 0;
    Node(int v) { memset(next, v, sizeof(next)); }
  };
  vector<Node> N;
  vi backp;
```

```
  void insert(string& s, int j) {
    assert(!s.empty());
    int n = 0;
    for (char c : s) {
      int& m = N[n].next[c - first];
      if (m == -1) { n = m = sz(N); N.emplace_back(-1); }
      else n = m;
    }
    if (N[n].end == -1) N[n].start = j;
    backp.push_back(N[n].end);
    N[n].end = j;
    N[n].nmatches++;
  }
  AhoCorasick(vector<string>& pat) : N(1, -1) {
    rep(i,0,sz(pat)) insert(pat[i], i);
    N[0].back = sz(N);
    N.emplace_back(0);

    queue<int> q;
    for (q.push(0); !q.empty(); q.pop()) {
      int n = q.front(), prev = N[n].back;
      rep(i,0,alpha) {
        int &ed = N[n].next[i], y = N[prev].next[i];
        if (ed == -1) ed = y;
        else {
          N[ed].back = y;
          (N[ed].end == -1 ? N[ed].end : backp[N[ed].start])
            = N[y].end;
          N[ed].nmatches += N[y].nmatches;
          q.push(ed);
        }
      }
    }
  }
  vi find(string word) {
    int n = 0;
    vi res; // ll count = 0;
    for (char c : word) {
      n = N[n].next[c - first];
      res.push_back(N[n].end);
      // count += N[n].nmatches;
    }
    return res;
  }
  vector<vi> findAll(vector<string>& pat, string word) {
    vi r = find(word);
    vector<vi> res(sz(word));
    rep(i,0,sz(word)) {
      int ind = r[i];
      while (ind != -1) {
        res[i - sz(pat[ind]) + 1].push_back(ind);
        ind = backp[ind];
      }
    }
    return res;
  }
};
```

# Various (11)

## 11.1 Intervals

### IntervalContainer.h

**Description:** Add and remove intervals from a set of disjoint intervals. Will merge the added interval with any overlapping intervals in the set when adding. Intervals are [inclusive, exclusive).

**Time:** $\mathcal{O}(\log N)$ edce47, 23 lines

```
set<pii>::iterator addInterval(set<pii>& is, int L, int R) {
  if (L == R) return is.end();
  auto it = is.lower_bound({L, R}), before = it;
  while (it != is.end() && it->first <= R) {
    R = max(R, it->second);
    before = it = is.erase(it);
  }
  if (it != is.begin() && (--it)->second >= L) {
    L = min(L, it->first);
    R = max(R, it->second);
    is.erase(it);
  }
  return is.insert(before, {L,R});
}

void removeInterval(set<pii>& is, int L, int R) {
  if (L == R) return;
  auto it = addInterval(is, L, R);
  auto r2 = it->second;
  if (it->first == L) is.erase(it);
  else (int&)it->second = L;
  if (R != r2) is.emplace(R, r2);
}
```

### IntervalCover.h

**Description:** Compute indices of smallest set of intervals covering another interval. Intervals should be [inclusive, exclusive). To support [inclusive, inclusive], change (A) to add `|| R.empty()`. Returns empty set on failure (or if G is empty).

**Time:** $\mathcal{O}(N \log N)$ 9e9d8d, 19 lines

```
template<class T>
vi cover(pair<T, T> G, vector<pair<T, T>> I) {
  vi S(sz(I)), R;
  iota(all(S), 0);
  sort(all(S), [&](int a, int b) { return I[a] < I[b]; });
  T cur = G.first;
  int at = 0;
  while (cur < G.second) { // (A)
    pair<T, int> mx = make_pair(cur, -1);
    while (at < sz(I) && I[S[at]].first <= cur) {
      mx = max(mx, make_pair(I[S[at]].second, S[at]));
      at++;
    }
    if (mx.second == -1) return {};
    cur = mx.first;
    R.push_back(mx.second);
  }
  return R;
}
```

### ConstantIntervals.h

**Description:** Split a monotone function on [from, to) into a minimal set of half-open intervals on which it has the same value. Runs a callback g for each such interval.

**Usage:** `constantIntervals(0, sz(v), [&](int x){return v[x];}, [&](int lo, int hi, T val){...});`

**Time:** $\mathcal{O}\left(k \log \frac{n}{k}\right)$ 753a4c, 19 lines

```
template<class F, class G, class T>
void rec(int from, int to, F& f, G& g, int& i, T& p, T q) {
  if (p == q) return;
  if (from == to) {
    g(i, to, p);
    i = to; p = q;
  } else {
    int mid = (from + to) >> 1;
    rec(from, mid, f, g, i, p, f(mid));
    rec(mid+1, to, f, g, i, p, q);
  }
}
template<class F, class G>
void constantIntervals(int from, int to, F f, G g) {
  if (to <= from) return;
  int i = from; auto p = f(i), q = f(to-1);
  rec(from, to-1, f, g, i, p, q);
  g(i, to, q);
}
```

## 11.2 Misc. algorithms

### TernarySearch.h

**Description:** Find the smallest i in $[a, b]$ that maximizes $f(i)$, assuming that $f(a) < \ldots < f(i) \geq \cdots \geq f(b)$. To reverse which of the sides allows non-strict inequalities, change the $<$ marked with (A) to $<=$, and reverse the loop at (B). To minimize $f$, change it to $>$, also at (B).

**Usage:** `int ind = ternSearch(0,n-1,[&](int i){return a[i];});`

**Time:** $\mathcal{O}(\log(b-a))$ 9155b4, 11 lines

```
template<class F>
int ternSearch(int a, int b, F f) {
  assert(a <= b);
  while (b - a >= 5) {
    int mid = (a + b) / 2;
    if (f(mid) < f(mid+1)) a = mid; // (A)
    else b = mid+1;
  }
  rep(i,a+1,b+1) if (f(a) < f(i)) a = i; // (B)
  return a;
}
```

### LIS.h

**Description:** Compute indices for the longest increasing subsequence.

**Time:** $\mathcal{O}(N \log N)$ 2932a0, 17 lines

```
template<class I> vi lis(const vector<I>& S) {
  if (S.empty()) return {};
  vi prev(sz(S));
  typedef pair<I, int> p;
  vector<p> res;
  rep(i,0,sz(S)) {
    // change 0 -> i for longest non-decreasing subsequence
    auto it = lower_bound(all(res), p{S[i], 0});
    if (it == res.end()) res.emplace_back(), it = res.end()-1;
    *it = {S[i], i};
    prev[i] = it == res.begin() ? 0 : (it-1)->second;
  }
  int L = sz(res), cur = res.back().second;
  vi ans(L);
  while (L--) ans[L] = cur, cur = prev[cur];
  return ans;
}
```

### FastKnapsack.h

**Description:** Given N non-negative integer weights w and a non-negative target t, computes the maximum S <= t such that S is the sum of some subset of the weights.

**Time:** $\mathcal{O}(N \max(w_i))$ b20ccc, 16 lines

```
int knapsack(vi w, int t) {
  int a = 0, b = 0, x;
  while (b < sz(w) && a + w[b] <= t) a += w[b++];
  if (b == sz(w)) return a;
  int m = *max_element(all(w));
  vi u, v(2*m, -1);
  v[a+m-t] = b;
```

```
  rep(i,b,sz(w)) {
    u = v;
    rep(x,0,m) v[x+w[i]] = max(v[x+w[i]], u[x]);
    for (x = 2*m; --x > m;) rep(j, max(0,u[x]), v[x])
      v[x-w[j]] = max(v[x-w[j]], j);
  }
  for (a = t; v[a+m-t] < 0; a--) ;
  return a;
}
```

## 11.3 Dynamic programming

KnuthDP.h

**Description:** When doing DP on intervals: $a[i][j] = \min_{i<k<j}(a[i][k] + a[k][j]) + f(i,j)$, where the (minimal) optimal $k$ increases with both $i$ and $j$, one can solve intervals in increasing order of length, and search $k = p[i][j]$ for $a[i][j]$ only between $p[i][j-1]$ and $p[i+1][j]$. This is known as Knuth DP. Sufficient criteria for this are if $f(b,c) \le f(a,d)$ and $f(a,c) + f(b,d) \le f(a,d) + f(b,c)$ for all $a \le b \le c \le d$. Consider also: LineContainer (ch. Data structures), monotone queues, ternary search.
**Time:** $\mathcal{O}\left(N^2\right)$

DivideAndConquerDP.h

**Description:** Given $a[i] = \min_{lo(i)\le k<hi(i)}(f(i,k))$ where the (minimal) optimal $k$ increases with $i$, computes $a[i]$ for $i = L..R-1$.
**Time:** $\mathcal{O}\left((N + (hi-lo))\log N\right)$
d38d2b, 18 lines

```
struct DP { // Modify at will:
  int lo(int ind) { return 0; }
  int hi(int ind) { return ind; }
  ll f(int ind, int k) { return dp[ind][k]; }
  void store(int ind, int k, ll v) { res[ind] = pii(k, v); }

  void rec(int L, int R, int LO, int HI) {
    if (L >= R) return;
    int mid = (L + R) >> 1;
    pair<ll, int> best(LLONG_MAX, LO);
    rep(k, max(LO,lo(mid)), min(HI,hi(mid)))
      best = min(best, make_pair(f(mid, k), k));
    store(mid, best.second, best.first);
    rec(L, mid, LO, best.second+1);
    rec(mid+1, R, best.second, HI);
  }
  void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
};
```

## 11.4 Debugging tricks

- `signal(SIGSEGV, [](int) { _Exit(0); });` converts segfaults into Wrong Answers. Similarly one can catch SIGABRT (assertion failures) and SIGFPE (zero divisions). `_GLIBCXX_DEBUG` failures generate SIGABRT (or SIGSEGV on gcc 5.4.0 apparently).
- `feenableexcept(29);` kills the program on NaNs (1), 0-divs (4), infinities (8) and denormals (16).

## 11.5 Optimization tricks

`__builtin_ia32_ldmxcsr(40896);` disables denormals (which make floats 20x slower near their minimum value).

### 11.5.1 Bit hacks

- `x & -x` is the least bit in `x`.
- `for (int x = m; x; ) { --x &= m; ... }` loops over all subset masks of `m` (except `m` itself).
- `c = x&-x, r = x+c; (((r^x) >> 2)/c) | r` is the next number after `x` with the same number of bits set.
- `rep(b,0,K) rep(i,0,(1 << K)) if (i & 1 << b) D[i] += D[i^(1 << b)];` computes all sums of subsets.

### 11.5.2 Pragmas for bitset (put before bits/stdc++.h)

- `#pragma GCC optimize("O3,unroll-loops")`
- `#include <bits/allocator.h>`
- `#pragma GCC target("avx2,bmi,bmi2,popcnt,lzcnt")`

FastMod.h

**Description:** Compute $a\%b$ about 5 times faster than usual, where $b$ is constant but not known at compile time. Returns a value congruent to $a$ (mod $b$) in the range $[0, 2b)$.
751a02, 8 lines

```
typedef unsigned long long ull;
struct FastMod {
  ull b, m;
  FastMod(ull b) : b(b), m(-1ULL / b) {}
  ull reduce(ull a) { // a % b + (0 or b)
    return a - (ull)((__uint128_t(m) * a) >> 64) * b;
  }
};
```

UniformRandom.h

**Description:** High-quality uniform RNG for integers.
**Usage:** `urand(a, b)` returns an integer in `[a, b]`.
**Time:** 400ms for 1e8 numbers.
39a02b, 3 lines

```
// can also use mt19937_64 for 64-bit integers
mt19937 rng(chrono::steady_clock::now().time_since_epoch().
    count());
int urand(int a, int b) { return uniform_int_distribution<int>(
    a, b)(rng); }
```

StressTest.sh
27 lines

```
# Usage: bash stress.sh [fast] [slow] [gen] [# iters]
# Example: bash stress.sh main main2 generator 1000
# cc8b47
# remove this and add -O2 if you want
flags="-std=c++20 -g -fsanitize=address,undefined"

g++ $flags $1.cpp -o $1
g++ $flags $2.cpp -o $2
g++ $flags $3.cpp -o $3

for ((t=1; t<=$4; t++)) do
  ./$3 > input
  ./$2 < input > outslow
  ./$1 < input > outwrong
  if [[ "$?" -ne 0 ]] || ! (cmp -s "outwrong" "outslow") then
    echo error found
    echo input:
    cat input
    echo wrong output:
    cat outwrong
    echo slow output:
    cat outslow
    exit
  fi
  echo passed $t tests
done
echo passed all tests
```

ExpressionTree.h

**Description:** Creates an expression tree for left-associative operations. Change N and prec() as needed.
**Usage:** `Val *root = parseExpression(s); // tree dp...`
**Time:** $\mathcal{O}(N)$
9842ea, 52 lines

```
const int N = 2e6; // max node count in expr tree. |S| is
    enough
struct Val { // 32 bytes/node
    int v; // only used if op = 0
    char op; Val *l, *r; // only used if op != 0
    Val(int v=0) : v(v), op(0), l(0), r(0) {}
    Val(char op, Val *l, Val *r) : op(op), l(l), r(r) {}
};
Val arr[N]; int last = 0;

Val *parseExpression(string &s) {
    using C = array<int, 3>; // precedence comparator
    vector<pair<C, char>> ops;
    vector<Val*> vals;
    int depth = 0;

    auto prec = [&](char c, int i) -> C { // change to your ops
        int r;
        if (c == '+' || c == '-') r = 0;
        else if (c == '*' || c == '/' || c == '_') r = 1;
        else assert(0); // i for right assoc, -i for left
        return {depth, r, c == '_' ? i : -i};
    };
    auto clear = [&](C minp) {
        while (!ops.empty()) {
            auto [p, c] = ops.back();
            if (p < minp) break;
            ops.pop_back();
            auto b = vals.back(); vals.pop_back();
            if (c == '_') {  // unary op
                vals.pb(&(arr[last++] = Val(c, b, 0)));
            } else { // binary op
                auto a = vals.back(); vals.pop_back();
                vals.pb(&(arr[last++] = Val(c, a, b)));
            }
        }
    };
    for (int i = -1; char c : s) { i++;
        bool pdigit = i >= 1 && '0' <= s[i-1] && s[i-1] <= '9';
        if (c == '(') depth++;
        else if (c == ')') depth--;
        else if ('0' <= c && c <= '9') {
            if (pdigit) vals.back()->v = 10*vals.back()->v + c-
                '0';
            else vals.pb(&(arr[last++] = Val(c-'0')));
        } else {
            if (c == '-' && !pdigit
                && !(i >= 1 && s[i-1] == ')')) c = '_'; //
                    unary op
            clear(prec(c, i)); ops.pb({prec(c, i), c});
        }
```

```
    }
    clear({-1});
    return vals[0];
}
```