

Appendix: Retained Local Transitions and Branchwise Charges

Yuli Li

Jingping Yang

Renhao Zhang

May 2026

A Verification format for retained local transitions

This appendix expands the retained local transition theorem into the mode-by-mode verifications used in the proof. The purpose of the notation in this appendix is only to make the entropy accounting checkable. At a retained state S we write ν_S for the current conditional law of the active samples. A local analysis may use a finite analysis partition $\mathcal{A}_S$, but the child retained state is always determined by a retained label Y . The child law is

$$\nu_{S,Y} = \text{Law}(\text{active samples} \mid S, Y),$$

where the conditioning event $\{Y = y\}$ is the union of all analysis atoms mapped to y .

Definition A.1 (Retained transition certificate). *A retained transition certificate at a state S consists of:*

- (i) *an analysis partition $\mathcal{A}_S$;*
- (ii) *a retained output map $\pi_S : \mathcal{A}_S \rightarrow \mathcal{Y}_S$;*
- (iii) *for each $y \in \mathcal{Y}_S$, a child mode or a terminal declaration;*
- (iv) *a nonnegative local charge $c(S, y)$;*
- (v) *a proof that every future selector on the child depends only on y , the fixed thresholds, and the quotient law $\nu_{S,y}$.*

The certificate is valid if

$$H(Y \mid S) + \mathbb{E}[\ell_{\text{pr}}(S, Y) \mid S] \leq \mathbb{E}[c(S, Y) \mid S].$$

Lemma A.2 (Quotient measurability). *Suppose a transition certificate is valid and suppose that all future selection rules are deterministic functions of the retained label and quotient law. Then replacing the analysis atom by the retained label changes neither the distribution of future retained labels nor the distribution of terminal value/equality shadows.*

Proof. Condition on a retained label $Y = y$. By definition the child law is the conditional law on the union of all analysis atoms mapped to y . Every later selector is a deterministic function of this conditional law, the thresholds, and y . Therefore the conditional distribution of the future retained process is the same whether one remembers the finer atom or only y . Iterating over the tree gives the assertion by induction on depth. Entropy cannot increase under the deterministic projection from the full analysis transcript to the retained terminal object. $\square$

Lemma A.3 (Universal retained charge form). *For every valid transition certificate in the modes below, the local charge is a sum of terms from the following list:*

<i>value shadow</i>	$C_{\text{val}} T_{\text{val}} + C_{\text{lab}} R,$
<i>equality shadow</i>	$C_{\text{eq}} T_{\text{eq}} + C_{\text{lab}} R,$
<i>fresh promotion</i>	$C_{\text{fr}} \Delta U_{\text{fr}} ,$
<i>old registration</i>	$C_{\text{old}} \sum_{i \in U} \Delta M(i) + C_{\text{blk}} \Delta B_{\text{old}} ,$
<i>hash window</i>	$C_{\text{hash}} (B_{\text{win}} + h + 1),$
<i>scale descent or birth</i>	$C_{\text{sc}} \Delta_{\text{sc}} + C_{\text{birth}},$
<i>pruning</i>	$-\log(\text{retained mass}).$

All constants depend only on the fixed threshold hierarchy.

Proof. The next appendices verify the modes one by one. The displayed list is deliberately redundant: a transition may use both a terminal term and a pruning term, or both an old registration and a hash token. What matters is that each retained output is recorded in exactly one monotone account, while analysis-only data is not retained. $\square$

B Close-pair and product-KL transitions

A close-pair state carries a public ordered block $J = (j_1, \dots, j_m)$ and three active samples with

$$X_J = Y_J = A, \quad Z_J = B, \quad B_j \neq A_j \quad (j \in J)$$

on the branch under consideration.

Lemma B.1 (Close-pair low-entropy terminalization). *If the conditional law of A_J has an atom a with conditional mass at least $\exp(-\lambda|J|)$, then the branch terminalizes as a projected value shadow of size $|J|$ and local charge at most $\lambda|J| + O(1)$.*

Proof. The event $A_J = a$ is the same as $X_J = Y_J = a$. It is a value shadow on two sample labels, or on one label if the duplicate pin is suppressed. The retained terminal object records J and a and no nonterminal child inherits the complement. The entropy of the retained atom is the negative logarithm of its mass, at most $\lambda|J|$ up to the fixed tie-break overhead. $\square$

Lemma B.2 (Close-pair equality terminalization). *If a public subblock $J' \subseteq J$ is retained only through the event $X_{J'} = Y_{J'}$ and this event has branch mass at least $\exp(-\lambda|J'| - c)$, then the branch terminalizes with equality-shadow charge $\lambda|J'| + c$ and no alphabet value is retained.*

Proof. This is the equality-shadow descent argument applied inside the current retained state. Conditioned on the parent state, J' is public. The terminal record is the pair of sample labels and J' ; it is independent of the alphabet values. The recurrence cost is paid by the equality-shadow size. $\square$

Lemma B.3 (Cross-collision one-coordinate routing). *Let p and q be the conditional one-coordinate laws of two actual sample coordinates at a public coordinate i . If $\sum_a p(a)q(a) > \gamma$, then there is an exhaustive retained routing into:*

- (i) *a terminal value pin of mass at least $\rho\tau$;*
- (ii) *a charged pruning branch of loss at most $-\log(1 - \rho)$;*

(iii) a labelled low-collision hash coordinate for one actual sample label.

The selected coordinate is i and the selected sample label is one of the actual labels in the close-pair state.

Proof. Apply the heavy-light decomposition to one of the two laws. If a heavy atom occurs, it is a terminal one-coordinate value shadow. On the light complement L , if the mass is below ρ , discard it as pruning. Otherwise the conditional collision is at most τ by the heavy threshold. This gives a low-collision coordinate law for the actual sample label at coordinate i . The retained nonterminal output is only the labelled coordinate together with the paid set event $X_i \in L$; the auxiliary comparison law is not retained. $\square$

Lemma B.4 (Product-KL first-crossing charge). *Let P be the conditional law of (A_J, B_J) and let Q be the product reference law used in the close-pair state. Write the interleaved actual-coordinate list*

$$V = (A_{j_1}, B_{j_1}, A_{j_2}, B_{j_2}, \dots, A_{j_m}, B_{j_m}).$$

If $D(P\|Q) > \epsilon m$, then the first-crossing scan along V produces either a terminal projected prefix, a terminal one-coordinate pin, a charged pruning branch, or a labelled low-collision hash coordinate for an actual sample coordinate. The retained cost of the prefix of length r is at most $O(r)$.

Proof. The interleaving is a bijective reindexing of (A_J, B_J) , so relative entropy is invariant. The chain rule gives

$$D(P_V\|Q_V) = \sum_{t=1}^{2m} \mathbb{E}_P D(P(V_t \mid V_{<t})\|Q(V_t \mid V_{<t})).$$

Use the first time at which the cumulative information exceeds the fixed linear budget. Before that time the prefix entropy is amortized by its length. At the crossing coordinate, the one-step law is routed by the heavy-light lemma. A heavy branch terminalizes as a value shadow. A small complement is pruning. A large light complement has bounded collision and enters the hash window for the actual sample coordinate V_t , which is either $A_{j_s} = X_{j_s} = Y_{j_s}$ or $B_{j_s} = Z_{j_s}$. The reference law Q is used only to locate the crossing and is discarded before a child state is entered. $\square$

Lemma B.5 (Close-pair complement transfer). *Assume the terminal, cross-collision, and product-KL alternatives above fail on a close-pair block J . Then the conditional law on the block is within the product reference law at relative entropy $O(|J|)$, has no heavy one-coordinate atom outside terminal branches, and has bounded average split count. Consequently either a projected near-sunflower residual block is returned with branch cost $O(|J|)$, or the state is declared a bounded leaf.*

Proof. Failure of the product-KL alternative gives the relative entropy bound. Failure of the terminal and cross-collision alternatives bounds the one-coordinate heavy atoms and the relevant collision averages. By the entropy transfer inequality, an event with product-law probability at least $\exp(-a|J|)$ has P -probability at least $\exp(-O_a(|J|))$ after discarding an explicitly charged exceptional set; otherwise the exceptional set is the pruning branch. Under the product law, independent coordinate estimates and the collision-split lemma give a near-sunflower split block of size proportional to the retained block size unless the block lies below the bounded-leaf threshold. The chosen block is selected by the fixed public tie-break from the quotient law; it therefore is a retained output with charge $O(|J|)$. $\square$

Proposition B.6 (Expanded close-pair transition certificate). *Every close-pair state admits a valid retained transition certificate. The retained outputs are terminal value shadows, terminal equality*

shadows, charged pruning branches, labelled actual-coordinate hash coordinates, or residual blocks selected from the quotient law. No child retains the pair alphabet or the product reference law.

Proof. Apply the alternatives in the following order: low-entropy terminalization, equality terminalization, cross-collision routing, product-KL first crossing, and complement transfer. The failure of all preceding alternatives is exactly the hypothesis of the next one. The retained charges are supplied by the lemmas above. Quotient measurability holds because terminal branches stop, hash branches retain only the actual labelled coordinate and paid event, and residual branches choose their block by a deterministic tie-break from the quotient law. $\square$

C Fixed labelled hash windows

Lemma C.1 (Stopped key contains no erased old atom). *At the moment a coordinate enters a labelled hash window, the window key consists only of the current retained state, the paid prefix/set events of the producing scan, and the public label of the sample coordinate. It contains no equality pattern or witness label that has been quotiented in a previous transition.*

Proof. A coordinate is appended only by a retained transition output. The output label is the actual sample label, the coordinate index, and the paid event under which the one-coordinate law has small collision. The child law has already been quotiented by any analysis partition. Thus an erased pattern atom is not a variable in the parent state of the hash window and cannot be part of its key. $\square$

Lemma C.2 (Hash-window copy charge). *If a labelled window has stopped key K with $H(K) \leq B_{\text{win}}$ and h surviving coordinates with collision at most β and codeword atoms below β , then its retained return has charge $O(B_{\text{win}} + h)$ and creates at most one token.*

Proof. Since $H_3(K) \leq H(K) \leq B_{\text{win}}$, the conditioned-copy cost for three matching copies is at most a fixed multiple of B_{win} in the Renyi-copying inequality. On the h coordinates, expected split exposure is $O(\beta h)$ and exact exposure of the returned block costs $O(h)$. The codeword atom bound makes the three copied words distinct with fixed positive probability. The retained result is one near-sunflower residual block and one bounded hash token. All auxiliary copy labels are erased by reservoir marginalization before a child state is entered. $\square$

Proposition C.3 (Expanded hash transition certificate). *Each labelled hash-window state admits a valid retained transition certificate. It either terminalizes a value prefix, closes as a bounded-support/fresh-old classification, or returns one residual block with charge $O(B_{\text{win}} + h)$ and one token which must be assigned to the next hard exit.*

Proof. If appending the next prefix or set event would exceed the stopped budget, the already paid prefix terminalizes as a value shadow. If fewer than h live coordinates are available and no further coordinate can be appended within the budget, the bounded coordinate list is classified by the retained fresh/old rule. If h live coordinates are present, apply the previous lemma. The token rule is injective along the descendant residual block: no descendant state or new window is entered until the token is assigned to a terminal, fresh, old, scale, or birth exit. $\square$

D Residual transitions

A residual state carries a public domain L and a split witness $W_L(X, Y, Z) \subseteq L$ under an actual triple of samples. Let U be the current old support.

Lemma D.1 (Fresh support certificate). *Let*

$$F = \{i \in L \setminus U : \mathbb{P}(i \in W_L) > 0\}.$$

The branch admits a retained transition in which either a nonempty fresh subset is promoted and paid once by the fresh potential, or all residual witnesses in the child are old-supported. The cost is $O(|F|)$ when F is bounded and is public when F is large.

Proof. The set F is determined by the quotient law. If it exceeds the fixed fresh threshold, promote it publicly to the old support; fresh coordinates are promoted only once, so the fresh potential pays. If it is below threshold, reveal the five-state pattern on F as a bounded analysis partition. On atoms with a split fresh coordinate, choose the majority role and promote that split part. On the remaining atoms, no fresh coordinate is split and the child is old-supported. The bounded pattern is either terminal/fresh data or erased before continuation. $\square$

Lemma D.2 (Dense residual DRC certificate). *If $\mathbb{E}|W_L| \geq \beta|L|$ and $|L|$ is above the fixed bounded threshold, then there is a public block $J \subseteq L$ of size $\Theta(|L|)$ on a subevent of mass $\exp(-O(|J|))$ such that all coordinates of J split. After a bounded role exposure, a subblock of size at least $|J|/3$ is a close-pair block. Its retained charge is $O(|J|)$.*

Proof. Apply the DRC row-block lemma to the events $E_i = \{i \in W_L\}$ on the probability space of the current actual triple. The deterministic public tie-break selects J . On the event that all $i \in J$ split, one of the three split roles occurs on at least a third of the block. Exposing the role vector costs $O(|J|)$ and is retained only through the selected subblock and role. Fresh subblocks are promoted; old subblocks are registered by old marks or enter the old-window queue. The child law is the quotient law under the retained output. $\square$

Lemma D.3 (Bounded residual certificate). *If $|L|$ is below the fixed threshold, the residual state has a bounded-leaf exit or a bounded explicit transition whose entropy is absorbed into the base constant.*

Proof. There are finitely many coordinate subsets, role patterns, and retained labels at ranks below the threshold. Choose the base constant larger than the maximum finite loss. No alphabet value is retained unless it terminalizes as a value shadow. $\square$

Lemma D.4 (Sparse old-supported retained certificate). *Suppose the residual witness is old-supported, $W_L \subseteq U$, and sparse, $\mathbb{E}|W_L| < \beta|L|$. Then the transition has a valid retained certificate with no retained selector of the form $W_L \subseteq L$.*

Proof. Let

$$O = \{u \in U : \mathbb{P}(u \in W_L) > 0\}.$$

This set is public from the quotient law. Use the five-state equality pattern on O only as an analysis partition. On each atom the actual split set $K = W_L$ is determined. If K yields a terminal value or equality shadow, stop. Otherwise take a majority role block $K_0 \subseteq K$. If registering K_0 would cross the old cap at some coordinate, use the high-revisit certificate in E. If no cap is crossed, update the capped vector M on K_0 and retain only the resulting mark increment, bounded role label, queue position, and scale label. Finally quotient all pattern atoms with the same retained update. Therefore W_L is not a child selector; only its effect on the finite retained old state is kept. The entropy of all such retained old information is paid by the old compression lemma. $\square$

Proposition D.5 (Expanded residual transition certificate). *Every residual state admits a retained transition certificate whose outputs are fresh promotion, dense close-pair birth, bounded leaf, sparse old registration, high-revisit exit, scale descent, terminal value/equality shadow, or charged pruning. The local charge is bounded by the corresponding row of $A.3$.*

Proof. Apply the fresh support certificate first. On the old-supported quotient child, split according to whether $\mathbb{E}|W_L| \geq \beta|L|$ and whether $|L|$ is bounded. The dense and bounded cases are handled by the preceding lemmas. The sparse case is D.4. Each branch either terminalizes or carries forward only retained data listed in the certificate. $\square$

E Old windows and high-revisit routing

Lemma E.1 (High-revisit local pressure). *Suppose a retained old-window state contains an actual close-pair coordinate i with role $X_i = Y_i \neq Z_i$ whose registration would increase $M(i)$ beyond the cap Q . Let $A_i = X_i = Y_i$ under the current quotient law. Then there is an exhaustive retained routing into a terminal value pin, a charged pruning branch, or a labelled low-collision hash coordinate for the actual sample label.*

Proof. Fix thresholds ρ, τ . Let

$$H = \{a : \mathbb{P}(A_i = a) \geq \rho\tau\}, \quad L = \Omega_i \setminus H.$$

Branches $A_i = a \in H$ are terminal value pins of mass at least $\rho\tau$. If $\mathbb{P}(A_i \in L) < \rho$, the light branch is discarded with pruning loss $-\log(1 - \mathbb{P}(A_i \in L)) = O(\rho)$. If $\mathbb{P}(A_i \in L) \geq \rho$, then conditioned on $A_i \in L$, every atom has mass below τ and the collision of the conditional one-coordinate law is at most τ/ρ after adjusting constants. With thresholds chosen hierarchically this is the required low-collision hash coordinate. The coordinate i is actual because it lies in the block whose mark would cross the cap. No old value vector is retained by a nonterminal child. $\square$

Lemma E.2 (Low-revisit registration). *If all actual old close-pair blocks in the current old window can be registered without crossing the cap Q , then the nonterminal retained state records only the increment of M , a bounded queue label, an active block label, role labels, and scale labels. Its entropy over the old epoch is $O(|U|)$.*

Proof. Each coordinate of U receives at most Q mark increments before high revisit. The vector $M : U \rightarrow \{0, \dots, Q\}$ has entropy at most $|U| \log(Q + 1)$. Queues, role labels, active block labels, and scale labels have only boundedly many statuses per coordinate and boundedly many active positions. Thus their total state space is $\exp(O(|U|))$. Analysis patterns and old block orders not encoded in these finite labels are quotiented before the child is entered. $\square$

Lemma E.3 (Signature change clearing). *Before an old-window transition changes the active sample-label signature, every bounded queue for the previous signature is terminalized, registered in M , charged to a hard exit, or erased by quotienting. The new child law is the conditional law on the union of atoms with the same retained state.*

Proof. Equality patterns are meaningful only for the actual sample-label signature under which they were created. A new signature cannot inherit them. Therefore the transition first processes all queued blocks for the previous signature. Blocks that matter later are either terminal shadows or finite retained labels; the rest are analysis-only and are projected away. The child for the new signature is then defined by conditioning on the retained label alone. $\square$

Proposition E.4 (Expanded old-window transition certificate). *Every fixed-scale old-window state admits a valid retained transition certificate. Its outputs are terminal value/equality shadows, high-revisit routing, low-revisit registration, signature-change clearing, charged pruning, or bounded-leaf exit. No high-symbol old value vector is retained by a nonterminal child.*

Proof. Process the queued actual blocks in public order. A low-entropy value branch terminalizes. A public close-pair block may terminalize as equality. If a registration would cross the cap, use E.1. Otherwise use E.2. At a signature change, use E.3. These alternatives are exhaustive because every block is either terminalized, registered, routed by high revisit, or cleared before the next signature. $\square$

F Reservoirs, scale birth, and hash-token matching

Lemma F.1 (Reservoir erasure). *Auxiliary sample labels created only for conditioned copying or for certifying a public event may be erased once the retained output is recorded. Marginalizing to the retained labels preserves all future selector laws and cannot increase any retained key entropy.*

Proof. Future selectors are measurable with respect to retained labels and the quotient law. The marginal law on those labels is exactly the pushforward of the full conditional law. Data processing gives the entropy monotonicity. $\square$

Lemma F.2 (Scale-birth certificate). *Every nonterminal active block born from a residual, close-pair, dense DRC, old-window, or hash return carries a certificate paid by one of: parent rank decrease, fresh promotion, old mark increment, scale descent, or hash-token assignment.*

Proof. The transition that creates the block is one of the retained outputs already verified. If it is fresh, the fresh potential pays. If it is old, the mark increment or queue label pays. If it comes from a rank-reducing DRC block, the parent rank potential pays the child deposit. If it follows a hash return, the single token is attached to the first subsequent hard exit and cannot be inherited beyond it. No other transition creates an active block. $\square$

Lemma F.3 (Hash-token matching). *Each hash-window return creates at most one token, and this token is assigned to the first terminal, fresh, old, scale, or birth exit reached by the returned residual block before any descendant state or new window is entered.*

Proof. The token is part of the retained state of the returned block. The transition rules give it priority over further descent: a child state can be entered only after the returned block has been classified by the residual rule. The first hard exit is unique along a branch, and the token is erased after assignment. Hence the assignment is injective. $\square$

G Branchwise charges

Proposition G.1 (Local charge table). *For every retained transition in the preceding appendices the following table gives a valid entropy bound.*

<i>transition</i>	<i>retained label</i>	<i>charge</i>
<i>value terminal</i>	(J, a, s)	$O(J + 1)$
<i>equality terminal</i>	(J, s, t)	$O(J + 1)$
<i>product-KL prefix</i>	$V_{\leq r} = u$	$O(r)$
<i>heavy one-coordinate pin</i>	$X_i = a$	$O(1)$ <i>plus paid prefix</i>
<i>light pruning</i>	<i>discarded mass</i>	$-\log(\text{retained mass})$
<i>hash coordinate</i>	$(s, i, \text{paid event})$	$O(B_{\text{win}} + 1)$
<i>hash return</i>	<i>residual block and token</i>	$O(B_{\text{win}} + h)$
<i>fresh promotion</i>	ΔU_{fr}	$O(\Delta U_{\text{fr}})$
<i>old registration</i>	ΔM , <i>bounded labels</i>	$O(\sum_i \Delta M(i)) + O(U \text{ reserve})$
<i>scale birth/descent</i>	<i>scale label</i>	$O(\Delta \Phi_{\text{sc}})$

Proof. The first two rows are terminal shadows. Product-KL prefixes are amortized by the first-crossing construction. Heavy pins and pruning are the two branches of the heavy-light decomposition. Hash rows are bounded by the stopped key and copying lemmas. Fresh rows are disjoint along a branch. Old rows are paid by the capped vector and finite per-coordinate annotations. Scale rows are paid by geometric descent or the birth certificate. The retained labels in different rows are disjoint accounting objects; hence there is no double charge. $\square$

Proposition G.2 (Telescoping potential inequality). *With constants chosen in the order*

$$B_{\text{win}}, h, Q, C_{\text{blk}}, \omega_{\text{old}}, B_o, B_f, B_{\text{sc}}, B_{\text{rk}}, A, D,$$

large enough at each stage, the sum of all branch charges satisfies

$$\sum_{v \text{ reached}} c_v \leq C(T(\Theta_{\text{val}}) + T(\Theta_{\text{eq}}) + R(\Theta) + \Delta \Phi).$$

Proof. Terminal rows contribute the displayed T and R terms. Fresh promotions are disjoint because a coordinate enters U only once. Old registrations are bounded by the initial reserve $B_o|U|$ minus the weighted debit $\omega_{\text{old}} \sum_i M(i)$, and high revisit stops registration past cap. Hash-window costs are fixed and are assigned by the token lemma to the first hard exit of the returned block. Scale descents are geometric after a certified birth. Choosing the coefficients in the displayed order makes each local inequality strict with fixed slack. Summing the nonnegative decreases over the branch gives the result. $\square$

H Finite truncation

Proposition H.1 (No zero-cost retained loop). *After bounded leaves are imposed below the fixed scale m_0 , the retained transition process has finite truncations whose discarded tails are controlled by recorded pruning loss.*

Proof. Consider the lexicographic resource vector consisting of remaining fresh coordinates, remaining old mark capacity $\sum_{i \in U} (Q - M(i))$, hash-token status and remaining window budget, active

scale levels, bounded queue capacity, and bounded rank. A nonterminal transition either records a terminal/pruning event, consumes one of these resources, or is a deterministic relabelling of the same retained state. The last possibility cannot repeat: with the same retained state and quotient law, the deterministic tie-break chooses the same transition and is declared a bounded leaf by the transition rule. Fresh promotions and old mark increments are finite; hash tokens must be assigned before descent; scales decrease geometrically unless a paid birth occurs; queues are bounded and must clear before signature change. Therefore every infinite branch has tails supported only on explicitly pruned mass. Letting truncation depth tend to infinity preserves the entropy inequality by monotone convergence. $\square$

I Correctness-critical retained checks

This section records the five local points at which the retained-state proof would otherwise differ from a full-transcript proof. They are not cosmetic: each one rules out a possible hidden selector or hidden key. The preceding appendices establish the mode certificates; the lemmas below make explicit the measurability and charging features which are used when the certificates are composed.

Lemma I.1 (Sparse old witnesses are not retained selectors). *Let S be an old-supported residual retained state with old support U and split witness*

$$W = W_L(X, Y, Z) \subseteq U.$$

Assume the sparse case $\mathbb{E}(|W| \mid S) < \beta|L|$. Let

$$O = \{u \in U : \mathbb{P}(u \in W \mid S) > 0\}.$$

There is a retained refinement in which the five-state equality pattern on O is used only as an analysis variable. If a nonempty old coordinate set K obtained from W is carried to a nonterminal child, then K is encoded as one of the following retained objects:

- (a) *an increment of the capped mark vector $M : U \rightarrow \{0, \dots, Q\}$;*
- (b) *a member of a bounded old queue whose coordinates are also marked by M before the queue can change signature;*
- (c) *an active old block whose coordinate set is the support of such a mark increment;*
- (d) *a terminal value or equality shadow.*

In particular the subset $W \subseteq L$ is never a child selector, and after quotienting no future selector is allowed to depend on the analysis atom which determined W .

Proof. The set O is determined by the parent quotient law, hence is public at S . Refine the current event by the five equality types

$$XYZ, \quad XY|Z, \quad XZ|Y, \quad YZ|X, \quad X|Y|Z$$

on the coordinates in O . This refinement is an analysis partition. On each atom the actual split set W is determined, since a coordinate is split exactly in the last three types. If the atom gives a terminal value or equality branch, no child is entered.

Otherwise choose, by the fixed public order and a majority role tie-break, a nonempty block $K \subseteq W$ which will be used in the next state. The retained label is not the full pattern on O ; it is

one of the four objects listed in the statement. If K is placed in an old queue or active old block, the retained label also records the corresponding mark increment on K . If this increment would cross the cap Q at a coordinate, the branch is not continued by retaining K ; it is routed by the high-revisit lemma below.

Now merge all analysis atoms which give the same retained label. The child law is the conditional law on this union. By the definition of retained transitions, all later choices are recomputed from this quotient law and the retained label. Since the five-state pattern atom is not part of that label, it cannot later choose a terminal shadow, a hash key, or a DRC block. This proves both the non-retention of W as a selector and the child-measurability assertion. $\square$

Lemma I.2 (Old-coordinate entropy is paid by the final retained state). *During one old-support epoch, suppose every nonterminal old coordinate block carried forward satisfies Lemma I.1. Conditional on the old support U , the total entropy of the old non-value information retained at the end of the epoch is at most $C_{\text{old}}|U| + O(1)$, where C_{old} depends only on Q and on the bounded queue/reservoir constants.*

Proof. The final old state consists of the capped vector $M \in \{0, \dots, Q\}^U$, bounded queue positions, bounded active old blocks, finite role labels, finite scale labels, and at most one bounded token. Each coordinate of U has only finitely many possible annotations, and the number of active positions is bounded. Thus the number of possible final old states is at most $\exp(C_{\text{old}}|U| + O(1))$. Taking logarithms gives the entropy bound.

The order in which analysis atoms were inspected and the full equality patterns on the sets O are not part of the final state. They were either terminalized or quotiented before continuation. Hence their entropy is not included in the terminal retained object. $\square$

Lemma I.3 (High-revisit actual-coordinate routing). *Assume a branch attempts to register an actual old coordinate i beyond the cap Q in the role $X_i = Y_i \neq Z_i$. Let $A = X_i = Y_i$ under the parent quotient law. For fixed thresholds $0 < \rho, \beta < 1$, the branch has an exhaustive retained routing into:*

- (i) *terminal value atoms $A = a$ with $\mathbb{P}(A = a) \geq \rho\beta$;*
- (ii) *a charged pruning branch of total mass below ρ ;*
- (iii) *a low-collision one-coordinate hash output for the actual coordinate i and the actual sample label X or Y .*

No high-symbol old value is retained by a nonterminal child.

Proof. Let

$$H = \{a : \mathbb{P}(A = a \mid S) \geq \rho\beta\}, \quad L = \Omega_i \setminus H,$$

and put $q = \mathbb{P}(A \in L \mid S)$. For each $a \in H$, the event $A = a$ is a one-coordinate value shadow of mass at least $\rho\beta$, so it terminalizes. If $q < \rho$, the light branch is discarded or normalized as a pruning branch with loss bounded in terms of ρ .

It remains to consider $q \geq \rho$. Conditional on $A \in L$, every atom has mass at most $(\rho\beta)/q \leq \beta$. Therefore the conditional one-coordinate collision is at most the maximum atom mass, hence at most β . The retained nonterminal output is the actual coordinate i , the actual sample label, and the paid event $A \in L$. The alphabet values in L are not retained. Thus the output is a labelled low-collision hash coordinate. These three cases partition the branch. $\square$

Lemma I.4 (Actual-coordinate KL first crossing). *Let P be the conditional law of a close-pair block and Q its product reference law. Write the scan variables as the actual tuple-coordinate list*

$$V = (A_{j_1}, B_{j_1}, \dots, A_{j_m}, B_{j_m}),$$

where $A_{j_s} = X_{j_s} = Y_{j_s}$ and $B_{j_s} = Z_{j_s}$ on the close-pair branch. If a positive-KL exit is taken, the retained output is either a terminal prefix/value shadow, a charged pruning branch, or a low-collision hash coordinate for one of the actual sample coordinates appearing in this list. No retained output is a low-collision statement about the pair alphabet or about the reference law Q .

Proof. Relative entropy is invariant under the displayed bijective coordinate listing, and the chain rule gives

$$D(P_V \| Q_V) = \sum_{t=1}^{2m} \mathbb{E}_P D(P(V_t | V_{<t}) \| Q(V_t | V_{<t})).$$

The first-crossing rule stops at the first actual variable V_t at which the cumulative information budget crosses the fixed threshold. The prefix $V_{<t}$ is either terminalized as a projected value shadow or charged as the paid prefix of the hash-producing branch. At V_t apply the one-coordinate heavy/light routing to the actual conditional law of V_t under P . Heavy atoms terminalize, small complements are pruning, and a large light complement gives a low-collision law for the actual coordinate and actual sample label represented by V_t .

The reference law Q is used only to certify the first crossing and the size of the paid prefix. It is not retained in the child state. Therefore the output cannot be a statement solely about the pair alphabet or about Q . $\square$

Lemma I.5 (No erased key in fixed-window copying). *A fixed labelled hash window may use only a key measurable with respect to the parent retained state and the paid stopped window transcript. If an equality pattern or witness label has been quotiented in an earlier transition, then it is not measurable with respect to this key and cannot be matched across conditioned copies.*

Proof. The window key is constructed from the retained parent state, the public sample label of the window, and the stopped list of paid prefix, tail, pruning, and coordinate-production events appended before the budget B_{win} closes. By the retained transition rule, an erased analysis atom is not a coordinate of the parent retained state and is not part of any paid event in the stopped transcript. Hence it is not a function of the key.

The conditioned-copy lemma is applied only to this key. Since $H_3(K) \leq H(K) \leq B_{\text{win}}$ for the stopped key K , the copy tax is bounded by the window budget. Any proof step which required equality of an erased pattern across independent copies would be outside this key and is therefore disallowed. $\square$

Proposition I.6 (Finite retained termination without zero-cost loops). *After imposing bounded leaves below the fixed threshold, the retained-state process has no infinite branch on which no terminal shadow, no pruning loss, and no monotone resource expenditure occurs.*

Proof. At a nonterminal retained state record the finite resource vector

$$\mathcal{R}(S) = (F_{\text{rem}}, O_{\text{rem}}, H_{\text{rem}}, T_{\text{tok}}, \Sigma_{\text{sc}}, Q_{\text{cap}}, r_{\text{bd}}),$$

where F_{rem} is the number of coordinates not yet fresh-promoted, $O_{\text{rem}} = \sum_{i \in U} (Q - M(i))$ is the remaining old mark capacity, H_{rem} is the remaining stopped budget in the current hash window, T_{tok} is the pending-token status, Σ_{sc} is the multiset of active scale levels, Q_{cap} is the remaining bounded

queue capacity, and r_{bd} is the bounded-rank indicator. Order these resources lexicographically after replacing scale levels by their fixed finite discretization.

Every nonterminal transition has one of the following effects. A fresh branch decreases F_{rem} . A low-revisit old branch decreases O_{rem} or fills bounded queue capacity which must be cleared before a signature change. A hash step decreases H_{rem} or creates a token, and a token must be assigned before any descendant state or new window is entered. A scale branch decreases a discretized scale unless a paid birth creates a new active block. A bounded branch stops. Terminal and pruning branches are excluded by the hypothesis of the proposition.

If none of these resources changes, then the retained state and quotient law are identical to the previous occurrence. Since the selection rules use deterministic tie-breaks from the retained state and quotient law, the same transition would be chosen again. The transition convention declares such a deterministic repetition to be a bounded leaf. Hence no zero-cost infinite branch exists. Finite truncations therefore lose only explicitly recorded pruning mass, and the retained entropy inequalities pass to the limit by monotone convergence. $\square$

J Appendix assembly

Theorem J.1 (Expanded retained local transition theorem). *The retained local transition theorem used in the main text follows from the transition certificates in Appendices B–I. Every nonterminal mode has a valid retained transition certificate, and every branchwise charge is one of the rows in G.1.*

Proof. Inactive states are routed by the collision/DRC activation lemmas of the main text. Close-pair and product-KL states are handled by B.6. Hash-window states are handled by C.3. Residual states are handled by D.5. Old-window states are handled by E.4. Reservoir, scale-birth, and token rules are handled by Appendices F and G. Finite truncation is H.1 and the strengthened no-loop statement is Proposition I.6. Quotient measurability is supplied by A.2, the sparse selector condition by Lemma I.1, the actual-coordinate KL condition by Lemma I.4, and hash-key cleanliness by Lemma I.5. Therefore every child state retains only terminal data, monotone finite-state data, charged pruning, or a quotient law from which all future selectors are recomputed. $\square$