

# Aruba HP switches configuration examples cookbook

## Table of Contents

Reset/wipe switch configuration to the factory defaults. ....	1
Restrict management access to specific IP addresses .....	1
Add default gateway on Layer 2 switch for management .....	2

Author: Yuri Slobodyanyuk, <https://www.linkedin.com/in/yurislobodyanyuk/>

## Reset/wipe switch configuration to the factory defaults

**WARNING** | This will erase all the configuration and cannot be undone.

If you don't have privileged EXEC access to the switch:

1. Push and hold the *Reset* button with sharp object like pen/pencil.
2. Now also push and hold *Clear* button with another sharp object.
3. When LEDs are turned on - release *Reset* button, while holding the *Clear*.
4. When LEDs start to blink, release the *Clear* button as well.

If you have privileged EXEC access to the switch, just run (config)# erase startup and reboot.

## Restrict management access to specific IP addresses

To limit access to the switch, use ip authorized-managers command. Example - limit access to a single IP of 192.168.13.127:

```
ip authorized-managers 192.168.13.127 255.255.255.255 access operator
ip authorized-managers 192.168.13.127 255.255.255.255 access manager
```

# Add default gateway on Layer 2 switch for management

We have to set default gateway on a switch for the management VLAN we choose to be reachable and managed remotely. The command does not mention explicitly the VLAN number, just make sure the network is the network configured on the management VLAN.

```
ip default t-gateway 10.13.13.127
```

It is, for example, when VLAN 200 is configured as management VLAN:

```
vlan 200
Ê name "MgmtVlan"
Ê tagged Trk1
Ê ip address 10.13.13.250 255.255.255.0
Ê exit
```