

# Syntax and Semantics of Abstract Binding Trees

Jon Sterling and Darin Morrison

Abstract binding trees (abts) are a generalization of abstract syntax trees where operators may express variable binding structure as part of their arities. Originally formulated by Peter Aczel [1], unsorted abts have been deployed successfully as the uniform syntactic framework for several implementations of Constructive Type Theory, including Nuprl [3], MetaPRL [12] and JonPRL [20].

In *Practical Foundations for Programming Languages* [11], Robert Harper develops the multi-sorted version of abstract binding trees and proposes an extension to include families of operators indexed by *symbols*, which are, unlike variables, subject to only distinctness-preserving renaming and not substitution; furthermore, symbols do not appear in the syntax of abts, and are only introduced as parameters to operators. This extension to support symbols is essential for a correct treatment of programming languages with open sums (e.g. ML's `exn` type), as well as assignable references.

In parallel, M. Fiore and his collaborators have developed the categorical semantics for several variations of second-order algebraic theories [7, 9, 5, 6]; of these, the simply sorted variants are equivalent to Harper's abstract binding trees augmented with a notion of second-order variable (metavariable).

The contribution of this paper is the development of the syntax and semantics of multi-sorted nominal abts, an extension of second order universal algebra to support symbol-indexed families of operators. Additionally, we have developed the categorical semantics for abts formally in Constructive Type Theory using the Agda proof assistant [17].

## 1 Categorical Preliminaries

Fix a set  $\mathcal{S}$  of *sorts*; we will say  $\tau$  *sort* when  $\tau \in \mathcal{S}$ . In this section, we will develop a theory of sets varying over collections of  $\mathcal{S}$ -sorted symbols.

Let  $\mathbb{I}$  be the category of finite cardinals and their injective maps; then the comma construction  $\mathbb{I} \downarrow \mathcal{S}$ , is the category of contexts of symbols whose objects are finite sets of symbols  $\mathbb{U}$  and sort-assignments  $\mathbb{U} \xrightarrow{\mathfrak{s}} \mathcal{S}$ , and whose morphisms are sort-preserving renamings; we will write  $\Upsilon$  for a symbol context  $(\mathbb{U}, \mathfrak{s})$ .

*Remark 1.1.* To be precise,  $\mathbb{I} \downarrow \mathcal{S}$  is an abuse of notation for the comma category  $|-|_{\mathbb{I}} \downarrow \Delta[\mathcal{S}]$ , with  $|-|_{\mathbb{I}}$  the forgetful functor from  $\mathbb{I}$  to **Set**, and  $\Delta[\mathcal{S}](*) \triangleq \mathcal{S}$  a constant functor from  $\mathbb{1}$  to

**Set.** Formally, an object of  $\mathbb{I} \downarrow \mathcal{S}$  is, then, a triple  $\langle \mathbb{U}, *, s \rangle$  with  $\mathbb{U}$  an object in  $\mathbb{I}$ ,  $*$  the unique object in  $\mathbb{1}$ , and  $s$  a function  $|\mathbb{U}|_{\mathbb{I}} \longrightarrow \mathcal{S}$ ; an arrow  $\rho : \langle \mathbb{U}, *, s \rangle \longrightarrow \langle \mathbb{V}, *, t \rangle$  is a commuting triangle like the following:

$$\begin{array}{ccc} |\mathbb{U}|_{\mathbb{I}} & \xrightarrow{|\rho|_{\mathbb{I}}} & |\mathbb{V}|_{\mathbb{I}} \\ & \searrow s \quad \swarrow t & \\ & \mathcal{S} & \end{array}$$

Because the object  $*$  in  $\mathbb{1}$  is unique, we will always omit it from the data of an object in  $\mathbb{I} \downarrow \mathcal{S}$ .

**Presheaves on  $\mathbb{I} \downarrow \mathcal{S}$**  A presheaf on a category  $\mathcal{C}$  is a contravariant functor  $\mathcal{C}^{\text{op}} \longrightarrow \mathbf{Set}$ ; when  $\mathcal{C} \equiv \mathcal{D}^{\text{op}}$ , we call this a *copresheaf* (covariant presheaf) on  $\mathcal{D}$ . Therefore, a copresheaf on  $\mathbb{I} \downarrow \mathcal{S}$  is a functor  $\mathbb{I} \downarrow \mathcal{S} \longrightarrow \mathbf{Set}$ ; colloquially, such a copresheaf can be thought of as a set that *varies over* symbol contexts.

This leads to a very intuitive setting in which to consider sets that vary over collections of  $\mathcal{S}$ -sorted symbols. In particular, for any morphism  $\Upsilon \xrightarrow{\rho} \Upsilon'$  in  $\mathbb{I} \downarrow \mathcal{S}$ , we have a corresponding functorial renaming action on any copresheaf  $X : \mathbf{Set}^{\mathbb{I} \downarrow \mathcal{S}}$ , namely  $X(\rho) : X(\Upsilon) \longrightarrow X(\Upsilon')$ . When the copresheaf  $X$  is clear from context, we will write  $m \cdot \rho$  for  $X(\rho)(m)$ .

Now, when  $m \in X(\Upsilon)$  for a copresheaf  $X : \mathbf{Set}^{\mathbb{I} \downarrow \mathcal{S}}$ , we can define the notion that  $m$  depends on *at most* a subcontext  $\Upsilon'$  of  $\Upsilon$ ; this is called *support*.

**Definition 1.2** (Support). When  $\Upsilon \xrightarrow{\rho} \Upsilon'$ , we say that  $\Upsilon$  supports  $m \in \Upsilon'$  (written  $\Upsilon \blacktriangleright_{\rho} m$ ) when, for all  $\Upsilon' \xrightarrow{\rho_1, \rho_2} \Upsilon''$ , if  $\rho_1 \circ \rho = \rho_2 \circ \rho$  then  $m \cdot \rho_1 = m \cdot \rho_2$ .

We can also always calculate the *least support* of a term  $m \in X(\Upsilon')$ , written  $\mathbf{supp}(m)$ :

$$\mathbf{supp}(m) \triangleq \bigcap_{\Upsilon \xrightarrow{\rho} \Upsilon'} \{ \Upsilon \mid \Upsilon \blacktriangleright_{\rho} m \}$$

Intuitively,  $\mathbf{supp}(m)$  is the exact symbol context that  $m$  depends on.

## 1.1 Sheaves on the atomic site

Intuitively, when  $\Upsilon$  supports  $m \in X(\Upsilon')$ , we would expect that we can work backward to a unique  $m' : \Upsilon$  such that  $m' \cdot \rho = m$ ; whilst it is not in general the case for presheaves  $X$ , this is precisely the sheaf condition for copresheaves on  $\mathbb{I} \downarrow \mathcal{S}$  under the atomic topology [15, p. 126]. The sheaf condition, then, ensures that the notion of support is well-behaved.

**Sites and coverages** We will briefly discuss the basics of sheaves on a site. A *site* is a pair  $\langle \mathcal{C}, J \rangle$ , with  $\mathcal{C}$  a category of “worlds” and  $J$  a Grothendieck topology (or “coverage”). A coverage is a predicate that picks out for each object  $C : \mathcal{C}$ , the *covering sieves* of  $C$ , subject to several axioms (see [15] for details).

**Covering sieves and matching families** A *sieve* on an object  $C$  is a subfunctor of the Yoneda embedding  $\mathbf{y}(C) \triangleq \mathcal{C}[-, C]$ . We say that such a sieve  $S$  covers  $C$  just when  $S \in J(C)$ . For a presheaf  $X$  on the site  $\langle \mathcal{C}, J \rangle$ , a *matching family* for the sieve  $S$  is a natural transformation  $\phi : S \longrightarrow X$ . An *amalgamation* for  $\phi$  is an object  $m \in X(C)$  such that  $m \cdot f = \phi_D(f)$  for each  $f \in S(D)$ , for all objects  $D$ .

**Separation and sheafhood** Then, we say that the presheaf  $X$  is *separated* in case for every sieve  $S \in J(C)$  and matching family  $\phi : S \longrightarrow X$ , there is at most one amalgamation  $m \in X(C)$  for  $\phi$ . Additionally,  $X$  is called a *sheaf* when there is *exactly one* such amalgamation.

**The atomic coverage** The atomic coverage  $J_{\text{atm}}$  is the one in which all non-empty sieves cover. A sieve  $S \sqsubseteq \mathbf{y}(C)$  is non-empty when the collection  $\bigcup_D S(D)$  of all its arrows is non-empty.

In the future, we will write  $\mathbb{I}[S]$  for the Grothendieck site  $\langle (\mathbb{I} \downarrow S)^{\text{op}}, J_{\text{atm}} \rangle$ , where  $J_{\text{atm}}$  is the atomic coverage. Sheafhood on the atomic site  $\mathbb{I}[S]$  amounts to the following condition, using Definition 1.2:

A presheaf  $X : \mathbf{Set}^{\mathbb{I} \downarrow S}$  is a sheaf on  $\mathbb{I}[S]$  just when, for all  $n \in X(\Upsilon')$ , if we have  $\Upsilon \xrightarrow{\rho} \Upsilon'$  and  $\Upsilon \blacktriangleright_{\rho} n$ , then there is a unique  $m \in X(\Upsilon)$  such that  $m \cdot \rho = n$ .

Therefore, a sheaf on  $\mathbb{I}[S]$  is a set that varies over  $S$ -sorted symbols, which has a well-behaved notion of support. Another way to put it is, if  $m \in X(\Upsilon)$  only “uses” some of the symbols available at world  $\Upsilon$ , there’s a canonical way to restrict  $m$  to a term in the world which contains *only* the symbols that it uses.

## 1.2 Constructions on sheaves

For any Grothendieck site  $\mathfrak{S} \equiv \langle \mathcal{C}, J \rangle$ , the inclusion  $\iota : \mathbf{Sh}(\mathfrak{S}) \longrightarrow \mathbf{Psh}(\mathcal{C})$  of sheaves into presheaves has a left adjoint  $(-)^{\#} \dashv \iota$ , which takes any presheaf  $X : \mathbf{Psh}(\mathcal{C})$  to a unique sheaf  $X^{\#} : \mathbf{Sh}(\mathfrak{S})$ , called the *sheafification* of  $X$ . Sheafification is the twice-iterated application of the *+construction*  $X^+$ , which turns a presheaf into a separated presheaf, and a separated presheaf into a sheaf [15]:

$$X^+(C) \triangleq \int^{S \in J(C)} \mathbf{Psh}(\mathcal{C})[S, X]$$

$$X^{\#} \triangleq X^{++}$$

We also have a canonical natural transformation  $\eta : X \longrightarrow X^+$ , defined using the maximal sieve  $t_C \triangleq \mathbf{y}(C)$ :

$$\eta_C(m) \triangleq \langle t_C, X(-)(m) \rangle \quad (m \in X(C))$$

Every category of sheaves on a site gives rise to a topos, which equips us with a number of standard constructions, including (among other things) the disjoint union of sheaves  $X \oplus Y$ , the product of sheaves  $X \otimes Y$ , and the terminal sheaf  $\mathbb{1}$ .

Returning to the site  $\mathbb{I}[S]$ , we will write  $\mathbf{S}_\tau$  for the sheaf of symbols of sort  $\tau$ , a subobject of the Yoneda embedding of the empty symbol context,  $\mathbf{y}(\cdot)$ .

### 1.3 Relation to Nominal Sets and the Schanuel Topos

Pitts defines a category **Nom** of nominal sets in [18] which function equivalently to the sheaves that we considered above, in the case of  $S \cong \mathbb{1}$ . Fix a countably infinite set of atoms  $\mathbb{A}$ ; then let **Perm**  $\mathbb{A}$  be the group of permutations (i.e. autoequivalences) on  $\mathbb{A}$ . Considered as a category, **Perm**  $\mathbb{A}$  has a single object  $\bullet$  with morphisms  $\pi : \bullet \longrightarrow \bullet$  for each  $\pi \in |\mathbf{Perm} \mathbb{A}|$ . Then, the category of nominal sets **Nom** is the subcategory of  $\mathbf{Set}^{\mathbf{Perm} \mathbb{A}}$  containing just the presheaves which satisfy a *finite support* condition.

The category **Nom** is equivalent to the category of covariant sheaves on  $\mathbb{I}$  under the atomic coverage, called the Schanuel Topos  $\mathbb{S} \triangleq \mathbf{Sh}(\mathbb{I}^{\text{op}})$  [18, 8]; equivalently, the Schanuel topos is the subcategory of  $\mathbf{Set}^{\mathbb{I}}$  containing only pullbacks-preserving functors.

In addition to the unsorted nominal sets framework, Pitts also briefly discusses a multi-sorted version of the apparatus in which the countably infinite set of atoms  $\mathbb{A}$  is equipped with a sort assignment  $s : \mathbb{A} \rightarrow S$  such that all the fibres of  $s$  are countably infinite; then, he defines for any such assignment the category **Nom** $_s$  of  $s$ -sorted nominal sets as a subcategory of the category of presheaves on the group of  $s$ -respecting permutations on  $\mathbb{A}$ , **Perm** $_s \mathbb{A}$ .

In the same way as the Schanuel topos is equivalent to the unsorted nominal sets, we expect to find an equivalence between  $\mathbf{Sh}(\mathbb{I}[S])$  and the limit  $\int_s \mathbf{Nom}_s$ . At the very least, the sheaf topos  $\mathbf{Sh}(\mathbb{I}[S])$  may serve as a multi-sorted generalization of the Schanuel topos, for which we may carry over certain useful results, including its characterization as the subcategory of  $\mathbf{Set}^{\mathbb{I} \downarrow S}$  which contains just the pullbacks-preserving functors (see Theorem A.1 for the proof).

## 2 Operators and signatures

A valence  $\{\vec{\sigma}\}[\vec{\tau}]$ .  $\tau$  specifies an expression of sort  $\tau$  which binds symbols in  $\vec{\sigma}$  and variables in  $\vec{\tau}$ .

$$\frac{\tau \text{ sort} \quad \sigma_i \text{ sort } (i \leq m) \quad \tau_i \text{ sort } (i \leq n)}{\{\sigma_0, \dots, \sigma_m\}[\tau_0, \dots, \tau_n]. \tau \text{ valence}}$$

An arity  $(\vec{v}) \tau$  specifies an operator of sort  $\tau$  with arguments of valences  $\vec{v}$ . We will call the set of valences  $\mathcal{V}$ , and the set of arities  $\mathcal{A}$ .

$$\frac{\tau \text{ sort } \quad v_i \text{ valence } (i \leq n)}{(v_0, \dots, v_n) \tau \text{ arity}}$$

Fix a family of sheaves of operators  $\mathcal{O}_a \in \mathbf{Sh}(\mathbb{I}[\mathcal{S}])$ , indexed by arities  $a \in \mathcal{A}$ ; for each  $\mathcal{O}_a$ , arrows in  $\mathbb{I} \downarrow \mathcal{S}$  will lift to renamings in operators' symbolic parameters. Together,  $\mathcal{S}$  and  $\mathcal{O}$  are said to form a *signature*  $\Sigma \triangleq \langle \mathcal{S}, \mathcal{O} \rangle$ .

We will write  $\Upsilon \Vdash \vartheta : a$  in case  $\vartheta \in \mathcal{O}_a(\Upsilon)$ ; note that this judgment enjoys the structural properties of weakening and exchange via functoriality of  $\mathcal{O}$ . An operator signature is defined by specifying, for each arity  $a$ , the sheaf  $\mathcal{O}_a$ , whose “elements” are the operators of arity  $a$ .

**Examples** For instance, consider a  $\lambda$ -calculus with a single sort, **exp**; we give its signature  $\Sigma_\lambda$  by asserting the following about its operators:

$$\begin{aligned} \Upsilon \Vdash \text{lam} &: ([\text{exp}]. \text{exp}) \text{exp} \\ \Upsilon \Vdash \text{fix} &: ([\text{exp}]. \text{exp}) \text{exp} \\ \Upsilon \Vdash \text{ap} &: (. \text{exp}, . \text{exp}) \text{exp} \end{aligned}$$

These rules correspond to the following definition of  $\mathcal{O}$ :

$$\begin{aligned} \mathcal{O}_{([\text{exp}]. \text{exp}) \text{exp}} &\triangleq \mathbb{1} \oplus \mathbb{1} \\ \mathcal{O}_{(. \text{exp}, . \text{exp}) \text{exp}} &\triangleq \mathbb{1} \end{aligned}$$

So far, we have made no use of symbols and parameters; however, consider the extension of the calculus with assignable (references):

$$\begin{aligned} \Upsilon \Vdash \text{decl} &: (. \text{exp}, \{\text{exp}\}. \text{exp}) \text{exp} \\ \Upsilon, u : \text{exp} \Vdash \text{get}[u] &: () \text{exp} \\ \Upsilon, u : \text{exp} \Vdash \text{set}[u] &: (. \text{exp}) \text{exp} \end{aligned}$$

These rules correspond to the following family of sheaves:

$$\begin{aligned} \mathcal{O}_{(. \text{exp}, \{\text{exp}\}. \text{exp}) \text{exp}} &\triangleq \mathbb{1} \\ \mathcal{O}_{() \text{exp}} &\triangleq \mathbf{S}_{\text{exp}} \\ \mathcal{O}_{(. \text{exp}) \text{exp}} &\triangleq \mathbf{S}_{\text{exp}} \end{aligned}$$

Declaring a new assignable consists in providing an initial value, and an expression binding a symbol (which shall represent the assignable in scope). Note that the functoriality of  $\mathcal{O}$  guarantees for any renaming  $\rho : \Upsilon \longrightarrow \Upsilon'$ , a family of lifted maps  $\mathcal{O}_a(\rho) : \mathcal{O}_a(\Upsilon) \longrightarrow \mathcal{O}_a(\Upsilon')$  natural in  $a$ , such that  $\Upsilon' \Vdash \mathcal{O}(\rho)(\vartheta) : a$  when  $\Upsilon \Vdash \vartheta : a$ . In particular, the renaming  $\Upsilon, u \longmapsto \Upsilon, v$  shall take  $\text{get}[u]$  to  $\text{get}[v]$ . Going forward, we will write  $\vartheta\rho$  for  $\mathcal{O}_a(\rho)(\vartheta)$ .

### 3 Contexts

In general, we will have three kinds of context: symbolic (parameter) contexts, variable contexts, and metavariable contexts. The symbol contexts have already been defined via the comma construction  $\mathbb{I} \downarrow \mathcal{S}$ , but they also admit a syntactic characterization,

$$\frac{}{\cdot \text{ sctx}} \quad \frac{\Upsilon \text{ sctx} \quad \tau \text{ sort} \quad u \notin |\Upsilon|}{\Upsilon, u : \tau \text{ sctx}}$$

Because, modulo notation, we have  $\Upsilon \in \mathbb{I} \downarrow \mathcal{S}$  just when  $\Upsilon \text{ sctx}$ , we will use the syntactic view when it is convenient.

Contexts of variables are similar to contexts of symbols, except that they admit *any* renamings, not just the injective ones. As such, when  $\mathbb{F}$  is the category of finite cardinals and all functions between them, the comma construction  $\mathbb{F} \downarrow \mathcal{S}$  is the category of variable contexts. As above, we can give them an equivalent syntactic treatment:

$$\frac{}{\cdot \text{ vctx}} \quad \frac{\Gamma \text{ vctx} \quad \tau \text{ sort} \quad x \notin |\Gamma|}{\Gamma, x : \tau \text{ vctx}}$$

A metavariable context consists of bindings of *valences* to metavariables; let  $\mathcal{V} \triangleq \{\mathbf{v} \mid \mathbf{v} \text{ valence}\}$  be the set of valences. Then, the category of metavariable contexts is the comma construction  $\mathbb{F} \downarrow \mathcal{V}$ , which likewise admits an equivalent inductive definition:

$$\frac{}{\cdot \text{ mctx}} \quad \frac{\Theta \text{ mctx} \quad \mathbf{v} \text{ valence} \quad m \notin |\Theta|}{\Theta, m : \mathbf{v} \text{ mctx}}$$

### 4 Nominal Abstract Binding Trees

Let the judgment  $\Theta \triangleright \Upsilon \parallel \Gamma \vdash M : \tau$  presuppose<sup>1</sup>  $\Theta \text{ mctx}, \Upsilon \text{ sctx}, \Gamma \text{ vctx}$  and  $\tau \text{ sort}$ , meaning that  $M$  is an abstract binding tree of sort  $s$ , with metavariables in  $\Theta$ , parameters in  $\Upsilon$ , and variables in  $\Gamma$ . Let the judgment  $\Theta \triangleright \Upsilon \parallel \Gamma \vdash E : \mathbf{v}$  presuppose  $\mathbf{v} \text{ valence}$ . Then, the syntax of abstract binding trees is inductively defined in four rules:

$$\frac{\Gamma \ni x : \tau}{\Theta \triangleright \Upsilon \parallel \Gamma \vdash x : \tau} \text{ var}$$

<sup>1</sup>In the *judgmental method*, as pioneered by Per Martin-Löf, a form of judgment is propounded first by specifying its range of significance (i.e. the circumstances under which it shall have a meaning), and then, a meaning explanation (definition) for the judgment is given. The range of significance of a judgment is called its *presupposition*, and the meaning of the judgment may proceed by induction on the evidence that the presupposition obtains. See [19] for a more detailed explanation of presuppositions and the judgmental method.

$$\begin{array}{c}
\Theta \ni m : \{\sigma_0, \dots, \sigma_m\}[\tau_0, \dots, \tau_n]. \tau \\
\Upsilon \ni u_i : \sigma_i \quad (i \leq m) \\
\Theta \triangleright \Upsilon \parallel \Gamma \vdash M_i : \tau_i \quad (i \leq n) \\
\hline
\Theta \triangleright \Upsilon \parallel \Gamma \vdash m\{u_0, \dots, u_m\}(M_0, \dots, M_n) : \tau \quad mvar \\
\\
\Upsilon \Vdash \vartheta : (v_1, \dots, v_n) \tau \\
\Theta \triangleright \Upsilon \parallel \Gamma \vdash E_i : v_i \quad (i \leq n) \\
\hline
\Theta \triangleright \Upsilon \parallel \Gamma \vdash \vartheta(E_0, \dots, E_n) : \tau \quad app \\
\\
\Theta \triangleright \Upsilon, \vec{u} : \vec{\sigma} \parallel \Gamma, \vec{x} : \vec{\tau} \vdash M : \tau \\
\hline
\Theta \triangleright \Upsilon \parallel \Gamma \vdash \lambda\{\vec{u}\}[\vec{x}]. M : \{\vec{\sigma}\}[\vec{\tau}]. \tau \quad abs
\end{array}$$

Abts are identified up to  $\alpha$ -equivalence.

#### 4.1 Calculating free variables

We can easily calculate the variables free in an expression by recursion on its structure:

$$\begin{array}{c}
\overline{\mathbf{FV}(x) \rightsquigarrow \{x\}} \quad var \\
\\
\frac{\mathbf{FV}(M_i) \rightsquigarrow \vec{x}_i \quad (i \leq n)}{\mathbf{FV}(m\{\vec{u}\}(M_0, \dots, M_n)) \rightsquigarrow \bigcup_{i \leq n} \vec{x}_i} \quad mvar \\
\\
\frac{\mathbf{FV}(E_i) \rightsquigarrow \vec{x}_i \quad (i \leq n)}{\mathbf{FV}(\vartheta(E_0, \dots, E_n)) \rightsquigarrow \bigcup_{i \leq n} \vec{x}_i} \quad app \\
\\
\frac{\mathbf{FV}(M) \rightsquigarrow \vec{x}}{\mathbf{FV}(\lambda\{\vec{u}\}[\vec{y}]. M) \rightsquigarrow \vec{x} \setminus \vec{y}} \quad abs
\end{array}$$

Because this is a total relation, henceforth we will write  $\mathbf{FV}(M)$  for  $\vec{x}$  when  $\mathbf{FV}(M) \rightsquigarrow \vec{x}$ .

#### 4.2 Calculating free symbols

Whereas the calculation of free variables pivoted on the *var* rule, the calculation of free symbols will pivot on the *app* and *mvar* rule, because the only way a symbol can be introduced is as a parameter to an operator or as a parameter to a metavariable.

$$\begin{array}{c}
\overline{\mathbf{FS}(x) \rightsquigarrow \{\}} \text{ var} \\
\\
\frac{\mathbf{FS}(M_i) \rightsquigarrow \vec{u}_i \ (i \leq n)}{\mathbf{FS}(\mathfrak{m}\{\vec{u}\}(M_0, \dots, M_n)) \rightsquigarrow \vec{u} \cup \bigcup_{i \leq n} \vec{u}_i} \text{ mvar} \\
\\
\frac{\mathbf{FS}(E_i) \rightsquigarrow \vec{u}_i \ (i \leq n)}{\mathbf{FS}(\vartheta(E_0, \dots, E_n)) \rightsquigarrow |\mathbf{supp}(\vartheta)| \cup \bigcup_{i \leq n} \vec{u}_i} \text{ app} \\
\\
\frac{\mathbf{FS}(M) \rightsquigarrow \vec{u}}{\mathbf{FS}(\lambda\{\vec{v}\}[\vec{x}]. M) \rightsquigarrow \vec{u} \setminus \vec{v}} \text{ abs}
\end{array}$$

Because this is a total relation, henceforth we will write  $\mathbf{FS}(M)$  for  $\vec{u}$  when  $\mathbf{FS}(M) \rightsquigarrow \vec{u}$ .

### 4.3 Renaming of symbols

The only place that symbols appear in our calculus is as parameters to operators (unlike variables, symbols are not terms). Therefore, the functorial action of the operator sheaf can be lifted into terms by recursion on their structure, via a pair of judgments  $M\{\rho\} \rightsquigarrow N$  and  $E\{\rho\} \rightsquigarrow F$ , presupposing  $\rho : \Upsilon \longrightarrow \Upsilon'$ , and  $\Theta \triangleright \Upsilon \parallel \Gamma \vdash M : \tau$  and  $\Theta \triangleright \Upsilon \parallel \Gamma \vdash E : v$  respectively:

$$\begin{array}{c}
\overline{x\{\rho\} \rightsquigarrow x} \text{ var} \\
\\
\frac{\rho(\vec{u}) \equiv \vec{v} \quad M_i\{\rho\} \rightsquigarrow N_i \ (i \leq n)}{\mathfrak{m}\{\vec{u}\}(M_0, \dots, M_n)\{\rho\} \rightsquigarrow \mathfrak{m}\{\vec{v}\}(N_0, \dots, N_n)} \text{ mvar} \\
\\
\frac{E_i\{\rho\} \rightsquigarrow F_i \ (i \leq n)}{\vartheta(E_0, \dots, E_n)\{\rho\} \rightsquigarrow \vartheta\rho(F_0, \dots, F_n)} \text{ app} \\
\\
\frac{M\{\rho \setminus \vec{u}\} \rightsquigarrow N}{\lambda\{\vec{u}\}[\vec{x}]. M\{\rho\} \rightsquigarrow \lambda\{\vec{u}\}[\vec{x}]. N} \text{ abs}
\end{array}$$

Above, the notation  $\rho \setminus \vec{u}$  means the omission of the variables  $\vec{u}$  from the renaming  $\rho$ . Because terms are identified up to  $\alpha$ -equivalence, the renaming judgment is functional in its input, and so we are justified in writing  $M\{\rho\}$  for  $N$  when  $M\{\rho\} \rightsquigarrow N$ .

### 4.4 Substitution of variables

Variable substitution in abts is defined inductively by a pair of judgments,  $[N/x]M \rightsquigarrow M'$  and  $[N/x]E \rightsquigarrow F$ :



$$\begin{array}{c}
\frac{x = y}{[N/x] y \rightsquigarrow \textcolor{red}{N}} \textit{var}_1 \quad \frac{x \# y}{[N/x] y \rightsquigarrow \textcolor{red}{y}} \textit{var}_2 \\
\\
\frac{[N/x] M_i \rightsquigarrow \textcolor{red}{M'_i} \ (i \leq n)}{[N/x] m\{\vec{u}\}(M_0, \dots, M_n) \rightsquigarrow m\{\vec{u}\}(\textcolor{red}{M'_0}, \dots, \textcolor{red}{M'_n})} \textit{mvar} \\
\\
\frac{[N/x] E_i \rightsquigarrow \textcolor{red}{F_i} \ (i \leq n)}{[N/x] \vartheta(E_0, \dots, E_n) \rightsquigarrow \textcolor{red}{\vartheta}(F_0, \dots, F_n)} \textit{app} \\
\\
\frac{x \notin \vec{y} \quad \vec{u} \# \textbf{FS}(N) \quad \vec{y} \# \textbf{FV}(N) \quad [N/x] M \rightsquigarrow \textcolor{red}{M'}}{[N/x] \lambda\{\vec{u}\}[\vec{y}]. M \rightsquigarrow \lambda\{\vec{u}\}[\vec{y}]. \textcolor{red}{M'}} \textit{abs}_1 \\
\\
\frac{x \in \vec{y} \quad \vec{u} \# \textbf{FS}(N) \quad \vec{y} \# \textbf{FV}(N)}{[N/x] \lambda\{\vec{u}\}[\vec{y}]. M \rightsquigarrow \lambda\{\vec{u}\}[\vec{y}]. \textcolor{red}{M}} \textit{abs}_2
\end{array}$$

Going forward, we will write  $[N/x] M$  for  $M'$  when  $[N/x] M \rightsquigarrow \textcolor{red}{M'}$ , and  $[\vec{N}/\vec{x}] M$  for the simultaneous substitution of  $\vec{N}$  for  $\vec{x}$  in  $M$ .

#### 4.5 Substitution of metavariables

Metavariables are substituted by bound terms; since a metavariable may only appear in an application expression  $m\{\dots\}(\dots)$ , we will instantiate the bound term at the supplied parameters and arguments. Substitution for metavariables is defined inductively by the judgments  $[E/m] M \rightsquigarrow \textcolor{red}{N}$  and  $[E/m] F \rightsquigarrow \textcolor{red}{F'}$ :

$$\begin{array}{c}
\frac{}{[E/m] x \rightsquigarrow \textcolor{red}{x}} \textit{var} \\
\\
\frac{m \# n \quad [E/n] M_i \rightsquigarrow \textcolor{red}{N_i} \ (i \leq n)}{[E/m] n\{\vec{u}\}(M_0, \dots, M_n) \rightsquigarrow n\{\vec{u}\}(\textcolor{red}{N_0}, \dots, \textcolor{red}{N_n})} \textit{mvar}_1 \\
\\
\frac{m = n \quad [\vec{M}/\vec{x}] N \rightsquigarrow \textcolor{red}{N'} \quad N'\{\vec{u} \mapsto \vec{v}\} \rightsquigarrow \textcolor{red}{N''}}{[\lambda\{\vec{u}\}[\vec{x}]. N / m] n\{\vec{v}\}(\vec{M}) \rightsquigarrow \textcolor{red}{N''}} \textit{mvar}_2 \\
\\
\frac{[E/m] F_i \rightsquigarrow \textcolor{red}{F'_i} \ (i \leq n)}{[E/m] \vartheta(F_0, \dots, F_n) \rightsquigarrow \textcolor{red}{\vartheta}(F'_0, \dots, F'_n)} \textit{app} \\
\\
\frac{\vec{u} \# \textbf{FS}(E) \quad \vec{x} \# \textbf{FV}(E) \quad [E/m] M \rightsquigarrow \textcolor{red}{N}}{[E/m] \lambda\{\vec{u}\}[\vec{x}]. M \rightsquigarrow \lambda\{\vec{u}\}[\vec{x}]. \textcolor{red}{N}} \textit{abs}
\end{array}$$

As usual, we will write  $[E/m] M$  for  $N$  when  $[E/m] M \rightsquigarrow \textcolor{red}{N}$ .

## 5 Model Theory

Let  $\mathbf{H} \triangleq (\mathbb{I} \downarrow \mathcal{S} \times \mathbb{F} \downarrow \mathcal{S})^{\text{op}}$ ; then we fix the functor category  $\widehat{\mathbf{H}}^{\mathcal{S}}$  as our semantic universe.

Let  $V_{\tau}(\Upsilon \parallel \Gamma) \triangleq \{x \in |\Gamma| \mid \Gamma(x) = \tau\}$  be called the presheaf of variables; additionally, we have a presheaf of symbols  $S_{\tau}(\Upsilon \parallel \Gamma) \triangleq \{u \in |\Upsilon| \mid \Upsilon(u) = \tau\}$ . Lastly, we have the presheaf of operators with arity  $a$ ,  $\mathcal{O}_a(\Upsilon \parallel \Gamma) \triangleq \mathcal{O}_a(\Upsilon)$

### 5.1 Substitution monoidal structures

For an object  $P : \widehat{\mathbf{H}}^{\mathcal{S}}$ , we will use the notation  $P^{[\Gamma]}$  to mean  $\prod_{x \in |\Gamma|} P_{\Gamma(x)}$ ; likewise,  $S^{\{\Upsilon\}}$  shall mean  $\prod_{u \in |\Upsilon|} S_{\Upsilon(u)}$ . For a presheaf  $A : \widehat{\mathbf{H}}$  and a sort-indexed family of presheaves  $P : \widehat{\mathbf{H}}^{\mathcal{S}}$ , we have an operation  $A \bullet P$ , defined as a coend in the following way:

$$(A \bullet P)(\Upsilon \parallel \Gamma) \triangleq \int^{(\Upsilon' \parallel \Delta) \in \mathbf{H}} A(\Upsilon' \parallel \Delta) \times S^{\{\Upsilon'\}}(\Upsilon \parallel \Gamma) \times P^{[\Delta]}(\Upsilon \parallel \Gamma)$$

Using this, we can define a tensor  $P \odot Q$  for  $P, Q : \widehat{\mathbf{H}}^{\mathcal{S}}$  as follows:

$$(P \odot Q)_{\tau} \triangleq P_{\tau} \bullet Q \quad (\tau \in \mathcal{S})$$

Then,  $V$  is the unit to this tensor. We will say that an object  $P : \widehat{\mathbf{H}}^{\mathcal{S}}$  is a  $\Sigma$ -monoid in case it is equipped with the following natural transformations where  $v$  embeds variables into  $P$  and  $\varsigma$  equips  $P$  with an operation for simultaneous substitutions of variables. Furthermore,  $v$  and  $\varsigma$  induce maps  $v_{\Gamma}$  and  $\varsigma_{\Upsilon \parallel \Gamma}^{\tau}$ :

$$\begin{aligned} V &\xrightarrow{v} P \xleftarrow{\varsigma} P \odot P \\ V^{[\Gamma]} &\xrightarrow{v_{\Gamma}} P^{[\Gamma]} \quad P_{\tau}^y(\Upsilon \parallel \Gamma) \times S^{\{\Upsilon\}} \times P^{[\Gamma]} \xrightarrow{\varsigma_{\Upsilon \parallel \Gamma}^{\tau}} P_{\tau} \end{aligned}$$

### 5.2 The signature endofunctor and its initial algebras

For each signature  $\Sigma \equiv \langle \mathcal{S}, \mathcal{O} \rangle$ , we have an endofunctor  $\mathcal{F}_{\Sigma} : \widehat{\mathbf{H}}^{\mathcal{S}} \longrightarrow \widehat{\mathbf{H}}^{\mathcal{S}}$ , which is defined as follows:

$$\mathcal{F}_{\Sigma}(X)_{\tau} \triangleq \coprod_{\vartheta \in \mathcal{O}_{(\vartheta)_{\tau}} \{\vec{\sigma}\}[\vec{\tau}], \tau_i \in \vec{\sigma}} \prod X_{\tau_i}^{y(\vec{\sigma} \parallel \vec{\tau})}$$

Then, a  $\Sigma$ -model is a  $\Sigma$ -monoid  $P$  which is equipped with an initial algebra  $\alpha : \mathcal{F}_{\Sigma}(P) \longrightarrow P$ , which shall interpret applications of each operator.

### 5.3 Interpretation of terms

The metavariable, symbol and variable contexts are interpreted for a model  $P$  as an environment presheaf in the following way:

$$\llbracket \Theta \triangleright \Upsilon \parallel \Gamma \rrbracket_P \triangleq \left( \prod_{(m:\{\vec{\sigma}\}[\vec{\tau}], \tau) \in \Theta} P_\tau^{y(\vec{\sigma} \parallel \vec{\tau})} \right) \times \mathbf{S}^{\{\Upsilon\}} \times \mathbf{V}^{[\Gamma]}$$

Then, the interpretation of a term in a model  $P$  is a map from its environment to  $P$ :

$$\llbracket \Theta \triangleright \Upsilon \parallel \Gamma \vdash M : \tau \rrbracket_P : \llbracket \Theta \triangleright \Upsilon \parallel \Gamma \rrbracket_P \longrightarrow P_\tau$$

Variables are interpreted by the map  $\llbracket \Theta \triangleright \Upsilon \parallel \Gamma \vdash x : \tau \rrbracket_P$  which projects them from the environment and embeds them into the model. Metavariables are resolved by the map  $\llbracket \Theta \triangleright \Upsilon \parallel \Gamma \vdash m\{\vec{u}\}(\vec{M}) : \tau \rrbracket_P$  (where  $\Theta \ni m : \{\vec{\sigma}\}[\vec{\tau}]. \tau$ ) which projects their interpretation from the environment and instantiates it via substitution:

$$\begin{array}{ccc} P_\tau & \xleftarrow{\llbracket \Theta \triangleright \Upsilon \parallel \Gamma \vdash m\{\vec{u}\}(\vec{M}) : \tau \rrbracket_P} & \llbracket \Theta \triangleright \Upsilon \parallel \Gamma \rrbracket_P \xrightarrow{\llbracket \Theta \triangleright \Upsilon \parallel \Gamma \vdash x : \tau \rrbracket_P} P_\tau \\ \uparrow \zeta_{\vec{\sigma} \parallel \vec{\tau}} & \nwarrow \langle \pi_m, \pi_1, \phi, \pi_2, \psi \rangle & \searrow \nu_\Gamma \pi_3 \uparrow \pi_x \\ P_\tau^{y(\vec{\sigma} \parallel \vec{\tau})} \times \mathbf{S}^{\{\vec{\sigma}\}} \times P^{[\vec{\tau}]} & & P^{[\Gamma]} \end{array}$$

$$P^{[\vec{\tau}]} \xleftarrow{\psi \triangleq \langle \llbracket \Theta \triangleright \Upsilon \parallel \Gamma \vdash M : \tau \rrbracket_P \rangle_{(M, \tau) \in (\vec{M}, \vec{\tau})}} \llbracket \Theta \triangleright \Upsilon \parallel \Gamma \rrbracket_P \quad \mathbf{S}^{\{\Upsilon\}} \xrightarrow{\phi \triangleq \langle \pi_u \rangle_{u \in \vec{u}}} \mathbf{S}^{\{\vec{\sigma}\}}$$

Interpretation of operator applications is the most complicated. Recall that, unlike in standard treatments of universal algebra, our operators are indexed by symbol collections; therefore, operators must pass through suitable renamings in order to be used in the interpretation. Let us begin by constructing for each operator  $\Upsilon \Vdash \vartheta : \mathbf{a}$  the morphism  $\llbracket \vartheta \rrbracket_P$  which shall rename the parameters of the operator using the environment:

$$\begin{array}{ccccc} & & \llbracket \vartheta \rrbracket_P & & \\ & \nearrow & \text{dashed arc} & \searrow & \\ \llbracket \Theta \triangleright \Upsilon \parallel \Gamma \rrbracket_P & \xrightarrow{\pi_2} & \mathbf{S}^{\{\Upsilon\}} & \xrightarrow{\mathcal{O}_a(\pi_{(-)})(\vartheta)} & \mathcal{O}_a \end{array}$$

We will proceed using the initial  $\mathcal{F}_\Sigma$ -algebra  $\alpha$ , as follows, by postcomposing it with a morphism  $\beta$  from the environment into the signature endofunctor, which interprets the syntax of operator applications:

$$\llbracket \Theta \triangleright \Upsilon \parallel \Gamma \rrbracket_P \xrightarrow{\beta} \mathcal{F}_\Sigma(P)_\tau \xrightarrow{\alpha_\tau} P_\tau$$

The construction of  $\beta$  proceeds by renaming the parameters of the operator  $\vartheta$  and constructing the (bound) exponentiated arguments  $\gamma$  of the operator.

$$\llbracket \Theta \triangleright \gamma \parallel \Gamma \rrbracket_P \xrightarrow{\beta \triangleq \langle \llbracket \vartheta \rrbracket_P, \lambda \gamma \rangle} \coprod_{\vartheta \in \mathcal{O}_{(\bar{v})} \tau} \prod_{\{\bar{\sigma}_i\}[\bar{\tau}_i]. \tau_i \in \bar{v}} p_{\tau_i}^{\mathbf{y}(\bar{\sigma}_i \parallel \bar{\tau}_i)}$$

Arguments  $\lambda \gamma_i$  are the exponential transposes (curried form) of the composites  $\gamma_i$ :

$$\begin{array}{ccc} \llbracket \Theta \triangleright \gamma \parallel \Gamma \rrbracket_P & \llbracket \Theta \triangleright \gamma \parallel \Gamma \rrbracket_P \times \mathbf{y}(\bar{\sigma}_i \parallel \bar{\tau}_i) & \xrightarrow{\langle \pi_{[1,1]}, \phi_i, \psi_i \rangle} \llbracket \Theta \triangleright \gamma, \bar{\sigma}_i \parallel \Gamma, \bar{\tau}_i \rrbracket_P \\ \downarrow \lambda \gamma_i & \downarrow \gamma_i & \swarrow \llbracket \Theta \triangleright \gamma, \bar{\sigma}_i \parallel \Gamma, \bar{\tau}_i \vdash M_i : \tau_i \rrbracket_P \\ p_{\tau_i}^{\mathbf{y}(\bar{\sigma}_i \parallel \bar{\tau}_i)} & p_{\tau_i} & \end{array}$$

where  $\phi_i, \psi_i$  are defined as follows:

$$\begin{array}{ccc} \llbracket \Theta \triangleright \gamma \parallel \Gamma \rrbracket_P \times \mathbf{y}(\bar{\sigma}_i \parallel \bar{\tau}_i) & \xrightarrow{\phi_i \triangleq \langle \pi_u \circ \pi_1 \rangle_{u \in |\gamma|}, \langle \pi_u \circ \pi_{[2,1]} \rangle_{u \in |\bar{\sigma}_i|}} & \mathbf{S}\{\gamma, \bar{\sigma}_i\} \\ \llbracket \Theta \triangleright \gamma \parallel \Gamma \rrbracket_P \times \mathbf{y}(\bar{\sigma}_i \parallel \bar{\tau}_i) & \xrightarrow{\psi_i \triangleq \langle \pi_x \circ \pi_1 \rangle_{x \in |\Gamma|}, \langle \pi_x \circ \pi_{[2,1]} \rangle_{x \in |\bar{\tau}_i|}} & \mathbf{V}\{\Gamma, \bar{\tau}_i\} \end{array}$$

This concludes the interpretation of well-sorted terms into any  $\Sigma$ -model.

## 6 Case Study: Wellformed Sequents

The representation of telescopes and sequents in a logical framework is notoriously difficult; whilst it is possible to use higher-order abstract syntax or abts to encode the binding-structure of telescopes and sequents, the encoding is sufficiently laborious and obscure that it is not used in practice. Cray has demonstrated a first-order encoding of contexts in the logical framework in bijection with actual LF-contexts [4], which has been successfully used in large-scale mechanization efforts, including that of Standard ML [14] and the Edinburgh Logical Framework itself [16].

We will approach the problem of encoding telescopes and sequents from the *refinements* perspective, where a conservative approximation of the grammar is first given using the abt logical framework, and then the correctness of a code is expressed separately in a judgment that refines the existing specification. Because we have not committed to using the built-in binding machinery to express the well-scopedness of telescopes and sequents, we are free to use *symbols* in order to model the variables in the context. This is in fact quite sensible if we are actually trying to faithfully represent the syntax of telescopes and sequents, rather than replace them with their counterparts on the meta-level.

The approach outlined above is actually quite similar to the standard practice in the Abella proof assistant [10]; in Abella, in addition to the canonical forms, each type is

inhabited by an infinite collection of nominal constants or symbols, which can be used in the syntax of contexts. In order to specify where such symbols are allowed to occur, a wellformedness predicate (a “scheme”) is separately defined. Our setting is similar in that we may also use symbols to encode the syntax of contexts, except that here, we have better control over their proliferation because, contrary to the state of affairs in Abella, symbols are *not* terms.

This insight leads the way to a simple abt signature for the theory of telescopes and sequents.

<b>tele</b> <i>sort</i>	<i>telescopes</i>
<b>exp</b> <i>sort</i>	<i>expressions</i>
<b>prop</b> <i>sort</i>	<i>propositions</i>
<b>judg</b> <i>sort</i>	<i>judgments</i>

$\Upsilon, u : \text{exp} \Vdash \text{hyp}[u] : () \text{exp}$

$\Upsilon \Vdash \text{nil} : () \text{tele}$

$\Upsilon, u : \text{exp} \Vdash \text{snoc}[u] : (. \text{tele}, . \text{prop}) \text{tele}$

$\Upsilon \Vdash \text{sequent} : (. \text{tele}, . \text{prop}) \text{judg}$

Suppose we have encoded a fragment of type theory as well:

$\Upsilon \Vdash P : () \text{prop}$

$\Upsilon \Vdash \text{pred} : (. \text{exp}) \text{prop}$

Terms written using the abstract syntax will be difficult to read, so let us define some notation:

$\diamond \triangleq \text{nil}$

$H, u : P \triangleq \text{snoc}[u](H, P)$

$H \gg A \triangleq \text{sequent}(H, A)$

$'u \triangleq \text{hyp}[u]$

Now, we have the following well-formed sequent:

$\cdot \triangleright u : \text{exp}, v : \text{exp} \parallel \cdot \vdash \diamond, u : P, v : \text{pred}('u) \gg \text{pred}('u) : \text{judg}$

The above sequent has free symbols, but we can close over them by adding a form of parametric higher-order judgment to our object language, indexed by a collection of sorts  $\vec{\sigma}$ :

$\Upsilon \Vdash \nabla[\vec{\sigma}] : (\{\vec{\sigma}\}. \text{judg}) \text{judg}$

Then, we may write a closed sequent judgment as follows:

$\cdot \triangleright \cdot \parallel \cdot \vdash \nabla[\text{exp}, \text{exp}](\lambda\{u, v\} \cdot \diamond, u : P, v : \text{pred}('u) \gg \text{pred}('u)) : \text{judg}$

## 6.1 Refinements for wellformedness

Having specified an approximation of the grammar of telescopes and sequents in the abt logical framework, we can proceed to define proper wellformedness via *inductive refinement* [11]. The basic idea is to introduce a new form of (meta)-judgment  $\Theta \triangleright \Upsilon \parallel \Gamma \vdash M \in_{\text{wf}} \tau$  which expresses the extrinsic wellformedness properties we wish to verify, presupposing  $\Theta \triangleright \Upsilon \parallel \Gamma \vdash M : \tau$ . Additionally, we introduce an analogous judgment on bound terms,  $\Theta \triangleright \Upsilon \parallel \Gamma \vdash E \in_{\text{wf}} v$  presupposing  $\Theta \triangleright \Upsilon \parallel \Gamma \vdash E : v$ , defined uniformly as follows:

$$\frac{\Theta \triangleright \Upsilon, \vec{u} : \vec{\sigma} \parallel \Gamma, \vec{x} : \vec{\tau} \vdash M \in_{\text{wf}} \tau}{\Theta \triangleright \Upsilon \parallel \Gamma \vdash \lambda\{\vec{u}\}[\vec{x}]. M \in_{\text{wf}} \{\vec{\sigma}\}[\vec{\tau}]. \tau}$$

Likewise, wellformedness for variables and metavariables is defined uniformly:

$$\frac{}{\Theta \triangleright \Upsilon \parallel \Gamma \vdash x \in_{\text{wf}} \tau} \quad \frac{\Theta \ni m : \{\vec{\sigma}\}[\tau_0, \dots, \tau_n]. \tau \quad \Theta \triangleright \Upsilon \parallel \Gamma \vdash M_i \in_{\text{wf}} \tau_i \ (i \leq n)}{\Theta \triangleright \Upsilon \parallel \Gamma \vdash m\{\vec{u}\}(M_0, \dots, M_n) \in_{\text{wf}} \tau}$$

*Remark 6.1.* Note that the refinement for variables  $x$  is not trivial, since it is only defined in case the presupposition  $\Theta \triangleright \Upsilon \parallel \Gamma \vdash x : \tau$  is satisfied.

The remainder of the definition of refinement proceeds by induction on sorts and operators. For the sake of this example, we will just stipulate that anything of sort **exp** or **prop** is grammatical if its subterms are grammatical:

$$\frac{\Upsilon \Vdash \vartheta : (v_0, \dots, v_n) \tau \quad \Theta \triangleright \Upsilon \parallel \Gamma \vdash E_i \in_{\text{wf}} v_i \ (i \leq n)}{\Theta \triangleright \Upsilon \parallel \Gamma \vdash \vartheta(E_0, \dots, E_n) \in_{\text{wf}} \tau} \text{ for } \tau \in \{\text{exp}, \text{prop}\}$$

The refinements for parametric judgment and sequents simply delegate to their subterms as well:

$$\frac{\Theta \triangleright \Upsilon, \vec{u} : \vec{\sigma} \parallel \Gamma \vdash J \in_{\text{wf}} \text{jdg}}{\Theta \triangleright \Upsilon \parallel \Gamma \vdash \nabla[\vec{\sigma}](\lambda\{\vec{u}\}[] . J) \in_{\text{wf}} \text{jdg}}$$

$$\frac{\Theta \triangleright \Upsilon \parallel \Gamma \vdash H \in_{\text{wf}} \text{tele} \quad \Theta \triangleright \Upsilon \parallel \Gamma \vdash A \in_{\text{wf}} \text{prop}}{\Theta \triangleright \Upsilon \parallel \Gamma \vdash H \gg A \in_{\text{wf}} \text{jdg}}$$

The refinement for telescopes proceeds by induction:

$$\frac{}{\Theta \triangleright \Upsilon \parallel \Gamma \vdash \diamond \in_{\text{wf}} \text{tele}} \quad \frac{\Theta \triangleright \Upsilon \setminus \{u\} \parallel \Gamma \vdash H \in_{\text{wf}} \text{tele} \quad \Theta \triangleright \Upsilon \setminus \{u\} \parallel \Gamma \vdash A \in_{\text{wf}} \text{prop}}{\Theta \triangleright \Upsilon \parallel \Gamma \vdash H, u : A \in_{\text{wf}} \text{tele}}$$

# Appendices

## A Sheafhood on $\mathbb{I}[\mathcal{S}]$

**Theorem A.1.** *A presheaf  $X : \mathbf{Set}^{\mathbb{I}\downarrow\mathcal{S}}$  is a sheaf on  $\mathbb{I}[\mathcal{S}]$  just when it preserves pullbacks.*

*Proof.* The proof is essentially the same as that of the analogous lemma for the Schanuel topos as presented in [13, A.2.1.11.h], but we will give a slightly more detailed version here. The presheaf  $X$  is a sheaf on the atomic site  $\mathbb{I}[\mathcal{S}]$  just when, for any renaming  $\rho : C \hookrightarrow D$  and any  $n \in X(D)$  if  $n \cdot \rho_0 = n \cdot \rho_1$  for all diagrams

$$C \xrightarrow{\rho} D \rightrightarrows_{\rho_1}^{\rho_0} E$$

such that  $\rho_0 \circ \rho = \rho_1 \circ \rho$ , then there exists a unique  $m \in X(C)$  such that  $m \cdot \rho = n$ . In other words, the arrow  $X(\rho)$  is an equalizer, as in the following:

$$\begin{array}{ccccc} X(C) & \xrightarrow{X(\rho)} & X(D) & \rightrightarrows_{X(\rho_1)}^{X(\rho_0)} & X(E) \\ \uparrow m & \nearrow n & & & \\ \mathbb{1} & & & & \end{array}$$

Now, because  $\mathbf{Set}$  is a regular category,  $X(\rho)$  is an equalizer precisely when it is a monomorphism. Therefore, if we have assumed that  $X$  preserves pullbacks, in order to demonstrate that  $X$  is a sheaf, it suffices to show that  $X(\rho)$  is monic. If  $X$  preserves pullbacks, then it also preserves monomorphisms, because in any category with pullbacks,  $f : A \longrightarrow B$  is monic just when the square

$$\begin{array}{ccc} A & \xrightarrow{1_A} & A \\ \downarrow 1_A & & \downarrow f \\ A & \xrightarrow{f} & B \end{array}$$

is a pullback [15, p. 16]. Because  $X$  preserves monomorphisms, and all arrows in  $\mathbb{I}\downarrow\mathcal{S}$  are monic, then  $X(\rho)$  is monic. Hence,  $X$  is a sheaf.

Next, we must show that if  $X$  is a sheaf, then it preserves pullbacks; we will loosely track the proof of Proposition 2.6.15 in [2]. Fix the following diagram such that it is a pullback

square in  $\mathbb{I} \downarrow \mathcal{S}$ :

$$\begin{array}{ccc} C & \xrightarrow{f_j} & C_j \\ \downarrow f_i & & \downarrow s_j \\ C_i & \xrightarrow{s_i} & D \end{array}$$

Then it suffices to show that the following diagram is also pullback square in **Set**:

$$\begin{array}{ccc} X(C) & \xrightarrow{X(f_j)} & X(C_j) \\ \downarrow X(f_i) & & \downarrow X(s_j) \\ X(C_i) & \xrightarrow{X(s_i)} & X(D) \end{array}$$

To prove that the above diagram is a pullback, it suffices to show that for any  $m_i \in X(C_i)$  and  $m_j \in X(C_j)$  such that  $X(s_i)(m_i) = X(s_j)(m_j)$ , we have a unique  $m \in X(C)$ ; the universal property of the pullback follows immediately from this.

Consider the singleton cover on  $C$  that contains  $h \triangleq s_i \circ f_i = s_j \circ f_j$ ; a matching family  $\phi$  for the cover  $\{h\}$  is a map that takes  $h$  to an object in  $X(D)$ , and an amalgamation for  $\phi$  consists in an object  $m \in X(C)$  such that  $\phi(h) = X(h)(m)$ . Now recall that  $X$  is a sheaf on  $\mathbb{I}[\mathcal{S}]$  if and only if every matching family has a unique amalgamation; for the matching family  $\phi(h) \triangleq X(s_i)(m_i)$ , then, we must have a unique amalgamation  $m \in X(C)$  since  $X$  is a sheaf. Therefore,  $X$  preserves pullbacks.

□



## References

- [1] P. Aczel. A general Church-Rosser theorem. Technical report, University of Manchester, 1978.
- [2] B. Biering. On the logic of bunched implications – and its relation to separation logic. Master’s thesis, University of Copenhagen, June 2004.
- [3] R. L. Constable, S. F. Allen, H. M. Bromley, W. R. Cleaveland, J. F. Cremer, R. W. Harper, D. J. Howe, T. B. Knoblock, N. P. Mendler, P. Panangaden, J. T. Sasaki, and S. F. Smith. *Implementing Mathematics with the Nuprl Proof Development System*. Prentice-Hall, Inc., Upper Saddle River, NJ, USA, 1986.
- [4] K. Crary. Explicit contexts in LF (extended abstract). *Electronic Notes in Theoretical Computer Science*, 228:53 – 68, 2009. Proceedings of the International Workshop on Logical Frameworks and Metalanguages: Theory and Practice (LFMTP 2008).
- [5] M. Fiore and C.-K. Hur. Second-order equational logic (extended abstract). In A. Dawar and H. Veith, editors, *Computer Science Logic*, volume 6247 of *Lecture Notes in Computer Science*, pages 320–335. Springer Berlin Heidelberg, 2010.
- [6] M. Fiore and O. Mamoud. Second-order algebraic theories – (extended abstract). In *Mathematical Foundations of Computer Science 2010, 35th International Symposium, MFCS 2010, Brno, Czech Republic, August 23-27, 2010. Proceedings*, pages 368–380, 2010.
- [7] M. Fiore, G. Plotkin, and D. Turi. Abstract syntax and variable binding. In *Proceedings of the 14th Symposium on Logic in Computer Science*, pages 193–202, 1999.
- [8] M. Fiore and S. Staton. Comparing operational models of name-passing process calculi. *Inf. Comput.*, 204(4):524–560, Apr. 2006.
- [9] M. P. Fiore. Mathematical models of computational and combinatorial structures. In *Foundations of Software Science and Computational Structures, 8th International Conference, FOSSACS 2005, Held as Part of the Joint European Conferences on Theory and Practice of Software, ETAPS 2005, Edinburgh, UK, April 4-8, 2005, Proceedings*, pages 25–46, 2005.
- [10] A. Gacek. The Abella Interactive Theorem Prover (System Description). In *IJCAR*, volume 5195 of *Lecture Notes in Computer Science*, pages 154–161. Springer International Publishing, 2008.
- [11] R. Harper. *Practical Foundations for Programming Languages*. Cambridge University Press, New York, NY, USA, 2016.
- [12] J. Hickey, A. Nogin, R. L. Constable, B. E. Aydemir, E. Barzilay, Y. Bryukhov, R. Eaton, A. Granicz, A. Kopylov, C. Kreitz, V. N. Krupski, L. Lorigo, S. Schmitt, C. Witty, and

- X. Yu. MetaPRL – a modular logical environment. In D. Basin and B. Wolff, editors, *Theorem Proving in Higher Order Logics*, volume 2758 of *Lecture Notes in Computer Science*, pages 287–303. Springer Berlin Heidelberg, 2003.
- [13] P. T. Johnstone. *Sketches of an elephant: a topos theory compendium, Vol. 1*. Oxford Logic Guides. Clarendon Press, Oxford, 2002.
- [14] D. K. Lee, K. Crary, and R. Harper. Towards a mechanized metatheory of Standard ML. In *Proceedings of the 34th Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, POPL '07, pages 173–184, New York, NY, USA, 2007. ACM.
- [15] S. Mac Lane and I. Moerdijk. *Sheaves in geometry and logic : a first introduction to topos theory*. Universitext. Springer, New York, 1992.
- [16] C. Martens and K. Crary. LF in LF: Mechanizing the metatheories of LF in Twelf. In *Proceedings of the Seventh International Workshop on Logical Frameworks and Meta-languages, Theory and Practice*, LFMTTP '12, pages 23–32, New York, NY, USA, 2012. ACM.
- [17] U. Norell. *Towards a practical programming language based on dependent type theory*. PhD thesis, Department of Computer Science and Engineering, Chalmers University of Technology, SE-412 96 Göteborg, Sweden, September 2007.
- [18] A. M. Pitts. *Nominal Sets: Names and Symmetry in Computer Science*, volume 57 of *Cambridge Tracts in Theoretical Computer Science*. Cambridge University Press, 2013.
- [19] P. Schroeder-Heister. *Structural Frameworks with Higher-level Rules: Philosophical Investigations on the Foundations of Formal Reasoning*. PhD thesis, Fachgruppe Philosophie, Universität Konstanz, 1987. Habilitation thesis.
- [20] J. Sterling, D. Gratzer, and V. Rahli. JonPRL. <http://www.jonprl.org/>, 2015.