

Type Refinements for the Working Class

Jon Sterling and Darin Morrison

There are two conflicting views which bedevil any discussion of the nature of type theory. First, there is the notion of type theory as an extension or generalization of universal algebra to support interdependency of sorts and operations, possibly subject to an arbitrary equational theory [1, 3]; we will call this *formal type theory*. Typing, in such a setting, is a mere matter of grammar and is nearly always decidable. In hindsight, we may observe that this is the sort of type theory which Martin-Löf first proposed in 1972 [12], even if we will admit that this was not the intention at the time. A model for such a type theory is usually given by interpreting the types or sorts as presheaves or sheaves over contexts of hypotheses, and as such, a proof theoretic interpretation of the hypothetical judgment is inevitable.

Secondly, there is the view of type theory as semi-formal theory of constructions for the Brouwer-Heyting-Kolmogorov interpretation of intuitionistic mathematical language, which we will call *behavioral* or *semantic type theory*. The most widely known development of this program is Martin-Löf's 1979 "extensional" type theory [13, 14], but we must give priority to Dana Scott for inventing this line of research in 1970 with his prophetic report, *Constructive Validity* [15]. Since the 1980s, behavioral type theory has been developed much further in the Nuprl family [2] of proof assistants, including MetaPRL [7] and JonPRL [16].

Martin-Löf's key innovation was the commitment to pervasive functionality (extensionality) as part of the *definitions* of the judgments and the types, in contrast to the state of affairs in formal type theory where functionality is a metatheorem which must be shown to obtain, based on the (somewhat arbitrary) equational theory which has been imposed. Furthermore, models for behavioral type theory interpret the types as partial equivalence relations on only closed terms, and the meaning of the hypothetical judgment is defined separately and uniformly in the logical relations style.

Our position is that these views of type theory are not in conflict, but rather merely describe two distinct layers in a single, harmonious system. From this perspective, formal type theories can do little more than negotiate matters of grammar, and therefore may serve as a syntactic (linguistic) framework for mathematical language, being responsible for the management of variable binding and substitution. On the other hand, the meaning of mathematical statements shall be specified *behaviorally* in the semantic type theory.

The types of the semantic theory can then be said to *refine* the types of the syntactic theory [5, 6, 4], both by placing restrictions on membership and by coarsening equivalence.

1 Abstract Binding Trees and Symbols

give a brief description of the framework, and present its rules.

In this paper, we hint at the *modes* of judgments and assertions [4] using colors, marking inputs with **blue** and outputs with **red**. As a rule of thumb, inputs are things which are supplied when checking the correctness of a judgment, and outputs are things which are synthesized in the process.

The diagram illustrates the relationship between a world W and its shadow $SCtx$. The top row shows W mapping to $SCtx$ via π . The bottom row shows worlds w_i, w_j, w_k mapping to their shadows $\gamma_i, \gamma_j, \gamma_k$. A mapping ι_ρ maps w_j to w_k , and its shadow $\pi(\iota_\rho)$ maps γ_j to γ_k . A mapping ρ maps γ_j to γ_k . A curved arrow maps w_i to γ_j , and another curved arrow maps γ_i to γ_k . A dotted arrow maps w_i to w_j .

Definition 2.1 (Hypothetical Judgment). For two judgments \mathcal{J}_1 and \mathcal{J}_2 , we can form the hypothetical judgment $\mathcal{J}_2 \mid \mathcal{J}_1$ using the exponential construction [11, p. 46], which expresses

the semantic consequence of \mathcal{J}_2 from \mathcal{J}_1 :

$$\begin{aligned} (\mathcal{J}_2 \vdash \mathcal{J}_1)(w) &\triangleq (\mathcal{J}_2^{\mathcal{J}_1})(w) \\ &\cong \mathbb{J}[\mathbf{y}(w) \times \mathcal{J}_1, \mathcal{J}_2] \\ &\cong \int_{w'} w' \succeq w \Rightarrow \mathcal{J}_2(w')^{\mathcal{J}_1(w')} \end{aligned}$$

In other words, the hypothetical judgment $\mathcal{J}_2 \vdash \mathcal{J}_1$ is evident when there shall forevermore be an effective transformation of evidence for the antecedent into evidence for the consequent. It is important to keep in mind that this is a *semantic* consequence and therefore expresses admissibilities, in contrast to the *logical* consequence which expresses derivabilities [4]. We will not have any need for the latter.

Notation For a hypothetical judgment with multiple hypotheses, we will write $\mathcal{J}_3 \vdash (\mathcal{J}_1, \mathcal{J}_2)$ rather than $\mathcal{J}_3 \vdash (\mathcal{J}_1 \times \mathcal{J}_2)$ or $(\mathcal{J}_3 \vdash \mathcal{J}_2) \vdash \mathcal{J}_1$.

Definition 2.2 (General Judgment). For a metavariable context Ω *mctx*, we can define the set of its substitutions as follows:

$$\square\Omega \triangleq \prod_{(m:v) \in \Omega} \{E \mid \cdot \triangleright \cdot \parallel \cdot \vdash E : v\}$$

For any diagram $\mathcal{J} : \mathbb{J}^{\square\Omega}$, we can define the general judgment $|_{\Omega} \mathcal{J}$ as follows, where $\mathbf{y}(-) : \mathcal{W} \longrightarrow \mathbb{J}$ is the Yoneda Embedding:

$$\begin{aligned} (|_{\Omega} \mathcal{J})(w) &\triangleq \mathbb{J}[\mathbf{y}(w), \varprojlim \mathcal{J}] \\ &\cong \int_{(w', \vec{E})} w' \succeq w \Rightarrow \mathcal{J}(\vec{E})(w') \end{aligned}$$

Intuitively, the general judgment $|_{\Omega} \mathcal{J}$ is evident when the family of judgments \mathcal{J} shall forevermore have a global section (i.e. for any substitution $\vec{E} \in \square\Omega$, $\mathcal{J}(\vec{E})$ shall be evident). Recall that metavariables have *valences* rather than sorts; as such, the general judgment allows us to quantify over terms of higher type.

Notation We will write $|_{\Omega}^{\Upsilon \parallel \Gamma} \mathcal{J}$ for $|_{\Omega'} \mathcal{J}$, where $\Omega' \ni m : \{\Upsilon, \vec{\sigma}\}[\Gamma, \vec{\tau}]. \tau$ if $\Omega \ni m : \{\vec{\sigma}\}[\vec{\tau}]. \tau$. Additionally, for clarity we will often write $|_{m:\sigma} \mathcal{J}$ rather than $|_{m:\{\cdot\}[\cdot]. \sigma} \mathcal{J}$; likewise, in the body of \mathcal{J} , when there are contextually salient \vec{u}, \vec{x} , we will simply write m rather than the more proper $m\{\vec{u}\}[\vec{x}]$.

Definition 2.3 (Internal Judgments). It often happens that the evidence for a judgment is the knowledge of the meaning of a new form of judgment. This can be neatly expressed in

our topos using the power object $\wp(-)$: for any judgment $\mathcal{J} \in \mathbb{J}$, the derivations of $\wp(\mathcal{J})$ shall consist in subsets of the derivations of \mathcal{J} . The evidence of $\wp(\mathcal{J})$ shall be called an *internal judgment* J . In most cases, we will say something like “To know \mathcal{J} is to have a judgment J ” rather than appealing directly to the power object or the subobject classifier.

After this section, we will define a judgment either by rules, or by an informal semantical explanation, in both cases leaving its intensional character implicit. A judgment is said to be *correct* or *valid* just in case it is globally inhabited.

3 Behavioral Refinements

Fixing a signature $\Sigma \equiv \langle \mathcal{S}, \mathcal{O} \rangle$ in the abt framework, we will define the notion of behavioral refinement by propounding several judgments and their semantical explanations.

3.1 Parametric Refinement

We will require two judgments, defined mutually: $\Phi \sqsubset^* \Upsilon$, which means that Φ is a symbol context which refines the symbol context Υ (presupposing $\Upsilon \text{ ctx}$), and parametric refinement $\Phi \parallel \phi \sqsubset \tau$ (which shall presuppose $\Phi \sqsubset^* \Upsilon$ and $\tau \text{ sort}$).

The first judgment we define inductively:

$$\frac{}{\cdot \sqsubset^* \cdot} \sqsubset_{\text{nil}}^* \quad \frac{\Phi \sqsubset^* \Upsilon \quad \Phi \parallel \phi \sqsubset \tau}{\Phi, u : \phi \sqsubset^* \Upsilon, u : \tau} \sqsubset_{\text{snoc}}^*$$

The second judgment is defined coinductively via the following meaning explanation:

Definition 3.1 (Parametric Refinement). To know $\Phi \parallel \phi \sqsubset \tau$ (presupposing $\Phi \sqsubset^* \Upsilon$ and $\tau \text{ sort}$) is to know, for any renaming $\rho : \Upsilon \hookrightarrow \Upsilon'$, and for any M, N , what it means for M and N to be identified under ϕ , supposing $\cdot \triangleright \Upsilon' \parallel \cdot \vdash M : \tau$ and $\cdot \triangleright \Upsilon' \parallel \cdot \vdash N : \tau$, requiring that if $M \sim_{\phi}^{\rho} N$ then $N \sim_{\phi}^{\rho} M$, and if $M \sim_{\phi}^{\rho} N$ and $N \sim_{\phi}^{\rho} O$, then $M \sim_{\phi}^{\rho} O$.

In other words, to know $\Phi \parallel \phi \sqsubset \tau$ (presupposing $\Phi \sqsubset^* \Upsilon$) is to know, for any renaming of Υ to Υ' , which partial equivalence relation on the closed τ -sorted Υ' -terms ϕ denotes. At this point, it should be remarked that this is very similar to the semantical explanation of typehood given in [13], except that we have generalized it to a multi-sorted setting, and that we have fibred the entire apparatus over collections Υ of symbols.

define maps of refined contexts, then change weakening lemma to monotonicity, which is stronger and more useful.

Theorem 3.2 (Weakening). If $\Phi \parallel \phi \sqsubset \tau$, then $\Phi, u : \psi \parallel \phi \sqsubset \tau$ (supposing $u \notin |\Phi|$ and $\Phi \parallel \psi \sqsubset \sigma$).

Proof. This follows trivially from the rule $\sqsubset_{\text{snoc}}^*$ and the canonical renaming $\Upsilon \longmapsto \Upsilon, u : \sigma$. \square

When we have $\cdot \parallel \phi \sqsubset \tau$, we say that ϕ *globally* refines τ and may simply write $\phi \sqsubset \tau$. By weakening, if $\phi \sqsubset \tau$ then for all Φ , we have $\Phi \parallel \phi \sqsubset \tau$ supposing $\Phi \sqsubset^* \Upsilon$.

3.1.1 Ordering and Equality of Parametric Refinement

We will write $\Phi \parallel \phi \subseteq \psi \sqsubset \tau$ to mean that ϕ is a *subrefinement* of ψ , presupposing $\Phi \sqsubset^* \Upsilon$, $\Upsilon \parallel \phi \sqsubset \tau$ and $\Upsilon \parallel \psi \sqsubset \tau$:

Definition 3.3. To know $\Phi \parallel \phi \subseteq \psi \sqsubset \tau$ is to know, for any substitution $\rho : \Upsilon \longmapsto \Upsilon'$, the following judgments:

$$|_{m,n:\tau} M \sim_{\psi}^{\rho} N \quad (M \sim_{\phi}^{\rho} N)$$

Two refinements are equal when they denote the same PER. That is, we have $\Phi \parallel \phi = \psi \sqsubset \tau$ just when both $\Phi \parallel \phi \subseteq \psi \sqsubset \tau$ and $\Phi \parallel \psi \subseteq \phi \sqsubset \tau$.

3.2 Parametric Equality

The primary judgment concerning refinements is the parametric equality, $\Phi \parallel M = N \in \phi$, which presupposes $\Phi \sqsubset^* \Upsilon$, $\Phi \parallel \phi \sqsubset \tau$, $\cdot \triangleright \Upsilon \parallel \cdot \vdash M : \tau$ and $\cdot \triangleright \Upsilon \parallel \cdot \vdash N : \tau$. The meaning of this judgment is that M and N are identified by ϕ at the identity renaming $1 : \Upsilon \longmapsto \Upsilon$:

$$\frac{M \sim_{\phi}^1 N}{\Phi \parallel M = N \in \phi}$$

3.3 Functional Refinement

Next, we define functional refinement $\Phi \parallel \Psi \models \phi = \psi \sqsubset \tau$ in terms of parametric refinement, simultaneously with parametric context refinement $\Phi \parallel \Psi \sqsubset^* \Gamma$ and functional equality $\Phi \parallel \Psi \models M = N \in \phi$. We will write $\Phi \parallel \Psi \models \phi \sqsubset \tau$ as a shorthand for $\Phi \parallel \Psi \models \phi = \phi \sqsubset \tau$.

Parametric context refinement $\Phi \parallel \Psi \sqsubset^* \Gamma$ shall be defined as follows, presupposing $\Phi \sqsubset^* \Upsilon$ and $\Gamma \text{ vctx}$:

$$\frac{}{\Phi \parallel \cdot \sqsubset^* \cdot} \parallel_{\text{nil}}^* \quad \frac{\Phi \parallel \Psi \sqsubset^* \Gamma \quad \Phi \parallel \Psi \models \phi \sqsubset \tau}{\Phi \parallel \Psi, x : \phi \sqsubset^* \Gamma, x : \tau} \parallel_{\text{snoc}}^*$$

Functional refinement $\Phi \parallel \Psi \models \phi = \psi \sqsubset \tau$ presupposes $\Phi \parallel \Psi \sqsubset^* \Gamma$ and $\tau \text{ sort}$, and is explained by induction on the evidence for its first presupposition.

Case $\frac{}{\Phi \parallel \cdot \sqsubset^* \cdot} \parallel_{\text{nil}}^*$.

$$\frac{\Phi \parallel \phi = \psi \sqsubset \tau}{\Phi \parallel \cdot \models \phi = \psi \sqsubset \tau}$$

$$\text{Case } \frac{\Phi \parallel \Psi \sqsubset^* \Gamma \quad \Phi \parallel \Psi \models \chi \sqsubset \sigma}{\Phi \parallel \Psi, x : \chi \sqsubset^* \Gamma, x : \sigma} \parallel \sqsubset_{\text{snoc}}^*, \text{ where } \Phi \sqsubset^* \Upsilon.$$

$$\frac{\begin{array}{c} \Upsilon \parallel \Gamma \\ \text{m, n : } \sigma \end{array} \Phi \parallel \Psi \models [m/x] \phi = [n/x] \psi \sqsubset \tau \quad (\Phi \parallel \Psi \models n = n \in \chi)}{\Phi \parallel \Psi, x : \chi \models \phi = \psi \sqsubset \tau}$$

3.4 Functional Equality

Functional equality $\Phi \parallel \Psi \models M = N \in \phi$ presupposes $\Phi \sqsubset^* \Upsilon$, $\Phi \parallel \Psi \sqsubset^* \Gamma$, $\Phi \parallel \Psi \models \phi \sqsubset \tau$, $\cdot \triangleright \Upsilon \parallel \Gamma \vdash M : \tau$ and $\cdot \triangleright \Upsilon \parallel \Gamma \vdash N : \tau$; the judgment is defined by induction on the evidence for the second presupposition $\Phi \parallel \Psi \sqsubset^* \Gamma$:

$$\text{Case } \frac{}{\Phi \parallel \cdot \sqsubset^* \cdot} \parallel \sqsubset_{\text{nil}}^*.$$

$$\frac{\Phi \parallel M = N \in \phi}{\Phi \parallel \cdot \models M = N \in \phi}$$

$$\text{Case } \frac{\Phi \parallel \Psi \sqsubset^* \Gamma \quad \Phi \parallel \Psi \models \psi \sqsubset \sigma}{\Phi \parallel \Psi, x : \psi \sqsubset^* \Gamma, x : \sigma} \parallel \sqsubset_{\text{snoc}}^*, \text{ where } \Phi \sqsubset^* \Upsilon.$$

$$\frac{\begin{array}{c} \Upsilon \parallel \Gamma \\ \text{m, n : } \sigma \end{array} \Phi \parallel \Psi \models [m/x] \phi = [n/x] \psi \in \phi \quad (\Phi \parallel \Psi \models m = n \in \psi)}{\Phi \parallel \Psi, x : \psi \models M = N \in \phi}$$

4 Constructions on Refinements

Refinements can be arranged in a partial order via the $\Phi \parallel \phi \sqsubseteq \psi \sqsubset \tau$ judgment, and admit a lattice structure at any sort τ .

We have the bottom refinement $\perp_\tau \sqsubset \tau$, which simply contains no elements. Next, the top refinement $\top_\tau \sqsubset \tau$ identifies all terms M, N such that $\cdot \triangleright \Upsilon \parallel \cdot \vdash M : \tau$ and $\cdot \triangleright \Upsilon \parallel \cdot \vdash N : \tau$. The join $\Phi \parallel \phi \cup_\tau \psi \sqsubset \tau$ of two refinements $\Phi \parallel \phi \sqsubset \tau$ and $\Phi \parallel \psi \sqsubset \tau$ is defined as follows:

$$\frac{\Phi \parallel M = N \in \phi}{\Phi \parallel M = N \in \phi \cup_\tau \psi} \quad \frac{\Phi \parallel M = N \in \psi}{\Phi \parallel M = N \in \phi \cup_\tau \psi}$$

Finally the meet $\Phi \parallel \phi \cap_\tau \psi \sqsubset \tau$ of two refinements $\Phi \parallel \phi \sqsubset \tau$ and $\Phi \parallel \psi \sqsubset \tau$ is defined dually:

$$\frac{\Phi \parallel M = N \in \phi \quad \Phi \parallel M = N \in \psi}{\Phi \parallel M = N \in \phi \cap_\tau \psi}$$

It is trivial to verify that these constructions on refinements give rise to a lattice.

5 Multi-Sorted Computational Type Theory

Martin-Löf’s type theory is a theory of *value types*: to define a type, you specify how to form its equal canonical inhabitants, or values. Then, the inhabitants of the types are explained uniformly by extending this relation over an operational semantics such that two terms are equal members of a type just when they compute to equal values of that type.

More generally, one may wish to consider types which include computations in addition to values; an example of such a type would be $\bar{\psi}$ when ψ is a type, which would include all the members of ψ as well as a divergent computation. Another example is the type \top_τ which identifies all closed terms of sort τ .

In order to ensure that such types are sensible, we must formulate a notion of computational equivalence, and then say that a refinement is a *type* just when it respects computational equivalence; then, we are able to define types as PERs on *programs* in addition to values.

5.1 Lazy Computation Systems

In this section we generalize Howe’s notion of lazy computation system [8] to the multi-sorted, symbol-parameterized setting. An *lazy computation language* is an abt signature $\Sigma \equiv \langle \mathcal{S}, \mathcal{O} \rangle$ along with a distinguished copresheaf $\mathcal{K} : \mathbf{Set}^{\mathbf{S}^{\mathbf{Ctx}} \times \mathcal{A} =}$ of *canonical* operators such that $\mathcal{K} \subseteq \mathcal{O}$. For a lazy computation language $\mathbf{L} \equiv \langle \mathcal{S}, \mathcal{O}, \mathcal{K} \rangle$, let us define the presheaves of closed expressions and closed values as follows:

$$\begin{aligned} \mathcal{E}_\tau(w) &\triangleq \{M \mid \cdot \triangleright \pi(w) \parallel \cdot \vdash M : \tau\} \\ \mathcal{V}_\tau(w) &\triangleq \left\{ M \equiv \vartheta(\vec{E}) \mid M \in \mathcal{E}_\tau(w) \wedge \exists a. \mathcal{K}(\pi(w), a) \ni \vartheta \right\} \end{aligned}$$

Remark 5.1. If read as a judgment, \mathcal{E}_τ (resp. \mathcal{V}_τ) means “there is a closed expression (resp. value) of sort τ ”, and has as its evidence any closed expression (resp. value) of sort τ .

Then, a *lazy computation system* (lcs) is a lazy computation language $\mathbf{L} \equiv \langle \Sigma, \mathcal{K} \rangle$ along with a \equiv_α -functional evaluation relation. Formally, the evaluation relation is given in our logical framework by a sort-indexed family of intensional sets of evaluation rules $\mathfrak{R}_\downarrow^\tau : \mathbb{J}$, such that the judgment $\wp \left(\mathfrak{R}_\downarrow^\tau \right) (\mathcal{E}_\tau, \mathcal{V}_\tau, \mathcal{N})$ shall be evident by means of some internal family of judgments $[\downarrow_\tau]$, where \mathcal{N} is the constant presheaf $w \longmapsto \mathbb{N}$. In other words, we shall forevermore know what it means to know that some expression evaluates to some value in n steps. By this token, we write $\Upsilon \parallel M \downarrow_\tau^n N$ to mean the judgment whose derivations at w are the set $[\downarrow_\tau](w, M, N, n)$.

References

- [1] J. Cartmell. Generalised algebraic theories and contextual categories. *Annals of Pure and Applied Logic*, 32:209 – 243, 1986.
- [2] R. L. Constable, S. F. Allen, H. M. Bromley, W. R. Cleaveland, J. F. Cremer, R. W. Harper, D. J. Howe, T. B. Knoblock, N. P. Mendler, P. Panangaden, J. T. Sasaki, and S. F. Smith. *Implementing Mathematics with the Nuprl Proof Development System*. Prentice-Hall, Inc., Upper Saddle River, NJ, USA, 1986.
- [3] P. Dybjer. Internal type theory. In S. Berardi and M. Coppo, editors, *Types for Proofs and Programs*, volume 1158 of *Lecture Notes in Computer Science*, pages 120–134. Springer Berlin Heidelberg, 1996.
- [4] R. Harper. *Practical Foundations for Programming Languages*. Cambridge University Press, New York, NY, USA, 2016.
- [5] R. Harper and R. Davies. Refining Objects (Preliminary Summary). <https://www.cs.cmu.edu/~rwh/papers/1c60/1c60.pdf>, 2014.
- [6] R. Harper and W. Duff. Type Refinements in an Open World. <https://www.cs.cmu.edu/~rwh/papers/trow/summary.pdf>, 2015.
- [7] J. Hickey, A. Nogin, R. L. Constable, B. E. Aydemir, E. Barzilay, Y. Bryukhov, R. Eaton, A. Granicz, A. Kopylov, C. Kreitz, V. N. Krupski, L. Lorigo, S. Schmitt, C. Witty, and X. Yu. MetaPRL – a modular logical environment. In D. Basin and B. Wolff, editors, *Theorem Proving in Higher Order Logics*, volume 2758 of *Lecture Notes in Computer Science*, pages 287–303. Springer Berlin Heidelberg, 2003.
- [8] D. J. Howe. Equality in lazy computation systems. In *Proceedings of Fourth IEEE Symposium on Logic in Computer Science*, pages 198–203.
- [9] B. Jacobs. *Categorical logic and type theory*. Studies in logic and the foundations of mathematics. Elsevier, Amsterdam, 2001.
- [10] S. Mac Lane. *Categories for the Working Mathematician*. Number 5 in Graduate Texts in Mathematics. Springer-Verlag, 1971.
- [11] S. Mac Lane and I. Moerdijk. *Sheaves in geometry and logic : a first introduction to topos theory*. Universitext. Springer, New York, 1992.
- [12] P. Martin-Löf. An intuitionistic theory of types, 1972.
- [13] P. Martin-Löf. Constructive mathematics and computer programming. In L. J. Cohen, J. Łoś, H. Pfeiffer, and K.-P. Podewski, editors, *Logic, Methodology and Philosophy of Science*

VI, *Proceedings of the Sixth International Congress of Logic, Methodology and Philosophy of Science, Hannover 1979*, volume 104 of *Studies in Logic and the Foundations of Mathematics*, pages 153–175. North-Holland, 1982.

- [14] P. Martin-Löf and G. Sambin. *Intuitionistic type theory*. Studies in proof theory. Bibliopolis, Napoli, 1984.
- [15] D. Scott. Constructive validity. In M. Laudet, D. Lacombe, L. Nolin, and M. Schtzenberger, editors, *Symposium on Automatic Demonstration*, volume 125 of *Lecture Notes in Mathematics*, pages 237–275. Springer Berlin Heidelberg, 1970.
- [16] J. Sterling, D. Gratzer, and V. Rahli. JonPRL. <http://www.jonprl.org/>, 2015.
- [17] J. Sterling and D. Morrison. Syntax and Semantics of Abstract Binding Trees. 2015.
- [18] P. Taylor. *Practical foundations of mathematics*. Cambridge studies in advanced mathematics. Cambridge University Press, Cambridge, New York (N. Y.), Melbourne, 1999.