



1. There is a line given by the equation $3x + 4y + 12 = 0$, where formula of this line is $a_1x + b_1y + c_1 = 0$. Plot in Matlab:



Img1. Graphic of function: $3x+4y+12=0$




Img2. The distance between line and the origin


The perpendicular distance between line and origin = $-c/(a^2 + b^2)^{1/2} = -12/(3^2+4^2)^{1/2} = -12/5 = -2.4$. From the Img2 the distance is close to this value.

2. There are 2 classes w_1 , w_2 generated by Gaussian distribution with different mean value $m_1 = \begin{bmatrix} 0 \\ 2 \end{bmatrix}$ and $m_2 = \begin{bmatrix} 1.5 \\ 0 \end{bmatrix}$ and identical covariance matrices. Plot in Matlab:

```
N = 100;
C = [2 1; 1 2]
A = chol(C);
X = randn(100,2);
m1 = [0 2];
m2 = [1.5 0];
X1 = X + kron(ones(N,1), m1); !shifting the mean
X2 = X1*A;
Y1 = X + kron(ones(N,1), m2);
Y2 = Y1*A;
C1 = C^(-1);
w = 2*C1*(m2-m1)';
b = m1*C1*m1' - m2*C1*m2';
a1 = w(1);
b1 = w(2);
c1 = b;
x1 = -4;
y1 = (-c1-a1*x1)/b1;
x2 = 6;
y2 = (-c1-a1*x2)/b1;
```



Img3. Plot of 2 classes with means m_1, m_2



Img4. Bayes' optimal class boundary

```
plot(X2(:,1),X2(:,2),'c.',Y2(:,1),Y2(:,2),'mx');
hold on;
plot([x1 x2],[y1 y2],'g'); ! plot of the
```

3. Bayes' optimal class boundary:


$$W = 2 * C1 * (m2 - m1)';$$

$$b = m1 * C1 * m1' - m2 * C1 * m2'; \quad ! \text{ as } \log(P[w1]/P[w2]) = \log(1/1)=0$$


$$a1x + b1y + c1 = w^t x + b = 0 \Rightarrow a1=w[1]; a2=w[2];$$

4. Perceptron Learning:



PercentageError = 11



PercentageError = 15



When we change learning rate we can get similar error, but the difference is the larger learning rates appear to help the model locate regions of general, large-scale optima, while smaller rates help the model focus on one particular local optimum. Usually perceptron start to search with a big learning rate, gradually decreasing it during the process of finding weights.



Img8. Evolution of percentage error (eta= 0.01)

Final error = 0

If the separation of the data that we want to classify is more evident(such as one of the data shown on Img7), it would be easier to determine which samples belong to one class or another.