

Domain Run Detail Report

Domain Info

Domain Name	:	SQL Server Assessments
Domain Id	:	2
Domain Run Id	:	18
Report Execution Date	:	2026-01-25 11:34:22
Domain Run Status	:	success

Assessment Results

Assessment Name	Status	Success (%)	Risk	Risk Level	Asset-Adjusted Risk	Asset-Adjusted Risk Level
SQL Server Assessment	success	72.50	27.41	medium	10.96	medium
MSSQL-Chekpoin	success	72.50	27.41	medium	16.44	medium

Generated by report_service.report_domain_detail

Assessment Run Detail Report

Assessment Info

Runid : 46
Report Execution Date : 2026-01-25 11:34:22
Assessment Status : **Successful**
Assessment Name : SQL Server Assessment
Database Type : mssql
Datasource Name : MSSQLDEV - local
Benchmark Name : SQL Server Benchmark
Asset Impact : **Low**

Metrics

Total Count	Passed Count	Failed Count	Errors Count	Success Rate (%)	Standard Risk	Asset-Adjusted Risk
40	29	11	0	72.50	27.41	10.96

Risk Levels

Standard Risk Level

Medium

Risk requiring monitoring and planned treatment. Mitigation actions should be identified and scheduled according to organizational priorities.

Asset-Adjusted Risk Level

Medium

Risk requiring monitoring and planned treatment. Mitigation actions should be identified and scheduled according to organizational priorities.

Category Based Metrics

Category	Critical				Major				Minor				Caution				Risk			
	pass	fail	error	total	pass	fail	error	total	pass	fail	error	total	pass	fail	error	total	Standard Risk	Standard Risk Level	Asset-Adjusted Risk	Asset-Adjusted Risk Level
AUTH	0	0	0	0	0	1	0	1	0	0	0	0	0	0	0	0	100.00	critical	40.00	high
PRIV	7	0	0	7	3	2	0	5	1	0	0	1	0	0	0	0	13.33	medium	5.33	low
CONFIG	1	0	0	1	8	3	0	11	2	0	0	2	0	0	0	0	21.95	medium	8.78	low
PATCH	1	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0.00	low	0.00	low
AUDIT	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.00	low	0.00	low
ENCRYPT	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.00	low	0.00	low
ACCOUNT	5	4	0	9	1	1	0	2	0	0	0	0	0	0	0	0	45.24	high	18.10	medium
OTHER	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.00	low	0.00	low

Checkpoint Test Results

Category Name: **AUTH** Std Risk 100.00 **critical**
Asset-Adjusted 40.00 **high**

#	Checkpoint Name	Severity	Result
1	AA_SqlServer_170_Windows Authentication This test checks that the authentication mode is set to Windows authentication only. Windows provides a more robust authentication mechanism than SQL Server authentication.	Major	Fail

Test Result

The authentication mode is not set to Windows authentication only.

Evidence

```

---
'0'

```

Category Name: PRIVStd Risk 13.33 mediumAsset-Adjusted 5.33 low

#	Checkpoint Name	Severity	Result
1	AA_SqlServer_320_No Access to Registry Access Extended procedures This test checks for the existence of, and user permissions on, registry access extended stored procedures. Either these procedures should be completely dropped, or access to them should be strictly limited. xp_reg%,xp_instance_reg%	Major	Fail

Test Result

There are some persmissions permissions on registry access extended stored procedures

Evidence

```

-----
'Principal : public Extended Procedure Name : xp_instance_regread Type : DATABASE_ROLE'
'Principal : public Extended Procedure Name : xp_regread Type : DATABASE_ROLE'

```

#	Checkpoint Name	Severity	Result
2	AA_SqlServer_300_No Access To General Extended procedures This test checks for the existence of, and user permissions on, extended stored procedures. Either these procedures should be completely dropped, or access to them should be strictly limited. xp_cmdshell, xp_enumgroups, xp_grantlogin ,xp_logevent, xp_logininfo, xp_msver, xp_revokellogin, xp_sprintf, xp_sqlmaint, xp_sscanf	Major	Fail

Test Result

There are some persmissions permissions on general extended stored procedures.

Evidence

```

-----
'Principal : public Extended Procedure Name : xp_msver Type : DATABASE_ROLE'
'Principal : public Extended Procedure Name : xp_sscanf Type : DATABASE_ROLE'
'Principal : public Extended Procedure Name : xp_revokellogin Type : DATABASE_ROLE'
'Principal : public Extended Procedure Name : xp_grantlogin Type : DATABASE_ROLE'
'Principal : public Extended Procedure Name : xp_sprintf Type : DATABASE_ROLE'

```

#	Checkpoint Name	Severity	Result
3	AA_SqlServer_190_Public server role permission public is a special fixed server role containing all logins. Unlike other fixed server roles, permissions can be changed for the public role. In keeping with the principle of least privileges, the public server role should not be used to grant permissions at the server scope as these would be inherited by all users. Every SQL Server login belongs to the public role and cannot be removed from this role. Therefore, any permissions granted to this role will be available to all logins unless they have been explicitly denied to specific logins or user-defined server roles.	Critical	Pass

Test Result

No server permissions are granted to public.

#	Checkpoint Name	Severity	Result
4	AA_SqlServer_200_Fixed Server Role members for users This test checks fixed server roles for analyst , developers and real persons. Fixed server roles could not be assigned to real person users (Developer, Analyst users) . Only Admin can use fixed server role.	Critical	Pass

Test Result

Fixed Server role usage is correct.

#	Checkpoint Name	Severity	Result
5	AA_SqlServer_210_Database Role members for users This test checks database role members for analyst and real person users. Database roles except db_datareader could not be assigned to real person users (Developer, Analyst users) .	Critical	Pass

Test Result

Database role member usage for users is correct

#	Checkpoint Name	Severity	Result
6	AA_SqlServer_220_2_Public Database Permissions This test checks database permissions for public . Public is a special role and permissions should not be granted to public role.	Critical	Pass

Test Result

There are no permissions which are assigned to public.

#	Checkpoint Name	Severity	Result
7	AA_SqlServer_220_Public Database Permissions This test checks database permissions for public . Public is a special role and permissions should not be granted to public role.	Critical	Pass

Test Result

There are no permissions which are assigned to public.

#	Checkpoint Name	Severity	Result
8	AA_SqlServer_240_guest Database Permissions This test checks database permissions for guest . guest is a special user and permissions should not be granted to guest user.	Critical	Pass

Test Result

There are no permissions which are assigned to guest.

#	Checkpoint Name	Severity	Result
9	AA_SqlServer_250_Database Role members for guest This test checks database role members for guest user. Database roles could not be assigned to guest role.	Critical	Pass

Test Result

Database role member usage for guest user is correct

#	Checkpoint Name	Severity	Result
10	AA_SqlServer_290_2_No Permissions with GRANT Option This test checks database permissions with grant option. No permission with grant option should be defined in the database.	Major	Pass

Test Result

There are no permissions with grant option.

#	Checkpoint Name	Severity	Result
11	AA_SqlServer_290_No Permissions with GRANT Option	Major	Pass

Test Result

There are no permissions with grant option.

#	Checkpoint Name	Severity	Result
12	AA_SqlServer_330_Revoke public login from SQL Server agent proxy account The public database role contains every user in the msdb database. SQL Agent proxies define a security context in which a job step can run. Granting access to SQL Agent proxies for the public role would allow all users to utilize the proxy which may have high privileges. This would likely break the principle of least privileges.	Major	Pass

Test Result

There are no public permissions on SQL Server agent proxy account

#	Checkpoint Name	Severity	Result
13	AA_SqlServer_340_No Individual User Access To syscomment and sp_helptext This test checks for grants on SYS COMMENTS.TEXT. Such grants allow any user to read the text comments associated with a database object, making the text publicly viewable.	Minor	Pass

Test Result

There are no public permissions on SQL Server agent proxy account

Category Name: **CONFIG** Std Risk 21.95 **medium**
 Asset-Adjusted 8.78 **low**

#	Checkpoint Name	Severity	Result
1	AA_SqlServer_110_Disable Remote Access option The remote access option controls the execution of local stored procedures on remote servers or remote stored procedures on local server. Functionality can be abused to launch a Denial-of-Service (DoS) attack on remote servers by off-loading query processing to a target.	Major	Fail

Test Result

Remote Access option is not disabled. Disable this option

Evidence

 'remote access Value : 1 Value in use : 1'

#	Checkpoint Name	Severity	Result
2	Checkpoint başarıyla oluşturuldu. This test checks if SQL Server Instance is not advertised by the SQL Server Browser service. To maintain a higher level of protection for database instances, we recommend that SQL Server Instance be hidden when it is not required. Please note that this test does not include Clustered Instances as turning off this feature may cause issues with the Clustered environment.	Major	Fail

Test Result

SQL Server Instance is not hidden. Hide the instance

Evidence

-
0

#	Checkpoint Name	Severity	Result
3	AA_SqlServer_160_Hide SQL Server Instance This test checks if SQL Server Instance is not advertised by the SQL Server Browser service. To maintain a higher level of protection for database instances, we recommend that SQL Server Instance be hidden when it is not required. Please note that this test does not include Clustered Instances as turning off this feature may cause issues with the Clustered environment.	Major	Fail

Test Result

SQL Server Instance is not hidden. Hide the instance

Evidence

-
0

#	Checkpoint Name	Severity	Result
4	AA_SqlServer_280_No Sample Databases This test checks whether the sample databases created optionally on installation are present. These sample databases contain many default permissions, and can be used as an entry point to your systems.	Critical	Pass

Test Result

There are no sample databases in the server

#	Checkpoint Name	Severity	Result
5	AA_SqlServer_050_Disable Ad hoc distributed queries option Adhoc queries allow undefined access to remote database sources. Access to untrusted databases could result in execution of malicious applications and/or a compromise of local data confidentiality and integrity. The DBA will configure the database to disable access from the database to objects stored externally to the database on the local host unless mission and/or operationally required and documented.	Major	Pass

Test Result

Ad Hoc Distributed Queries is disabled

#	Checkpoint Name	Severity	Result
6	AA_SqlServer_060_Disable CLR option The clr_enabled parameter configures SQL Server to allow or disallow use of Command Language Runtime objects. CLR objects is managed code that integrates with the .NET Framework. This is a more secure method than external stored procedures, although it still contains some risk. Where no external application execution requirements are required, disallowing use of any improves the overall security posture of the database.	Major	Pass

Test Result

CLR option is disabled

#	Checkpoint Name	Severity	Result
7	AA_SqlServer_070_Disable Cross db ownership chaining option Cross database ownership chaining allows permissions to objects to be assigned by users other than the Information Owner. This allows access to objects that are not authorized directly by the Information Owner based on job functions defined by the owner. Unauthorized access may lead to a compromise of data integrity or confidentiality. The DBA will ensure database privileges are assigned via roles and not directly assigned to database accounts. Privileges may be assigned directly to application owner accounts where the DBMS does not otherwise support access via roles.	Major	Pass

Test Result

Cross db ownership chaining option is disabled

#	Checkpoint Name	Severity	Result
8	AA_SqlServer_080_Disable Database Mail XPs option SQL Mail accepts incoming database commands via email. This can introduce malicious codes or viruses into the SQL server environment.	Major	Pass

Test Result

Database Mail XPs option is disabled

#	Checkpoint Name	Severity	Result
9	AA_SqlServer_100_Disable xp_cmdshell Server Configuration option The xp_cmdshell extended stored procedures allows execution of host executables outside the controls of database access permissions. This access may be exploited by malicious users who have compromised the integrity of the SQL Server database process to control the host operating system to perpetrate additional malicious activity. The DBA should disable the use of external procedures by the database unless it is mission critical or operationally required	Major	Pass

Test Result

xp_cmdshell Server Configuration option is disabled

#	Checkpoint Name	Severity	Result
10	AA_SqlServer_120_Disable Remote Admin Connections option The remote admin connections option controls whether a client application on a remote computer can use the Dedicated Administrator Connection (DAC).The Dedicated Administrator Connection (DAC) lets an administrator access a running server to execute diagnostic functions or Transact-SQL statements, or to troubleshoot problems on the server, even when the server is locked or running in an abnormal state and not responding to a SQL Server Database Engine connection. In a cluster scenario, the administrator may not actually be logged on to the same node that is currently hosting the SQL Server instance and thus is considered "remote". Therefore, this setting should usually be enabled (1) for SQL Server failover clusters; otherwise it should be disabled (0) which is the default.	Major	Pass

Test Result

Remote Admin Connections option is disabled

#	Checkpoint Name	Severity	Result
11	AA_SqlServer_150_Disable database trustworthy status The TRUSTWORTHY database setting restricts access to database resources by databases that contain assemblies with the EXTERNAL_ACCESS or UNSAFE permission settings and modules that use impersonation of accounts assigned elevated privileges. Unless all assemblies and code for the database have been reviewed, especially in the case where databases have been detached and attached between server instances, leaving the TRUSTWORTHY status to off can help reduce threats from malicious assemblies or modules.	Major	Pass

Test Result

database trustworthy status is disabled

#	Checkpoint Name	Severity	Result
12	AA_SqlServer_310_No Access to OLE Automation procedures This test checks for the existence of, and user permissions on OLE automation extended stored procedures. Either these procedures should be completely dropped, or access to them should be strictly limited.	Major	Pass

Test Result

OLE Automation procedures option is disabled

#	Checkpoint Name	Severity	Result
13	AA_SqlServer_130_Disable Ole Automation Procedures option This test checks if Ole Automation Procedures option is disabled. Ole Automation Procedures option allows SQL Server users to execute functions external to SQL Server. Enabling this option will increase the attack surface of SQL Server and allow users to execute functions in the security context of SQL Server. We recommend that the Ole Automation Procedures option to be disabled when it is not document as a requirement.	Minor	Pass

Test Result

Ole Automation Procedures option is disabled

#	Checkpoint Name	Severity	Result
14	AA_SqlServer_140_Disable Scan for Startup Procedures option This test checks if scan for startup procedures is disabled. This feature causes SQL Server to scan for and automatically run all stored procedures that are set to execute upon service startup. If there are no user-defined stored procedures set to execute when SQL server starts, we recommend this feature to be disabled.	Minor	Pass

Test Result

Scan for Startup Procedures option is disabled

Category Name: PATCH

Std Risk - Low

Asset-Adjusted - Low

#	Checkpoint Name	Severity	Result
1	AA_SqlServer_010_Supported SQL Server version This test checks whether your current SQL Server version is a vendor-supported version. Microsoft does not provide security fixes or software updates to unsupported software versions	Critical	Pass

Test Result

The version of the database is acceptable.

Category Name: **AUDIT** Std Risk - **low**
 Asset-Adjusted - **low**

No checkpoint results are available for this category.

Category Name: **ENCRYPT** Std Risk - **low**
 Asset-Adjusted - **low**

No checkpoint results are available for this category.

Category Name: **ACCOUNT** Std Risk 45.24 **high**
 Asset-Adjusted 18.10 **medium**

#	Checkpoint Name	Severity	Result
1	AA_SqlServer_020_Disable the sa Login Account This test checks if the 'sa' Login Account is disabled. The sa account is a widely known and often widely used SQL Server account with sysadmin privileges. Enforcing this control reduces the probability of an attacker executing brute force attacks against a well-known principal.	Critical	Fail

Test Result

Disable sa login account

Evidence

'sa user name : sa is disabled : 0

#	Checkpoint Name	Severity	Result
2	AA_SqlServer_025_sa Change password This test checks that sa password change . The sa password should be changed in every two days	Critical	Fail

Evidence

```
--
11
```

#	Checkpoint Name	Severity	Result
3	AA_SqlServer_030_Ensure no Login exists with sa Login Account The 'sa' account is a well-known account. Well-known account names provide an easier target for attack. The lack of the sa account helps reduce the risk of an attack to this built-in account.	Critical	Fail

Test Result

There is the sa Login account in the database.Drop this user or rename et.

Evidence

```
name
----
'sa'
```

#	Checkpoint Name	Severity	Result
4	AA_SqlServer_360_CHECK_EXPIRATION Is Checked This test checks that CHECK_EXPIRATION is enabled for all users. Passwords that have been in use for long periods of time are likely to become known to unauthorized users.	Critical	Fail

Test Result

CHECK_EXPIRATION is not enabled for all users

Evidence

```
name
----
'sa'
```

#	Checkpoint Name	Severity	Result
5	AA_SqlServer_040_Rename the sa Login Account The 'sa' account is a well-known account. Well-known account names provide an easier target for attack. Renaming the sa account helps reduce the risk of an attack to this built-in account.	Major	Fail

Test Result

sa Login Account is not renamed. Rename this account

Evidence

```
name
----
'sa'
```

#	Checkpoint Name	Severity	Result
6	AA_SqlServer_230_Real person users All logins to the database should be made with AD groups, real person users should not be connected database directly	Critical	Pass

Test Result

Real person users are not found in the logins

#	Checkpoint Name	Severity	Result
7	AA_SqlServer_240_2_guest Database Permissions This test checks database permissions for guest . guest is a special user and permissions should not be granted to guest user.	Critical	Pass

Test Result

There are no permissions which are assigned to guest.

#	Checkpoint Name	Severity	Result
8	AA_SqlServer_260_SQL Logins with Null Password This test checks sql logins with null password. SQL Logins should not have null passwords.	Critical	Pass

Test Result

There are no sql logins with null passwords

#	Checkpoint Name	Severity	Result
9	AA_SqlServer_270_SQL Logins with username and passwords are equal This test checks sql login password which are equal to username. Username and password must be different for SQL logins.	Critical	Pass

Test Result

There is no SQL login name which is equal to password.

#	Checkpoint Name	Severity	Result
10	AA_SqlServer_350_User Password Policy Is Checked This test checks that CHECK_POLICY is enabled for all users. Enabling CHECK_POLICY ensures that Windows passwords policies are enforced.	Critical	Pass

Test Result

CHECK_POLICY is enabled for all users

#	Checkpoint Name	Severity	Result
11	AA_SqlServer_180_No Guest User Accounts This test checks for the existence of guest user accounts with CONNECT permission in database other than master, msdb and tempdb. This test also exclude databases that are flagged as distributor. If the GUEST user exists and a specific login has not been granted to a database, a login will be mapped to GUEST. The presence of the GUEST user allows all logins to access the database.	Major	Pass

Test Result

There is no guest user with CONNECT permission.

Category Name: OTHER

Std Risk - Low

Asset-Adjusted - Low

No checkpoint results are available for this category.

Assessment Run Detail Report

Assessment Info

Runid : 47
Report Execution Date : 2026-01-25 11:34:25
Assessment Status : **Successful**
Assessment Name : MSSQL-Chekpoint
Database Type : mssql
Datasource Name : MSSQLDEV - local
Benchmark Name : SQL Server Benchmark
Asset Impact : **medium**

Metrics

Total Count	Passed Count	Failed Count	Errors Count	Success Rate (%)	Standard Risk	Asset-Adjusted Risk
40	29	11	0	72.50	27.41	16.44

Risk Levels

Standard Risk Level

Medium

Risk requiring monitoring and planned treatment. Mitigation actions should be identified and scheduled according to organizational priorities.

Asset-Adjusted Risk Level

Medium

Risk requiring monitoring and planned treatment. Mitigation actions should be identified and scheduled according to organizational priorities.

Category Based Metrics

Category	Critical				Major				Minor				Caution				Risk			
	pass	fail	error	total	pass	fail	error	total	pass	fail	error	total	pass	fail	error	total	Standard Risk	Standard Risk Level	Asset-Adjusted Risk	Asset-Adjusted Risk Level
AUTH	0	0	0	0	0	1	0	1	0	0	0	0	0	0	0	0	100.00	critical	60.00	high
PRIV	7	0	0	7	3	2	0	5	1	0	0	1	0	0	0	0	13.33	medium	8.00	low
CONFIG	1	0	0	1	8	3	0	11	2	0	0	2	0	0	0	0	21.95	medium	13.17	medium
PATCH	1	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0.00	low	0.00	low
AUDIT	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.00	low	0.00	low
ENCRYPT	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.00	low	0.00	low
ACCOUNT	5	4	0	9	1	1	0	2	0	0	0	0	0	0	0	0	45.24	high	27.14	medium
OTHER	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.00	low	0.00	low

Checkpoint Test Results

Category Name: **AUTH** Std Risk 100.00 **critical**
Asset-Adjusted 60.00 **high**

#	Checkpoint Name	Severity	Result
1	AA_SqlServer_170_Windows Authentication This test checks that the authentication mode is set to Windows authentication only. Windows provides a more robust authentication mechanism than SQL Server authentication.	Major	Fail

Test Result

The authentication mode is not set to Windows authentication only.

Evidence

```

---
'0'

```

Category Name: PRIV**Std Risk** 13.33 medium**Asset-Adjusted** 8.00 low

#	Checkpoint Name	Severity	Result
1	AA_SqlServer_320_No Access to Registry Access Extended procedures This test checks for the existence of, and user permissions on, registry access extended stored procedures. Either these procedures should be completely dropped, or access to them should be strictly limited. xp_reg%,xp_instance_reg%	Major	Fail

Test Result

There are some persmissions permissions on registry access extended stored procedures

Evidence

```

-----
'Principal : public Extended Procedure Name : xp_instance_regread Type : DATABASE_ROLE'
'Principal : public Extended Procedure Name : xp_regread Type : DATABASE_ROLE'

```

#	Checkpoint Name	Severity	Result
2	AA_SqlServer_300_No Access To General Extended procedures This test checks for the existence of, and user permissions on, extended stored procedures. Either these procedures should be completely dropped, or access to them should be strictly limited. xp_cmdshell, xp_enumgroups, xp_grantlogin ,xp_logevent, xp_logininfo, xp_msver, xp_revokelogin, xp_sprintf, xp_sqlmaint, xp_sscanf	Major	Fail

Test Result

There are some persmissions permissions on general extended stored procedures.

Evidence

```

-----
'Principal : public Extended Procedure Name : xp_msver Type : DATABASE_ROLE'
'Principal : public Extended Procedure Name : xp_sscanf Type : DATABASE_ROLE'
'Principal : public Extended Procedure Name : xp_revokelogin Type : DATABASE_ROLE'
'Principal : public Extended Procedure Name : xp_grantlogin Type : DATABASE_ROLE'
'Principal : public Extended Procedure Name : xp_sprintf Type : DATABASE_ROLE'

```

#	Checkpoint Name	Severity	Result
3	AA_SqlServer_190_Public server role permission public is a special fixed server role containing all logins. Unlike other fixed server roles, permissions can be changed for the public role. In keeping with the principle of least privileges, the public server role should not be used to grant permissions at the server scope as these would be inherited by all users. Every SQL Server login belongs to the public role and cannot be removed from this role. Therefore, any permissions granted to this role will be available to all logins unless they have been explicitly denied to specific logins or user-defined server roles.	Critical	Pass

Test Result

No server permissions are granted to public.

#	Checkpoint Name	Severity	Result
4	AA_SqlServer_200_Fixed Server Role members for users This test checks fixed server roles for analyst , developers and real persons. Fixed server roles could not be assigned to real person users (Developer, Analyst users) . Only Admin can use fixed server role.	Critical	Pass

Test Result

Fixed Server role usage is correct.

#	Checkpoint Name	Severity	Result
5	AA_SqlServer_210_Database Role members for users This test checks database role members for analyst and real person users. Database roles except db_datareader could not be assigned to real person users (Developer, Analyst users) .	Critical	Pass

Test Result

Database role member usage for users is correct

#	Checkpoint Name	Severity	Result
6	AA_SqlServer_220_2_Public Database Permissions This test checks database permissions for public . Public is a special role and permissions should not be granted to public role.	Critical	Pass

Test Result

There are no permissions which are assigned to public.

#	Checkpoint Name	Severity	Result
7	AA_SqlServer_220_Public Database Permissions This test checks database permissions for public . Public is a special role and permissions should not be granted to public role.	Critical	Pass

Test Result

There are no permissions which are assigned to public.

#	Checkpoint Name	Severity	Result
8	AA_SqlServer_240_guest Database Permissions This test checks database permissions for guest . guest is a special user and permissions should not be granted to guest user.	Critical	Pass

Test Result

There are no permissions which are assigned to guest.

#	Checkpoint Name	Severity	Result
9	AA_SqlServer_250_Database Role members for guest This test checks database role members for guest user. Database roles could not be assigned to guest role.	Critical	Pass

Test Result

Database role member usage for guest user is correct

#	Checkpoint Name	Severity	Result
10	AA_SqlServer_290_2_No Permissions with GRANT Option This test checks database permissions with grant option. No permission with grant option should be defined in the database.	Major	Pass

Test Result

There are no permissions with grant option.

#	Checkpoint Name	Severity	Result
11	AA_SqlServer_290_No Permissions with GRANT Option	Major	Pass

Test Result

There are no permissions with grant option.

#	Checkpoint Name	Severity	Result
12	AA_SqlServer_330_Revoke public login from SQL Server agent proxy account The public database role contains every user in the msdb database. SQL Agent proxies define a security context in which a job step can run. Granting access to SQL Agent proxies for the public role would allow all users to utilize the proxy which may have high privileges. This would likely break the principle of least privileges.	Major	Pass

Test Result

There are no public permissions on SQL Server agent proxy account

#	Checkpoint Name	Severity	Result
13	AA_SqlServer_340_No Individual User Access To syscomment and sp_helptext This test checks for grants on SYS COMMENTS.TEXT. Such grants allow any user to read the text comments associated with a database object, making the text publicly viewable.	Minor	Pass

Test Result

There are no public permissions on SQL Server agent proxy account

Category Name: **CONFIG** Std Risk 21.95 **medium**
 Asset-Adjusted 13.17 **medium**

#	Checkpoint Name	Severity	Result
1	AA_SqlServer_110_Disable Remote Access option The remote access option controls the execution of local stored procedures on remote servers or remote stored procedures on local server. Functionality can be abused to launch a Denial-of-Service (DoS) attack on remote servers by off-loading query processing to a target.	Major	Fail

Test Result

Remote Access option is not disabled. Disable this option

Evidence

 'remote access Value : 1 Value in use : 1'

#	Checkpoint Name	Severity	Result
2	Checkpoint başarıyla oluşturuldu. This test checks if SQL Server Instance is not advertised by the SQL Server Browser service. To maintain a higher level of protection for database instances, we recommend that SQL Server Instance be hidden when it is not required. Please note that this test does not include Clustered Instances as turning off this feature may cause issues with the Clustered environment.	Major	Fail

Test Result

SQL Server Instance is not hidden. Hide the instance

Evidence

-
0

#	Checkpoint Name	Severity	Result
3	AA_SqlServer_160_Hide SQL Server Instance This test checks if SQL Server Instance is not advertised by the SQL Server Browser service. To maintain a higher level of protection for database instances, we recommend that SQL Server Instance be hidden when it is not required. Please note that this test does not include Clustered Instances as turning off this feature may cause issues with the Clustered environment.	Major	Fail

Test Result

SQL Server Instance is not hidden. Hide the instance

Evidence

-
0

#	Checkpoint Name	Severity	Result
4	AA_SqlServer_280_No Sample Databases This test checks whether the sample databases created optionally on installation are present. These sample databases contain many default permissions, and can be used as an entry point to your systems.	Critical	Pass

Test Result

There are no sample databases in the server

#	Checkpoint Name	Severity	Result
5	AA_SqlServer_050_Disable Ad hoc distributed queries option Adhoc queries allow undefined access to remote database sources. Access to untrusted databases could result in execution of malicious applications and/or a compromise of local data confidentiality and integrity. The DBA will configure the database to disable access from the database to objects stored externally to the database on the local host unless mission and/or operationally required and documented.	Major	Pass

Test Result

Ad Hoc Distributed Queries is disabled

#	Checkpoint Name	Severity	Result
6	AA_SqlServer_060_Disable CLR option The clr_enabled parameter configures SQL Server to allow or disallow use of Command Language Runtime objects. CLR objects is managed code that integrates with the .NET Framework. This is a more secure method than external stored procedures, although it still contains some risk. Where no external application execution requirements are required, disallowing use of any improves the overall security posture of the database.	Major	Pass

Test Result

CLR option is disabled

#	Checkpoint Name	Severity	Result
7	AA_SqlServer_070_Disable Cross db ownership chaining option Cross database ownership chaining allows permissions to objects to be assigned by users other than the Information Owner. This allows access to objects that are not authorized directly by the Information Owner based on job functions defined by the owner. Unauthorized access may lead to a compromise of data integrity or confidentiality. The DBA will ensure database privileges are assigned via roles and not directly assigned to database accounts. Privileges may be assigned directly to application owner accounts where the DBMS does not otherwise support access via roles.	Major	Pass

Test Result

Cross db ownership chaining option is disabled

#	Checkpoint Name	Severity	Result
8	AA_SqlServer_080_Disable Database Mail XPs option SQL Mail accepts incoming database commands via email. This can introduce malicious codes or viruses into the SQL server environment.	Major	Pass

Test Result

Database Mail XPs option is disabled

#	Checkpoint Name	Severity	Result
9	AA_SqlServer_100_Disable xp_cmdshell Server Configuration option The xp_cmdshell extended stored procedures allows execution of host executables outside the controls of database access permissions. This access may be exploited by malicious users who have compromised the integrity of the SQL Server database process to control the host operating system to perpetrate additional malicious activity. The DBA should disable the use of external procedures by the database unless it is mission critical or operationally required	Major	Pass

Test Result

xp_cmdshell Server Configuration option is disabled

#	Checkpoint Name	Severity	Result
10	AA_SqlServer_120_Disable Remote Admin Connections option The remote admin connections option controls whether a client application on a remote computer can use the Dedicated Administrator Connection (DAC).The Dedicated Administrator Connection (DAC) lets an administrator access a running server to execute diagnostic functions or Transact-SQL statements, or to troubleshoot problems on the server, even when the server is locked or running in an abnormal state and not responding to a SQL Server Database Engine connection. In a cluster scenario, the administrator may not actually be logged on to the same node that is currently hosting the SQL Server instance and thus is considered "remote". Therefore, this setting should usually be enabled (1) for SQL Server failover clusters; otherwise it should be disabled (0) which is the default.	Major	Pass

Test Result

Remote Admin Connections option is disabled

#	Checkpoint Name	Severity	Result
11	AA_SqlServer_150_Disable database trustworthy status The TRUSTWORTHY database setting restricts access to database resources by databases that contain assemblies with the EXTERNAL_ACCESS or UNSAFE permission settings and modules that use impersonation of accounts assigned elevated privileges. Unless all assemblies and code for the database have been reviewed, especially in the case where databases have been detached and attached between server instances, leaving the TRUSTWORTHY status to off can help reduce threats from malicious assemblies or modules.	Major	Pass

Test Result

database trustworthy status is disabled

#	Checkpoint Name	Severity	Result
12	AA_SqlServer_310_No Access to OLE Automation procedures This test checks for the existence of, and user permissions on OLE automation extended stored procedures. Either these procedures should be completely dropped, or access to them should be strictly limited.	Major	Pass

Test Result

OLE Automation procedures option is disabled

#	Checkpoint Name	Severity	Result
13	AA_SqlServer_130_Disable Ole Automation Procedures option This test checks if Ole Automation Procedures option is disabled. Ole Automation Procedures option allows SQL Server users to execute functions external to SQL Server. Enabling this option will increase the attack surface of SQL Server and allow users to execute functions in the security context of SQL Server. We recommend that the Ole Automation Procedures option to be disabled when it is not document as a requirement.	Minor	Pass

Test Result

Ole Automation Procedures option is disabled

#	Checkpoint Name	Severity	Result
14	AA_SqlServer_140_Disable Scan for Startup Procedures option This test checks if scan for startup procedures is disabled. This feature causes SQL Server to scan for and automatically run all stored procedures that are set to execute upon service startup. If there are no user-defined stored procedures set to execute when SQL server starts, we recommend this feature to be disabled.	Minor	Pass

Test Result

Scan for Startup Procedures option is disabled

Category Name: **PATCH**

Std Risk - **Low**

Asset-Adjusted - **Low**

#	Checkpoint Name	Severity	Result
1	AA_SqlServer_010_Supported SQL Server version This test checks whether your current SQL Server version is a vendor-supported version. Microsoft does not provide security fixes or software updates to unsupported software versions	Critical	Pass

Test Result

The version of the database is acceptable.

Category Name: **AUDIT** Std Risk - **low**
 Asset-Adjusted - **low**

No checkpoint results are available for this category.

Category Name: **ENCRYPT** Std Risk - **low**
 Asset-Adjusted - **low**

No checkpoint results are available for this category.

Category Name: **ACCOUNT** Std Risk 45.24 **high**
 Asset-Adjusted 27.14 **medium**

#	Checkpoint Name	Severity	Result
1	AA_SqlServer_020_Disable the sa Login Account This test checks if the 'sa' Login Account is disabled. The sa account is a widely known and often widely used SQL Server account with sysadmin privileges. Enforcing this control reduces the probability of an attacker executing brute force attacks against a well-known principal.	Critical	Fail

Test Result

Disable sa login account

Evidence

'sa user name : sa is disabled : 0

#	Checkpoint Name	Severity	Result
2	AA_SqlServer_025_sa Change password This test checks that sa password change . The sa password should be changed in every two days	Critical	Fail

Evidence

```
--
11
```

#	Checkpoint Name	Severity	Result
3	AA_SqlServer_030_Ensure no Login exists with sa Login Account The 'sa' account is a well-known account. Well-known account names provide an easier target for attack. The lack of the sa account helps reduce the risk of an attack to this built-in account.	Critical	Fail

Test Result

There is the sa Login account in the database.Drop this user or rename et.

Evidence

```
name
----
'sa'
```

#	Checkpoint Name	Severity	Result
4	AA_SqlServer_360_CHECK_EXPIRATION Is Checked This test checks that CHECK_EXPIRATION is enabled for all users. Passwords that have been in use for long periods of time are likely to become known to unauthorized users.	Critical	Fail

Test Result

CHECK_EXPIRATION is not enabled for all users

Evidence

```
name
----
'sa'
```

#	Checkpoint Name	Severity	Result
5	AA_SqlServer_040_Rename the sa Login Account The 'sa' account is a well-known account. Well-known account names provide an easier target for attack. Renaming the sa account helps reduce the risk of an attack to this built-in account.	Major	Fail

Test Result

sa Login Account is not renamed. Rename this account

Evidence

```
name
----
'sa'
```

#	Checkpoint Name	Severity	Result
6	AA_SqlServer_230_Real person users All logins to the database should be made with AD groups, real person users should not be connected database directly	Critical	Pass

Test Result

Real person users are not found in the logins

#	Checkpoint Name	Severity	Result
7	AA_SqlServer_240_2_guest Database Permissions This test checks database permissions for guest . guest is a special user and permissions should not be granted to guest user.	Critical	Pass

Test Result

There are no permissions which are assigned to guest.

#	Checkpoint Name	Severity	Result
8	AA_SqlServer_260_SQL Logins with Null Password This test checks sql logins with null password. SQL Logins should not have null passwords.	Critical	Pass

Test Result

There are no sql logins with null passwords

#	Checkpoint Name	Severity	Result
9	AA_SqlServer_270_SQL Logins with username and passwords are equal This test checks sql login password which are equal to username. Username and password must be different for SQL logins.	Critical	Pass

Test Result

There is no SQL login name which is equal to password.

#	Checkpoint Name	Severity	Result
10	AA_SqlServer_350_User Password Policy Is Checked This test checks that CHECK_POLICY is enabled for all users. Enabling CHECK_POLICY ensures that Windows passwords policies are enforced.	Critical	Pass

Test Result

CHECK_POLICY is enabled for all users

#	Checkpoint Name	Severity	Result
11	AA_SqlServer_180_No Guest User Accounts This test checks for the existence of guest user accounts with CONNECT permission in database other than master, msdb and tempdb. This test also exclude databases that are flagged as distributor. If the GUEST user exists and a specific login has not been granted to a database, a login will be mapped to GUEST. The presence of the GUEST user allows all logins to access the database.	Major	Pass

Test Result

There is no guest user with CONNECT permission.

Category Name: OTHER

Std Risk - Low

Asset-Adjusted - Low

No checkpoint results are available for this category.