

## Cat.6 UTP 90° Quick Solution w/ Dust Cover - Keystone Jack



CAT 6 UTP 90° Keystone Jack is designed with easy installation in mind and compatible with CAT 6 component performance (ANSI/TIA-568-C.2 Category 6).

Compatible with SYSThames One Punch Tool which can reduce jack termination time and save time up to 8 times compared to traditional termination.

### Features

Front Connection Spring Wire: Phosphor Bronze Alloy. Plated with 50 micro-inch of Gold over 70-100 micro-inch of Nickel  
 IDC Material: Phosphor Bronze Alloy with 10 micro-inch 100% Tin Alloy  
 Can terminate stranded or solid 22~24AWG wires.  
 T568A/B wiring

### Applications

Voice; T1; ISDN  
 10GBASE-T  
 16Mbps Token Ring (IEEE802.5)  
 100VG-AnyLAN (IEEE802.12)  
 100BASE-T Ethernet (IEEE802.3)  
 155/622Mbps 1.2/2.4 Gbps ATM  
 1000Mbps Gigabit Ethernet  
 550MHz Broadband Video

### Standards

UL 1863 Safety listed  
 UL 94V-0 Fire Retardant Plastic  
 ANSI/TIA Standard 568-2.D  
 ISO/IEC 11801 2. Ed.  
 CENELEC EN 50173

### Available Colours

1616-11011 - White  
 1616-21011 - Blue  
 1616-31011 - Yellow

