




Ajay Patel

❤️.NET

# I don't know about [ApiController]

in .NET






## ApiController attribute

**The [ApiController] attribute** in ASP.NET Core is used to indicate that a controller is intended to serve as an API endpoint. It simplifies the development of RESTful APIs.

It can be applied to a controller class to enable the following **opinionated**, API-specific behaviors:

- Attribute routing requirement
- Automatic HTTP 400 responses
- Binding source parameter inference
- Problem details for error status codes





## # How to Use ApiController Attribute?

Apply directly to individual controllers:



```
[ApiController]  
[Route("[controller]")]
```

3 references

```
public class WeatherForecastController : ControllerBase
```

Apply attribute on an assembly




Program.cs

```
using Microsoft.AspNetCore.Mvc;
```

```
[assembly:ApiController]
```

Lastly, We can also apply it to a custom controller base class. Then, all its subclasses will inherit ApiController behavior.





## Key Features

### 1. Attribute routing requirement

When you apply the `[ApiController]` attribute to a controller in ASP.NET Core, it enforces attribute routing, meaning actions in that controller will not be accessible via conventional routing (e.g., `UseEndpoints`, `UseMvc`, or `UseMvcWithDefaultRoute`)




```
[ApiController]
```

```
[Route("[controller]")]
```

3 references

```
public class WeatherForecastController : ControllerBase
```





## 2. Automatic HTTP 400 Responses:

When [ApiController] is applied, it automatically validates the model and responds with an HTTP 400 status if there are validation errors.


**This means we don't need to manually check ModelState.IsValid in our actions.**



```
if (!ModelState.IsValid)
{
    return BadRequest(ModelState);
}
```



ASP.NET Core MVC uses the **ModelStateInvalidFilter** action filter to do the preceding check.






## 3. Default BadRequest response:

The default response type for an HTTP 400 response is **ValidationProblemDetails**. The following response body is an example of the serialized type:

```
{
  "type": "https://tools.ietf.org/html/rfc7231#section-6.5.1",
  "title": "One or more validation errors occurred.",
  "status": 400,
  "traceId": "|7fb5e16a-4c8f23bbfc974667.",
  "errors": {
    "Name": [
      "The Name field is required."
    ]
  }
}
```

We can fully customize our validation problem responses as well. To do that, we provide our own implementation of the `InvalidModelStateResponseFactory` delegate in the **ConfigureApiBehaviorOptions()** extension method in Program.cs file.






## 4. Binding source parameter inference:

[ApiController] automatically determines the source of certain action parameters, so we don't always need to use binding attributes like [FromBody] or [FromQuery]. It follows specific inference rules to make this decision.

Attribute	Binding source
[FromBody]	Request body
[FromForm]	Form data in the request body
[FromHeader]	Request header
[FromQuery]	Request query string parameter
[FromRoute]	Route data from the current request
[FromServices]	The request service injected as an action parameter
[AsParameters]	Method parameters





**Ajay Patel**

**♥NET**

**Knowledge is  
contagious,  
let's spread it!**



**DO YOU LIKE THIS POST?**

**REPOST IT!**



**THANKS FOR READING**