

# KENDARAAN BISNIS YANG AMAN, EKONOMIS DAN TANGGUH

## KARIMUN BLIND VAN GS AGS

Rasakan kenyamanan dalam berkendara dengan pilihan transmisi manual dan matic sehingga membuat bisnis Anda lebih menguntungkan.



### DRIVER AIRBAG

Melindungi pengemudi apabila terjadi kecelakaan.



### 2DIN HEAD UNIT

Dilengkapi dengan fitur CD, MP3, Radio, USB, Aux-in.



### KEYLESS ENTRY

Sistem keamanan terkinin yang meningkatkan keamanan serta kenyamanan.



### AUTO GEAR SHIFT

Solusi berkendara mudah dan nyaman, tanpa pedal kopling. BISA MATIC – BISA MANUAL.



### UNDER SEAT TRAY

Memberikan ruang yang lebih banyak dan penyimpanan rahasia barang berharga.



### FLAT DECK LUGGAGE

Base floor dapat dilipat/dibuka dua arah sehingga dapat mengangkut/menyimpan barang bawaan lebih banyak.



### UNDER LUGGAGE SPARE TIRE

Menyimpan ban cadangan lebih aman.

## KARIMUN BLIND VAN

Kendaraan bisnis yang aman dan tangguh. Didesain khusus agar dapat menjelajah area perkotaan, menembus jalan-jalan sempit dengan lincah dan berenergi. Sangat menguntungkan untuk bisnis.



### DRIVER AIRBAG

Memberikan perlindungan maksimal untuk pengemudi jika terjadi kecelakaan.



### UNDER SEAT TRAY

Memberikan ruang yang lebih banyak dan penyimpanan rahasia barang berharga.



### FLAT DECK LUGGAGE

Base floor dapat dilipat/dibuka dua arah sehingga dapat mengangkut/menyimpan barang bawaan lebih banyak.



### UNDER LUGGAGE SPARE TIRE

Menyimpan ban cadangan lebih aman.

## APV BLIND VAN

Kendaraan bisnis yang memuat lebih banyak, untuk kebutuhan mengangkut atau mengirim barang dengan lebih aman, tanpa terpaan hujan ataupun panas terik yang menyengat dan dapat merusak barang.



### DUAL SRS - AIRBAG

Melindungi pengemudi & penumpang apabila terjadi kecelakaan.



### DASHBOARD COMPARTMENT

Laci penyimpanan memudahkan pengemudi untuk menyimpan barang-barang Anda.



### SPEEDOMETER

Mudahnya pengemudi untuk melihat kondisi kendaraan.



### AIR CONDITIONER

Memberikan pendinginan merata pada saat suhu udara tinggi.



### ERGONOMIC SEATS

Kursi ergonomis yang membuat pengemudi tidak cepat lelah.



### SPACIOUS LUGGAGE

Bagasi yang luas dan lapang, memungkinkan mengangkut berbagai keperluan bisnis.



### POWER STEERING

Memberikan kenyamanan ekstra saat berkendara dan memarkirkan kendaraan.

### SPECIFICATION

DIMENSIONS / DIMENSI	KARIMUN BV GS AGS	TRANSMISSION / TRANSMISI	KARIMUN BV GS AGS
Overall length / Panjang Keseluruhan (mm)	3.835	Gear Ratio / Perbandingan Gigi 1st	3.545
Overall width / Lebar Keseluruhan (mm)	1.475	2nd	1.904
Overall height / Tinggi Keseluruhan (mm)	1.670	3rd	
Wheelbase / Jarak Posisi Roda (mm)	2.400	4th	0.906
Tread / Jarak Pijak - Front / depan (mm)	1.285	5th	
Tread / Jarak Pijak - Rear / belakang (mm)	1.290	Reverse Number	3.272
Ground clearance / Jarak tembus (mm)	170	Final Gear ratio / Perbandingan Gigi Akhir	4.308
Minimum Turning Radius / Radius Putar Terendah (m)	4.6	CHASSIS / RANGKA	4.6
CAPACITIES / KAPASITAS		Steering / Sistem Kemudi	Rock & Pinion, EPS
Steering Capacity	persons	Suspension / Suspensi	Front: McPherson Strut Coil Spring
Suspension / Suspensi	Front: depan	Rear: /belakang	3 Links Rigid w/ coil spring
Fuel Tank Capacity	litres	Brake / Rem	Ventilated Disc
Fuel Tank Capacity	35	Tire / Ban	145/80 R13
ENGINE / MESIN		SAFETY / KEAMANAN	
Type / Jenis	K10B, DOHC	Steerwheel / Sabuk pengemudi	Front 3-point B.R.v2
Cylinder / Silinder	3 In-line	Brake Displacement / isi silinder (cc)	998
Number of Cylinders / jumlah silinder	3	Brake X Stroke / Diameter X Langkah (mm)	73 x 95.5
Piston Displacement / isi silinder (cc)	998	Maximum output / Daya maksimum (PS/rpm)	68/6000
Bore X Stroke / Diameter X Langkah (mm)	73 x 95.5	Maximum torque / momen putar maksimum (Nm/rpm)	90/3.500
Maximum output / Daya maksimum (PS/rpm)	68/6000	Fuel distribution / Distribusi bahan bakar	Multi Point Injection
Maximum torque / momen putar maksimum (Nm/rpm)	90/3.500		
Reversing Entry	Y		
Security Alarm	Y		
Fuel distribution / Distribusi bahan bakar	Multi Point Injection		

### VARIAN WARNA



### SPECIFICATION

DIMENSIONS / DIMENSI	KARIMUN BV	TRANSMISSION / TRANSMISI	KARIMUN BV
Overall length / Panjang Keseluruhan (mm)	3.600	Gear Ratio / Perbandingan Gigi 1st	3.545
Overall width / Lebar Keseluruhan (mm)	1.475	2nd	1.004
Overall height / Tinggi Keseluruhan (mm)	1.670	3rd	1.280
Wheelbase / Jarak Posisi Roda (mm)	2.400	4th	0.966
Tread / Jarak Pijak - Front / depan (mm)	1.295	5th	0.763
Tread / Jarak Pijak - Rear / belakang (mm)	1.290	Reverse Number	3.272
Ground clearance / Jarak tembus (mm)	170	Final Gear ratio / Perbandingan Gigi Akhir	4.308
Minimum Turning Radius / Radius Putar Terendah (m)	4.6	CHASSIS / RANGKA	
CAPACITIES / KAPASITAS		Steering / Sistem Kemudi	Rock & Pinion, EPS
Steering Capacity	persons	Suspension / Suspensi	Front: McPherson Strut Coil Spring
Fuel Tank Capacity	litres	Rear: /belakang	3 Links Rigid w/ coil spring
Fuel Tank Capacity	35	Brake / Rem	Ventilated Disc
ENGINE / MESIN		Tire / Ban	145/80 R13
Type / Jenis	K10B, DOHC	SAFETY / KEAMANAN	
Cylinder / Silinder	3 In-line	Steerwheel / Sabuk pengemudi	Front 3-point B.R.v2
Number of Cylinders / jumlah silinder	3	Brake Displacement / isi silinder (cc)	998
Piston Displacement / isi silinder (cc)	998	Brake X Stroke / Diameter X Langkah (mm)	73 x 95.5
Bore X Stroke / Diameter X Langkah (mm)	73 x 95.5	Maximum output / Daya maksimum (PS/rpm)	68/6000
Maximum output / Daya maksimum (PS/rpm)	68/6000	Maximum torque / momen putar maksimum (Nm/rpm)	90/3.500
Maximum torque / momen putar maksimum (Nm/rpm)	90/3.500	Fuel distribution / Distribusi bahan bakar	Multi Point Injection
Reversing Entry	Y		
Security Alarm	Y		
Fuel distribution / Distribusi bahan bakar	Multi Point Injection		

### SPECIFICATION

DIMENSIONS / DIMENSI	APV BV	TRANSMISSION / TRANSMISI	APV BV
Overall length / Panjang Keseluruhan (mm)	4.155	Gear Ratio / Perbandingan Gigi 1st	4.545
Overall width / Lebar Keseluruhan (mm)	1.455	2nd	2.628
Overall height / Tinggi Keseluruhan (mm)	1.665	3rd	1.865
Wheelbase / Jarak Posisi Roda (mm)	2.625	4th	1.241
Tread / Jarak Pijak - Front / depan (mm)	1.435	5th	1.000
Tread / Jarak Pijak - Rear / belakang (mm)	1.435	Reverse Number	4.491
Ground clearance / Jarak tembus (mm)	100	Final Gear ratio / Perbandingan Gigi Akhir	4.300
Minimum Turning Radius / Radius Putar Terendah (m)	4.9	CHASSIS / RANGKA	
CAPACITIES / KAPASITAS		Steering / Sistem Kemudi	Rock & Power Steering
Steering Capacity	persons	Suspension / Suspensi	McPherson Strut & Coil Spring
Fuel Tank Capacity	litres	Rear / belakang	Leaf Rigid Axle
Fuel Tank Capacity	46	Brake / Rem	Hybrid Disc
ENGINE / MESIN		Tire / Ban	Leaf & Inflating drum
Type / Jenis	615A	SAFETY / KEAMANAN	
Cylinder / Silinder	4	Steerwheel / Sabuk pengemudi	Front 3-point ELR.v2
Number of Cylinders / jumlah silinder	16	Brake Displacement / isi silinder (cc)	1.493
Piston Displacement / isi silinder (cc)	998	Brake X Stroke / Diameter X Langkah (mm)	73 x 94.5
Bore X Stroke / Diameter X Langkah (mm)	73 x 94.5	Maximum output / Daya maksimum (PS/rpm)	92.4/6.000
Maximum output / Daya maksimum (PS/rpm)	92.4/6.000	Maximum torque / momen putar maksimum (Nm/rpm)	126/1.000
Maximum torque / momen putar maksimum (Nm/rpm)	126/1.000	Fuel distribution / Distribusi bahan bakar	Multi Point Injection
Fuel distribution / Distribusi bahan bakar	Multi Point Injection		

Pengelengkapan standar dan opsional yang tersedia dapat beragam. Silakan bertemu dengan dealer Suzuki terdekat untuk mendapatkan spesifikasi dan ilustrasi diatas bisa saja tidak tersedia di wilayah Anda. Suzuki berhak mengubah spesifikasi, harga, warna, peralatan dan model tanpa pembatasan terlebih dahulu.



YOUR GEAR



**SUZUKI**  
**BLIND VAN** SERIES