

# Manual of plotastrodata

Yusuke Aso

## 1 Read Data

The data class `AstroData` can take a fits file.

```
from plotastrodata.analysis_utils import AstroData

d = AstroData(fitsimage='file_name.fits')
```

The data class `AstroFrame` is necessary to form the `AstroData` instance in a useful format. `AstroFrame` can take quantities related to coordinate ranges.

```
from plotastrodata.analysis_utils import AstroFrame

f = AstroFrame(vmin=-5.0, vmax=5.0, vsys=2.0,
               center='00h00m00s 00d00m00s', rmax=3.0)
```

`vmin`, `vmax`, and `vsys` are in the unit of  $\text{km s}^{-1}$ . `rmax` is in the unit of arcsec. Instead of `rmax`, other arguments (`xmin`, `xmax`, `ymin`, `ymax`, `xoff`, `yoff`) can be used to adjust the x and y ranges in more detail.

Forming the `AstroData` instance needs the following command.

```
f.read(d)
```

After this command, the `AstroData` instance has useful attributes in the format of numpy array: for example, a 1D array of `d.x` (as well as `d.y` and `d.v`), a 2D or 3D array of `d.data`, a 1D array of `d.beam`. `d.x` and `d.y` are the relative coordinates from the given `center` in the unit of arcsec. Similarly, `d.v` is the relative coordinate from the given `vsys` in the unit of  $\text{km s}^{-1}$ . `d.beam` is `array([bmaj, bmin, bpa])`, where `bmaj` and `bmin` are in the unit of arcsec, while `bpa` is in the unit of degree.

## 2 Analyze Data

`AstroData` also has handy methods to analyze the 2D/3D data. For example, the following method can be used to deproject the 2D data with a given position angle (P.A.) and inclination angle.

```
d.deproject(pa=45, incl=45)
```

`pa` is the position angle from the north to the east in the unit of degree. `incl` is the inclination angle; `incl=0` means the face-on configuration and thus no deprojection. This command replaces `d.data` with the deprojected 2D data.

After `d.data` is updated, the data can be output as a fits file by the following command.

```
d.writetofits(fitsimage='new_file_name.fits')
```

The output fits file reuses the header components of the fits file used to make the AstroData instance ('file\_name.fits' above); some header components are updated properly, such as NAXIS1.

### 3 Plot Data

The class PlotAstroData can take an AstroData instance through the method of `d.todict()`.

```
from plotastrodata.plot_utils import PlotAstroData

p = PlotAstroData(rmax=3.0)
p.add_color(**d.todict())
p.add_scalebar(length=50 / 140, label='50 au')
p.set_axis()
p.savefig('figure_name.png')
```

These commands make a color map using the AstroData instance `d`. PlotAstroData can take the same arguments as AstroFrame to define the plotting ranges; particularly `rmax` is necessary. The method `p.add_color()` can take a fits file directly instead of the AstroData instance: `p.add_color(fitsimage='file_name.fits')`. The command `p.add_scalebar()` can be omitted if the map does not need to show a scale bar. The command `p.set_axis()` (or `p.set_axis_radec()`) is necessary even without any argument. More detail usage can be found in the `example.py` file and <https://plotastrodata.readthedocs.io/en/latest/#>.