

Number of Islands (LC 200)

200. Number of Islands
Medium

Given an m x n 2D binary grid which represents a map of '1's (land) and '0's (water), return the number of islands.

An island is surrounded by water and is formed by connecting adjacent lands horizontally or vertically. You may assume all four edges of the grid are all surrounded by water.

```
class Solution:
    def numIslands(self, grid: List[List[str]]) -> int:
        if not grid:
            return 0
        rows, cols = len(grid), len(grid[0])
        visit = set()
        islands = 0

        def dfs(r, c):
            if grid[r][c] == "0" or (r,c) in visit:
                return
            visit.add((r, c))
            if 0 <= r + 1 < rows and 0 <= c < cols:
                dfs(r + 1, c)
            if 0 <= r - 1 < rows and 0 <= c < cols:
                dfs(r - 1, c)
            if 0 <= r < rows and 0 <= c + 1 < cols:
                dfs(r, c + 1)
            if 0 <= r < rows and 0 <= c - 1 < cols:
                dfs(r, c - 1)

        for row in range(rows):
            for col in range(cols):
                if grid[row][col] == "1" and (row, col) not in visit:
                    dfs(row, col)
                    islands += 1


        return islands
```

```
class Solution:
    def numIslands(self, grid: List[List[str]]) -> int:
        if not grid:
            return 0
        rows, cols = len(grid), len(grid[0])
        visit = set()
        islands = 0

        def bfs(r, c):
            q = collections.deque()
            visit.add((r, c))
            while q:
                r, c = q.popleft()
                directions = [[1, 0], [-1, 0], [0, 1], [0, -1]]
                for dr, dc in directions:
                    r2, c2 = r + dr, c + dc
                    if (r2, c2) not in visit and grid[r2][c2] == "1":
                        visit.add((r2, c2))
                        q.append((r2, c2))

        for row in range(rows):
            for col in range(cols):
                if grid[row][col] == "1" and (row, col) not in visit:
                    bfs(row, col)
                    islands += 1

        return islands
```



Explore and record if the area has not been visited.

Example 1:
Input: grid = [
["1","1","0","0","0"],
["1","1","0","0","0"],
["0","0","1","0","0"],
["0","0","1","0","0"],
["0","0","0","1","1"]
]
Output: 3

Max Area of Island (LC 695)

695. Max Area of Island
Medium

You are given an m x n binary matrix grid. An island is a group of '1's (representing land) connected 4-directionally (horizontal or vertical). You may assume all four edges of the grid are surrounded by water.

The area of an island is the number of cells with a value 1 in the island.

Return the maximum area of an island in grid. If there is no island, return 0.

```
class Solution:
    def maxAreaOfIsland(self, grid: List[List[int]]) -> int:
        if not grid:
            return 0
        rows, cols = len(grid), len(grid[0])
        visited = set()
        maxArea = 0

        def dfs(r, c):
            if ((r,c) in visited or
                r not in range(rows) or
                c not in range(cols) or
                grid[r][c] == 0):
                return 0
            visited.add((r,c))
            return 1 + dfs(r+1,c) + dfs(r-1,c) + dfs(r,c+1) + dfs(r,c-1)

        for row in range(rows):
            for col in range(cols):
                if grid[row][col] == 1 and (row, col) not in visited:
                    island_area = dfs(row, col)
                    maxArea = max(maxArea, island_area)
                    visited.add((row, col))

        return maxArea
```


```
class Solution:
    def maxAreaOfIsland(self, grid: List[List[int]]) -> int:
        rows, cols = len(grid), len(grid[0])
        self.max_area = 0
        visited = set()

        def bfs(r, c):
            area = 1
            q = collections.deque()
            q.append((r,c))
            directions = [(1,0), (-1,0), (0,1), (0,-1)]
            while q:
                qr, qc = q.popleft()
                for dr, dc in directions:
                    r2, c2 = qr + dr, qc + dc
                    if (r2 in range(rows) and
                        c2 in range(cols) and
                        grid[r2][c2] == 1 and
                        (r2, c2) not in visited):
                        visited.add((r2, c2))
                        q.append((r2, c2))
                        area += 1

            self.max_area = max(self.max_area, area)

        for row in range(rows):
            for col in range(cols):
                if grid[row][col] == 1 and (row, col) not in visited:
                    bfs(row, col)

        return self.max_area
```



Explore and record the area of an island, as long as it has not been visited before

Example 1:
Input: grid = [
[0,0,1,0,0,0,0,1,0,0,0,0,0],
[0,0,0,0,0,0,0,1,1,1,0,0,0],
[0,1,1,0,1,0,0,0,0,0,0,0,0],
[0,1,0,0,1,0,0,0,1,0,1,0,0],
[0,1,0,0,1,1,0,0,1,1,1,0,0],
[0,0,0,0,0,0,0,0,0,1,0,0,0],
[0,0,0,0,0,0,0,1,1,1,0,0,0],
[0,0,0,0,0,0,0,1,1,0,0,0],
[0,0,0,0,0,0,1,1,0,0,0,0]
]
Output: 6
Explanation: The answer is not 11, because the island must be connected 4-directionally.

Pacific Atlantic Water Flow (LC 417)

417. Pacific Atlantic Water Flow
Medium

There is an m x n rectangular island that borders both the Pacific Ocean and Atlantic Ocean. The Pacific Ocean touches the island's left and top edges, and the Atlantic Ocean touches the island's right and bottom edges.

The island is partitioned into a grid of square cells. You are given an m x n integer matrix heights where heights[r][c] represents the height above sea level of the cell at coordinate (r, c).

The island receives a lot of rain, and the rain water can flow to neighboring cells directly north, south, east, and west if the neighboring cell's height is less than or equal to the current cell's height. Water can flow from any cell adjacent to an ocean into the ocean.

Return a 2D list of grid coordinates result where result[i] = [r, c] denotes that rain water can flow from cell (r, c) to both the Pacific and Atlantic oceans.

```
class Solution:
    def pacificAtlantic(self, heights: List[List[int]]) -> List[List[int]]:
        ROWS, COLS = len(heights), len(heights[0])
        pacific, atlantic = set(), set()

        def dfs(r, c, visit, prevHeight):
            if (
                (r, c) in visit or
                r < 0 or
                c < 0 or
                r == ROWS or
                c == COLS or
                heights[r][c] < prevHeight
            ):
                return
            visit.add((r, c))
            dfs(r + 1, c, visit, heights[r+1][c])
            dfs(r - 1, c, visit, heights[r-1][c])
            dfs(r, c + 1, visit, heights[r][c+1])
            dfs(r, c - 1, visit, heights[r][c-1])

        for r in range(ROWS):
            dfs(r, 0, pacific, heights[r][0])
            dfs(r, COLS - 1, atlantic, heights[r][COLS - 1])

        for c in range(COLS):
            dfs(0, c, pacific, heights[0][c])
            dfs(ROWS - 1, c, atlantic, heights[ROWS - 1][c])



        result = []
        for r in range(ROWS):
            for c in range(COLS):
                if (r, c) in pacific and (r, c) in atlantic:
                    result.append((r, c))

        return result
```

Example 1:
Input: heights = [[1,2,2,3,5],
[3,2,3,4,4],
[2,4,3,2,1],
[6,7,1,4,5],
[5,1,1,2,4]]
Output: [[0,4],[1,3],[1,4],[2,2],[3,0],[3,1],[4,0]]

[1] create two sets:
- pacific = set()
- atlantic = set()

[2] starting at the edge of the matrix,
- run the dfs (or bfs) and explore adjacent cells, particularly if the previous cell value < current cell value
- Check to see if starting from the edge of one side reaches the other side and:
- is saved in the pacific set
- is saved in the atlantic set



Lastly, visit each (row, col) in the matrix, and if (row,col) exists in both pacific set and atlantic set, add to answer.

Surrounded Regions (LC 130)

130. Surrounded Regions
Medium

Given an m x n matrix board containing 'X' and 'O', capture all regions that are 4-directionally surrounded by 'X'.

A region is captured by flipping all 'O's into 'X's in that surrounded region.

```
class Solution:
    def solve(self, board: List[List[str]]) -> None:
        """
        Do not return anything, modify board in-place instead.
        """
        rows, cols = len(board), len(board[0])
        o_s = set()

        def dfs(r, c, visited):
            if (r not in range(rows) or
                c not in range(cols) or
                board[r][c] == "X" or
                (r, c) in visited):
                return
            visited.add((r,c))
            directions = [(1,0),(-1,0),(0,1),(0,-1)]
            for dr, dc in directions:
                row, col = r + dr, c + dc
                dfs(row, col, visited)

        for row in range(rows):
            dfs(row, 0, o_s)
            dfs(row, cols-1, o_s)
        for col in range(cols):
            dfs(0, col, o_s)
            dfs(rows-1, col, o_s)

        for row in range(rows):
            for col in range(cols):
                if (row, col) not in o_s and board[row][col] == "O":
                    board[row][col] = "X"
```

Clone Graph (LC 133)

133. Clone Graph
Medium

Given a reference of a node in a connected undirected graph.

Return a deep copy (clone) of the graph.

Each node in the graph contains a value (int) and a list (List[Node]) of its neighbors.

```
class Node {
    public int val;
    public List<Node> neighbors;
}

class Node:
    def __init__(self, val = 0, neighbors = None):
        self.val = val
        self.neighbors = neighbors if neighbors is not None else []

class Solution:
    def cloneGraph(self, node: Optional[Node]) -> Optional[Node]:
        hashmap = {}

        def dfs(node):
            if node in hashmap:
                return hashmap[node]
            copy = Node(node.val)
            hashmap[copy] = copy
            for next_node in node.neighbors:
                copy.neighbors.append(dfs(next_node))
            return copy

        return dfs(node) if node else None
```