



Computer Vision

Multiview Geometry / Stereo Vision

Based on:

- Aanæs, H. (2014). Lecture notes on Computer Vision
- Jeremy Cohen. Pseudo-lidar - stereo vision for self-driving cars (medium.com, 2020)



Computer Vision

Multiview Geometry / Stereo Vision

Based on:

- Aanæs, H. (2014). Lecture notes on Computer Vision
- Jeremy Cohen. Pseudo-lidar - stereo vision for self-driving cars (medium.com, 2020)



Computer Vision


Multiview Geometry / Stereo Vision

Based on:


- Aanæs, H. (2014). Lecture notes on Computer Vision
- Jeremy Cohen. Pseudo-lidar - stereo vision for self-driving cars (medium.com, 2020)

Stereo Vision

- Reconstructing 3D geometry based on camera images from two or more viewpoints
- Human Vision



Middlebury 2001 data set.



Stereo Vision

- How to estimate the distance using stereo vision?
 - Calibrate the cameras (Intrinsic and extrinsic calibration)
 - Create an epipolar scheme using epipolar geometry
 - Build a disparity and a depth map
- Depth map will be combined with an obstacle detection algorithm

Monocular Vision





Stereo Vision




Time of Flight Camera

- Estimates distance by measuring the time of flight of a light signal between the camera and the subject for each point of the image




$$\varphi = \arctan \frac{I_1 - I_3}{I_2 - I_4} \quad D = \frac{c}{4\pi f} \varphi$$

Microsoft Kinect 2




Taxonomy




Camera Geometry - Pinhole Model

- Tag udgangspunkt i jeremy stereo vision artikel



$$w \cdot \begin{bmatrix} u \\ v \\ 1 \end{bmatrix} = \begin{bmatrix} f_x & 0 & 0 \\ 0 & f_y & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} X \\ Y \\ Z \end{bmatrix}$$






Camera Calibration


- Converting 3D point in the world to a 2D pixel
- Using multiple images
- A known object
- Different positions
 - Rotated
 - Translated
 - Tilted
- Computes camera matrix and distortion parameters
- Removes distortion





Camera Calibration - Distortion




Barrel Distortion



Pincushion Distortion



Imperfect lens alignment



Tangential Distortion

Camera Calibration


- From world coordinates to camera coordinates
 - Extrinsic parameters
 - Rotation matrix
 - Translation matrix
- From camera coordinates to pixel coordinates
 - Intrinsic parameters
 - Intrinsic matrix
 - Focal length
 - Optical centre

$$\mathbf{q}_i = \mathbf{A} \begin{bmatrix} \mathbf{R} & \mathbf{t} \end{bmatrix} Q_i = \mathbf{P} Q_i \quad , \quad \mathbf{P} = \mathbf{A} \begin{bmatrix} \mathbf{R} & \mathbf{t} \end{bmatrix}$$


$$\mathbf{P} = \begin{bmatrix} p_{11} & p_{12} & p_{13} & p_{14} \\ p_{21} & p_{22} & p_{23} & p_{24} \\ p_{31} & p_{32} & p_{33} & p_{34} \end{bmatrix}$$

Multi View Geometry - Stereo Vision

- How can cameras estimate depth?
 - Left and right camera
 - Aligned in the same X and Y axis
 - Z is the difference of the two cameras and is used for estimating the depth



Multi View Geometry - Stereo Vision



$$\frac{Z}{f} = \frac{X}{x_L}$$

$$\frac{Z}{f} = \frac{X-b}{x_R}$$

$$x_L = \frac{X}{Z} \cdot f$$

$$x_R = \frac{X-b}{Z} \cdot f$$


$$Disparity = x_L - x_R$$

Disparity and Depth Maps

- Disparity is the difference in image location of the same 3D point from 2 different camera angles.
- In a pair of images, you can measure the apparent motion in pixels for every point and make an intensity image from the measurements




Middlebury 2001 data set.



$$Z = \frac{fb}{d}$$
$$X = \frac{Zx_L}{f}$$
$$Y = \frac{Zy_L}{f}$$


Epipolar Geometry

- Given a point in one camera - its corresponding point in the other camera lies on the epipolar line
- 7 Degree of freedom fundamental matrix




Stereo Correspondence Problem

- How to solve it and compute the disparity?
 - Take a pixel in the left image
 - Search on the epipolar line for the pixel in the right image
 - The point is located on the epipolar line and the search is 1D
 - Cameras need to be aligned along the same axis





Epipolar Search in Images

- Take each pixel on the line in the left image
- Compare the left image pixels to the right image pixels on the epipolar line
- Take the pixel with the minimum cost
- Compute the disparity




Practical Example of Using Stereo Vision

- First we calibrate the camera/images
- Then we have the image parameters for both images



Compute Disparity Maps


- Determine disparity between the two images
- Decompose the projection into the camera matrix
 - Both intrinsic and extrinsic parameters
- Estimate the depth by using the information from the last steps




Create the Depth Maps

- Use the projection matrix for each camera
 - Use the focal length
 - Compute baseline using corresponding values from the translation vectors
- Compute depth map of images from the disparity maps

Left depth map



Right depth map



$$Z = \frac{fb}{d}$$
$$X = \frac{Zx_L}{f}$$
$$Y = \frac{Zy_L}{f}$$

Depth Estimation - Results

- Run an obstacle detection algorithm and use it together with a depth map
- Take the closest point of the detected obstacle
 - We know the distance of every single point in the image

Left detection



Right detection



OpenCV Example

- Kig på opgave til lektionen



Homographies



Stereo Vision Triangulation



Direct Linear Transform (DLT)



Triangulation Error



Non-Linear optimization

