

Digital Image Fundamentals


[Image Quality]

■ Objective / subjective



- Machine/human beings
- Mathematical and Probabilistic/
human intuition and perception




Structure of the Human Eye



photoreceptor cells



Approximate Rod/Cone Distribution



Structure of the Human Eye

■ The Blind Spot




R

L

Instructions: Close one eye and focus the other on the appropriate letter (**R** for right or **L** for left). Place your eye a distance from the screen approximately equal to 3x the distance between the **R** and the **L**. Move your eye towards or away from the screen until you notice the other letter disappear. For example, close your right eye, look at the "L" with your left eye, and the "R" will disappear







Human Visual Perception

- Perceived brightness is NOT a simple function of intensity






Human Visual Perception

Optical Illusion





[Human Visual Perception]

■ Optical Illusion










Human Visual Perception

■ Optical Illusion





[Human Visual Perception]

■ Optical Illusion



[Human Visual Perception]

■ Optical Illusion



[Image Sensing and Acquisition]

■ Illumination Source

- EM energy, ultrasound, synthesized, ...


■ Scene Element

- Objects, human organs, buried mineral,...


■ Sensing Material

- Single sensor: photodiode
- Sensor strips: require extensive processing
- Sensor arrays: CCD & CMOS


[Image Sensing and Acquisition]



Single sensor




Sensor Strip



Circular Sensor Strip

[Image Sensing and Acquisition]




[Image Formation Model]

- An image \rightarrow 2D function

$$0 < f(x, y) < \infty$$

where x and y are spatial coordinates



- Categorized by two components

$$f(x, y) = i(x, y)r(x, y)$$

- **Illumination:** $0 < i(x, y) < \infty$

- **Reflectance:** $0 < r(x, y) < 1$

- black velvet/ flat-white wall paint/ snow/ silver-plated metal



0.1

0.8




0.93

0.9

[Image Sampling & Quantization]



[Image Sampling & Quantization]



$$A = \begin{bmatrix} a_{0,0} & a_{0,1} & \cdots & a_{0,N-1} \\ a_{1,0} & a_{1,1} & \cdots & a_{1,N-1} \\ \vdots & \vdots & \ddots & \vdots \\ a_{M-1,0} & a_{M-1,1} & \cdots & a_{M-1,N-1} \end{bmatrix}$$

$$F(j, k) = \begin{bmatrix} F(0,0) & F(0,1) & \cdots & F(0,N-1) \\ F(1,0) & F(1,1) & \cdots & F(1,N-1) \\ \vdots & \vdots & \ddots & \vdots \\ F(M-1,0) & F(M-1,1) & \cdots & F(M-1,N-1) \end{bmatrix}$$

Digital Image Representation

■ Dynamic Range

- The range of values spanned by the gray scale

$$\{0, 1, \dots, L - 1\} \quad L = 2^k$$

■ Image Size

- for a square image, $M = N$

total number of bits required to store the image: $b = N^2 \cdot k$

N/k	1 ($L = 2$)	2 ($L = 4$)	3 ($L = 8$)	4 ($L = 16$)	5 ($L = 32$)	6 ($L = 64$)	7 ($L = 128$)	8 ($L = 256$)
32	1,024	2,048	3,072	4,096	5,120	6,144	7,168	8,192
64	4,096	8,192	12,288	16,384	20,480	24,576	28,672	32,768
128	16,384	32,768	49,152	65,536	81,920	98,304	114,688	131,072
256	65,536	131,072	196,608	262,144	327,680	393,216	458,752	524,288
512	262,144	524,288	786,432	1,048,576	1,310,720	1,572,864	1,835,008	2,097,152
1024	1,048,576	2,097,152	3,145,728	4,194,304	5,242,880	6,291,456	7,340,032	8,388,608
2048	4,194,304	8,388,608	12,582,912	16,777,216	20,971,520	25,165,824	29,369,128	33,554,432
4096	16,777,216	33,554,432	50,331,648	67,108,864	83,886,080	100,663,296	117,440,512	134,217,728
8192	67,108,864	134,217,728	201,326,592	268,435,456	335,544,320	402,653,184	469,762,048	536,870,912

[

Downsampling


]

- $1024 \times 1024 \rightarrow 32 \times 32$


- Downsampled by a factor of 2




1024



512



256



128



64




32

[


Re-Sampling

]


- Zero-Order-Hold Method (ZOH)
 - Row and column duplication



Re-Sampling



[L=256,128,64,32,16,8,4,2]




[

Digital Image Representation

]

- 8-bit image is commonly used
 - Storage
 - Human perception



32 steps (5 bits) in gray level



64 steps (6 bits) in gray level