

```
1:
2: Simple compiler: Translate exprs to stack machine insns.
3:
4: Syntax:      the ETF grammar
5: Lexical:     identifiers, numbers
6: Comments:    // and /**/ C-style
7: Directives:  #-cpp style
8: Activity:    Build AST
9: Codegen:     Stack machine code
10:
11: $Id: README,v 1.1 2015-07-08 13:29:32-07 - - $
12:
```

```
1: /* $Id: lexer.l,v 1.8 2019-04-10 14:51:55-07 - - $ */
2:
3: %{
4:
5: #include "lyutils.h"
6:
7: #define YY_USER_ACTION { lexer::advance(); }
8:
9: int yylval_token (int symbol) {
10:     yylval = new astree (symbol, lexer::lloc, yytext);
11:     return symbol;
12: }
13:
14: %}
15:
16: %option 8bit
17: %option debug
18: %option nobackup
19: %option nodefault
20: %option noinput
21: %option nounput
22: %option noyywrap
23: %option warn
24: /*%option verbose*/
25:
26: LETTER          [A-Za-z_]
27: DIGIT           [0-9]
28: MANTISSA        ({DIGIT}+\.?{DIGIT}*|\.{DIGIT}+)
29: EXPONENT        ([Ee] [+−]?{DIGIT}+)
30: NUMBER          ({MANTISSA}{EXPONENT}?)
31: NOTNUMBER       ({MANTISSA}[Ee] [+−]?)
32: IDENT          ({LETTER}({LETTER}|{DIGIT}))*
33:
34: %%
35:
36: "#".*           { lexer::include(); }
37: [ \t]+          { }
38: \n              { lexer::newline(); }
39:
40: {NUMBER}        { return yylval_token (NUMBER); }
41: {IDENT}         { return yylval_token (IDENT); }
42: "="             { return yylval_token ('='); }
43: "+"             { return yylval_token ('+'); }
44: "−"             { return yylval_token ('−'); }
45: "*"             { return yylval_token ('*'); }
46: "/"             { return yylval_token ('/'); }
47: "^"             { return yylval_token ('^'); }
48: "("             { return yylval_token ('('); }
49: ")"             { return yylval_token (')'); }
50: ";"             { return yylval_token (';'); }
51:
52: {NOTNUMBER}     { lexer::badtoken (yytext);
53:                  return yylval_token (NUMBER); }
54: .               { lexer::badchar (*yytext); }
55:
56: %%
57:
```

```
1: // $Id: parser.y,v 1.14 2016-10-06 16:26:41-07 - - $
2:
3: %{
4:
5: #include <assert.h>
6: #include <stdlib.h>
7: #include <string.h>
8:
9: #include "astree.h"
10: #include "lyutils.h"
11:
12: %}
13:
14: %debug
15: %defines
16: %error-verbose
17: %token-table
18: %verbose
19:
20: %destructor { destroy ($$); } <>
21: %printer { astree::dump (yyoutput, $$); } <>
22:
23: %initial-action {
24:     parser::root = new astree (ROOT, {0, 0, 0}, "<<ROOT>>");
25: }
26:
27: %token    ROOT IDENT NUMBER
28:
29: %right    '='
30: %left    '+' '-'
31: %left    '*' '/'
32: %right    '^'
33: %right    POS NEG
34:
35: %start    program
36:
```

```
37:
38: %%
39:
40: program : stmtseq                { $$ = $1 = nullptr; }
41:         ;
42:
43: stmtseq : stmtseq expr ';'        { destroy ($3); $$ = $1->adopt ($2); }
44:         | stmtseq error ';'       { destroy ($3); $$ = $1; }
45:         | stmtseq ';'             { destroy ($2); $$ = $1; }
46:         |                         { $$ = parser::root; }
47:         ;
48:
49: expr    : expr '=' expr           { $$ = $2->adopt ($1, $3); }
50:         | expr '+' expr           { $$ = $2->adopt ($1, $3); }
51:         | expr '-' expr           { $$ = $2->adopt ($1, $3); }
52:         | expr '*' expr           { $$ = $2->adopt ($1, $3); }
53:         | expr '/' expr           { $$ = $2->adopt ($1, $3); }
54:         | expr '^' expr           { $$ = $2->adopt ($1, $3); }
55:         | '+' expr %prec POS      { $$ = $1->adopt_sym ($2, POS); }
56:         | '-' expr %prec NEG      { $$ = $1->adopt_sym ($2, NEG); }
57:         | '(' expr ')'            { destroy ($1, $3); $$ = $2; }
58:         | IDENT                   { $$ = $1; }
59:         | NUMBER                   { $$ = $1; }
60:         ;
61:
62: %%
63:
64: const char* parser::get_tname (int symbol) {
65:     return yytname [YYTRANSLATE (symbol)];
66: }
67:
```

```
1: // $Id: astree.h,v 1.10 2016-10-06 16:42:35-07 - - $
2:
3: #ifndef __ASTREE_H__
4: #define __ASTREE_H__
5:
6: #include <string>
7: #include <vector>
8: using namespace std;
9:
10: #include "auxlib.h"
11:
12: struct location {
13:     size_t filenr;
14:     size_t linenr;
15:     size_t offset;
16: };
17:
18: struct astree {
19:
20:     // Fields.
21:     int symbol;                // token code
22:     location lloc;            // source location
23:     const string* lexinfo;    // pointer to lexical information
24:     vector<astree*> children; // children of this n-way node
25:
26:     // Functions.
27:     astree (int symbol, const location&, const char* lexinfo);
28:     ~astree();
29:     astree* adopt (astree* child1, astree* child2 = nullptr);
30:     astree* adopt_sym (astree* child, int symbol);
31:     void dump_node (FILE*);
32:     void dump_tree (FILE*, int depth = 0);
33:     static void dump (FILE* outfile, astree* tree);
34:     static void print (FILE* outfile, astree* tree, int depth = 0);
35: };
36:
37: void destroy (astree* tree1, astree* tree2 = nullptr);
38:
39: void errllocprintf (const location&, const char* format, const char*);
40:
41: #endif
42:
```

```
1: // $Id: astree.cpp,v 1.17 2019-03-15 14:32:40-07 - - $
2:
3: #include <assert.h>
4: #include <inttypes.h>
5: #include <stdarg.h>
6: #include <stdio.h>
7: #include <stdlib.h>
8: #include <string.h>
9:
10: #include "astree.h"
11: #include "string_set.h"
12: #include "lyutils.h"
13:
14: astree::astree (int symbol_, const location& lloc_, const char* info) {
15:     symbol = symbol_;
16:     lloc = lloc_;
17:     lexinfo = string_set::intern (info);
18:     // vector defaults to empty -- no children
19: }
20:
21: astree::~~astree() {
22:     while (not children.empty()) {
23:         astree* child = children.back();
24:         children.pop_back();
25:         delete child;
26:     }
27:     if (yydebug) {
28:         fprintf (stderr, "Deleting astree (");
29:         astree::dump (stderr, this);
30:         fprintf (stderr, ")\n");
31:     }
32: }
33:
34: astree* astree::adopt (astree* child1, astree* child2) {
35:     if (child1 != nullptr) children.push_back (child1);
36:     if (child2 != nullptr) children.push_back (child2);
37:     return this;
38: }
39:
40: astree* astree::adopt_sym (astree* child, int symbol_) {
41:     symbol = symbol_;
42:     return adopt (child);
43: }
44:
```

```
45:
46: void astree::dump_node (FILE* outfile) {
47:     fprintf (outfile, "%p->{%s %zd.%zd.%zd \"%s\":" ,
48:             static_cast<const void*> (this),
49:             parser::get_tname (symbol),
50:             lloc.filename, lloc.lineno, lloc.offset,
51:             lexinfo->c_str());
52:     for (size_t child = 0; child < children.size(); ++child) {
53:         fprintf (outfile, " %p",
54:                 static_cast<const void*> (children.at(child)));
55:     }
56: }
57:
58: void astree::dump_tree (FILE* outfile, int depth) {
59:     fprintf (outfile, "%*s", depth * 3, "");
60:     dump_node (outfile);
61:     fprintf (outfile, "\n");
62:     for (astree* child: children) child->dump_tree (outfile, depth + 1);
63:     fflush (nullptr);
64: }
65:
66: void astree::dump (FILE* outfile, astree* tree) {
67:     if (tree == nullptr) fprintf (outfile, "nullptr");
68:     else tree->dump_node (outfile);
69: }
70:
71: void astree::print (FILE* outfile, astree* tree, int depth) {
72:     fprintf (outfile, "; %*s", depth * 3, "");
73:     fprintf (outfile, "%s \"%s\" (%zd.%zd.%zd)\n",
74:             parser::get_tname (tree->symbol), tree->lexinfo->c_str(),
75:             tree->lloc.filename, tree->lloc.lineno, tree->lloc.offset);
76:     for (astree* child: tree->children) {
77:         astree::print (outfile, child, depth + 1);
78:     }
79: }
80:
81: void destroy (astree* tree1, astree* tree2) {
82:     if (tree1 != nullptr) delete tree1;
83:     if (tree2 != nullptr) delete tree2;
84: }
85:
86: void errllocprintf (const location& lloc, const char* format,
87:                   const char* arg) {
88:     static char buffer[0x1000];
89:     assert (sizeof buffer > strlen (format) + strlen (arg));
90:     snprintf (buffer, sizeof buffer, format, arg);
91:     errprintf ("%s:%zd.%zd: %s",
92:               lexer::filename (lloc.filename), lloc.lineno, lloc.offset,
93:               buffer);
94: }
```

```
1: // $Id: lyutils.h,v 1.6 2017-10-05 16:39:39-07 - - $
2:
3: #ifndef __UTILS_H__
4: #define __UTILS_H__
5:
6: // Lex and Yacc interface utility.
7:
8: #include <string>
9: #include <vector>
10: using namespace std;
11:
12: #include <stdio.h>
13:
14: #include "astree.h"
15: #include "auxlib.h"
16:
17: #define YYEOF 0
18:
19: extern FILE* yyin;
20: extern char* yytext;
21: extern int yy_flex_debug;
22: extern int yydebug;
23: extern size_t yyleng;
24:
25: int yylex();
26: int yylex_destroy();
27: int yyparse();
28: void yyerror (const char* message);
29:
30: struct lexer {
31:     static bool interactive;
32:     static location lloc;
33:     static size_t last_yyleng;
34:     static vector<string> filenames;
35:     static const string* filename (int filenr);
36:     static void newfilename (const string& filename);
37:     static void advance();
38:     static void newline();
39:     static void badchar (unsigned char bad);
40:     static void badtoken (char* lexeme);
41:     static void include();
42: };
43:
44: struct parser {
45:     static astree* root;
46:     static const char* get_tname (int symbol);
47: };
48:
49: #define YYSTYPE_IS_DECLARED
50: typedef astree* YYSTYPE;
51: #include "yyparse.h"
52:
53: #endif
54:
```



```
1: // $Id: lyutils.cpp,v 1.4 2019-03-15 14:32:40-07 - - $
2:
3: #include <assert.h>
4: #include <ctype.h>
5: #include <stdio.h>
6: #include <stdlib.h>
7: #include <string.h>
8:
9: #include "auxlib.h"
10: #include "lyutils.h"
11:
12: bool lexer::interactive = true;
13: location lexer::lloc = {0, 1, 0};
14: size_t lexer::last_yyleng = 0;
15: vector<string> lexer::filenames;
16:
17: astree* parser::root = nullptr;
18:
19: const string* lexer::filename (int filenr) {
20:     return &lexer::filenames.at(filenr);
21: }
22:
23: void lexer::newfilename (const string& filename) {
24:     lexer::lloc.filenr = lexer::filenames.size();
25:     lexer::filenames.push_back (filename);
26: }
27:
28: void lexer::advance() {
29:     if (not interactive) {
30:         if (lexer::lloc.offset == 0) {
31:             printf (";%2zd.%3zd: ",
32:                 lexer::lloc.filenr, lexer::lloc.linernr);
33:         }
34:         printf ("%s", yytext);
35:     }
36:     lexer::lloc.offset += last_yyleng;
37:     last_yyleng = yylen;
38: }
39:
40: void lexer::newline() {
41:     ++lexer::lloc.linernr;
42:     lexer::lloc.offset = 0;
43: }
44:
45: void lexer::badchar (unsigned char bad) {
46:     char buffer[16];
47:     snprintf (buffer, sizeof buffer,
48:         isgraph (bad) ? "%c" : "\\%03o", bad);
49:     errllocprintf (lexer::lloc, "invalid source character (%s)\n",
50:         buffer);
51: }
52:
```

```
53:
54: void lexer::badtoken (char* lexeme) {
55:     errllocprintf (lexer::lloc, "invalid token (%s)\n", lexeme);
56: }
57:
58: void lexer::include() {
59:     size_t linenr;
60:     static char filename[0x1000];
61:     assert (sizeof filename > strlen (yytext));
62:     int scan_rc = sscanf (yytext, "# %zu \"%^[^\"]\"\"", &linenr, filename);
63:     if (scan_rc != 2) {
64:         errprintf ("%s: invalid directive, ignored\n", yytext);
65:     } else {
66:         if (yy_flex_debug) {
67:             fprintf (stderr, "--included # %zd \"%s\"\n",
68:                     linenr, filename);
69:         }
70:         lexer::lloc.linenr = linenr - 1;
71:         lexer::newfilename (filename);
72:     }
73: }
74:
75: void yyerror (const char* message) {
76:     assert (not lexer::filenames.empty());
77:     errllocprintf (lexer::lloc, "%s\n", message);
78: }
79:
```

```
1: // $Id: string_set.h,v 1.2 2016-08-18 15:12:57-07 - - $
2:
3: #ifndef __STRING_SET__
4: #define __STRING_SET__
5:
6: #include <string>
7: #include <unordered_set>
8: using namespace std;
9:
10: #include <stdio.h>
11:
12: struct string_set {
13:     string_set();
14:     static unordered_set<string> set;
15:     static const string* intern (const char*);
16:     static void dump (FILE*);
17: };
18:
19: #endif
20:
```

```
1: // $Id: string_set.cpp,v 1.5 2019-03-15 14:32:40-07 - - $
2:
3: #include <string>
4: #include <unordered_set>
5: using namespace std;
6:
7: #include "auxlib.h"
8: #include "string_set.h"
9:
10: unordered_set<string> string_set::set;
11:
12: string_set::string_set() {
13:     set.max_load_factor (0.5);
14: }
15:
16: const string* string_set::intern (const char* string) {
17:     auto handle = set.insert (string);
18:     DEBUGF ('s', "inserted \"%s\" %s\n", handle.first->c_str(),
19:             handle.second ? "newly inserted" : "already there");
20:     return &*handle.first;
21: }
22:
23: void string_set::dump (FILE* out) {
24:     static unordered_set<string>::hasher hash_fn
25:         = string_set::set.hash_function();
26:     size_t max_bucket_size = 0;
27:     for (size_t bucket = 0; bucket < set.bucket_count(); ++bucket) {
28:         bool need_index = true;
29:         size_t curr_size = set.bucket_size (bucket);
30:         if (max_bucket_size < curr_size) max_bucket_size = curr_size;
31:         for (auto itor = set.cbegin (bucket);
32:              itor != set.cend (bucket); ++itor) {
33:             if (need_index) fprintf (out, "string_set[%4zu]: ", bucket);
34:             else fprintf (out, "          %4s ", "");
35:             need_index = false;
36:             const string* str = &*itor;
37:             fprintf (out, "%22zu %p->\"%s\"\\n", hash_fn(*str),
38:                     reinterpret_cast<const void*> (str), str->c_str());
39:         }
40:     }
41:     fprintf (out, "load_factor = %.3f\\n", set.load_factor());
42:     fprintf (out, "bucket_count = %zu\\n", set.bucket_count());
43:     fprintf (out, "max_bucket_size = %zu\\n", max_bucket_size);
44: }
45:
```

```
1: // $Id: emitter.h,v 1.1 2015-07-09 14:08:38-07 - - $
2:
3: #ifndef __EMIT_H__
4: #define __EMIT_H__
5:
6: #include "astree.h"
7:
8: void emit_sm_code (astree*);
9:
10: #endif
11:
```

```
1: // $Id: emitter.cpp,v 1.5 2017-10-05 16:39:39-07 - - $
2:
3: #include <assert.h>
4: #include <stdio.h>
5:
6: #include "astree.h"
7: #include "emitter.h"
8: #include "auxlib.h"
9: #include "lyutils.h"
10:
11: void emit (astree* root);
12:
13: void emit_insn (const char* opcode, const char* operand, astree* tree) {
14:     printf ("%10s%-10s%-20s; %s %zd.%zd\n", "",
15:             opcode, operand,
16:             lexer::filename (tree->lloc.filenamer)->c_str(),
17:             tree->lloc.linelnr, tree->lloc.offset);
18: }
19:
20: void postorder (astree* tree) {
21:     assert (tree != nullptr);
22:     for (size_t child = 0; child < tree->children.size(); ++child) {
23:         emit (tree->children.at(child));
24:     }
25: }
26:
27: void postorder_emit_stmts (astree* tree) {
28:     postorder (tree);
29: }
30:
31: void postorder_emit_oper (astree* tree, const char* opcode) {
32:     postorder (tree);
33:     emit_insn (opcode, "", tree);
34: }
35:
36: void postorder_emit_semi (astree* tree) {
37:     postorder (tree);
38:     emit_insn ("", "", tree);
39: }
40:
41: void emit_push (astree* tree, const char* opcode) {
42:     emit_insn (opcode, tree->lexinfo->c_str(), tree);
43: }
44:
45: void emit_assign (astree* tree) {
46:     assert (tree->children.size() == 2);
47:     astree* left = tree->children.at(0);
48:     emit (tree->children.at(1));
49:     if (left->symbol != IDENT) {
50:         errllocprintf (left->lloc, "%s\n",
51:             "left operand of '=' not an identifier");
52:     }else{
53:         emit_insn ("popvar", left->lexinfo->c_str(), left);
54:     }
55: }
56:
```

```
57:
58: void emit (astree* tree) {
59:     switch (tree->symbol) {
60:         case ROOT    : postorder_emit_stmts (tree);          break;
61:         case ';'      : postorder_emit_semi (tree);          break;
62:         case '='       : emit_assign (tree);                  break;
63:         case '+'       : postorder_emit_oper (tree, "add");    break;
64:         case '-'       : postorder_emit_oper (tree, "sub");    break;
65:         case '*'       : postorder_emit_oper (tree, "mul");    break;
66:         case '/'       : postorder_emit_oper (tree, "div");    break;
67:         case '^'       : postorder_emit_oper (tree, "pow");    break;
68:         case POS       : postorder_emit_oper (tree, "pos");    break;
69:         case NEG       : postorder_emit_oper (tree, "neg");    break;
70:         case IDENT    : emit_push (tree, "pushvar");          break;
71:         case NUMBER   : emit_push (tree, "pushnum");          break;
72:         default       : assert (false);                        break;
73:     }
74: }
75:
76: void emit_sm_code (astree* tree) {
77:     printf ("\n");
78:     if (tree) emit (tree);
79: }
80:
```

```
1: // $Id: auxlib.h,v 1.5 2017-10-11 14:33:45-07 - - $
2:
3: #ifndef __AUXLIB_H__
4: #define __AUXLIB_H__
5:
6: #include <string>
7: using namespace std;
8:
9: #include <stdarg.h>
10:
11: //
12: // DESCRIPTION
13: //     Auxiliary library containing miscellaneous useful things.
14: //
15:
16: //
17: // Error message and exit status utility.
18: //
19:
20: struct exec {
21:     static string execname;
22:     static int exit_status;
23: };
24:
25: void veprintf (const char* format, va_list args);
26: // Prints a message to stderr using the vector form of
27: // argument list.
28:
29: void eprintf (const char* format, ...);
30: // Print a message to stderr according to the printf format
31: // specified. Usually called for debug output.
32: // Precedes the message by the program name if the format
33: // begins with the characters `%:'.
34:
35: void errprintf (const char* format, ...);
36: // Print an error message according to the printf format
37: // specified, using eprintf.
38: // Sets the exitstatus to EXIT_FAILURE.
39:
40: void syserrprintf (const char* object);
41: // Print a message resulting from a bad system call. The
42: // object is the name of the object causing the problem and
43: // the reason is taken from the external variable errno.
44: // Sets the exit status to EXIT_FAILURE.
45:
46: void eprint_status (const char* command, int status);
47: // Print the status returned by wait(2) from a subprocess.
48:
```



```
49:
50: //
51: // Support for stub messages.
52: //
53: #define STUBPRINTF(...) \
54:     __stubprintf (__FILE__, __LINE__, __PRETTY_FUNCTION__, \
55:         __VA_ARGS__)
56: void __stubprintf (const char* file, int line, const char* func,
57:     const char* format, ...);
58:
59: //
60: // Debugging utility.
61: //
62:
63: void set_debugflags (const char* flags);
64: // Sets a string of debug flags to be used by DEBUGF statements.
65: // Uses the address of the string, and does not copy it, so
66: // it must not be dangling. If a particular debug flag has
67: // been set, messages are printed. The format is identical to
68: // printf format. The flag "@" turns on all flags.
69:
70: bool is_debugflag (char flag);
71: // Checks to see if a debugflag is set.
72:
73: #ifdef NDEBUG
74: // Do not generate any code.
75: #define DEBUGF(FLAG,...) /**/
76: #define DEBUGSTMT(FLAG,STMTS) /**/
77: #else
78: // Generate debugging code.
79: void __debugprintf (char flag, const char* file, int line,
80:     const char* func, const char* format, ...);
81: #define DEBUGF(FLAG,...) \
82:     __debugprintf (FLAG, __FILE__, __LINE__, __PRETTY_FUNCTION__, \
83:         __VA_ARGS__)
84: #define DEBUGSTMT(FLAG,STMTS) \
85:     if (is_debugflag (FLAG)) { DEBUGF (FLAG, "\n"); STMTS }
86: #endif
87:
88: #endif
89:
```

```
1: // $Id: auxlib.cpp,v 1.4 2019-04-10 15:50:29-07 - - $
2:
3: #include <assert.h>
4: #include <errno.h>
5: #include <libgen.h>
6: #include <limits.h>
7: #include <stdarg.h>
8: #include <stdio.h>
9: #include <stdlib.h>
10: #include <string.h>
11: #include <wait.h>
12:
13: #include "auxlib.h"
14:
15: string exec::execname;
16: int exec::exit_status = EXIT_SUCCESS;
17:
18: const char* debugflags = "";
19: bool alldebugflags = false;
20:
21: static void eprint_signal (const char* kind, int signal) {
22:     eprintf (" %s %d", kind, signal);
23:     const char* sigstr = strsignal (signal);
24:     if (sigstr != nullptr) fprintf (stderr, " %s", sigstr);
25: }
26:
27: void eprint_status (const char* command, int status) {
28:     if (status == 0) return;
29:     eprintf ("%s: status 0x%04X", command, status);
30:     if (WIFEXITED (status)) {
31:         eprintf (" exit %d", WEXITSTATUS (status));
32:     }
33:     if (WIFSIGNALED (status)) {
34:         eprint_signal ("Terminated", WTERMSIG (status));
35:         #ifdef WCOREDUMP
36:         if (WCOREDUMP (status)) eprintf (" core dumped");
37:         #endif
38:     }
39:     if (WIFSTOPPED (status)) {
40:         eprint_signal ("Stopped", WSTOPSIG (status));
41:     }
42:     if (WIFCONTINUED (status)) {
43:         eprintf (" Continued");
44:     }
45:     eprintf ("\n");
46: }
47:
```

```
48:
49: void veprintf (const char* format, va_list args) {
50:     assert (exec::execname.size() != 0);
51:     assert (format != nullptr);
52:     fflush (nullptr);
53:     if (strstr (format, "%:") == format) {
54:         fprintf (stderr, "%s: ", exec::execname.c_str());
55:         format += 2;
56:     }
57:     vfprintf (stderr, format, args);
58:     fflush (nullptr);
59: }
60:
61: void eprintf (const char* format, ...) {
62:     va_list args;
63:     va_start (args, format);
64:     veprintf (format, args);
65:     va_end (args);
66: }
67:
68: void errprintf (const char* format, ...) {
69:     va_list args;
70:     va_start (args, format);
71:     veprintf (format, args);
72:     va_end (args);
73:     exec::exit_status = EXIT_FAILURE;
74: }
75:
76: void syserrprintf (const char* object) {
77:     errprintf ("%s: %s\n", object, strerror (errno));
78: }
79:
80: void __stubprintf (const char* file, int line, const char* func,
81:                   const char* format, ...) {
82:     va_list args;
83:     fflush (nullptr);
84:     printf ("%s: %s[%d] %s: ", exec::execname.c_str(), file, line, func);
85:     va_start (args, format);
86:     vprintf (format, args);
87:     va_end (args);
88:     fflush (nullptr);
89: }
90:
```

```
91:
92: void set_debugflags (const char* flags) {
93:     debugflags = flags;
94:     assert (debugflags != nullptr);
95:     if (strchr (debugflags, '@') != nullptr) alldebugflags = true;
96:     DEBUGF ('x', "Debugflags = \"%s\", all = %d\n",
97:             debugflags, alldebugflags);
98: }
99:
100: bool is_debugflag (char flag) {
101:     return alldebugflags or strchr (debugflags, flag) != nullptr;
102: }
103:
104: void __debugprintf (char flag, const char* file, int line,
105:                    const char* func, const char* format, ...) {
106:     va_list args;
107:     if (not is_debugflag (flag)) return;
108:     fflush (nullptr);
109:     va_start (args, format);
110:     fprintf (stderr, "DEBUGF(%c): %s[%d] %s():\n",
111:             flag, file, line, func);
112:     vfprintf (stderr, format, args);
113:     va_end (args);
114:     fflush (nullptr);
115: }
116:
```

```
1: // $Id: main.cpp,v 1.18 2017-10-19 16:02:14-07 - - $
2:
3: #include <string>
4: #include <vector>
5: using namespace std;
6:
7: #include <assert.h>
8: #include <errno.h>
9: #include <libgen.h>
10: #include <stdio.h>
11: #include <stdlib.h>
12: #include <string.h>
13: #include <unistd.h>
14:
15: #include "astree.h"
16: #include "auxlib.h"
17: #include "emitter.h"
18: #include "lyutils.h"
19: #include "string_set.h"
20:
21: const string cpp_name = "/usr/bin/cpp";
22: string cpp_command;
23:
24: // Open a pipe from the C preprocessor.
25: // Exit failure if can't.
26: // Assigns opened pipe to FILE* yyin.
27: void cpp_popen (const char* filename) {
28:     cpp_command = cpp_name + " " + filename;
29:     yyin = popen (cpp_command.c_str(), "r");
30:     if (yyin == nullptr) {
31:         syserrprintf (cpp_command.c_str());
32:         exit (exec::exit_status);
33:     } else {
34:         if (yy_flex_debug) {
35:             fprintf (stderr, "-- popen (%s), fileno(yyin) = %d\n",
36:                     cpp_command.c_str(), fileno (yyin));
37:         }
38:         lexer::newfilename (cpp_command);
39:     }
40: }
41:
42: void cpp_pclose() {
43:     int pclose_rc = pclose (yyin);
44:     eprint_status (cpp_command.c_str(), pclose_rc);
45:     if (pclose_rc != 0) exec::exit_status = EXIT_FAILURE;
46: }
47:
```

```
48:
49: void scan_opts (int argc, char** argv) {
50:     opterr = 0;
51:     yy_flex_debug = 0;
52:     yydebug = 0;
53:     lexer::interactive = isatty (fileno (stdin))
54:         and isatty (fileno (stdout));
55:     for(;;) {
56:         int opt = getopt (argc, argv, "@:ly");
57:         if (opt == EOF) break;
58:         switch (opt) {
59:             case '@': set_debugflags (optarg);    break;
60:             case 'l': yy_flex_debug = 1;         break;
61:             case 'y': yydebug = 1;               break;
62:             default: errprintf ("bad option (%c)\n", optopt); break;
63:         }
64:     }
65:     if (optind > argc) {
66:         errprintf ("Usage: %s [-ly] [filename]\n",
67:             exec::execname.c_str());
68:         exit (exec::exit_status);
69:     }
70:     const char* filename = optind == argc ? "-" : argv[optind];
71:     cpp_popen (filename);
72: }
73:
74: int main (int argc, char** argv) {
75:     exec::execname = basename (argv[0]);
76:     if (yydebug or yy_flex_debug) {
77:         fprintf (stderr, "Command:");
78:         for (char** arg = &argv[0]; arg < &argv[argc]; ++arg) {
79:             fprintf (stderr, " %s", *arg);
80:         }
81:         fprintf (stderr, "\n");
82:     }
83:     scan_opts (argc, argv);
84:     int parse_rc = yyparse();
85:     cpp_pclose();
86:     yylex_destroy();
87:     if (yydebug or yy_flex_debug) {
88:         fprintf (stderr, "Dumping parser::root:\n");
89:         if (parser::root != nullptr) parser::root->dump_tree (stderr);
90:         fprintf (stderr, "Dumping string_set:\n");
91:         string_set::dump (stderr);
92:     }
93:     if (parse_rc) {
94:         errprintf ("parse failed (%d)\n", parse_rc);
95:     } else {
96:         astree::print (stdout, parser::root);
97:         emit_sm_code (parser::root);
98:         delete parser::root;
99:     }
100:     return exec::exit_status;
101: }
102:
```

```
1: # $Id: Makefile,v 1.38 2019-04-10 15:51:41-07 - - $
2:
3: DEPSFILE = Makefile.deps
4: NOINCLUDE = ci clean spotless
5: NEEDINCL = ${filter ${NOINCLUDE}, ${MAKECMDGOALS}}
6: WARNING = -Wall -Wextra -Wpedantic -Wshadow -Wold-style-cast
7: CPP = g++ -std=gnu++17 -g -O0
8: CPPWARN = ${CPP} ${WARNING} -fdiagnostics-color=never
9: CPPYY = ${CPP} -Wno-sign-compare -Wno-register
10: MKDEPS = g++ -std=gnu++17 -MM
11: GRIND = valgrind --leak-check=full --show-reachable=yes
12: FLEX = flex --outfile=${LEXCPP}
13: BISON = bison --defines=${PARSEHDR} --output=${PARSECPP}
14:
15: MODULES = astree lyutils string_set emitter auxlib
16: HDRSRC = ${MODULES:=.h}
17: CPPSRC = ${MODULES:=.cpp} main.cpp
18: FLEXSRC = lexer.l
19: BISONSRC = parser.y
20: PARSEHDR = yyparse.h
21: LEXCPP = yylex.cpp
22: PARSECPP = yyparse.cpp
23: CGENS = ${LEXCPP} ${PARSECPP}
24: ALLGENS = ${PARSEHDR} ${CGENS}
25: EXECBIN = zexprsm
26: ALLCSRC = ${CPPSRC} ${CGENS}
27: OBJECTS = ${ALLCSRC:.cpp=.o}
28: LEXOUT = yylex.output
29: PARSEOUT = yyparse.output
30: REPORTS = ${LEXOUT} ${PARSEOUT}
31: MODSRC = ${foreach MOD, ${MODULES}, ${MOD}.h ${MOD}.cpp}
32: MISCSRC = ${filter-out ${MODSRC}, ${HDRSRC} ${CPPSRC}}
33: ALLSRC = README ${FLEXSRC} ${BISONSRC} ${MODSRC} ${MISCSRC} Makefile
34: TESTINS = ${wildcard test*.in}
35: EXECTEST = ${EXECBIN} -ly
36: LISTSRC = ${ALLSRC} ${DEPSFILE} ${PARSEHDR}
37:
38: all : ${EXECBIN}
39:
40: ${EXECBIN} : ${OBJECTS}
41:     ${CPPWARN} -o${EXECBIN} ${OBJECTS}
42:
43: yylex.o : yylex.cpp
44:     ${CPPYY} -c $<
45:
46: yyparse.o : yyparse.cpp
47:     ${CPPYY} -c $<
48:
49: %.o : %.cpp
50:     - cpplint.py.perl $<
51:     - checksource $<
52:     ${CPPWARN} -c $<
53:
```

```
54:
55: ${LEXCPP} : ${FLEXSRC}
56:     ${FLEX} ${FLEXSRC}
57:
58: ${PARSECPP} ${PARSEHDR} : ${BISONSRC}
59:     ${BISON} ${BISONSRC}
60:
61: ci : ${ALLSRC} ${TESTINS}
62:     - checksource ${ALLSRC}
63:     cid + ${ALLSRC} ${TESTINS} test?.inh
64:
65: lis : ${LISTSRC} tests
66:     mkpspdf List.source.ps ${LISTSRC}
67:     mkpspdf List.output.ps ${REPORTS} \
68:         ${foreach test, ${TESTINS:.in=}, \
69:         ${patsubst %, ${test}%, in out err log}}
70:
71: clean :
72:     - rm ${OBJECTS} ${ALLGENS} ${REPORTS} ${DEPSFILE} core
73:     - rm ${foreach test, ${TESTINS:.in=}, \
74:         ${patsubst %, ${test}%, out err log}}
75:
76: spotless : clean
77:     - rm ${EXECBIN} List.*.ps List.*.pdf
78:
79: deps : ${ALLCSRC}
80:     @ echo "# ${DEPSFILE} created `date` by ${MAKE}" >${DEPSFILE}
81:     ${MKDEPS} ${ALLCSRC} >>${DEPSFILE}
82:
83: ${DEPSFILE} :
84:     @ touch ${DEPSFILE}
85:     ${MAKE} --no-print-directory deps
86:
87: tests : ${EXECBIN}
88:     touch ${TESTINS}
89:     make --no-print-directory ${TESTINS:.in=.out}
90:
91: %.out %.err : %.in
92:     ${GRIND} --log-file=*.log ${EXECTEST} $< 1>*.out 2>*.err; \
93:     echo EXIT STATUS = $$? >>*.log
94:
95: again :
96:     gmake --no-print-directory spotless deps ci all lis
97:
98: ifeq "${NEEDINCL}" ""
99: include ${DEPSFILE}
100: endif
101:
```



```
1: # Makefile.deps created Wed Apr 10 15:51:41 PDT 2019 by gmake
2: astree.o: astree.cpp astree.h auxlib.h string_set.h lyutils.h yyparse.h
3: lyutils.o: lyutils.cpp auxlib.h lyutils.h astree.h yyparse.h
4: string_set.o: string_set.cpp auxlib.h string_set.h
5: emitter.o: emitter.cpp astree.h auxlib.h emitter.h lyutils.h yyparse.h
6: auxlib.o: auxlib.cpp auxlib.h
7: main.o: main.cpp astree.h auxlib.h emitter.h lyutils.h yyparse.h \
8:   string_set.h
9: yylex.o: yylex.cpp lyutils.h astree.h auxlib.h yyparse.h
10: yyparse.o: yyparse.cpp astree.h auxlib.h lyutils.h yyparse.h
```

```
1: /* A Bison parser, made by GNU Bison 3.0.4.  */
2:
3: /* Bison interface for Yacc-like parsers in C
4:
5:    Copyright (C) 1984, 1989-1990, 2000-2015 Free Software Foundation, In
c.
6:
7:    This program is free software: you can redistribute it and/or modify
8:    it under the terms of the GNU General Public License as published by
9:    the Free Software Foundation, either version 3 of the License, or
10:   (at your option) any later version.
11:
12:   This program is distributed in the hope that it will be useful,
13:   but WITHOUT ANY WARRANTY; without even the implied warranty of
14:   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
15:   GNU General Public License for more details.
16:
17:   You should have received a copy of the GNU General Public License
18:   along with this program.  If not, see <http://www.gnu.org/licenses/>.
*/
19:
20: /* As a special exception, you may create a larger work that contains
21:    part or all of the Bison parser skeleton and distribute that work
22:    under terms of your choice, so long as that work isn't itself a
23:    parser generator using the skeleton or a modified version thereof
24:    as a parser skeleton.  Alternatively, if you modify or redistribute
25:    the parser skeleton itself, you may (at your option) remove this
26:    special exception, which will cause the skeleton and the resulting
27:    Bison output files to be licensed under the GNU General Public
28:    License without this special exception.
29:
30:   This special exception was added by the Free Software Foundation in
31:   version 2.2 of Bison.  */
32:
33: #ifndef YY_YYPARSE_H_INCLUDED
34: # define YY_YYPARSE_H_INCLUDED
35: /* Debug traces.  */
36: #ifndef YYDEBUG
37: # define YYDEBUG 1
38: #endif
39: #if YYDEBUG
40: extern int yydebug;
41: #endif
42:
43: /* Token type.  */
44: #ifndef YYTOKENTYPE
45: # define YYTOKENTYPE
46:   enum yytokentype
47:   {
48:     ROOT = 258,
49:     IDENT = 259,
50:     NUMBER = 260,
51:     POS = 261,
52:     NEG = 262
53:   };
54: #endif
55:
56: /* Value type.  */
```

```
57: #if ! defined YYSTYPE && ! defined YYSTYPE_IS_DECLARED
58: typedef int YYSTYPE;
59: # define YYSTYPE_IS_TRIVIAL 1
60: # define YYSTYPE_IS_DECLARED 1
61: #endif
62:
63:
64: extern YYSTYPE yylval;
65:
66: int yyparse (void);
67:
68: #endif /* !YY_YYPARSE_H_INCLUDED */
```