NEC

SILICON TRANSISTOR ARRAY

μPA1428A

NPN SILICON POWER TRANSISTOR ARRAY
HIGH SPEED SWITCHING USE (DARLINGTON TRANSISTOR)
INDUSTRIAL USE

DESCRIPTION

The μPA1428A is NPN silicon epitaxial Darlington Power Transistor Array that built in Surge Absorber 4 circuits designed for driving solenoid, relay, lamp and so on.

FEATURES

- Surge Absorber built in.
- Easy mount by 0.1 inch of terminal interval.
- High h_{FE} for Darlington Transistor.

ORDERING INFORMATION

Part Number	Package	Quality Grade
μPA1428AH	10 Pin SIP	Standard

Please refer to "Quality grade on NEC Semiconductor Device" (Document number IEI-1209) published by NEC Corporation to know the specification of quality grade on the devices and its recommended applications.

ABSOLUTE MAXIMUM RATINGS (T_a = 25 ˚C)

Collector to Base Voltage	V_{CBO}	60 ±10	V
Collector to Emitter Voltage	V_{CEO}	60 ±10	V
Emitter to Base Voltage	V_{EBO}	8	V
Surge Sustaining Energy	$E_{CEO(sus)}$	30	mJ/unit
Collector Current (DC)	$I_{C(DC)}$	±2	A/unit
Collector Current (pulse)	$I_{C(pulse)}$*	±3	A/unit
Base Current (DC)	$I_{B(DC)}$	0.2	A/unit
Total Power Dissipation	P_{T1}**	3.5	W
Total Power Dissipation	P_{T2}***	28	W
Junction Temperature	T_j	150	˚C
Storage Temperature	T_{stg}	–55 to +150	˚C

* PW ≤ 350 μs, Duty Cycle ≤ 2 %

** 4 Circuits, T_a = 25 ˚C

*** 4 Cuircuits, T_c = 25 ˚C

PACKAGE DIMENSION
(in millimeters)



CONNECTION DIAGRAM



PIN NO.

2, 4, 6, 8: Base (B)
3, 5, 7, 9: Collector (C)
1, 10: Emitter (E)
R_1 ≒ 10 kΩ
R_2 ≒ 900 Ω

The information in this document is subject to change without notice.

Document No. IC-3479
(O.D. No. IC-8359)
Date Published September 1994 P
Printed in Japan

ELECTRICAL CHARACTERISTICS (T_a = 25 °C)

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITIONS
Collector Leakage Current	I_{CBO}			1	μA	V_{CB} = 40 V, I_E = 0
Emitter Leakage Current	I_{EBO}			5	mA	V_{EB} = 5 V, I_C = 0
Collector to Emitter Sustaining Voltage	$V_{CEO(sus)}$	50	60	70	V	I_C = 1 A, L = 1 mH
DC Current Gain	h_{FE1} *	2000		20000	—	V_{CE} = 2 V, I_C = 1 A
DC Current Gain	h_{FE2} *	500			—	V_{CE} = 2 V, I_C = 2 A
Collector Saturation Voltage	$V_{CE(sat)}$ *		1.0	1.5	V	I_C = 1 A, I_B = 1 mA
Base Saturation Voltage	$V_{BE(sat)}$ *		1.7	2	V	I_C = 1 A, I_B = 1 mA
Turn On Time	t_{on}		0.4		μs	I_C = 1 A I_{B1} = –I_{B2} = 2 mA V_{CC} ≒ 50 V, R_L = 50 Ω See test circuit
Storage Time	t_{stg}		1.5		μs	
Fall Time	t_f		0.4		μs	

* PW ≤ 350 μs, Duty Cycle ≤ 2 %/pulsed

SWITCHING TIME TEST CIRCUIT



TYPICAL CHARACTERISTICS (T_a = 25 °C)

DERATING CURVE OF SAFE OPERATING AREA



SAFE OPERATING AREA



TOTAL POWER DISSIPATION vs. AMBIENT TEMPERATURE



TOTAL POWER DISSIPATION vs. CASE TEMPERATURE



DC CURRENT GAIN vs. COLLECTOR CURRENT



TRANSIENT THERMAL RESISTANCE



COLLECTOR SATURATION VOLTAGE vs. COLLECTOR CURRENT



BASE SATURATION VOLTAGE vs. COLLECTOR CURRENT



SWITCHING TIME vs. COLLECTOR CURRENT



DUMPER DIODE CHARACTERISTICS



REFERENCE

Document Name	Document No.
NEC semiconductor device reliability/quality control system.	TEI-1202
Quality grade on NEC semiconductor devices.	IEI-1209
Semiconductor device mounting technology manual.	IEI-1207
Semiconductor device package manual.	IEI-1213
Guide to quality assurance for semiconductor devices.	MEI-1202
Semiconductor selection guide.	MF-1134

[MEMO]

M4 92.6