

Data Structure and Algorithm, Spring 2024

Mini-Homework A

TA E-mail: dsa_ta@csie.ntu.edu.tw

Due: 13:00:00, Tuesday, **April 16, 2024**

RED CORRECTION: 05:30:00, February 29, 2024

Rules and Instructions

- Any form of cheating, lying, or plagiarism will not be tolerated. Students can get zero scores and/or fail the class and/or be kicked out of school and/or receive other punishments for those kinds of misconducts.
- Discussions on course materials and homework solutions are encouraged. But you should write the final solutions alone and understand them fully. Books, notes, and Internet resources (including chatGPT) can be consulted, but not copied from.
- Since everyone needs to write the final solutions alone, there is **absolutely no need to lend your homework solutions and/or source codes to your classmates at any time**. In order to maximize the level of fairness in this class, lending and borrowing homework solutions are both regarded as dishonest behaviors and will be punished according to the honesty policy.
- In each mini-homework, we will have one programming problem that is closely connected to what we have taught in the class. The purpose of the problem is for you to *practice* what you have learned, before conquering the more challenging problems in other homework sets.
- Like other programming problems, you should write your code in C programming language, and then submit the code via the *DSA Judge*:

<https://dsa2024.csie.org/>.

Each day, you can submit up to 5 times for each problem. The judge system will compile your code with

```
gcc main.c -static -O2 -std=c11
```

- For debugging in the programming part, we strongly suggest you produce your own test-cases with programs and/or use tools like `gdb` or compile with flag `-fsanitize=address` to help you solve issues like illegal memory usage. For `gdb`, you are strongly encouraged to use compile flag `-g` to preserve symbols after compiling.

Note: For students who use IDE (VScode, DevC++...) you can modify the compile command in the settings/preference section. Below are some examples:

- `gcc main.c -O2 -std=c11 -fsanitize=address # Works on Unix-like OS`
- `gcc main.c -O2 -std=c11 -g # use it with gdb`

- The score of the part that is submitted after the deadline will get some penalties according to the following rule:

$$Late\ Score = \max \left(\left(\frac{5 \times 86400 - Delay\ Time(sec.)}{5 \times 86400} \right) \times Original\ Score, 0 \right)$$

- If you have questions about this mini-homework, please go to the the Discord channel and discuss the issues with your classmates. This is *strongly preferred* because it will provide everyone with a more interactive learning experience. If you really need an email answer, please follow the rules outlined below to get a fast response:
 - The subject should contain one tag, "[hwa]", specifying the problem where you have questions. For example, "[hwa] Will there be a repeated number?". Adding these tags allows the TAs to track the status of each email and to provide faster responses to you.
 - If you want to provide your code segments to us as part of your question, please upload it to [Gist](#) or similar platforms and provide the link. Please remember to protect your uploaded materials with proper permission settings. Screenshots or code segments directly included in the email are discouraged and may not be reviewed.

Selection Sort (20 pts)

Problem Description

Given an array \mathbf{a} with N numbers $\mathbf{a}[1], \mathbf{a}[2], \dots, \mathbf{a}[N]$ (possibly repeated), run the following selection sort algorithm on the array, as introduced in Lecture 1 of the class, for a budget of B swaps or until the array is sorted. Then, print out the content of the array.

Note that there are many different variant versions of the selection sort algorithm. You are asked to implement the version below *exactly* to produce the correct answer for this problem.

SELECTION-SORT(\mathbf{a})

```
1  for  $i = 1$  to  $\mathbf{a.length}$ 
2       $m = \text{GET-MIN-INDEX}(\mathbf{a}, i, \mathbf{a.length})$ 
3      if  $i \neq m$ 
4          SWAP( $\mathbf{a}[i], \mathbf{a}[m]$ )
5  return  $\mathbf{a}$  // which has been sorted in place
```

GET-MIN-INDEX(\mathbf{a}, ℓ, r)

```
1   $m = \ell$  // store current min. index
2  for  $i = \ell + 1$  to  $r$ 
3      // update if  $i$ -th element smaller
4      if  $\mathbf{a}[m] > \mathbf{a}[i]$ 
5           $m = i$ 
6  return  $m$ 
```

Input

The first line includes two integers N and B , representing the size of the array and the budget on the number of swaps. The second line includes N integers, representing the elements of the array $\mathbf{a}[1], \mathbf{a}[2], \dots, \mathbf{a}[N]$. All numbers are separated by a space.

Output

- If the array can be sorted within B swaps, output a line of

The array is [the content of the array] after [X] swaps.

where [the content of the array] lists the final $\mathbf{a}[1], \mathbf{a}[2], \dots, \mathbf{a}[N]$ after sorting, and [X] is the actual number of swaps taken, which would be a unique number using the version of the selection sort algorithm above.

- If the array is not sorted after B swaps, output a line of

The array is [the content of the array] after [B] swaps.

where [the content of the array] lists the intermediate $\mathbf{a}[1], \mathbf{a}[2], \dots, \mathbf{a}[N]$ after the B swaps, and [B] is just the number B .

Constraint

- $1 \leq N \leq 2^{10}$
- $1 \leq B \leq 2^{10}$
- $-2^{30} \leq \mathbf{a}[n] \leq 2^{30}$ for $n \in \{1, 2, \dots, N\}$

Sample Testcases

Sample Input 1

3 2
1 3 2

Sample Input 2

4 2
2 3 4 1

Sample Input 3

4 2
2 2 4 1

Sample Output 1

The array is 1 2 3 after 1 swaps.

Sample Output 2

The array is 1 2 4 3 after 2 swaps.

Sample Output 3

The array is 1 2 2 4 after 2 swaps.

Hint

- By design, you can pass this homework by simulating the selection sort algorithm properly. There is no need for other arithmetic calculations or cuts.